

## 01 – START SIMPLE

The general Github-address with example code is [github.com/PeterKassenaar/voorbeeldenAngular2](https://github.com/PeterKassenaar/voorbeeldenAngular2)

a) **Goal: create a basic Angular Hello world app.**

- Create your own Hello World app. This can be done in multiple ways. Choose one:
- Use 100-helloworld as a base. You only need to install dependencies by using `npm install` and subsequently `npm start`.
- OR (recommended!) : Install Angular CLI and create a project using the command line.
- Directions can be found at <https://cli.angular.io/>.
- Learn to use the commands `ng new`, `ng serve` and `ng generate`. Look up for yourself on how to use these commands.

b) **Goal: write your own component. Use this instead of the default `app.component.ts`.**

- Remove the `<hello-world>` component from your existing app. Then, follow these steps to create your own, new component from scratch:
- **If manually:** Create a new file, for example `\app\new.component.ts`.
- Import the correct dependencies (`import {Component, OnInit} from '@angular/core';`).
- Add an `@Component` annotation, a selector and an HTML-template.
- **If using Angular-CLI:** use the command `ng generate component [cmp-name]` and edit some text inside the generated `.ts` and `.html`-files.
- Edit the Module `app.module.ts`, such that the new component is imported and bootstrapped.
- Edit `index.html`, such that the new selector is being used.
- Run `npm start` to test your new component.

c) **Optional Goal: getting to know TypeScript a bit better**

- Visit [typescriptlang.org](https://typescriptlang.org) and practice creating a class. Type your code in the left pane, look at the generated code in the right pane.
- Define for example a class `Person`, with properties `firstName`, `lastName` en `email`.
- Create an instance of the class (`let person = new Person()`) and log the properties to the console. Use the Run button above the right pane.
- See for yourself for the other examples from the dropdown menu. (like `Types`, `Generics`, `Modules`) to extend your knowledge of TypeScript.
- Visit the link `Documentation`, `Handbook`, `Basic Types` and read what types can be used in TypeScript.
- If time permitting, also look at the other documentation (`Variable Declarations`, `Interfaces`, `Classes`, etc).

- a) **Goal: create properties on your class and bind them to the user interface.**
- Expand your app from the previous lab (Hello World) with a field/property. Bind the property in the template being used.
  - First*, use direct initialization of variables, like `name: string = '<your-name>'`.
  - Second*, use separate declaration and initialize in the constructor. Code can look like:
 

```
name: string;
constructor(){ this.name = 'Peter' }
```
  - Third*, use the (recommended) approach using `ngOnInit()`. Code can look like
 

```
ngOnInit(){ this.name = '<your-name>' }
```
  - Demo code available at /101-databinding.
- b) **Goal: working with arrays of properties and using `*ngFor`.**
- Create an array of properties. Bind them in the template using the directive `*ngFor`.
  - Use TypeScript to explicitly declare the property as an array of strings. Pick one of these alternatives (they both mean the same):
 

```
cities: string[]
cities: Array<string>
```

 Of course you can use other data than cities, for example persons, products, and so on.
  - Demo code available at /101-databinding.
- c) **Goal: create your own Model and use this as a type in your application.**
- Create a Model for the contents of your array. The model consists of an object with one or more properties. See for instance `app/shared/city.model.ts` as an example.
  - Adapt the signature of the array so it looks like `cities: City[]` or `cities: Array<City>`.
  - Rewrite your array, so the content now are properties of type `<YourModel>`.
  - Advanced: instead of using a class for the Model you can also use the TypeScript-construct Interface. Look up for yourself how this can be done.
  - Demo code available at /101-databinding.
- d) **Goal: using `*ngIf`**
- Create a `<div>` on the page that is only shown if your array has three or more objects in it. The code can look like `<div *ngIf="cities.length > 3">...</div>`.
  - Create one more use case of `*ngIf` for yourself.
- e) **Goal: using an external template**
- Edit your component, such that the HTML is now in an external template. In the example code this is in `app/app.html`.
  - Next, use the property `templateUrl` in `@Component` to point at the file. Test if the databinding still works.
  - Demo code available at /101-databinding.

## a) Goal: using event binding

- Add an element with event-binding to the application. For instance, create a button to capture a click event. The code can look like  
`<button (click)="onClick()">...</button>`.
- Call an event handler in the component if the event occurs. For example, write a function `onClick() { alert('message...') }` or show a `console.log()`-text.
- Demo code available at /103-eventbinding.

## b) Optional goal: using other event bindings

- Test other types of DOM-events, for example `blur`, `focus`, `keypress`, `mousemove`, and more. If you need inspiration, see the overview of possible events at mozilla.org (<https://developer.mozilla.org/en-US/docs/Web/Events>).

## c) Optional goal: using @HostListener

- Use the `@HostListener()` decorator in your component to listen to other (non-DOM) events, like networking changes, battery charging change or resize events.
- Show a message in the console or on the component if the event occurs.

## d) Goal: learn local template variables

- Create a text field with a local template variable. The notation can look like  
`<input type="text" #myText>`.
- Pass the variable to an event handler using an event of your liking (for example `click` or `keyup`) and show the value in an `alert()` or `console.log()`.
- Create another textbox on the page. The user can type numbers in the textbox.
- Pass the number to an event handler and add the number to a property `total`. Show the addition of all numbers (i.e. the total value) in the page.
- Remember to use `parseInt()` to convert the stringvalue of the textbox to a number!
- Demo code available at /103-eventbinding.

## e) Goal : creating a simple client sided CRUD application

- Create a simple client-sided CRUD-application: users can add elements to the array (names, cities, products, etc) and remove them from the array.
- Adding can be done by using `ArrayName.push(...)`
- Deleting can be done by using `.indexOf()` and `ArrayName.splice(...)`, OR: using a more reactive approach, by using `.filter()` operator on the array.

## 04 - ATTRIBUTE BINDING AND TWO-WAY BINDING

### a) Goal: getting to know attribute binding

- Create a button on the page. If the button is clicked, a `<div>` with a text is shown.
- If the button is clicked again, the text is hidden.
- Do this by adding a property to the class and assign it to the `[hidden]` property of the div. For example:  

```
<div [hidden] = "myBoolean">...</div>.
```
- Demo code available at `/103-attributebinding`

### b) Optional goal: using other attribute bindings

- If time permitting: create a component with a textbox.
- If the user types an English color in the box and clicks a button, a corresponding `<div>` receives this color as a background color.
- Hint: use `[style.backgroundColor] = "bgCcolor"` on the div. Create a `bgCcolor` property on the class.
- Optional: create a second textbox to set the text/foreground color.
- Advanced: investigate how this works if the color can be picked from a series of radio buttons or from a dropdown list.

### c) Optional goal: using class binding and style binding

- If time permitting: investigate for yourself how the Angular-concepts *class binding* en *style binding* work. Read for example the documentation at <https://angular.io/docs/ts/latest/guide/template-syntax.html#!#other-bindings>.
- Create a component that demonstrates these concepts. Show and explain your code to the teacher or to a colleague.

### d) Goal: using two-way binding with `[(ngModel)]`

- Create a text field in your component that uses two-way binding.
- Use `[(ngModel)]` as a directive on the `<input>` box. Bind the value of the typed text directly to the page.
- Don't forget to import and add `FormsModule` to the `app.module.ts` file!
- Create a copy-function. Create two text boxes on the page. Text that is typed into the first textbox, should also appear in the second textbox.
- Demo code available at `/104-twowaybinding`

**a) Goal: using a service to display data in component/user interface.**

- While working, you have developed some components, displaying data. Move this data from the component class to a service.
- Create a new file (for example `city.service.ts`) and import the correct annotations. Use `@Injectable()` to decorate the service.
- Write a `getCities()` method and optional methods to add or delete cities - or the data you are working with, of course.
- Inject your service in the module. Remember to use the property `[providers]` in the `@NgModule`-annotation.
- Import your service in the component and instantiate in the constructor. The code will look like `constructor(private cityService: CityService) { ... }`. Test your application.
- Demo code available at `/200-services-static`.

**b) Optional goal: provide other data via service.**

- Create another service, providing different data (for example your favorite food, sports teams, hobbies, etc).
- Follow the same steps as above, consuming the data from the service in your component.
- This is an illustration of the fact that you can inject multiple services into the same component.

**c) Goal: use a service to fetch contents of a json file asynchronous.**

- Create a `.json` file with data and load this data in your application using an asynchronous service call (for example: `cities.json`). Remember the following steps:
- Import and inject `HttpClientModule` in `app.module.ts`.
- Inject `HttpClient` in the service;
- Adapt your `get`-method. For example, `getCities()` now has this body:  
`return this.http.get<City[]>('app/cities.json');`
- Adapt your component, to use a `.subscribe()` method to retrieve and unwrap the values from the service. Our `subscribe` block can look like  
`.subscribe(cityData => this.cities = cityData)`
- Demo code available at `/201-services-http`.

**d) Optional goal: learn to work with other RxJs methods.**

- Use a `.pipe()` method after your `.get()`-function. Try different operators, like for example: `map()`, `delay()`, `retry()` among others.
- Demo code available at `/202-services-rxjs`.
- If time permitting: read the Observable Cheat Sheet at [onehungrymind.com/observable-cheat-sheet/](http://onehungrymind.com/observable-cheat-sheet/). See what observables can do for you and how you can transform the data stream to be directly consumed by your components.

**e) Goal : using a live API**

- See how a service connects to a real backend by running and studying `/210-services-live`. Look at:
- ...how the service connects to the backend by using the URL;
- ...how the results are mapped and unwrapped from json using `map()`;
- Having studied the example, build an app on your own! You can of course use the Open Movie Database API, but there are a lot of other API's available.
- See for example [openweathermap.org/API](http://openweathermap.org/API), or <https://pokeapi.co>
- See also the textfile `JavaScript APIs.txt` and even more API's at <https://github.com/toddmotto/public-apis>.

- Remember to use `HttpClient`.
- Always read the API documentation of the external API **very carefully!**
- f) **Goal : sending POST requests to a backend**
  - See how a service sends POST requests to a real backend by running and studying `/212-post-demo`. Look at:
    - ...how the component now directly connects to the backend by using the URL;
    - ...how the data attribute is built from the dummy `email` and `password` fields;
    - ...how the `headers` field is composed and added to the POST request.
  - Having seen this, go ahead and create your own POST-demo, using <http://regres.in>.
  - There are POST-endpoints available for dummy creating records, dummy registration and dummy login successful/unsuccessful. Pick one and assemble a component talking to this backend.
  - Demo code available at `/212-post-demo`.

## 06 - APPLICATIONS WITH MULTIPLE COMPONENTS

- a) **Goal: creating a detail component showing the selected data.**
- Create a new application, or use your application from previous exercises.
  - Add a detail component. Details are shown after a mouseclick on the list in the parent component.
  - Follow the steps (4 steps) from the presentation, to add the DetailComponent to your app. These are:
    1. Create a separate detail component, for instance `city.detail.ts`.
    2. Inject detail component in `app.module.ts`.
    3. Encapsulate detail component in HTML of parent component by using its selector, for instance `<city-detail></city-detail>`. Also alter component so that detail component is loaded after mouseclick on the list.
    4. Run the app and look if detail component appears after clicking
  - Demo code available at `/300-components`.
- b) **Goal: using `@Input ( )` annotation to transfer data from parent to child component.**
- Add/enhance the click handler in your parent component: make sure the current city (or again: the data you are working with) is transferred to the component (i.e. `(click)=getCity(city)`).
  - In your event handler, set a property. For instance `this.currentCity = city`.
  - Make sure to transfer the `currentCity` property to the child component. Use a notation like `[city]="currentCity"` in the template of the parent component.
  - Annotate the detail component with `@Input ( )` decorator. Don't forget the `( )` after `@Input`. This way, the `City` object is passed into the detail component and shown in the user interface.
  - Demo code available at `/301-components-inputs`.
- c) **Goal: using `@Output` annotation to transfer data from child to parent component.**
- Import `@Output ( )` service and `EventEmitter` in the child component using `import {..., Output, EventEmitter} from '@angular/core';`
  - Enhance the class with `@Output ( )` decorator and define a new `EventEmitter` (see `city.detail.ts` in example code).
  - Write a click handler that emits a new event. In the example code a `number` is thrown, but you can throw anything you like.
  - Capture the event in the parent component by using event binding syntax like `(eventName)="handleEvent(event)`.
  - Write an event handler in the parent component to handle the event and let the application react accordingly.
  - Demo code available at `/302-components-outputs`.
- d) **Optional goal: create a complete application:**
- If time permitting: create a simple eCommerce application, implementing the following requirements:
    - A Store. Write a service for a store that delivers 4 or 5 products. (This can be static data).
    - A master component. Show a list of items in the store, retrieved by your service.
    - A detail component. Clicking a product shows details of the product in its own component.
    - A Shopping Cart. The user can place the product in his shopping cart (which of course is another component). The contents of the shopping cart are visible in user interface.
    - An "Order" button. If clicked, show the contents of the shopping cart and calculate the total price.

## a) Goal: install routing in your app.

- Adapt the application from your previous exercises, or create a new application, using routing. These are the requirements:
- Add the `<base href="/">` tag to your `index.html`.
- Create a routing table in a new file called `app.routes.ts`. Make sure to export a constant that is an array with routing properties.
- Import your routes in `app.module.ts`. Don't forget to also import `RouterModule`.
- Make sure the application has a `mainComponent` (also known as: `rootComponent`). This component shows the main menu and has a `<router-outlet></router-outlet>`.
- Adapt the bootstrapper `main.ts`, such that now the new `mainComponent` is loaded/bootstrapped.
- Adapt `index.html`, such that the correct selector is loaded.
- Create the (new) component for every route you designed. This can be `EditComponents`, `addComponent`, `AboutUsComponent`, `ContactComponent`, and so on.
- Test and make sure the different components are loaded when they are selected in the main menu.
- Demo code available at `/400-router`.

## b) Optional Goal – using routing with Angular-CLI

- Create a new project with the Angular-CLI, and use the `--routing` flag to add routing to the project.
- Study the separate routing module that the CLI created and see how it is integrated in the app.
- Add one or two new components (and routes) to the application and show them via a main menu inside `<router-outlet>` in `AppComponent.ts`.

## c) Goal: use routing parameters

- Adapt your `app.routes.ts`, such that now a route with parameter is available. This can be written like  

```
{path: 'detail/:id', component: CityDetailComponent}
```
- Add a new component, for instance `city.detail.component.ts`. Make sure to import `ActivatedRoute` into this component.
- Instantiate a private route in the constructor, of type `ActivatedRoute`. The code can look like  

```
constructor(private route: ActivatedRoute) { ... }
```
- Add your detail component to the Module, so it is available.
- Adapt the master page, to point to the detail route. Hyperlinks can look like  

```
<a [routerLink]="['/detail', city.id]"> {{ city.name }}</a>
```
- Save and test your app.
- Demo code available at `labs/401-router-parameter`.

## d) Optional goal: securing parts of your application with RouteGuards.

- If time permitting: add some guards to your application. For instance, the `CanActivate` guard or `CanDeactivate` guard.
- Write a *guard as a function*, using the `provide:` and `useValue:` properties of the `providers: []` section in `app.module.ts`.
- Remember to use/add the guard token in `app.routes.ts`.
- Write a guard as a class, using the `CanActivate` interface. See for instance `canActivateViaAuthGuard.ts` as an example.
- Again, don't forget to add the guard in `app.routes.ts`.



- Try to let the example `authService` return true or false and see what happens. Can you still navigate to the route?
- Demo code available at [/402-router-guards](#).

**a) Goal: build a template driven form**

- Create a simple HTML5 form in a component, or use a form from an earlier exercise (for example the login form from 11-post-demo).
- Add the local template variable `#myForm="ngForm"` to the `<form>` tag.
- Add the directives `ngModel` to the separate form fields. You don't need two-way databinding with `[( )]`.
- Write for example `myForm.value` to the user interface, or show the contents of the form in an alert (or in the console) when a button is clicked.
- Demo code available at `/500-forms-template-driven, Component 1`.

**b) Goal: address individual controls inside the form and add HTML5 validators.**

- Assign a local template variable to the form fields.
- Bind `ngModel` to the local template variable. The code can look like `#email="ngModel"`
- Retrieve the values from the local template variable and show them in the user interface, for example its value and its validity.
- Add the HTML5 attribute `required` to the form fields and see how this affects the state of the form field. Write its validity to the user interface.
- Demo code available at `/500-forms-template-driven, Component 2`.

**c) Goal: combining individual form fields to an ngModelGroup**

- Add some field to the form (for example some extra text fields or checkboxes).
- Groep them inside a `<div>`, assign the `<div>` the directive `ngModelGroup`. The code can look like   
`<div ngModelGroup="customer" #customer="ngModelGroup">`
- Run the code and identify the model group in the returned form value object.
- Optional: set the value of a form field from inside your class, by using the local template variable and bind to `[ngModel]`.
- Demo code available at `/500-forms-template-driven, Component 3`.

**d) Goal: submitting template driven forms**

- Add a submit button to the form.
- Make sure the submit button is only active when the form as a whole is valid. Your code can look like   
`<button type="submit" (click)="onSubmit(myForm)" [disabled]="!myForm.valid"> ... </button>`
- Demo code available at `/500-forms-template-driven, Component 4`.

**e) Optional goal: working with model driven forms**

- Start with a simple form, for example build a form on your own, or use the dummy login form from `/212-post-demo`.
- Import `ReactiveFormsModule` into your `app.module.ts`.
- Add the `[formGroup]="..."` directive to the `<form>` tag, add `formControlName="..."` to the individual controls.
- Import `FormGroup` and `FormBuilder` into your class and build the form, based on the layout of your HTML.
- Submit the form and write the value to an alert box or to the console.
- Demo code available at `/501-forms-model-driven, Component 1 and Component 2`.