

Creating a 3D Scene using OpenGL

Aim

- To write a C++ program using Opengl to draw at least four 3D objects.
- Apply lighting and texture and render the scene.
- Apply transformations to create a simple 3D animation

Algorithm

- Use glBindTexture to bind the texture to the 3d object
- Use glShadeMode select flat or smooth shading.
- The glMaterialfv function assigns values to material parameters
- The glLightfv function sets the value or values of individual light source parameters.
- glGenTexture specifies an array in which the generated texture names are stored

Program

ex10.cpp

```
#include <iostream>
#include <cstring>
#include <GL/glut.h>
#include <math.h>

using namespace std;

int INC = 1;
void initialize(void)

{

    glClearColor(1.0, 1.0, 1.0, 0.0);
```

UCS1712 - Graphics and Multimedia Lab

Ex. No: 10
Date : 10/11/2022

Name: Jagadish R
Reg. no: 195001039

```
glShadeModel(GL_SMOOTH);
GLfloat light_diffuse[] = {1.0, 1.0, 1.0, 1.0};
GLfloat light_position[] = {0, 0, 1, 0};

glLightfv(GL_LIGHT0, GL_DIFFUSE, light_diffuse);
glLightfv(GL_LIGHT0, GL_POSITION, light_position);

glEnable(GL_LIGHTING);

glEnable(GL_LIGHT0);

glEnable(GL_DEPTH_TEST);
}

GLuint LoadTexture(const char *filename)
{

    GLuint texture;
    int width, height;

    unsigned char *data;

    FILE *file;

    file = fopen(filename, "rb");

    if (file == NULL)
        return 0;

    width = 1024;

    height = 512;
```

UCS1712 - Graphics and Multimedia Lab

Ex. No: 10
Date : 10/11/2022

Name: Jagadish R
Reg. no: 195001039

```
data = (unsigned char *)malloc(width * height * 3); // int size =
fseek(file,);

fread(data, width * height * 3, 1, file);

fclose(file);

for (int i = 0; i < width * height; ++i)
{
    int index = i * 3;

    unsigned char B, R;
    B =

        data[index];

    R = data[index + 2];

    data[index] = R;

    data[index + 2] = B;
}

glGenTextures(1, &texture);

glBindTexture(GL_TEXTURE_2D, texture);

glTexEnvf(GL_TEXTURE_ENV, GL_TEXTURE_ENV_MODE, GL_MODULATE);

glTexParameterf(GL_TEXTURE_2D,

                GL_TEXTURE_MIN_FILTER,
```

UCS1712 - Graphics and Multimedia Lab

Ex. No: 10
Date : 10/11/2022

Name: Jagadish R
Reg. no: 195001039

```
        GL_LINEAR_MIPMAP_NEAREST);

glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER,

               GL_LINEAR);
glTexParameterf(GL_TEXTURE_2D,

               GL_TEXTURE_WRAP_S, GL_REPEAT);

glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T,

               GL_REPEAT);
gluBuild2DMipmaps(GL_TEXTURE_2D, 3, width, height,

               GL_RGB, GL_UNSIGNED_BYTE, data);

free(data);
return texture;
}

void drawScene(int state)

{
    if (state == 0)
        INC = 1;

    else if (state == 10)
        INC = -1;

    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
    GLuint texture;
    texture = LoadTexture("silver.jpg");
    glBindTexture(GL_TEXTURE_2D, texture);
```

UCS1712 - Graphics and Multimedia Lab

Ex. No: 10
Date : 10/11/2022

Name: Jagadish R
Reg. no: 195001039

```
glLoadIdentity();
gluLookAt(0.0, 1.0, 7.0, 0.0, 0.0, 0.0, 0.0, 1.0, 0.0);
glMatrixMode(GL_MODELVIEW);
glPushMatrix();
GLfloat cube_color[] = {1, 0.5, 0.0, 0.0};
glMaterialfv(GL_FRONT, GL_DIFFUSE, cube_color);
glScalef(4, 1.5, 1.0);
glTranslatef(0.2, -1.0, 0.0);
glutSolidCube(1.0);
glPopMatrix();
glPushMatrix();
GLfloat torus_color[] = {0.59, 0.1, 0.55, 1.0};
glMaterialfv(GL_FRONT, GL_DIFFUSE, torus_color);
glTranslatef(-3, -1.5, 0.0);
glutSolidTorus(0.3, 0.7, 10, 10);
glPopMatrix();
glPushMatrix();
glEnable(GL_TEXTURE_2D);
GLfloat teapot_color[] = {0.7, 0.7, 0.7, 0.0};
GLfloat mat_shininess[] = {100};
glMaterialfv(GL_FRONT, GL_DIFFUSE, teapot_color);
glMaterialfv(GL_FRONT, GL_SHININESS, mat_shininess);
glRotatef(45, 0, 0, 1);
glTranslatef(-1.2, 0.8, 0.0);
glutSolidTeapot(0.7);
glDisable(GL_TEXTURE_2D);
glPopMatrix();
glPushMatrix();
GLfloat ball_color[] = {0.0, 1, 1, 1.0};
glMaterialfv(GL_FRONT, GL_DIFFUSE, ball_color);
glTranslatef(2, 2.1 - 0.25 * state, 0);
glutSolidSphere(0.5, 10, 10);
glPopMatrix();
glutSwapBuffers();
```

UCS1712 - Graphics and Multimedia Lab

Ex. No: 10
Date : 10/11/2022

Name: Jagadish R
Reg. no: 195001039

```
        glutTimerFunc(1000 / 60, drawScene, state + INC);
    }

void reshape(int w, int h)

{
    glViewport(0, 0, (GLsizei)w, (GLsizei)h);
    glMatrixMode(GL_PROJECTION);
    glLoadIdentity();
    gluPerspective(75, 1, 1, 20);
}




void sceneDemo()
{
    glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
    glutTimerFunc(1000 / 60, drawScene, 0);
}

int main(int argc, char **argv)
{
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_DOUBLE | GLUT_RGB);
    glutInitWindowSize(500, 500);
    glutCreateWindow("3D Scene");
    initialize();
    glutDisplayFunc(sceneDemo);
    glutReshapeFunc(reshape);
    glutMainLoop();
    return 0;
}
```

Ex. No: 10
Date : 10/11/2022

Name: Jagadish R
Reg. no: 195001039

Output



Learning Outcomes

- Learned to apply textures, lighting 3d objects
- Learned to create a scene using three 3d objects