C Coding Standard

- The following documentation and comment styles are to be used for the code submitted by the teams.
- Replace all the ***<Description>*** tags from the comments below to add appropriate content for your application.

1. File Level Comments

Each user's code file should start with **File Level** comments in the format as follows:

```
/*
* Team Id:          <Team Id>
* Author List:      <Name of the team members who worked on this function
*                   (Comma separated eg. Name1, Name2)>
* Filename:         <Filename>
* Theme:            <Theme name -- Specific to eYRC>
* Functions:        <Comma separated list of Functions defined in this file>
* Global Variables: <List of global variables defined in this file, None if no global
*                    variables>
*/
```

2. Function Level Comments

Each function should have the following comment section before it:

```
/*
* Function Name:<Function Name>
* Input:          <Inputs (or Parameters) list with description if any>
* Output:         <Return value with description if any>
* Logic:          <Description of the function performed and the logic used
*                  in the function>
* Example Call:   <Example of how to call this function>
 */
```

3. Variable Comments

In general the variable/function names should be descriptive enough to give a good idea of what the variable is used for.,For example, variable names like *'black_line_threshold_value'*, *'left_motor_turn_right'* are preferable and makes your code readable. Variable names like *'a', 'b'* and *'temp'* are not acceptable variable names.

In some cases, variable names might require some description for which the following format can be used:

```
// Variable Name: Description of the variable and the range of expected values of the variable.
```

4. Implementation Comments

In your implementation/actual code, you should have comments in tricky, non-obvious, interesting, or important parts of the code.

The comments can be of the format as below:

```
// Describe what the code below is doing
```

An Illustrative Example:

We provide sample comments in a rudimentary program that outputs the Fibonacci Series (For more information on Fibonacci Series visit: http://en.wikipedia.org/wiki/Fibonacci_number). Please note that this is not the complete and perfect example of generating Fibonacci Numbers but acts as a simple way to illustrate the coding style and comments explained above.

```
/*
 * Team Id: 10000
 * Author List: e-Yantra Team
 * Filename: fibonacci.c
 * Theme: eYRC Specific Theme
 * Functions: print_fibonacci_series(int) , main()
 * Global Variables: NONE
 */

#include<stdio.h>


/*
 * Function Name:       print_fibonacci_series
 * Input:               num_elements -> integer which stores the number of elements of
 *                      the fibonacci series to be printed
 * Output:              prints the first num_elements of the fibonacci series
 * Logic:               The next element of the Fibonacci series is given by
 *                      next = current_element + prev_element
 *                      The code loops for num_elements and prints out the next
 *                      element
 * Example Call:        print_fibonacci_series(10);
 *
 */
void print_fibonacci_series(int num_elements) {
        int first = 0, second = 1, next;
        printf("First %d terms of Fibonacci series are :-\n", num_elements);

        //counter: will iterate from 0 to (num_elements - 1)
        for ( int counter = 0 ; counter < num_elements ; counter++ ) {
                if ( counter <= 1 )
                        next = counter;
                else {
//The next element is equal to the sum of the current  element (second variable) and the previous element (first variable)
                        next = first + second;
```

```
// first element becomes the second element and second element becomes the next element for the next loop iteration
                        first = second;
                        second = next;
                }
                        printf("%d\n", next);
        }
}

/*
 * Function Name:       main
 * Input:               None
 * Output:              int to inform the caller that the program exited correctly or
 *                      Incorrectly (C code standard)
 * Logic:               Ask the user to input the number of elements required from the
 *                      Fibonacci Series and call the function  print_fibonacci_series
 * Example Call:        Called automatically by the Operating System
 *
 */
int main() {
        int num_elements;

        //Ask the user to input the number of elements required
        printf("Enter the number of terms\n");
        scanf("%d",&num_elements);
        //Call the function to print the first num_elements of the Fibonacci Series
        print_fibonacci_series(num_elements);
        return 0;
}
```

```
/*
 *      Following a coding style might look to be tedious at first but is one of the most important
 *      thing to be done while developing any piece of code. This ensures that it is readable so
 *      that others can understand what your code is doing. Even you yourself may find it useful
 *      after some time!
 */
```

"Any fool can write code that a computer can understand. Good programmers write code that humans can understand." - Martin Fowler

---

"Programs must be written for people to read, and only incidentally for machines to execute." - Hal Abelson & Gerald Jay Sussman

---

"Always code as if the guy who ends up maintaining your code will be a violent psychopath who knows where you live." - Rick Osborne