```
****************************************
Report : timing
        -path full
        -delay max
        -max_paths 1
Design : fifo
Version: I-2013.12-SP5-4
Date   : Mon Apr 29 23:49:37 2019
****************************************

Operating Conditions: TYPICAL   Library: saed90nm_typ
Wire Load Model Mode: enclosed

  Startpoint: r2w1/r2wsync_ff2_reg[3]
              (rising edge-triggered flip-flop clocked by clk_in)
  Endpoint: w1/wptr_reg[0]
            (rising edge-triggered flip-flop clocked by clk_in)
  Path Group: clk_in
  Path Type: max

  Des/Clust/Port     Wire Load Model       Library
  ------------------------------------------------
  fifo               280000                saed90nm_typ
  write_logic_depth7_width8
                     8000                  saed90nm_typ

  Point                                                   Incr       Path
  ------------------------------------------------------------------------
---
  clock clk_in (rise edge)                                0.00       0.00
  clock network delay (ideal)                             0.00       0.00
  r2w1/r2wsync_ff2_reg[3]/CLK (DFFARX1)                   0.00       0.00
r
  r2w1/r2wsync_ff2_reg[3]/Q (DFFARX1)                     0.19       0.19
f
  r2w1/r2wsync_ff2[3] (sync_rd2wr_width8_depth7)          0.00       0.19
f
  w1/r2wsync_ff2[3] (write_logic_depth7_width8)           0.00       0.19
f
  w1/U85/Q (XNOR2X2)                                      0.64       0.83
f
  w1/U77/Q (AND4X1)                                       0.13       0.96
f
  w1/U70/Q (AND4X1)                                       0.11       1.07
f
  w1/U69/QN (NAND2X0)                                     0.07       1.14
r
  w1/U65/Q (AND2X1)                                       0.10       1.24
r
  w1/U67/Q (OA21X1)                                       0.09       1.33
r
  w1/U58/Q (AO22X1)                                       0.10       1.43
r
```

```
  w1/wptr_reg[0]/D (DFFARX1)                              0.03       1.46
r
  data arrival time                                                  1.46

  clock clk_in (rise edge)                                1.00       1.00
  clock network delay (ideal)                             0.00       1.00
  w1/wptr_reg[0]/CLK (DFFARX1)                            0.00       1.00
r
  library setup time                                     -0.09       0.91
  data required time                                                 0.91
  ------------------------------------------------------------------------
---
  data required time                                                 0.91
  data arrival time                                                 -1.46
  ------------------------------------------------------------------------
---
  slack (VIOLATED)                                                  -0.55


  Startpoint: w2r1/w2rsync_ff2_reg[7]
              (rising edge-triggered flip-flop clocked by clk_out)
  Endpoint: r1/rptr_reg[4]
            (rising edge-triggered flip-flop clocked by clk_out)
  Path Group: clk_out
  Path Type: max

  Des/Clust/Port     Wire Load Model       Library
  ------------------------------------------------
  fifo               280000                saed90nm_typ
  read_logic_depth7_width8
                     8000                  saed90nm_typ

  Point                                                   Incr       Path
  ------------------------------------------------------------------------
---
  clock clk_out (rise edge)                               0.00       0.00
  clock network delay (ideal)                             0.00       0.00
  w2r1/w2rsync_ff2_reg[7]/CLK (DFFARX1)                   0.00       0.00
r
  w2r1/w2rsync_ff2_reg[7]/Q (DFFARX1)                     0.19       0.19
f
  w2r1/w2rsync_ff2[7] (sync_wr2rd_width8_depth7)          0.00       0.19
f
  r1/w2rsync_ff2[7] (read_logic_depth7_width8)            0.00       0.19
f
  r1/U6/Z (NBUFFX4)                                       0.75       0.94
f
  r1/U4/Q (XNOR2X1)                                       0.19       1.13
r
  r1/U13/QN (NAND2X0)                                     0.07       1.20
f
  r1/U12/QN (NOR2X0)                                      0.09       1.29
r
```

```
  r1/U59/QN (NOR3X0)                                      0.11       1.39
f
  r1/U58/Q (AO21X1)                                       0.11       1.50
f
  r1/U55/QN (NOR2X0)                                      0.09       1.59
r
  r1/U53/Q (OA21X1)                                       0.11       1.70
r
  r1/U50/Q (AO22X1)                                       0.12       1.82
r
  r1/rptr_reg[4]/D (DFFARX1)                              0.03       1.85
r
  data arrival time                                                  1.85

  clock clk_out (rise edge)                               2.00       2.00
  clock network delay (ideal)                             0.00       2.00
  r1/rptr_reg[4]/CLK (DFFARX1)                            0.00       2.00
r
  library setup time                                     -0.09       1.91
  data required time                                                 1.91
  ------------------------------------------------------------------------
---
  data required time                                                 1.91
  data arrival time                                                 -1.85
  ------------------------------------------------------------------------
---
  slack (MET)                                                        0.06


1
```