

in the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to in sufficient to the culculation of results due to the culculation of the culculation of results due to the culculation of This errors can't be treated mothematically & not possible to eliminate Completely but these errors can be minim by taken precoutions mound all put baseline are small By taking Care of reading and recording in the cooland tion By taking atleast 3 or more readings preteriably by Dystematic periors or prist -These errors are mainly due to short coming of instruments characteristic of material used in instrument envinormental These are further dassified as: Instrumentalillos 3110 of Instrument, misuse of instrument These error can be minimized by selecting a surtable instrument for a Suitable application -> Applying the Conection factor after finding the amount Meccument of instrumental error. to the instruments such and temperature the champes external field magnetic for electrostatic fields, hundity or These teriors can be minimized by using attractioning temperature enclosures to have " temperature enclosures to beep the Surrounding Conditions Constant.

Use of magnetic or electrostatic shields to reduce the effect of external fields in mitalians who is -> Hermitically Celling of Certain Components to reduce although the effect of humidity & dust 1 1 has some and to climinate Complete Observational error These are introduced by the human mituring mit The most Common error is parallexerror while reading a meter. these can be reduced by using instruments with minor & EnHe edge painter -> Using an instrument with digital display Random error: These are due to unknown causes, even the instrument is calculated accurately then these errors are called trandom error la lead -> These Connot be determined of they follows the low probablity so some instrument, load The Only way to reduce these errors is by taking more observations it statistically analysis uppich tragives the best approximation

