

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Friday, 29 November 2024, 9:37 AM
Duration	24 days 7 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a,b;
4     scanf("%d%d",&a,&b);
5     if(a%10==b%10)
6     {
7         printf("true");
8     }
9     else
10    {
11        printf("false");
12    }
13    return 0;
14 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

Flag question

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, *n*, perform the following conditional actions:

- If *n* is odd, print *Weird*
- If *n* is even and in the inclusive range of 2 to 5, print *Not Weird*
- If *n* is even and in the inclusive range of 6 to 20, print *Weird*
- If *n* is even and greater than 20, print *Not Weird*

Complete the stub code provided in your editor to print whether or not *n* is weird.

Input Format

A single line containing a positive integer, *n*.

Constraints

- $1 \leq n \leq 100$

print **Not Weird**

- If n is even and in the inclusive range of 6 to 20, print **Weird**

- If n is even and greater than 20, print **Not Weird**

Complete the stub code provided in your editor to print whether or not n is weird.

Input Format

A single line containing a positive integer, n .

Constraints

- $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a;
4     scanf("%d",&a);
5     if(a%2==1)
6     {
7         printf("Weird");
8     }
9     else if(a>2 || a<5)
10    {
11        printf("Not Weird");
12    }
13    else if(a>6 || a<20)
14    {
15        printf("Weird");
16    }
17    else
18    {
19        printf("Not Weird");
20    }
21    return 0;
22 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a;
4     scanf("%d",&a);
5     if(a%2==1)
6     {
7         printf("Weird");
8     }
9     else if(a>2 || a<5)
10    {
11        printf("Not Weird");
12    }
13    else if(a>6 || a<20)
14    {
15        printf("Weird");
16    }
17    else
18    {
19        printf("Not Weird");
20    }
21    return 0;
22 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00

Flag
question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a , b , and c . They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a,b,c,d;
4     scanf("%d%d%d",&a,&b,&c);
5     d=a*a+c*c;
6     if((b*b==a*a+c*c)|| (a*a==b*b+c*c)|| (c*c==a*a+b*b))
7     {
8         printf("yes");
9     }
10    else if(d!=c*c)
11    {
12        printf("no");
13    }
14    return 0;}
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review