

Rajalakshmi Engineering College

Name: Karthik V
Email: 240701234@rajalakshmi.edu.in
Roll no: 240701234
Phone: 8015689541
Branch: REC
Department: I CSE FC
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 12

Section 1 : MCQ

1. What is the value of x in the following program?

```
x = int(43.55+2/2)
print(x)
```

Answer

44

Status : Correct

Marks : 1/1

2. Which of the following can convert the string to a float number?

Answer

```
float(str)
```

Status : Correct

Marks : 1/1

3. Which of the following represents the bitwise XOR operator?

Answer

`^`

Status : Correct

Marks : 1/1

4. Which of the following expressions results in an error?

Answer

`int('10.8')`

Status : Correct

Marks : 1/1

5. Evaluate the expression given below if A= 16 and B = 15

`A % B // A`

Answer

1

Status : Wrong

Marks : 0/1

6. What will be the output of the following code?

```
X = 2+9*((3*12)-8)/10
print(X)
```

Answer

27.2

Status : Correct

Marks : 1/1

7. What will be the output of the following code?

```
x = int(34.56 - 2 * 2)
print(x)
```

Answer

30

Status : Correct

Marks : 1/1

8. Which of the following is an example of the type casting?

Answer

All of the above

Status : Correct

Marks : 1/1

9. What does 3^4 evaluate to?

Answer

7

Status : Correct

Marks : 1/1

10. What is the value of the following expression?

$8/4/2$, $8/(4/2)$

Answer

(1.0,4.0)

Status : Correct

Marks : 1/1

11. What is the value of the following expression?

$\text{float}(22//3+3/3)$

Answer

8.0

Status : Correct

Marks : 1/1

12. Which of the following operators has its associativity from right to left?

Answer

//

Status : Wrong

Marks : 0/1

13. The value of the expressions $4/(3*(2-1))$ and $4/3*(2-1)$ is the same. True or False?

Answer

False

Status : Wrong

Marks : 0/1

14. Which of the following functions converts a string to a float in Python?

Answer

float(x)

Status : Correct

Marks : 1/1

15. What is used to concatenate two strings in Python?

Answer

+ operator

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Karthik V
Email: 240701234@rajalakshmi.edu.in
Roll no: 240701234
Phone: 8015689541
Branch: REC
Department: I CSE FC
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_COD

Attempt : 1
Total Mark : 5
Marks Obtained : 5

Section 1 : Coding

1. Problem Statement

A company has hired two employees, Alice and Bob. The company wants to swap the salaries of both employees. Alice's salary is an integer value and Bob's salary is a floating-point value.

Write a program to swap their salaries and print the new salary of each employee.

Input Format

The first line of input consists of an integer N, representing Alice's salary.

The second line consists of a float value F, representing Bob's salary.

Output Format

The first line of output displays "Initial salaries:"

The second line displays "Alice's salary = N", where N is Alice's salary.

The third line of output displays "Bob's salary = F", where F is Bob's salary.

After a new line space, the following line displays "New salaries after swapping:"

The next line displays "Alice's salary = X", where X is the swapped salary.

The last line displays "Bob's salary = Y", where Y is the swapped salary.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10000

15400.55

Output: Initial salaries:

Alice's salary = 10000

Bob's salary = 15400.55

New salaries after swapping:

Alice's salary = 15400.55

Bob's salary = 10000

Answer

You are using Python

```
a=int(input())
```

```
b=float(input())
```

```
print("Initial salaries:\nAlice's salary = ",a)
```

```
print("Bob's salary = ",b)
```

```
c=b
```

```
b=a
```

```
a=c
```

```
print("\nNew salaries after swapping:\nAlice's salary = ",a)
```

```
print("Bob's salary = ",b)
```

Status : Correct

Marks : 1/1

2. Problem Statement

Quentin, a mathematics enthusiast, is exploring the properties of numbers. He believes that for any set of four consecutive integers, calculating the average of their fourth powers and then subtracting the product of the first and last numbers yields a constant value.

To validate his hypothesis, check if the result is indeed constant and display.

Example:

Input:

5

Output:

Constant value: 2064.5

Explanation:

Find the Average:

Average: $(625 + 1296 + 2401 + 4096)/4 = 2104.5$

Now, we calculate the product of a and $(a + 3)$:

Product = $5 \times (5 + 3) = 5 \times 8 = 40$

Final result: $2104.5 - 40 = 2064.5$

Input Format

The input consists of an integer a , representing the first of four consecutive integers.

Output Format

The output displays "Constant value: " followed by the computed result based on Quentin's formula.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

Output: Constant value: 2064.5

Answer

```
# You are using Python
a=int(input())
b=a**4+(a+1)**4+(a+2)**4+(a+3)**4
c=a*(a+3)
b=b/4
print("Constant value: ",b-c)
```

Status : Correct

Marks : 1/1

3. Problem Statement

Bob, the owner of a popular bakery, wants to create a special offer code for his customers. To generate the code, he plans to combine the day of the month with the number of items left in stock.

Help Bob to encode these two values into a unique offer code.

Note: Use the bitwise operator to calculate the offer code.

Example

Input:

15

9

Output:

Offer code: 6

Explanation:

Given the day of the month 15th day (binary 1111) and there are 9 items

left (binary 1001), the offer code is calculated as 0110 which is 6.

Input Format

The first line of input consists of an integer D, representing the day of the month.

The second line consists of an integer S, representing the number of items left in stock.

Output Format

The output displays "Offer code: " followed by an integer representing the encoded offer code.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 15

9

Output: Offer code: 6

Answer

```
# You are using Python
a=int(input())
b=int(input())
print("Offer code: ",a^b)
```

Status : Correct

Marks : 1/1

4. Problem Statement

A science experiment produces a decimal value as the result. However, the scientist needs to convert this value into an integer so that it can be used in further calculations.

Write a Python program that takes a floating-point number as input and converts it into an integer.

Input Format

The input consists of a floating point number, F.

Output Format

The output prints "The integer value of F is: {result}", followed by the integer number equivalent to the floating point number.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10.36

Output: The integer value of 10.36 is: 10

Answer

```
# You are using Python
a=float(input())
print("The integer value of ",a,"is: ",int(a))
```

Status : Correct

Marks : 1/1

5. Problem Statement

In a family, two children receive allowances based on the gardening tasks they complete. The older child receives an allowance rate of Rs.5 for each task, with a base allowance of Rs.50. The younger child receives an allowance rate of Rs.3 for each task, with a base allowance of Rs.30.

Your task is to calculate and display the allowances for the older and younger children based on the number of gardening tasks they complete, along with the total allowance for both children combined.

Input Format

The first line of input consists of an integer n, representing the number of chores completed by the older child.

The second line consists of an integer m, representing the number of chores

completed by the youngest child.

Output Format

The first line of output displays "Older child allowance: Rs." followed by an integer representing the allowance calculated for the older sibling.

The second line displays "Younger child allowance: Rs." followed by an integer representing the allowance calculated for the youngest sibling.

The third line displays "Total allowance: Rs." followed by an integer representing the sum of both siblings' allowances.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10

5

Output: Older child allowance: Rs.100

Younger child allowance: Rs.45

Total allowance: Rs.145

Answer

You are using Python

```
a=int(input())
```

```
b=int(input())
```

```
a=50+(a*5)
```

```
b=30+(b*3)
```

```
print("Older child allowance: Rs.",a)
```

```
print("Younger child allowance: Rs.",b)
```

```
print("Total allowance: Rs.",a+b)
```

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: Karthik V
Email: 240701234@rajalakshmi.edu.in
Roll no: 240701234
Phone: 8015689541
Branch: REC
Department: I CSE FC
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23221_Python Programming

REC_Python_Week 1_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 20

Section 1 : Coding

1. Problem Statement

Alex is an air traffic controller who needs to record and manage flight delays efficiently. Given a flight number, the delay in minutes (as a string), and the coordinates of the flight's current position (as a complex number),

Help Alex convert and store this information in a structured format.

Input Format

The first line of input consists of an integer N, representing the flight number.

The second line consists of a string representing the delay in minutes.

The third line consists of two floats separated by a space, representing the real and imaginary parts of the complex number for the flight's position.

Output Format

The first line of output displays the complex number.

The second line displays a string with the flight number, delay, and the real and imaginary parts of the complex number, separated by commas.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 12345

30.5

12.3 45.6

Output: (12.3+45.6j)

12345, 30.5, 12.3, 45.6

Answer

```
# You are using Python
```

```
a=int(input())
```

```
b=(input())
```

```
c,d=map(float,(input()).split())
```

```
complex(c)
```

```
if d >=0:
```

```
    print("(","c,","+",d,"j)")
```

```
else:
```

```
    print("(","c,d,"j)")
```

```
print(a, b, c, d,sep=",")
```

Status : Correct

Marks : 10/10

2. Problem Statement

John is developing a financial application to help users manage their investment portfolios. As part of the application, he needs to write a program that receives the portfolio's main value and the values of two specific investments as inputs. The program should then display these values in reverse order for clear visualization.

Help John achieve this functionality by writing the required program.

Input Format

The first line of input consists of a float, representing the first investment value.

The second line of input consists of a float, representing the second investment value.

The third line of input consists of an integer, representing the portfolio ID.

Output Format

The first line of output prints "The values in the reverse order:".

The second line prints the integer, representing the portfolio ID.

The third line prints the second float, representing the second investment value.

The fourth line prints the first float, representing the first investment value.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 35.29

9374.11

48

Output: The values in the reverse order:

48

9374.11

35.29

Answer

```
# You are using Python
```

```
a=float(input())
```

```
b=float(input())
```

```
c=int(input())
```

```
d=a
```

```
a=c
```

```
c=d
print("The values in the reverse order:")
print(a)
print(b)
print(c)
```

Status : Correct

Marks : 10/10

3. Problem Statement

Emily is organizing a taco party and needs to determine the total number of tacos required and the total cost. Each attendee at the party will consume 2 tacos. To ensure there are enough tacos:

If there are 10 or more attendees, Emily will need to provide an additional 5 tacos. If there are fewer than 10 attendees, Emily must ensure a minimum of 20 tacos are provided.

The cost of each taco is \$25. Write a program that calculates both the total number of tacos required and the total cost based on the number of attendees.

Input Format

The input consists of an integer n , representing the number of attendees.

Output Format

The first line prints "Number of tacos needed: " followed by an integer representing the number of tacos needed for n attendees.

The second line prints "Total cost: " followed by an integer representing the total cost.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10

Output: Number of tacos needed: 25

Total cost: 625

Answer

-

Status : Skipped

Marks : 0/10

4. Problem Statement

Shawn is planning for his younger sister's college education and wants to ensure she has enough funds when the time comes. He starts with an initial principal amount and plans to make regular monthly contributions to a savings account that offers a fixed annual interest rate.

Shawn needs to calculate the total amount that will accumulate by the time his sister is ready for college. Your task is to write a program that calculates the final amount in the savings account based on the initial principal, monthly contributions, annual interest rate, and the number of months the money is invested.

Formula:

$$A = P \times (1 + r/n)^{(n \times t)} + C \times [(1 + r/n)^{(n \times t)} - 1] / (r/n)$$

Where:

A = Final amount after the specified time

P = Initial principal amount

C = Monthly contribution

r = Annual interest rate (as a decimal, e.g., 5% = 0.05)

n = Number of compounding periods per year (12 for monthly compounding)

t = Total time in years (months / 12)

Input Format

The first line of input consists of a float P, representing the initial principal amount.

The second line of input consists of a float R, representing the annual interest rate (in percentage).

The third line of input consists of a float C, representing the monthly contribution.

The fourth line of input consists of an integer M, representing the number of months.

Output Format

The output displays "Final amount after X months: Rs." followed by the total accumulated amount, formatted to two decimal places, where X is the number of months.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10000.0
5.0
2000.0
12

Output: Final amount after 12 months: Rs.35069.33

Answer

-

Status : Skipped

Marks : 0/10