Lovely Professional University

CSE570 – Machine Learning with Python
Academic Task 2 · Skill Based Assignment

Student Performance Prediction Using Machine Learning

An End-to-End Machine Learning Solution for a Real-World Problem

Student name	Dondla Karthik
Registration number	12625778
Roll number	37
Section	K3P26DS
Course code / title	CSE570 – Machine Learning with Python
Submitted to	*[faculty name]*
GitHub repository	https://github.com/karthik3344411/student-performance-prediction
LinkedIn post	*[add link after publishing]*
Date of submission	12 November 2026

Table of Contents

1. Title Page
2. Abstract
3. Introduction & Problem Statement
4. Dataset Description
5. Data Preprocessing
6. Exploratory Data Analysis (EDA)
7. Methodology
8. Model Development
9. Results & Model Comparison
10. Conclusion & Limitations
11. References
12. GitHub & LinkedIn Evidence

2. Abstract

This project builds an end-to-end machine-learning system that estimates a secondary-school student's final Mathematics grade (G3, scale 0–20) from 30 demographic, family, school and lifestyle attributes of the UCI *Student Performance* dataset (395 students). Earlier period grades (G1, G2) are deliberately excluded so that the model shows what can be predicted from background information alone. After the data was audited and cleaned, exploratory analysis with hypothesis tests showed that past class failures are the strongest single correlate of the final grade (Spearman $\rho = -0.36$). It also revealed that all 38 students with G3 = 0 have zero recorded absences, which suggests they did not sit the final exam. Five regression pipelines (mean baseline, Linear, Ridge, Decision Tree and Random Forest) were compared with 5-fold cross-validation on the training set and evaluated once on a held-out test set. A Random Forest tuned with GridSearchCV performed best: test MAE 3.04, RMSE 3.76 and R^2 0.31, compared with 3.65, 4.55 and −0.01 for the baseline. The final pipeline is saved with Joblib and served through a Streamlit web application. An optional pass/fail classification experiment is also reported. The results show that background data gives a useful but coarse estimate of performance, and that the largest errors come from students who probably dropped out.

Keywords: educational data mining, regression, random forest, cross-validation, scikit-learn pipeline, Streamlit

3. Introduction & Problem Statement

3.1 Introduction

Academic performance in core subjects such as Mathematics strongly affects students' future options. If a school can recognise students who are likely to struggle early, teachers can offer tutoring, counselling or other support before the final exam. Machine learning can learn patterns from historical records, for example that students with previous failures tend to score lower, and apply them to new students. This report documents the complete workflow, from problem definition to a deployed web application. Every number in it was produced by the code in the GitHub repository; nothing was entered by hand.

3.2 Problem statement

Item	Description
Context	Portuguese secondary-school students (two schools) taking Mathematics. Teachers need an early indication of which students may perform poorly.
Target variable	`G3` – final Mathematics grade, an integer from 0 to 20 (≥ 10 is a pass).
ML task	**Supervised regression** (predict a numeric grade). An optional binary classification (pass/fail) is reported as an extension.
Inputs	30 attributes covering demographics, family background, school, study habits and lifestyle. **G1 and G2 are excluded.**
Success criteria	(1) The final model beats a mean-predicting baseline on **both MAE and RMSE**, in cross-validation **and** on the held-out test set; (2) there is no data leakage (all preprocessing is fitted on training data only); (3) a working application returns a prediction in the valid range 0–20.
Assumptions	Historical records represent future students in the same schools; survey answers are reasonably truthful.
Constraints	Small dataset (395 rows); beginner-friendly, explainable methods; must run on a normal Windows laptop; academic demonstration only.

Why exclude G1 and G2? They are the first- and second-period grades of the same course, and their Pearson correlations with G3 are 0.80 and 0.90 (Figure 10). Including them would give a high R^2 simply because "the final grade is close to the previous grade". Such a model would only be usable late in the school year and would hide which background factors matter.

3.3 Objectives

1. Load and audit the official UCI dataset (shape, data types, missing values, duplicates).
2. Clean and preprocess the data without data leakage (encoding, scaling, and a train/test split inside pipelines).
3. Perform univariate, bivariate and multivariate EDA with descriptive statistics and statistical tests.
4. Train a baseline and at least three regression models, and compare them with MAE, MSE, RMSE and R^2.
5. Tune the best model with GridSearchCV, using cross-validation on the training data only.
6. Interpret the final model (feature importance, residuals) and state its limitations.
7. Save the complete pipeline and build a Streamlit application for predictions.

3.4 Scope

- **In scope:** the Mathematics file (`student-mat.csv`); regression of G3 from 30 non-grade features; classical scikit-learn models; a local Streamlit app; an optional pass/fail classification experiment.
- **Out of scope:** the Portuguese-language file, deep learning, cloud deployment, and any use for real decisions about students.

3.5 Applications

- **Early-warning support:** helping teachers and counsellors decide which students to check on first.
- **Resource planning:** estimating how many students may need tutoring in a class.
- **Education analytics:** understanding which background factors are associated with performance.
- **Teaching:** a complete, reproducible example of an ML workflow (pipelines, cross-validation, tuning, deployment).

4. Dataset Description

Property	Value
Name	Student Performance (UCI Machine Learning Repository, ID 320)
Source	https://archive.ics.uci.edu/dataset/320/student+performance
Citation	Cortez, P. & Silva, A. (2008) [1], [2]
License	Creative Commons Attribution 4.0 (CC BY 4.0)
File used	`student-mat.csv` (Mathematics course), separator `;`
Size	**395 records × 33 columns** (30 input attributes + G1, G2, G3)
Feature types	13 numeric (mostly ordinal scales) + 17 categorical (4 nominal multi-class, 13 binary)
Missing values / duplicates	**0 / 0**
Target variable	**G3** (0–20): mean 10.42, median 11, std 4.58, 95% CI of the mean [9.96, 10.87]

4.1 Target (class) distribution

Table 1. Distribution of the final grade G3 (n = 395).

G3 band	Students	Share
0 (probably did not sit the exam)	38	9.6%
1–9 (fail)	92	23.3%
10–13 (pass)	165	41.8%
14–15 (good)	60	15.2%
16–20 (very good / excellent)	40	10.1%
Pass (G3 ≥ 10) / Fail (G3 < 10)	**265 / 130**	**67.1% / 32.9%**

For regression the target is the numeric grade. For the optional classification task the classes are moderately imbalanced (about 2 passes for every fail).

4.2 Data dictionary

Table 2. Data dictionary (from the official UCI description).

#	Feature	Type	Description / values
1	school	binary	GP = Gabriel Pereira, MS = Mousinho da Silveira
2	sex	binary	F = female, M = male
3	age	numeric	15–22
4	address	binary	U = urban, R = rural
5	famsize	binary	LE3 = ≤ 3, GT3 = > 3
6	Pstatus	binary	parents living together (T) or apart (A)
7	Medu	ordinal	mother's education: 0 none, 1 primary, 2 5th–9th grade, 3 secondary, 4 higher
8	Fedu	ordinal	father's education (same scale)
9	Mjob	nominal	mother's job: teacher, health, services, at_home, other
10	Fjob	nominal	father's job (same categories)
11	reason	nominal	reason for choosing the school: home, reputation, course, other
12	guardian	nominal	mother, father, other
13	traveltime	ordinal	1 < 15 min, 2 15–30 min, 3 30–60 min, 4 > 1 h
14	studytime	ordinal	weekly study: 1 < 2 h, 2 2–5 h, 3 5–10 h, 4 > 10 h
15	failures	numeric	past class failures (0–3; 3 means 3 or more)
16	schoolsup	binary	extra educational support from school
17	famsup	binary	family educational support
18	paid	binary	extra paid classes in the subject
19	activities	binary	extra-curricular activities
20	nursery	binary	attended nursery school
21	higher	binary	wants to take higher education
22	internet	binary	internet access at home
23	romantic	binary	in a romantic relationship
24	famrel	ordinal	quality of family relationships, 1 (very bad) – 5 (excellent)
25	freetime	ordinal	free time after school, 1–5
26	goout	ordinal	going out with friends, 1–5
27	Dalc	ordinal	workday alcohol consumption, 1–5
28	Walc	ordinal	weekend alcohol consumption, 1–5
29	health	ordinal	current health status, 1–5
30	absences	numeric	number of school absences (0–93; observed maximum 75)
31	G1	numeric	first-period grade, 0–20 – **not used as an input**
32	G2	numeric	second-period grade, 0–20 – **not used as an input**

#	Feature	Type	Description / values
33	**G3**	numeric	**final grade, 0–20 – target**

4.3 Why this dataset is appropriate

- It is a well-documented, peer-reviewed public dataset that matches the problem exactly: real student records with a real final grade.
- It mixes numeric, ordinal, binary and nominal features, so it exercises every preprocessing step taught in the course.
- It has no missing values, yet it contains real data-quality issues (skewed absences, a group of zero grades) to investigate.
- At 395 rows it trains in seconds on a laptop, but it is small enough that careful validation really matters.

5. Data Preprocessing

Table 3. Cleaning and preprocessing steps.

Step	Finding	Action
Loading	The file is `;`-separated and grade values are quoted (`"5"`)	`pd.read_csv(sep=";")`; pandas parses the quoted grades as integers
Data types	16 numeric and 17 text columns, all as documented	`pd.to_numeric` on numeric columns (as a safety check); spaces stripped from text columns
Missing values	0	None needed. The code still fills numeric columns with the median and text columns with the mode, and never fills the target
Duplicates	0 exact duplicates	`drop_duplicates()` (no rows removed)
Range validation	Every value lies inside its official range	`clean_data()` raises an error if any value is out of range
Outliers (IQR rule)	`absences`: 15 values > 20 (max 75); `age`: one 22-year-old; `failures`: 83 flagged only because 79% of students have 0	**Kept.** They are plausible, real observations, and tree models are robust to them
G3 = 0	38 students (9.6%)	**Kept** as real outcomes; analysed in Section 6.4
Feature selection	G1 and G2 are strongly correlated with G3	Excluded from the inputs (Section 3.2)
Encoding	17 categorical columns	`OneHotEncoder(handle_unknown="ignore")`: the 30 inputs become 56 model columns
Scaling	13 numeric columns on different scales (absences 0–75 vs. 1–5 scales)	`StandardScaler` (needed for Linear/Ridge, harmless for trees)
Train/test split	—	80% train (316) / 20% test (79), `random_state = 42`

Leakage prevention. The scaler and encoder sit inside a scikit-learn `Pipeline` together with the model, so they learn means, standard deviations and categories **only from training data**, including within each cross-validation fold. A unit test checks that the fitted scaler's means equal the training-set means.




Figure 4. Absences are strongly right-skewed (median 4, mean 5.7, maximum 75); the boxplot marks 15 high values as IQR outliers.




Figure 5. Outlier inspection with IQR boxplots. No values fall outside the documented ranges.

6. Exploratory Data Analysis (EDA)

6.1 Descriptive statistics

Table 4. Descriptive statistics of the numeric variables (n = 395).

Variable	Mean	Median	Std	Min	Max
age	16.70	17	1.28	15	22
Medu	2.75	3	1.09	0	4
Fedu	2.52	2	1.09	0	4
traveltime	1.45	1	0.70	1	4
studytime	2.04	2	0.84	1	4
failures	0.33	0	0.74	0	3
famrel	3.94	4	0.90	1	5
freetime	3.24	3	1.00	1	5
goout	3.11	3	1.11	1	5
Dalc	1.48	1	0.89	1	5
Walc	2.29	2	1.29	1	5
health	3.55	4	1.39	1	5
absences	5.71	4	8.00	0	75
G1	10.91	11	3.32	3	19
G2	10.71	11	3.76	0	19
G3	**10.42**	**11**	**4.58**	**0**	**20**

6.2 Univariate analysis




Figure 1. Distribution of the final grade G3: mean 10.42 (95% CI 9.96–10.87), median 11.

Most grades lie between 8 and 15, with a separate spike at 0 (38 students). Because of this spike the distribution is not normal (Shapiro–Wilk W = 0.93, p < 0.001), so non-parametric tests are reported alongside parametric ones.




Figure 2. 208 female (53%) and 187 male (47%) students: a balanced sample.




Figure 3. Most students study 2–5 h per week (198); only 27 study more than 10 h.

6.3 Bivariate analysis and statistical tests




Figure 9. Final grade by number of past failures.

Failures: mean G3 falls from 11.25 (0 failures, n = 312) to 8.12 (1, n = 50), 6.24 (2, n = 17) and 5.69 (3+, n = 16). Kruskal–Wallis H = 53.1, **p < 0.001**. This is the strongest relationship in the data.




Figure 6. G3 by weekly study time (orange dots = group means).




Figure 7. G3 by gender.

- **Study time:** the group means are 10.05, 10.17, 11.40 and 11.26 for < 2, 2–5, 5–10 and > 10 h. The trend is upward but **not statistically significant** at α = 0.05 (one-way ANOVA F = 1.73, p = 0.161; Kruskal–Wallis p = 0.056).
- **Gender:** male students average 10.91 and female students 9.97 (Welch t = −2.07, **p = 0.040**). The difference is small, about one grade point.
- **Higher education vs passing:** the pass rate is 68.8% for students who want higher education (n = 375) and 35.0% for those who do not (n = 20); chi-square = 8.35, df = 1, **p = 0.004**. Only 20 students answered "no", so this estimate is uncertain.

Table 5. Correlation of numeric inputs with G3 (n = 395).

Feature	Spearman ρ	p-value	Pearson r
failures	−0.361	< 0.001	−0.360
Medu	+0.225	< 0.001	+0.217
age	−0.173	< 0.001	−0.162
Fedu	+0.170	< 0.001	+0.152
goout	−0.166	< 0.001	−0.133
Dalc	−0.121	0.016	−0.055
traveltime	−0.121	0.017	−0.117
studytime	+0.105	0.037	+0.098
Walc	−0.104	0.038	−0.052
famrel	+0.055	0.276	+0.051
health	−0.048	0.343	−0.061
absences	+0.018	0.725	+0.034
freetime	−0.005	0.921	+0.011

Table 6. Group comparison: mean G3 (n) by selected categories.

Feature	Group A	Group B
higher	yes: 10.61 (375)	no: 6.80 (20)
address	urban: 10.67 (307)	rural: 9.51 (88)
internet	yes: 10.62 (329)	no: 9.41 (66)
romantic	no: 10.84 (263)	yes: 9.58 (132)
schoolsup	no: 10.56 (344)	yes: 9.43 (51)
paid	yes: 10.92 (181)	no: 9.99 (214)
school	GP: 10.49 (349)	MS: 9.85 (46)

Students who receive extra school support have *lower* average grades. This is most likely because support goes to students who were already struggling, a reminder that **correlation does not imply causation**.

6.4 Key finding: the G3 = 0 group and absences




Figure 8. Absences vs final grade. Orange crosses mark the 38 students with G3 = 0.

Across all students, absences appear unrelated to G3 ($\rho = 0.02$, $p = 0.73$). However, **all 38 students with G3 = 0 have exactly 0 recorded absences**, compared with only 21.6% of the other students. Twenty-five of them had a non-zero second-period grade, and they average 0.92 past failures against 0.27 for the rest. The most plausible explanation is that these students left the course or did not sit the final exam. **Excluding them, absences correlate negatively with G3 ($\rho = -0.24$, $p < 0.001$)**, the expected direction. This hidden pattern also explains why the Random Forest later ranks `absences` as highly important.

6.5 Multivariate analysis




Figure 10. Pearson correlation heatmap of the numeric variables (G1/G2 shown for reference only).

G1, G2 and G3 are very strongly inter-correlated (0.80–0.90), which justifies excluding G1 and G2. Among the inputs there are correlated pairs: Medu–Fedu (0.62), Dalc–Walc (0.65) and goout–Walc (0.42). This multicollinearity makes individual Linear Regression coefficients unstable, which is one reason Ridge Regression was also tested.




Figure 11. Mean G3 by study time and gender, with 95% CIs.




Figure 12. Mean G3 by higher-education wish and past failures.

In Figure 11 the confidence intervals overlap widely, so the gender and study-time effects are small and uncertain. Figure 12 shows that failures lower the mean grade in both groups; the best combination (wants higher education, no failures, n = 305) averages 11.3.

6.6 Key observations

1. Past failures are the clearest signal of a low final grade.
2. Mother's education, wish for higher education, going out, age, and absences (among students who sat the exam) carry weaker signals.
3. Study time, family relationships, free time and health show little or no relationship with G3.
4. The 38 zero grades form a separate group (probable dropouts) that distorts simple statistics.
5. All of these are associations, not causes.

7. Methodology




Figure 0. Complete machine-learning workflow followed in this project.

1. **Data acquisition:** download the official UCI file and load it with pandas.
2. **Audit and cleaning:** check data types, missing values, duplicates, value ranges and outliers (Section 5).
3. **EDA:** run univariate, bivariate and multivariate analysis with statistical tests (Section 6).
4. **Feature/target definition:** use 30 input features and set G3 as the target; G1 and G2 are dropped.
5. **Train/test split:** 316 training and 79 test students (`random_state = 42`).
6. **Pipeline:** a `ColumnTransformer` (`StandardScaler` + `OneHotEncoder`) followed by the model, so no data leaks from validation or test data into preprocessing.
7. **Model comparison:** 5-fold cross-validation on the training set only; models are ranked by CV RMSE and CV MAE together.
8. **Tuning:** `GridSearchCV` on the best model, again using training data only.
9. **Final evaluation:** each model is evaluated **once** on the untouched test set.
10. **Interpretation:** residual analysis, plus permutation and impurity feature importance.
11. **Deployment:** the whole pipeline is saved with `joblib`, and a Streamlit app loads it for predictions.

Why cross-validation? With only 79 test students, a single split is noisy and can rank models by chance (Section 9.3 shows a real example). Making every decision with 5-fold CV and touching the test set only once gives an honest final estimate.

Software: Python 3.10, pandas 2.3, NumPy 2.2, scikit-learn 1.7, SciPy 1.15, Matplotlib 3.10, Seaborn 0.13, Joblib 1.6, Streamlit 1.65 and pytest 9.2 (21 automated tests).

8. Model Development

All models share the same preprocessing pipeline.

Table 7. Models trained.

Model	Why it was included	Initial settings
Dummy Regressor (baseline)	Always predicts the training mean (≈ 10.4); any useful model must beat it	`strategy="mean"`
Linear Regression	Simple, interpretable linear model	default
Ridge Regression	Linear model with L2 regularisation; handles correlated inputs	`alpha=1.0`
Decision Tree Regressor	Non-linear, captures interactions, easy to visualise	`random_state=42`, no depth limit
Random Forest Regressor	Ensemble of trees that reduces the overfitting of a single tree	`n_estimators=300`, `random_state=42`

Training and selection. Each pipeline was scored with 5-fold CV (MAE, RMSE, R^2) on the 316 training students. The non-baseline models were ranked by CV RMSE and CV MAE, and **Random Forest** ranked first on both. R^2 was not used on its own, because MAE and RMSE are in grade points and are easier to explain to teachers.

Hyperparameter tuning. `GridSearchCV` (5-fold CV on the training set, scored by RMSE) searched 2 × 3 × 3 × 3 = **54 combinations** (270 model fits):

Table 8. Random Forest hyperparameter grid.

Hyperparameter	Values tried	Meaning	Best
`n_estimators`	200, 500	number of trees	**200**
`max_depth`	None, 6, 10	maximum depth of each tree	**None**
`min_samples_leaf`	1, 3, 5	minimum number of students in a leaf	**1**
`max_features`	1.0, 0.5, "sqrt"	share of features considered at each split	**0.5**

Tuning tested whether limiting tree depth or sampling features reduces overfitting. The best setting uses half of the features at each split, which makes the trees more diverse. The tuned model replaced the default because its **CV** RMSE was lower (3.897 vs 3.925); the test set played no part in that choice. The final pipeline is saved as `models/best_model.joblib` (4.3 MB), with its metrics in `models/model_metrics.json`.

9. Results & Model Comparison

9.1 Evaluation metrics

- **MAE** – mean absolute error: the average number of grade points by which a prediction is off.
- **MSE** – mean squared error: penalises large errors more heavily.
- **RMSE** – the square root of MSE, in grade points.
- **R^2** – the share of the variance in G3 explained by the model (0 = no better than predicting the mean; negative = worse than the mean).

9.2 Final model performance

Table 9. Final model vs baseline on the held-out test set (79 students).

Metric	Baseline	Final model (tuned Random Forest)	Improvement
MAE	3.646	**3.035**	−0.61 (−17%)
MSE	20.704	**14.145**	−6.56 (−32%)
RMSE	4.550	**3.761**	−0.79 (−17%)
R^2	−0.010	**0.310**	+0.32

9.3 Model comparison

Table 10. All models: test set (79 students) and 5-fold cross-validation on the training set (316 students).

Model	Test MAE	Test MSE	Test RMSE	Test R^2	CV MAE	CV RMSE	CV R^2	Train RMSE
Dummy (baseline)	3.646	20.704	4.550	−0.010	3.403	4.563	−0.035	4.583
Linear Regression	3.395	17.604	4.196	0.141	3.523	4.607	−0.092	3.865
Ridge Regression	3.393	17.585	4.193	0.142	3.506	4.584	−0.080	3.865
Decision Tree	3.633	23.405	4.838	−0.141	4.102	5.527	−0.570	0.000
Random Forest	**3.010**	14.175	3.765	0.309	**2.934**	3.925	0.212	1.457
RF (tuned) – final	3.035	**14.145**	**3.761**	**0.310**	2.960	**3.897**	**0.232**	1.451




Figure 13. MAE and RMSE for every model (blue = 5-fold CV, orange = test set).

- **Linear and Ridge Regression:** both beat the baseline on the test set (R^2 0.14) but are *worse* than the baseline in cross-validation (CV $R^2 < 0$). A single split can mislead, which is why the models were selected with CV.
- **Decision Tree:** its training RMSE is 0.00 but its CV RMSE is 5.53, a textbook case of **overfitting** in which the tree memorises the training students.
- **Random Forest:** averaging many decorrelated trees greatly reduces this variance. It is the best model in CV and on the test set, and it captures non-linear patterns that linear models miss.
- **Tuned vs default Random Forest:** tuning gave only a small improvement (CV RMSE 3.925 → 3.897; test RMSE 3.765 → 3.761, with test MAE slightly worse at 3.010 → 3.035). The two are practically equivalent; the tuned version was kept according to the pre-defined CV rule.
- **Justification:** the tuned Random Forest has the lowest CV RMSE and the best test RMSE, MSE and R^2. It beats the baseline by 17% on both MAE and RMSE, which meets the success criterion.

9.4 Model behaviour




Figure 14. Actual vs predicted G3 (test set).




Figure 15. Residuals vs predictions and the residual distribution.

- The predictions are compressed towards the centre (about 8–14); the model avoids extreme values.
- The residuals are centred near zero (mean −0.18). 43% of predictions are within ±2 points and 73% within ±4 points.
- The five test students with G3 = 0 produce the largest errors (**MAE 8.06**, against **2.70** for the other 74 students).




Figure 16. Permutation importance on the test set (increase in RMSE when a feature is shuffled).




Figure 17. Random Forest impurity-based importance.

Both methods agree that **failures** and **absences** dominate, followed by going out, gender, school support, mother's education and age. As a cross-check, the standardised Linear Regression coefficients show the same directions: failures −1.36 points per standard deviation, wanting higher education +0.88, male +0.75, study time +0.63.

9.5 Optional extension: pass/fail classification

The target was converted to **pass (G3 ≥ 10) / fail** (67.1% pass), keeping the same features and pipeline, with a stratified 80/20 split and class-balanced models.

Table 11. Pass/fail classification on the test set (precision, recall and F1 are for the "fail" class).

Model	CV macro-F1	Accuracy	Precision	Recall	F1	Macro-F1	ROC-AUC
Dummy (always "pass")	0.402	**0.671**	0.000	0.000	0.000	0.402	0.500
Logistic Regression	**0.652**	0.595	0.400	**0.462**	**0.429**	0.557	0.595
Decision Tree (depth 4)	0.568	0.519	0.333	0.462	0.387	0.496	0.466
Random Forest	0.591	0.684	**0.529**	0.346	0.419	**0.601**	**0.652**




Figure 18. Confusion matrix for Logistic Regression: 12 of 26 failing students detected.




Figure 19. ROC curves of the three classifiers.

The baseline has the highest accuracy while detecting **no** failing students, which shows why accuracy alone is misleading on imbalanced classes. All classifiers are only moderately better than chance (ROC-AUC 0.47–0.65), consistent with the regression results.

10. Conclusion & Limitations

10.1 Conclusion

This project delivers a complete, reproducible machine-learning workflow for predicting students' final Mathematics grades from background information. A tuned Random Forest was selected through a fair, leakage-free comparison of five models (test MAE 3.04, RMSE 3.76, R^2 0.31). It clearly outperforms the baseline, the linear models and the single decision tree. Past failures and absences are the most important predictors. The analysis also revealed that students with a final grade of 0 form a distinct group that the model cannot predict well. The trained pipeline is deployed in a Streamlit application. The model can serve as a rough, explainable early-warning signal, but its moderate accuracy means it should support teachers' judgement, never replace it.

10.2 Limitations

- **Small sample:** only 395 students (79 in the test set), so the metrics carry noticeable uncertainty (CV RMSE standard deviation ≈ 0.37).
- **Limited scope:** two Portuguese schools, one subject, and data from 2005–2006; the results may not transfer elsewhere.
- **Self-reported, sensitive features:** alcohol use and family information may be inaccurate, and using gender or background for decisions raises fairness concerns.
- **G3 = 0 group:** probable dropouts are mixed with genuine low scores in a single numeric target.
- **Moderate accuracy:** R^2 ≈ 0.31, and the predictions are compressed towards the average.
- **Associations, not causes:** no relationship found here proves that changing a feature would change the grade.

10.3 Future improvements

- Model the G3 = 0 outcome separately (a dropout classifier plus a grade regressor for students who sit the exam).
- Combine the Mathematics and Portuguese datasets (649 more students).
- Try gradient boosting and SHAP explanations, and use repeated or nested cross-validation.
- Run a fairness audit of errors by gender, address and school.
- Add K-Means clustering with PCA (syllabus Unit V) and deploy the app on Streamlit Community Cloud.

11. References

1. P. Cortez and A. Silva, "Using Data Mining to Predict Secondary School Student Performance," in *Proc. 5th FUture BUsiness TEChnology Conference (FUBUTEC 2008)*, Porto, Portugal: EUROSIS, 2008, pp. 5–12.
2. P. Cortez, "Student Performance," UCI Machine Learning Repository, 2008. DOI: 10.24432/C5TG7T. https://archive.ics.uci.edu/dataset/320/student+performance
3. F. Pedregosa *et al.*, "Scikit-learn: Machine Learning in Python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.
4. W. McKinney, "Data Structures for Statistical Computing in Python," in *Proc. 9th Python in Science Conference*, 2010, pp. 56–61.
5. C. R. Harris *et al.*, "Array programming with NumPy," *Nature*, vol. 585, pp. 357–362, 2020.
6. P. Virtanen *et al.*, "SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python," *Nature Methods*, vol. 17, pp. 261–272, 2020.
7. J. D. Hunter, "Matplotlib: A 2D Graphics Environment," *Computing in Science & Engineering*, vol. 9, no. 3, pp. 90–95, 2007.
8. M. L. Waskom, "seaborn: statistical data visualization," *Journal of Open Source Software*, vol. 6, no. 60, p. 3021, 2021.
9. L. Breiman, "Random Forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.
10. Streamlit Inc., *Streamlit documentation*, https://docs.streamlit.io
11. Joblib developers, *Joblib documentation*, https://joblib.readthedocs.io

12. GitHub & LinkedIn Evidence

12.1 GitHub repository

- **Repository URL:** https://github.com/karthik3344411/student-performance-prediction
- **Contents:** README, problem/objectives, dataset source, Python scripts (`src/`), executed notebook, `requirements.txt`, saved model, figures, this report, viva questions, and 21 automated tests.
- **Workflow:** branch-based development, with one feature branch and one pull request per development phase.

Table 12. Pull requests (opened 12 Nov 2026).

PR	Branch	Title
#1	feature/data-preprocessing	Phase 1-2: Data loading, audit, cleaning and preprocessing pipeline
#2	feature/eda-statistical-analysis	Phase 3: Exploratory data analysis and statistical tests
#3	feature/model-training-and-tuning	Phase 4-7: Model training, evaluation, GridSearchCV tuning and model saving
#4	feature/streamlit-app	Phase 8: Streamlit prediction app
#5	feature/classification-extension	Optional extension: pass/fail classification (Unit IV)
#6	docs/notebook-report-readme	Phase 9: Notebook, README, academic report and viva preparation
#7	docs/pdf-report	Final report in CSE570 format (PDF) with GitHub evidence

Table 13. Commit history (all commits authored by karthik3344411 on 12 Nov 2026).

Commit	Message
a3db858	Initial project setup: folder structure, dataset, requirements and license
bb0e815	Add dataset loading, audit and cleaning functions
bbd323f	Add unit tests for cleaning, feature selection and leakage-safe preprocessing
ba54cf1	Add EDA module with univariate, bivariate and multivariate plots
fb2c2e4	Add generated EDA figures and statistical test results
dff606c	Add training pipeline with baseline and four regression models
200e34e	Tune Random Forest with GridSearchCV and save final pipeline
52be37f	Add prediction helper with input validation and tests
f06e4e4	Add Streamlit app for grade prediction
370f17b	Add Streamlit smoke test for the prediction form
3b23b90	Add optional pass/fail classification experiment
577f1ac	Add classification results, confusion matrix and ROC curves
efa2c99	Add executed analysis notebook covering all project phases
1bd7adb	Write full README with setup, usage, results and limitations
7343341	Add academic project report with real results and references
0b88e50	Add viva preparation questions and answers




Figure 20. Repository home page (screenshot captured 12 Nov 2026, 14:07 IST).




Figure 21. Pull requests, one per development phase (screenshot captured 12 Nov 2026, 14:07 IST).




Figure 22. Commit history with descriptive messages (screenshot captured 12 Nov 2026, 14:07 IST).

12.2 LinkedIn post

- **Post URL:** *[add the LinkedIn post URL here after publishing]*
- **Content:** problem, dataset, approach, one key insight (the G3 = 0 / absences finding, Figure 8), best-model result (tuned Random Forest, MAE 3.04 vs baseline 3.65), key learning, and the GitHub link.
- **Dated screenshot:** *[insert a dated screenshot of the post showing likes and comments]*