OpenLecture

Team Number: Team 43

Team Members

- Nallala Karthik (2025201095)
- Aayush Pandey (2025201058)
- Jagadish Kollu (2025201006)
- Suresh Kumar Vuyala (2025201051)

GitHub Repository

https://github.com/karthik443/openLecture

Problem Statement

Traditional classroom systems are primarily designed for use within a single institution and are not built to support large-scale, distributed learning environments. While online platforms have enabled recorded lecture sharing, they often lack the capability to provide **live, interactive experiences** for a large and geographically distributed audience.

When lectures are delivered by highly reputed professors, they attract interest from students across multiple universities. However, existing systems struggle to accommodate such demand due to several limitations:

- **Scalability constraints**, where systems cannot efficiently handle thousands of concurrent users
- **High latency in live streaming**, leading to poor user experience
- **Limited real-time interaction**, making it difficult for students to engage with instructors
- **Lack of cross-institution access control**, restricting participation to enrolled students only

As a result, there is no unified system that can reliably deliver **live lectures at scale while maintaining interactivity and performance**. This creates a gap in enabling truly global, real-time academic collaboration.

Proposed Solution: GlobalClassroom Platform

To address these challenges, we propose **OpenLecture**, a distributed classroom platform designed to support **large-scale live lecture streaming with real-time interaction**.

GlobalClass enables instructors from participating institutions to host lectures that can be attended by students across multiple universities through a unified platform. The system is architected using a **microservices-based design** to ensure scalability, fault isolation, and efficient resource utilization.

Key aspects of the solution include:

- **Scalable Live Streaming Architecture**
  A hybrid streaming approach combining WebRTC (for low-latency interaction) and HLS (for large-scale broadcast) allows the system to efficiently serve both interactive and passive viewers.
- **Real-time Interactive Q&A System**
  Students can ask and vote on questions during lectures, enabling prioritized interaction with instructors even in large audiences.
- **Distributed and Fault-Tolerant Design**
  Core services such as streaming, API handling, and real-time synchronization are decoupled, ensuring that failures in one component do not impact the entire system.
- **Efficient Load Handling**
  An API gateway with load balancing distributes traffic across multiple service instances, enabling the platform to handle high concurrency.
- **Cross-Institution Accessibility**
  The platform provides a unified interface for students from different institutions, removing access barriers while maintaining secure authentication and authorization.

Task 1: Requirements and Subsystems

Functional Requirements

Functional requirements define the specific behaviors and capabilities the system must support. The following requirements are derived from the core and supporting features described in the project proposal.

FR1 – Scalable Live Lecture Streaming

ID: FR1 | **Priority:** Critical

Description The system shall support live video streaming of lectures from an instructor to thousands of concurrent students across multiple institutions simultaneously.

Architectural Significance This is the core feature of the platform. It drives the choice of WebRTC for low-latency transport, a microservices architecture for isolation of the streaming subsystem, and load balancing strategies to distribute viewer traffic. Without scalable streaming the platform cannot fulfill its primary purpose.

FR2 – Cross-Institution Course Enrollment

ID: FR2 | **Priority:** High

Description The system shall maintain a global course catalog and allow students from any participating institution to browse, enroll in, and access lectures offered by instructors at other institutions.

Architectural Significance Requires a unified identity and authentication model across institutions. Role-based access control (RBAC) must distinguish students, instructors, and administrators from different organizations. A shared relational schema (PostgreSQL) is needed to link users, institutions, courses, and enrollments.

FR3 – User Authentication and Role-Based Access Control

ID: FR3 | **Priority:** Critical

Description The system shall authenticate users from multiple institutions and enforce role-based permissions that differentiate students, instructors, and administrators.

Architectural Significance Security is a cross-cutting concern. The authentication subsystem must handle federated identity across institutions. Architectural decisions around JWT tokens, OAuth2/SSO integration, and API gateway enforcement are all driven by this requirement.

FR4 – Real-Time Question Submission and Voting

ID: FR4 | **Priority:** High

Description During a live lecture, students shall be able to submit questions and upvote existing questions. The system shall rank and surface the most-voted questions to the instructor in real time.

Architectural Significance Drives the adoption of an event-driven architecture (Node.js with WebSockets) for real-time bidirectional communication. The Strategy Pattern is applied for flexible question-ranking algorithms. This subsystem must remain operational even under peak streaming load, requiring independent deployment.

FR5 – Lecture Recording and Playback

ID: FR5 | **Priority:** Medium

Description The system shall record live lectures and make them available for on-demand playback by enrolled students after the session ends.

Architectural Significance Introduces storage and media management concerns. The recording pipeline must be decoupled from the live stream to avoid adding latency. Object storage (e.g., S3-compatible) and a separate playback service are architecturally required.

FR6 – Lecture Participation Analytics

ID: FR6 | **Priority:** Medium

Description The system shall collect and display analytics on lecture participation including viewer counts, question activity, and attendance trends, accessible to instructors and administrators via dashboards.

Architectural Significance Analytics data must be aggregated without impacting live stream performance. This motivates a dedicated analytics microservice, use of an event bus (Observer Pattern), and eventual consistency for non-critical metrics.

FR7 – Notifications for Lecture Updates

ID: FR7 | **Priority:** Low–Medium

Description The system shall notify enrolled students of upcoming lectures, schedule changes, and newly published recordings via push or email notifications.

Architectural Significance Implements the Observer Pattern. A notification service subscribes to lecture lifecycle events and delivers alerts asynchronously, fully decoupled from core lecture management logic.

Non-Functional Requirements

Non-functional requirements (NFRs) govern the quality attributes of the system. The following NFRs are quantified based on the scale and interaction model of GlobalClass, where peak loads may involve thousands of simultaneous users consuming live video.

NFR1 – Scalability

Target The system shall support a minimum of 10,000 concurrent viewers per live lecture session without degradation in stream quality, Q&A responsiveness, or API response times.

Rationale GlobalClass is specifically designed for high-demand lectures. A university with 5,000 enrolled students supplemented by learners from partner institutions can easily exceed the capacity of traditional videoconferencing tools. Ten thousand concurrent users is therefore a conservative baseline that the architecture must satisfy from day one.

Architectural Impact

- Microservices architecture isolates the streaming service so it can be scaled horizontally, independently of other services.
- A Content Delivery Network (CDN) or Selective Forwarding Unit (SFU) relay layer distributes WebRTC streams and reduces origin server load.
- Stateless API services behind a load balancer allow auto-scaling of Node.js instances under surge demand.

- The Factory Pattern supports dynamic provisioning of new lecture session objects and their associated resources at runtime.

NFR2 – Reliability

Target 99.9% delivery rate for student question submissions. Stream interruptions must trigger automatic client reconnection within 5 seconds. No submitted question shall be permanently lost due to a transient service failure.

Rationale In a live academic setting students rely on their questions being registered and surfaced to the instructor. Lost interactions erode trust in the platform and discourage participation. Stream drops that affect hundreds of simultaneous viewers must be handled gracefully to minimize disruption.

Architectural Impact

- Fault isolation via microservices ensures that a failure in the analytics subsystem does not cascade into the streaming or Q&A subsystems.
- Durable message queuing (e.g., Kafka or RabbitMQ) between the Q&A service and the database protects question submissions during transient failures.
- Client-side reconnection logic and server-side session resumption are first-class concerns in the streaming service design.
- The Repository Pattern abstracts database access, enabling fallback strategies such as write-behind caching when the primary database is briefly unavailable.

NFR3 – Latency

Target

- Live video stream end-to-end latency: ≤3 seconds under normal network conditions.
- Q&A interactions (question submission, vote updates visible to all): ≤1 second round-trip.
- Lecture catalog and enrollment API responses: ≤200 ms at the 95th percentile under normal load.

Rationale If the stream lags significantly behind the instructor's speech, students cannot respond to real-time demonstrations, polls, or time-sensitive questions. Sub-second Q&A interaction is essential for the platform to feel live rather than asynchronous.

Architectural Impact

- WebRTC is selected over HLS precisely because it achieves sub-3-second latency, whereas adaptive HLS typically introduces 10–30 seconds of delay.
- Edge caching via CDN for static assets and course catalog data reduces perceived API latency for geographically distributed users.
- The Q&A service uses persistent WebSocket connections rather than HTTP polling to achieve sub-second message delivery at scale.
- Database query optimization and indexing on hot-path queries (course lookup, enrollment verification) are required to satisfy the 200 ms API target.

NFR4 – Availability

Target The platform shall maintain ≥99.5% uptime during scheduled lecture hours (measured monthly). Planned maintenance shall occur outside scheduled lecture windows. Mean Time to Recovery (MTTR) from an unplanned outage shall not exceed 10 minutes.

Rationale A live lecture interrupted mid-session cannot simply be restarted without disrupting the instructor and potentially hundreds of students. Unlike asynchronous tools, high availability during scheduled hours is non-negotiable.

Architectural Impact

- Active-active or active-passive redundancy for the streaming gateway, authentication service, and Q&A service.
- Automated health monitoring with fast failover reduces MTTR below the 10-minute target.
- PostgreSQL streaming replication with automatic leader election prevents the data tier from becoming a single point of failure.
- Circuit breakers between microservices (e.g., using a service mesh) prevent a failing downstream service from causing cascading outages.

NFR5 – Performance

Target

- REST API p95 response time: ≤200 ms under normal load (< 1,000 concurrent users).
- REST API p95 response time: ≤500 ms under peak load (up to 10,000 concurrent users).
- Lecture join time (from button click to first video frame): ≤4 seconds.
- Analytics dashboard Time to Interactive: ≤2 seconds.

Rationale Students and instructors interact with the platform immediately before and during live sessions. Any slowness in the catalog, enrollment, or join flow causes students to miss live content and creates a poor first impression of the platform.

Architectural Impact

- In-memory caching (Redis) for frequently read data such as course catalogs, live viewer counts, and enrollment states eliminates redundant database round-trips.
- Connection pooling at the database layer reduces overhead under high-concurrency request bursts.
- Lazy loading of non-critical dashboard components (analytics charts, historical trends) prioritizes Time to Interactive for the lecture join flow.
- Node.js's event-driven, non-blocking I/O model efficiently handles large numbers of lightweight concurrent API requests without thread-per-connection overhead.

Architecturally Significant Requirements: Summary

Not all requirements equally influence architectural decisions. The table below identifies the requirements that most constrain or shape the system architecture and briefly states the primary reason for their significance.

ID	Requirement	Why Architecturally Significant
FR1	Live Lecture Streaming	Forces microservices decomposition, WebRTC adoption, CDN/SFU integration, and horizontal scaling.
FR3	Authentication & RBAC	Cross-cutting security concern; shapes API gateway design, token management, and inter-service authorization.
FR4	Real-Time Q&A	Requires persistent WebSocket connections, event-driven backend, and independent scaling from the stream.

ID	Requirement	Why Architecturally Significant
NFR1	Scalability (10K users)	Mandates stateless services, load balancing, CDN relay, and auto-scaling infrastructure.
NFR2	Reliability (99.9% delivery)	Drives message queue adoption, fault isolation patterns, and durable write strategies.
NFR3	Latency (≤3 s stream)	Determines streaming protocol choice (WebRTC over HLS), caching strategy, and database indexing requirements.
NFR4	Availability (99.5% uptime)	Necessitates service redundancy, automated failover, circuit breakers, and replicated database topology.
NFR5	Performance (200 ms API p95)	Requires Redis caching, connection pooling, and query optimization on all hot data paths.

These eight requirements collectively constrain the most consequential architectural decisions in GlobalClass: the choice of streaming protocol, the microservices decomposition, the database and caching topology, and the fault-tolerance mechanisms. Satisfying them simultaneously requires careful trade-off analysis throughout the design process.

Subsystems Overview

1. API Gateway (Nginx)

File: `nginx/nginx.conf` | **Port:** 80

Single entry point for all traffic. Clients never talk directly to a backend service.

Routing:

Path	Upstream
`/api/stream/*`	`streaming-engine:4001`
`/api/*`	`core-api:4000`
`/qaws`	`core-api:4000` (WebSocket upgrade)
`/hls/*`	`minio:9000` (HLS segment delivery)

Uses `least_conn` load balancing across both upstreams. When services are scaled with `--scale`, Docker's DNS resolves the service name to all container IPs automatically — no Nginx config changes needed. Sets `Upgrade`/`Connection` headers for WebSocket proxying and `Cache-Control: no-cache` for live HLS segments.

---

2. Core API Service

Directory: `backend/src/` | **Port:** 4000

Owns the application domain: users, lectures, enrollments, and Q&A.

Auth — Register/login with bcrypt + JWT. Every REST request requires `Authorization: Bearer <token>`; every WebSocket connection requires `?token=<jwt>`. `authenticate` and `requireRole` middleware enforce this on every route.

Lecture Catalog — CRUD for lectures, enrollment (`ON CONFLICT DO NOTHING`), and status transitions (`scheduled → live → ended`).

Q&A (write-behind buffer) — All writes go to Redis first; a `setInterval` flushes to PostgreSQL every 5 seconds. Votes use `HSETNX` (atomic dedup) + `HINCRBY` (atomic count). Reads during a live lecture come entirely from Redis — PostgreSQL is only hit as a fallback for ended lectures.

Q&A WebSocket (`/qaws`) — JWT verified at upgrade. Routes `SUBMIT_QUESTION`, `VOTE`, `MARK_ANSWERED`, `SET_STRATEGY` messages to `qaService`, then broadcasts `QUESTIONS_UPDATE` to all room clients. Uses Redis Pub/Sub (`qa:broadcast:<lectureId>`) to sync broadcasts across scaled instances.

Ranking — Three strategies (`votes`, `recency`, `default`) behind a single `rank()` interface. Swappable at runtime by the instructor via `SET_STRATEGY`.

---

3. Streaming Engine

Directory: `streaming-engine/src/` | **Port:** 4001

Isolated service for everything video — decoupled so a streaming failure doesn't affect Q&A or auth.

Start (`POST /api/stream/start/:lectureId`) — Marks lecture `live` in DB, issues a LiveKit publisher token (canPublish: true), starts HLS egress in the background.

Join (`POST /api/stream/join/:lectureId`) — Checks current LiveKit room occupancy against `WEBRTC_PRIORITY_LIMIT` (default 500). Under the limit → WebRTC token (<1s latency). Over the limit → HLS URL (~2-3s latency). Falls back to WebRTC if HLS is unavailable.

End (`POST /api/stream/end/:lectureId`) — Marks lecture `ended`, stops HLS egress, calls `RoomServiceClient.deleteRoom` to disconnect all LiveKit participants.

Egress — In prototype mode, returns Apple's public LL-HLS test stream as a stand-in. The real `EgressClient` code that writes segments to MinIO is written and commented in, ready to enable.

---

4. Infrastructure

PostgreSQL

Durable source of truth. Five tables: `users`, `lectures`, `enrollments`, `questions`, `votes`. The `UNIQUE(question_id, student_id)` constraint on `votes` is a second line of defence against duplicate votes at flush time. Largely off the hot path during live lectures — Q&A reads/writes go through Redis.

Redis

Serves three roles: **(1) Q&A write buffer** — live questions and votes stored in three hashes per lecture (`qa:live:q`, `qa:live:voted`, `qa:live:vc`). **(2) Live read source** — `getRankedQuestions` reads directly from these hashes, no TTL, no cache miss. **(3) Pub/Sub broadcast bus** — `qa:broadcast:<lectureId>` channel keeps all scaled Core API instances in sync.

MinIO

Local S3-compatible storage acting as the CDN origin for HLS segments. LiveKit Egress writes segments to MinIO under `hls/<lectureId>/`; Nginx proxies `/hls/*` to serve them to bulk-tier viewers. Fully running as infrastructure in the prototype even though the egress write path is currently mocked.

Task 2: Architecture Framework

Stakeholder Identification (IEEE 42010)

IEEE 42010 defines a system architecture as a set of **architecture descriptions** that address **stakeholder concerns** through **viewpoints** and **views**. This section identifies all relevant stakeholders for the GlobalClass platform, documents their concerns, and maps those concerns to architectural viewpoints and views.

---

1. Stakeholders and Their Concerns

A stakeholder is any individual, team, or organization that has an interest in, or is affected by, the system. The following stakeholders have been identified for the GlobalClass platform.

1.1 Students

Description: Learners from participating universities who attend live lectures and interact via Q&A. They may belong to the institution hosting the lecture or to a partner institution.

Concerns:

- The live stream must be low-latency (≤3 s) so that interaction with the instructor feels synchronous.
- Questions submitted during a lecture must be reliably delivered and surfaced to the instructor.
- The platform must be accessible from any institution without administrative friction.
- The enrollment and join flow must be fast (join ≤4 s) so that live sessions are not missed.
- Recorded lectures must be available for on-demand playback after the session.
- The interface must be intuitive and responsive across devices and network conditions.

1.2 Instructors / Professors

Description: Faculty members who host and deliver live lectures. They may be affiliated with any participating institution and attract students from across multiple universities.

Concerns:

- The streaming infrastructure must handle thousands of concurrent viewers without quality degradation.
- The Q&A panel must surface high-priority questions in real time to facilitate meaningful interaction.
- Participation analytics (viewer counts, question activity, attendance trends) must be available during and after the session.
- The platform must remain available throughout the scheduled lecture window without interruption.
- Lecture recordings must be automatically captured and made available to enrolled students without manual intervention.
- Scheduling and lecture management must be straightforward and integrated with course administration.

1.3 University Administrators

Description: Administrative staff and faculty governance bodies at participating institutions responsible for course offerings, enrollment policies, and institutional compliance.

Concerns:

- Enrollment must be controllable per institution and per course, ensuring only authorized students can access content.
- Role-based access control must distinguish institutional boundaries (students, instructors, admins) across organizations.
- Institution-level analytics and attendance records must be accessible for academic compliance reporting.
- Student data handled by the platform must comply with relevant privacy regulations (e.g., FERPA, GDPR).
- Cross-institution partnerships must be configurable without exposing one institution's data to another.

1.4 Platform Operators / DevOps Engineers

Description: The team responsible for deploying, operating, monitoring, and maintaining the GlobalClass infrastructure.

Concerns:

- Individual service failures must not cascade into full-system outages (fault isolation).
- The system must support horizontal scaling of the streaming, API, and Q&A services independently.
- Health monitoring and automated failover must keep MTTR under 10 minutes.
- Deployment must be containerized and reproducible across environments.
- Service dependencies (database, message queue, object storage) must be observable through centralized monitoring.
- Load balancing must distribute traffic evenly across service instances during peak demand.

1.5 Software Architects / Developers

Description: The engineering team responsible for designing, implementing, and evolving the GlobalClass system.

Concerns:

- The system must be decomposed into independently deployable microservices with clearly defined interfaces.
- Key architectural decisions (streaming protocol, caching strategy, database topology) must be documented and traceable.

- Design patterns (Factory, Repository, Strategy, Observer) must be consistently applied to address recurring structural problems.
- The codebase must be maintainable and extensible to accommodate future requirements (e.g., additional institution integrations).
- Non-functional requirements (latency, scalability, availability) must be verifiable through measurable targets.

1.6 IT / Infrastructure Teams at Participating Institutions

Description: Technical teams at partner universities responsible for network configuration, identity management, and local infrastructure.

Concerns:

- The platform must integrate with existing institutional identity providers (SSO/OAuth2) without requiring local infrastructure changes.
- Network policies must not block WebRTC or WebSocket traffic needed for streaming and Q&A.
- Data residency and cross-border data transfer implications must be clearly defined and acceptable per institutional policy.

1.7 Regulatory and Compliance Bodies

Description: External standards bodies and legal frameworks governing the handling of student data, accessibility, and privacy (e.g., FERPA in the US, GDPR in the EU).

Concerns:

- Personally identifiable information (PII) of students must be protected in storage and in transit.
- Data retention and deletion policies must be configurable and enforced.
- Audit logs of access and actions must be available for compliance review.
- Accessibility standards (e.g., WCAG 2.1) must be considered in the student-facing interface.

---

2. Stakeholder Concerns Summary

Stakeholder	Primary Concerns
Students	Low-latency stream, reliable Q&A delivery, cross-institution access, fast join, on-demand playback
Instructors	Scalable viewer support, real-time Q&A ranking, analytics, session reliability, automatic recording
University Administrators	Enrollment control, RBAC, compliance reporting, data privacy, institutional isolation
Platform Operators	Fault isolation, independent scaling, automated failover, observability, load balancing
Architects / Developers	Microservices decomposition, documented decisions, design patterns, maintainability, measurable NFRs
Institutional IT Teams	SSO/OAuth2 integration, network compatibility, data residency
Regulatory Bodies	PII protection, data retention, audit logs, accessibility compliance

---

3. Architectural Viewpoints

An **architectural viewpoint** defines the conventions for constructing, interpreting, and using an architectural view to address the concerns of specific stakeholders. The following viewpoints are defined for GlobalClass.

Viewpoint 1: Functional Viewpoint

Stakeholders Addressed: Students, Instructors, University Administrators

Concerns Addressed:

- What core capabilities does the system provide?
- How do users interact with the platform (live streaming, enrollment, Q&A, analytics)?
- How are roles and permissions enforced across institutions?

Modeling Conventions: Use Case Diagrams, Component Interaction Diagrams (C4 Level 2), sequence diagrams for key flows (lecture join, question submission).

Key View Content:

- Core subsystems: Streaming Engine, Q&A Service, Course Catalog, Authentication Service, Analytics Service, Notification Service.
- Interactions between students and instructors via the live lecture flow.
- RBAC enforcement at the API Gateway for each user role.

Viewpoint 2: Deployment and Infrastructure Viewpoint

Stakeholders Addressed: Platform Operators, Architects / Developers, Institutional IT Teams

Concerns Addressed:

- How are services deployed and scaled in production?
- How is load distributed across service instances?
- How does the system achieve horizontal scalability to support ≥10,000 concurrent viewers?

Modeling Conventions: Deployment Diagrams (C4 Level 4 / UML Deployment), infrastructure topology diagrams.

Key View Content:

- Containerized microservices deployed via Docker/Kubernetes.
- An API Gateway with load balancer fronting the Core API and Streaming Engine.
- LiveKit SFU cluster distributing WebRTC media streams, offloading the origin server.
- MinIO/S3-compatible object storage for HLS segment distribution and lecture recordings.
- PostgreSQL with streaming replication for the data tier; Redis for in-memory caching.

Viewpoint 3: Security and Access Control Viewpoint

Stakeholders Addressed: University Administrators, Institutional IT Teams, Regulatory Bodies, Students, Instructors

Concerns Addressed:

- How are users from multiple institutions authenticated and authorized?
- How is access to lectures and data restricted to authorized parties?
- How is student data protected in transit and at rest?

Modeling Conventions: Security architecture diagrams, RBAC matrix, data flow diagrams annotated with trust boundaries.

Key View Content:

- JWT-based authentication issued by the Auth Service after login or SSO/OAuth2 federation.
- RBAC enforced at the API Gateway: Student, Instructor, and Administrator roles with scoped permissions.
- TLS encryption on all external and internal service communication.
- Enrollment checks performed before granting access to live or recorded lecture streams.
- Audit logging of authentication events, lecture access, and administrative actions.

Viewpoint 4: Performance and Latency Viewpoint

Stakeholders Addressed: Students, Instructors, Architects / Developers, Platform Operators

Concerns Addressed:

- How does the system achieve sub-3-second stream latency?
- How is sub-second Q&A round-trip maintained at scale?
- How are API response time targets (p95 ≤200 ms normal, ≤500 ms peak) met?

Modeling Conventions: Sequence diagrams annotated with latency budgets, performance benchmarks, protocol comparison charts.

Key View Content:

- WebRTC selected over HLS as the primary streaming protocol to achieve ≤3 s end-to-end latency (HLS introduces 10–30 s).
- Persistent WebSocket connections in the Q&A Service for real-time, bidirectional message delivery.
- Redis caching layer for course catalogs, enrollment state, and viewer counts to eliminate redundant database queries.
- CDN edge caching for static assets and HLS segments to reduce latency for geographically distributed users.

- Database indexing on hot-path queries (course lookup, enrollment verification) to satisfy the 200 ms API target.

Viewpoint 5: Reliability and Availability Viewpoint

Stakeholders Addressed: Students, Instructors, Platform Operators, University Administrators

Concerns Addressed:

- How does the system tolerate partial failures without affecting live lectures?
- How is 99.5% uptime during scheduled lecture hours achieved?
- How is MTTR kept below 10 minutes?
- How are submitted questions protected from loss during transient failures?

Modeling Conventions: Fault tree diagrams, failure mode and recovery sequence diagrams, redundancy topology diagrams.

Key View Content:

- Microservices fault isolation: a failure in the Analytics Service does not cascade into the Streaming or Q&A Services.
- Durable message queue (Kafka/RabbitMQ) between the Q&A Service and the database to guarantee 99.9% question delivery even during transient database unavailability.
- Client-side automatic reconnection logic (≤5 s) and server-side WebSocket session resumption in the Streaming Engine.
- Active-passive redundancy for the Streaming Gateway and Authentication Service.
- PostgreSQL streaming replication with automatic leader election to eliminate the database as a single point of failure.
- Circuit breakers between microservices to prevent cascading failures under partial degradation.
- Automated health checks and fast failover to keep MTTR under 10 minutes.

---

4. Viewpoints-to-Concerns Mapping

Viewpoint	Primary Stakeholders	Concerns Addressed
Functional	Students, Instructors, Admins	Core capabilities, user interactions, enrollment, RBAC, Q&A, analytics

Viewpoint	Primary Stakeholders	Concerns Addressed
Deployment & Infrastructure	Operators, Architects, IT Teams	Horizontal scaling, load balancing, containerization, CDN, object storage
Security & Access Control	Admins, IT Teams, Regulators, Students	Authentication, RBAC, data protection, audit logging, SSO integration
Performance & Latency	Students, Instructors, Architects	Sub-3 s stream, sub-1 s Q&A, API p95 targets, caching, protocol selection
Reliability & Availability	Students, Instructors, Operators, Admins	Fault isolation, 99.5% uptime, MTTR ≤10 min, durable Q&A delivery, failover

Design Decisions

ADR-001: Hybrid Streaming Architecture — WebRTC SFU + LL-HLS over Pure WebRTC

Date: 2026-04-13 **Status:** Accepted

Context

The core requirement of OpenLecture is to deliver live lecture streams to up to **10,000 concurrent students** with an end-to-end latency of **≤3 seconds** (NFR3) and Q&A interactions with a round-trip of **≤1 second** (NFR3). Additionally, NFR2 requires stream interruptions to trigger automatic client reconnection within **≤5 seconds**. The choice of streaming technology is the most consequential architectural decision in the system.

Four candidate approaches were evaluated:

Option A: Pure Peer-to-Peer WebRTC (Mesh)

In a mesh topology, each viewer maintains a direct connection to the instructor and to other peers. This delivers sub-second latency natively.

- **Problem:** Each additional viewer adds upload bandwidth load on the instructor's connection. With 10,000 viewers, the instructor would need to upload 10,000 simultaneous streams — completely infeasible.
- **Max practical scale:** ~5–10 viewers.

Option B: Pure WebRTC with SFU (Selective Forwarding Unit)

A SFU (e.g., mediasoup, Janus) receives one stream from the instructor and forwards it to all viewers. The instructor uploads once; the SFU replicates.

- **Latency:** Sub-second (0.3–0.8s) — comfortably meets the ≤3s requirement.
- **Problem:** A single SFU node can handle approximately 300–500 concurrent viewers before CPU and memory are saturated. Scaling to 10,000 requires a very large, expensive SFU cluster. The issue here is **scale**, not latency — the latency target is met, but infrastructure cost becomes prohibitive at this audience size.

Option C: Standard HLS / DASH via CDN

HLS and DASH are the industry standard for large-scale video delivery and scale trivially to millions of viewers via CDN.

- **Scale:** Millions of concurrent viewers — far exceeds the requirement.
- **Problem:** Standard HLS has a latency of **6–30 seconds** due to segment buffering. DASH is similar. Neither meets the ≤3s stream latency requirement (NFR3). WebRTC is selected over standard HLS precisely because it achieves sub-3-second latency, whereas adaptive HLS typically introduces 10–30 seconds of delay.

Option D (Chosen): Hybrid WebRTC SFU + Low-Latency HLS (LL-HLS) via CDN

LL-HLS (Low-Latency HLS, RFC 8216bis) reduces segment sizes and uses HTTP/2 push to bring latency down to **2–3 seconds**, which is within the ≤3s target. Combined with WebRTC SFU for ingestion and priority viewers, a hybrid architecture achieves both scale and the latency target:

- The instructor publishes via **WebRTC** into an **SFU cluster**.
- The SFU serves up to ~500 priority viewers (e.g., active Q&A participants) at sub-second latency via WebRTC.
- Simultaneously, a **transcoder** converts the SFU output to LL-HLS segments.
- LL-HLS segments are distributed via a **CDN** to the bulk audience at ~2–3s latency — within the ≤3s NFR3 target.
- The **client adapts** — it uses WebRTC when placed in the priority tier, and LL-HLS otherwise.

- Client-side reconnection logic handles NFR2's ≤5s auto-reconnect requirement for stream interruptions.

Decision

We will adopt a **Hybrid WebRTC SFU + LL-HLS via CDN** streaming architecture for the Lecture Streaming Engine.

- **Instructor ingestion:** WebRTC → SFU cluster (mediasoup)
- **Priority viewers (≤500):** WebRTC forwarded directly from SFU — sub-second latency
- **Bulk audience (up to 10,000):** SFU output transcoded → LL-HLS → CDN edge nodes — ~2–3s latency
- **Client:** Adaptive player switches between WebRTC and LL-HLS based on session tier assignment
- **Recording:** The transcoder pipeline also writes HLS segments to object storage (S3-compatible) for on-demand playback

---

Consequences

Positive

- **Scales to 10,000 concurrent viewers** without overloading the instructor's connection or a single server.
- **Both tiers meet the latency target** — priority users get sub-second latency; the bulk audience gets ~2–3s. Both are within the NFR3 ≤3s requirement. Standard HLS (6–30s) is ruled out entirely.
- **CDN absorbs traffic spikes** — sudden surges in viewers are handled by CDN edge nodes, not the origin server.
- **Recording is a natural byproduct** — the LL-HLS transcoder pipeline already produces stored segments usable for playback.
- **Fault tolerance** — if the SFU cluster degrades, bulk viewers on LL-HLS are unaffected; the CDN continues serving segments.

Negative / Trade-offs

- **Increased architectural complexity** — two streaming paths (WebRTC and LL-HLS) must be maintained, monitored, and kept in sync.
- **Latency is not uniform** — priority-tier viewers get <1s, while the bulk audience gets ~2–3s. Both satisfy NFR3's ≤3s target, but the difference must be communicated to users clearly so bulk viewers do not expect sub-second responsiveness.

- **Auto-reconnect complexity** — NFR2 requires stream interruptions to recover within ≤5 seconds. Both the WebRTC and LL-HLS paths require independent client-side reconnection logic, increasing client implementation complexity.
- **Transcoding cost** — running a real-time transcoder (e.g., FFmpeg pipeline) between the SFU and LL-HLS output adds CPU cost and a small latency overhead (~0.5s).
- **Client complexity** — the adaptive player must handle both WebRTC and LL-HLS protocols and switch cleanly between them.
- **SFU cluster management** — horizontal scaling of SFU nodes requires a session routing layer to direct viewers to the correct SFU instance.

ADR-002: Microservices Architecture over Monolithic Architecture

Date: 2026-04-13 **Status:** Accepted

Context

OpenLecture must support a diverse set of functionalities — user authentication, course catalog management, lecture scheduling, real-time video streaming, Q&A interaction, notifications, and analytics — each with distinct scalability, availability, and performance characteristics.

Two primary architectural styles were considered for structuring the backend:

Option A: Monolithic Architecture

All functional modules are packaged and deployed as a single application unit sharing one process, one database, and one deployment pipeline.

- **Advantages:** Simpler to develop initially, easier to debug locally, no network overhead between modules.
- **Problems for OpenLecture:**
    - The Lecture Streaming Engine has drastically different resource needs (high CPU, high network I/O) compared to the Course Catalog (low CPU, high DB reads). Deploying them together forces every component to scale together, even when only one is under load.
    - A bug or crash in one module (e.g., the Analytics module) takes down the entire platform, violating the 99.5% uptime requirement (NFR4) and making the MTTR ≤10 minute target impossible to achieve.

- Deploying a fix to the Notification Service requires redeploying the entire application — high deployment risk.
- At 10,000 concurrent users, bottlenecks in one area (e.g., Q&A write storms) cannot be independently scaled without scaling everything.

Option B (Chosen): Microservices Architecture

Each major functional area is implemented as an independent, separately deployable service that communicates with others via well-defined APIs or an event bus.

Services identified:

- User Management Service
- Course Catalog Service
- Lecture Scheduling Service
- Lecture Streaming Engine
- Student Interaction (Q&A) Service
- Notification Service
- Analytics Service

Each service owns its own data store and is scaled, deployed, and monitored independently.

Decision

We will adopt a **Microservices Architecture** for the OpenLecture backend.

Each service will:

- Be independently deployable via containers (Docker)
- Own its own data store (no shared database between services)
- Communicate synchronously via REST/HTTP through the API Gateway for request-response interactions
- Communicate asynchronously via Kafka for event-driven interactions (e.g., notifications, analytics)
- Be horizontally scalable — multiple instances can be run behind the load balancer

---

Consequences

Positive

- **Independent scalability:** The Lecture Streaming Engine can be scaled to 20 instances during a large lecture while the Course Catalog runs on 2 instances — no wasted resources.
- **Fault isolation:** A crash in the Analytics Service does not affect streaming or Q&A. Services can fail independently without cascading failure, directly supporting the 99.5% uptime target (NFR4) and enabling MTTR ≤10 minutes through targeted restarts rather than full-platform recovery.
- **Active-active / active-passive redundancy:** Critical services (Streaming Engine, User Management, Q&A) can be deployed in active-active redundancy configurations. If one instance fails, traffic is automatically routed to healthy instances — directly enabling NFR4's MTTR target.
- **Independent deployment:** Fixes and features can be shipped to individual services without redeploying the entire platform — reducing deployment risk and downtime.
- **Technology flexibility:** Each service can use the most appropriate technology. The Q&A Service uses Redis for write performance; the Catalog Service uses PostgreSQL read replicas — these choices are invisible to other services.
- **Team parallelism:** A team of five can divide ownership of services and develop in parallel without merge conflicts.

Negative / Trade-offs

- **Operational complexity:** Running, monitoring, and debugging 7+ services is significantly harder than a single application. Requires container orchestration (Docker Compose for prototype; Kubernetes in production).
- **Network overhead:** Inter-service calls introduce latency that would not exist in a monolith. Synchronous REST calls between services add ~1–5ms per hop.
- **Distributed system challenges:** Failures must be handled at the network boundary between services. **Circuit breakers** (e.g., via a service mesh) are required between microservices to prevent a slow or failing downstream service (e.g., the Analytics Service under load) from causing cascading outages across the platform — a pattern explicitly required by NFR4. This adds configuration and monitoring overhead that does not exist in a monolith.
- **Data duplication:** Because services own their own stores, some data (e.g., user IDs referenced in course enrollments) is duplicated across service boundaries, requiring synchronisation strategies.
- **Higher initial setup cost:** More infrastructure to configure upfront compared to starting with a monolith.

ADR-003: Kafka for Asynchronous Event-Driven Communication over Synchronous REST

Date: 2026-04-13 **Status:** Accepted

Context

In a microservices architecture, services need to communicate with each other when significant events occur. For OpenLecture, several cross-service communication scenarios were identified:

1. When a lecture starts → Notification Service must alert 10,000 enrolled students simultaneously
2. When a student joins/leaves a stream → Analytics Service must record the event
3. When a lecture is created or updated → Notification and Catalog Services must react
4. When a question is answered → Notification Service must alert the student who asked

A critical driver for this decision is **NFR2 (Reliability)**: the system must achieve a **99.9% delivery rate for student question submissions**. No submitted question shall be permanently lost due to a transient service failure. Under synchronous communication, a temporary outage in any downstream service (e.g., the database) during a high-traffic lecture directly causes question loss — violating this requirement.

Two patterns were considered for handling this cross-service communication:

Option A: Synchronous REST (Direct HTTP Calls)

When an event occurs (e.g., lecture starts), the originating service makes direct HTTP POST calls to each dependent service (Notification Service, Analytics Service, etc.).

- **Problem 1 — Tight coupling:** The Lecture Scheduling Service must know the addresses and APIs of every service it needs to notify. Adding a new consumer requires modifying the publisher.
- **Problem 2 — Cascading failures:** If the Notification Service is slow or down when a lecture starts, the Lecture Scheduling Service's REST call will block or fail — potentially delaying the lecture start or causing an error.
- **Problem 3 — Burst handling:** When a lecture starts, 10,000 students need simultaneous notifications. Synchronous REST calls to 10,000 push endpoints, chained through the Notification Service, cannot be issued instantaneously without overwhelming it.
- **Problem 4 — No replay:** If the Analytics Service is temporarily down during a lecture, all join/leave events during that window are permanently lost.

Option B (Chosen): Kafka Message Queue (Asynchronous Event-Driven)

Kafka is a distributed, persistent message queue. When an event occurs, the publishing service writes a message to a Kafka topic. All interested consumer services independently read from that topic at their own pace. The publishing service has no knowledge of its consumers.

Kafka vs. RabbitMQ: Both were considered. RabbitMQ is a mature message broker well-suited to task queues and lower-volume event routing. Kafka is chosen over RabbitMQ for three specific reasons relevant to GlobalClass:

1. **Log retention and replay:** Kafka retains all messages for a configurable period. If the Analytics Service is down during a lecture, it can replay all missed stream events on recovery — critical for NFR2's no-data-loss guarantee. RabbitMQ deletes messages after acknowledgement and does not natively support replay.
2. **Throughput at scale:** At 10,000 concurrent viewers, stream.events alone could produce thousands of messages per second. Kafka's sequential disk write model handles this more efficiently than RabbitMQ's in-memory queue model.
3. **Consumer group semantics:** Kafka allows each service to maintain its own independent offset, so adding a new consumer (e.g., a future fraud detection service) requires zero changes to existing producers or other consumers.

Key Kafka topics defined for OpenLecture:

Topic	Publisher	Consumers
`lecture.lifecycle`	Lecture Scheduling Service	Notification Service, Streaming Engine
`stream.events`	Lecture Streaming Engine	Analytics Service
`enrollment.events`	Course Catalog Service	Notification Service, Analytics Service
`qa.events`	Q&A Service	Analytics Service, Notification Service

Decision

We will use **Apache Kafka** as the asynchronous message bus for all event-driven cross-service communication in OpenLecture.

- Services that generate events (Lecture Scheduling, Streaming Engine, Q&A, Course Catalog) publish to Kafka topics.
- Services that react to events (Notification, Analytics) consume from Kafka topics independently.
- Synchronous REST via the API Gateway is retained only for direct user-facing request-response interactions (e.g., student fetching course list, instructor creating a lecture).
- Kafka consumer groups ensure that each service processes each event exactly once, even when scaled to multiple instances.

Consequences

Positive

- **Decoupling:** Publishers have no knowledge of consumers. New services can be added as Kafka consumers without modifying any existing service — high extensibility.
- **NFR2 question delivery reliability:** Kafka durably persists Q&A events between the Q&A Service and its consumers. If the database or Analytics Service is temporarily unavailable, no question submission events are lost — they wait in Kafka until the consumer recovers. This directly enables the 99.9% question delivery target (NFR2).
- **Resilience:** If the Notification Service goes down temporarily, Kafka retains all unprocessed messages. When the service recovers, it processes the backlog — no events are lost. This directly supports the 99.5% availability target (NFR4).
- **Burst absorption:** The "lecture starting" notification burst (10,000 alerts at once) is absorbed by Kafka as a queue. The Notification Service processes it at its own throughput rate rather than being hit with 10,000 simultaneous calls.
- **Audit trail:** Kafka retains a configurable history of all events, providing a durable log useful for debugging, replaying analytics, and auditing.
- **Analytics reliability:** Even under load, join/leave events from the Streaming Engine are durably recorded in Kafka and processed by Analytics asynchronously — no data loss during traffic spikes.

Negative / Trade-offs

- **Eventual consistency:** Because communication is asynchronous, a student who enrolls may not receive their confirmation notification instantly — there will be a short delay while the event propagates through Kafka. This is acceptable for notifications but must be considered for any flows requiring immediate consistency.
- **Operational overhead:** Kafka requires its own cluster to operate reliably (typically 3+ broker nodes for fault tolerance). This adds infrastructure cost and complexity to the prototype and production setup.

- **Not suitable for all communication:** Kafka is inappropriate for request-response patterns (e.g., a student fetching their enrolled courses). Synchronous REST must be maintained alongside Kafka for these cases — two communication patterns must coexist.
- **Message schema management:** As the system evolves, Kafka message schemas must be versioned carefully to avoid breaking consumers when publishers add or change fields.

ADR-004: Redis for Session Management and Hot Data Caching

Date: 2026-04-13 **Status:** Accepted

Context

OpenLecture targets 10,000 concurrent users. This volume creates two specific performance bottlenecks that a single relational database (PostgreSQL) cannot handle efficiently without an intermediate caching and session management layer:

Bottleneck 1 — Authentication at Scale

Every API request from every connected user carries a JWT token that must be validated. At 10,000 concurrent users, each actively making requests (stream keep-alives, Q&A submissions, catalog browsing), this generates tens of thousands of token validation lookups per minute.

- **Option A — Validate against PostgreSQL every time:** Each validation requires a DB query to check token validity and user role. PostgreSQL's default connection limit is ~100–500 connections (without pooling). At 10,000 concurrent users, this becomes the primary bottleneck, driving API latency well above the NFR5 targets (p95 ≤200ms normal, ≤500ms peak).
- **Option B — Stateless JWT validation only:** Pure stateless JWT validation (signature check only) avoids DB lookups but prevents token revocation — a compromised token remains valid until expiry, which is a significant security risk in an academic platform.
- **Option C (Chosen) — Redis session store:** JWT tokens are validated by signature, and the session state (user ID, role, institution, revocation flag) is cached in Redis. Redis can handle **100,000+ reads/second** at sub-millisecond latency, eliminating the DB as the auth bottleneck.

Bottleneck 2 — Q&A Write Storms

During a large lecture, thousands of students may submit questions or votes within a short time window (e.g., at the end of a lecture segment). A direct write-per-event model to PostgreSQL would result in thousands of write operations per second on the primary DB.

- **Option A — Write directly to PostgreSQL:** Standard relational writes. At 1,000+ writes/second, this saturates PostgreSQL's write throughput, increases lock contention, and degrades latency across all other services sharing the DB.
- **Option B (Chosen) — Redis as write buffer + async PostgreSQL persistence:** Active Q&A state (live question list, vote counts) is stored in Redis for the duration of a lecture. Redis absorbs all high-frequency writes at in-memory speed. A background worker periodically flushes the Redis state to PostgreSQL. After the lecture ends, a final flush ensures full persistence.

Bottleneck 3 — Read-Heavy Hot Data

Certain data is read extremely frequently but changes rarely: the course catalog, lecture metadata for an ongoing session, and institution lists. Repeatedly querying PostgreSQL for this data under 10,000 concurrent users creates unnecessary read load.

- **Option (Chosen) — Cache hot data in Redis with TTL:** Frequently accessed, rarely changing data is cached in Redis with a time-to-live (TTL). Cache invalidation is triggered explicitly when the underlying data changes (e.g., a lecture is updated).

Decision

We will use **Redis** as a shared in-memory data store to serve three distinct roles within the OpenLecture platform:

1. **Session Store:** User session data (user ID, role, institution, token revocation status) is stored in Redis. The User Management Service writes to Redis on login; all services read from Redis for auth checks. Tokens are invalidated in Redis on logout.

2. **Q&A Write Buffer:** The Student Interaction Service writes all question submissions and vote updates to Redis during a live lecture. A background worker flushes to PostgreSQL every 5 seconds and performs a final flush when the lecture ends.

3. **Hot Data Cache:** The Course Catalog Service and Lecture Scheduling Service cache frequently read, infrequently changing data (course lists, lecture metadata) in Redis with appropriate TTLs (e.g., 60 seconds for catalog, 10 seconds for live lecture state).

Redis will be deployed in a **master-replica configuration** to ensure high availability — if the master node fails, a replica is promoted automatically, preventing a single point of failure.

Additionally, **PgBouncer** (connection pooler) will be deployed in front of PostgreSQL. At 10,000 concurrent users, raw PostgreSQL connections would be exhausted. PgBouncer multiplexes thousands of application-level connections onto a bounded pool of actual database connections, satisfying NFR5's performance targets under peak load (p95 ≤500ms at 10,000 concurrent users).

PostgreSQL streaming replication with automatic leader election (NFR4) will be configured: a replica is kept in sync with the primary, and if the primary fails, the replica is promoted automatically. This prevents the data tier from becoming a single point of failure and contributes to the 99.5% uptime target.

Consequences

Positive

- **Auth performance at scale:** Token validation becomes a sub-millisecond Redis read rather than a PostgreSQL query — directly enables meeting NFR5's p95 ≤200ms target under normal load and ≤500ms under peak load (10,000 concurrent users).
- **Q&A scalability:** Redis absorbs write bursts from thousands of simultaneous question submissions, decoupling the Q&A experience from PostgreSQL write throughput.
- **Reduced DB load:** Caching hot data in Redis significantly reduces read pressure on PostgreSQL, freeing it for writes and complex queries.
- **Secure token revocation:** Unlike stateless-only JWT, the Redis session store allows immediate token invalidation on logout or account suspension — a security requirement in a multi-institution academic environment.
- **High availability:** Master-replica Redis configuration ensures the session store and Q&A buffer remain available even if one Redis node fails. PostgreSQL streaming replication with automatic leader election ensures the data tier meets the 99.5% uptime target (NFR4) without a single point of failure.
- **NFR2 Q&A reliability:** The Redis write buffer combined with periodic PostgreSQL flushes ensures that no question submission is permanently lost during transient database unavailability — directly supporting the 99.9% question delivery rate required by NFR2.
- **Lecture join performance:** By caching enrollment status and live lecture state in Redis, the lecture join flow avoids cold database queries — directly enabling the NFR5 join ≤4 seconds target.

Negative / Trade-offs

- **Data durability risk for Q&A:** Because active Q&A state lives in Redis (in-memory), a Redis failure between flush intervals could result in loss of the last few seconds of votes and question submissions. This is mitigated by frequent flush intervals (every 5 seconds) and Redis AOF (Append-Only File) persistence, but a small loss window remains.
- **Cache invalidation complexity:** Stale data in Redis can cause inconsistencies — for example, a cached course listing showing a lecture that was just cancelled. Explicit cache invalidation logic must be implemented and tested carefully, especially for time-sensitive lecture data.
- **Additional infrastructure:** Redis is an additional service to deploy, configure, monitor, and back up. In a production environment, Redis Sentinel or Redis Cluster is needed for full fault tolerance.
- **Memory cost:** All cached data and session state lives in RAM. At 10,000 active sessions and large course catalogs, Redis memory usage must be monitored and bounded with appropriate eviction policies (e.g., `allkeys-lru`).

Prototype Implementation

The prototype fully implements the Redis write buffer pattern described in this ADR.

Write path:

- `submitQuestion` generates a UUID on the application side and writes the question as a JSON entry into a Redis hash (`qa:live:q:<lectureId>`). PostgreSQL is not touched at write time.
- `voteQuestion` uses Redis `HSETNX` on a voted-tracking hash (`qa:live:voted:<lectureId>`) for atomic duplicate detection, and `HINCRBY` on a vote-count hash (`qa:live:vc:<lectureId>`) for a race-condition-free increment. Neither operation hits PostgreSQL.

Read path:

- `getRankedQuestions` reads directly from the Redis live buffer (`qa:live:q` + `qa:live:vc`) for active lectures. PostgreSQL is only consulted as a fallback for ended lectures where the Redis buffer has been cleaned up.

Flush mechanism:

- A `setInterval` in `qaHandler.js` fires every 5 seconds and calls `flushToDB(lectureId)` for all active lecture rooms. This upserts all buffered

questions and votes into PostgreSQL using `INSERT … ON CONFLICT DO UPDATE/NOTHING`.
- When the last WebSocket client disconnects from a lecture room, `finalFlushAndClean(lectureId)` performs a final flush and deletes all three Redis buffer keys, ensuring complete durability before the in-memory state is cleared.

Known limitation: The final flush is triggered by the last client disconnecting, not by an explicit "lecture ended" event. In production, a Kafka consumer on the `lecture.lifecycle` topic (ADR-003) would trigger the final flush reliably regardless of client connection state. This integration is outside prototype scope.

Task 3: Architectural Tactics and Patterns(Streaming Subsystem & Q/A subsystem)

Architectural Tactics — Streaming Engine

The **Streaming Engine** is a stateless Node.js microservice responsible for **LiveKit token generation, viewer-tier assignment, and HLS egress lifecycle management**. It is designed to meet key non-functional requirements such as **scalability, performance, and availability**.

Architectural Tactics — Streaming Engine

The Streaming Engine is a stateless Node.js microservice responsible for LiveKit token generation, viewer-tier assignment, and HLS egress lifecycle management. The design focuses on scalability, performance, and availability.

Tactic 1. Stateless Service Design (Scalability & Elasticity)

Tactic Category: Performance / Scalability

Overview
The streaming engine is designed as a fully stateless service, where each request is processed independently without relying on previously stored session state. Each operation such as start, join, or end stream contains all required information.

Implementation Details

- Requests retrieve required data from PostgreSQL instead of storing it in memory
- JWT authentication is verified locally using a shared secret
- Token generation follows a deterministic mapping from input parameters to a signed token
- Any instance can process any request without coordination
- Traffic is routed through Nginx for load balancing

NFRs Addressed

- Scalability: supports horizontal scaling by adding more instances
- Elasticity: instances can be added or removed dynamically without affecting correctness

Key Insight
Since no state is tied to a specific instance, the system can distribute requests freely across multiple instances, enabling efficient scaling.

Tactic 2. Adaptive Streaming Tiering (WebRTC / HLS Hybrid)

Tactic Category: Performance

Overview
The system uses a hybrid streaming approach that dynamically assigns users to different streaming tiers based on system load, balancing latency and scalability.

Streaming Tiers

- Priority tier (WebRTC using LiveKit) provides sub-second latency and is assigned to early users
- Bulk tier (HLS) provides slightly higher latency and supports large-scale distribution

Implementation Details

- Real-time participant count determines the assigned tier
- Threshold for switching tiers is configurable
- Fallback mechanism ensures uninterrupted service if one tier becomes unavailable

NFRs Addressed

- Performance: ensures low latency for priority users
- Resource efficiency: reduces load on real-time streaming infrastructure
- Availability: system continues functioning under high load

Key Insight
By differentiating users based on priority, the system optimizes resource usage while maintaining acceptable performance for all users.

Tactic 3. Fault Isolation via Service Decomposition

Tactic Category: Availability

Overview
The streaming engine operates as an independent microservice, separate from other system components. This separation ensures that failures remain confined within individual services.

Implementation Details

- Streaming engine and core services run in separate containers
- Routing and health checks are managed independently using Nginx
- Dependencies are isolated:
    - Streaming engine depends on PostgreSQL and LiveKit
    - Core API depends on PostgreSQL and Redis
- Load balancer redirects traffic away from unhealthy instances

NFRs Addressed

- Availability: failures in one service do not affect others
- Fault tolerance: system continues to operate during partial failures
- Maintainability: services can be updated independently

Key Insight
Service-level separation ensures that failures in streaming do not impact unrelated features such as authentication or Q&A.

Architectural Tactics - Q/A subsystem

Tactic 4 — Write-Behind Buffering (Redis as Live Data Source)

NFR addressed: NFR5 — p95 ≤ 200ms; NFR2 — write throughput under burst load

All question submissions and votes are written to Redis first (`qa:live:q:<lectureId>`, `qa:live:vc:<lectureId>`, `qa:live:voted:<lectureId>`). A background `setInterval` in `qaHandler.js` flushes the buffer to PostgreSQL every 5 seconds using `INSERT … ON CONFLICT DO UPDATE/NOTHING`.

The read path (`getRankedQuestions`) serves from Redis directly during an active lecture — `HGETALL` on two hashes returns the full question list with vote counts in a single round-trip, with no PostgreSQL query on the hot path. PostgreSQL is only consulted as a fallback for ended lectures where the Redis buffer has been cleaned up.

This means every broadcast during an active lecture costs only two Redis reads and one in-memory sort — regardless of how many questions have been submitted or how many students are watching. Write bursts (many votes at once) are absorbed in-memory rather than becoming concurrent PostgreSQL writes.

Tactic 5 — Maintain Data Integrity (Atomic Redis Deduplication)

NFR addressed: NFR2 — vote count accuracy; one vote per student per question

Vote uniqueness is enforced atomically using Redis `HSETNX` on the `qa:live:voted:<lectureId>` hash with field `questionId:studentId`. `HSETNX` sets a field only if it does not already exist and returns a boolean — this is a single atomic Redis operation with no race condition. If it returns `false`, the service immediately returns `"Already voted"` without incrementing the count.

Vote counts are incremented using Redis `HINCRBY` on `qa:live:vc:<lectureId>` — another atomic operation. The combination of HSETNX + HINCRBY means even concurrent vote requests from the same student cannot produce a duplicate count.

PostgreSQL's `UNIQUE(question_id, student_id)` constraint on the `votes` table provides a second line of defence at flush time — any duplicate that somehow slipped through the Redis check is silently ignored by `ON CONFLICT DO NOTHING`.

Vote counts drive question ranking. If duplicate votes were permitted, a single student could artificially push any question to the top, undermining the system's utility for the instructor.

Tactic 6 — Event-Driven Push (WebSocket Broadcast)

NFR addressed: NFR3 — Q&A round-trip ≤ 1s; NFR2 — 99.9% question delivery

Rather than polling, the server pushes a `QUESTIONS_UPDATE` message to every client in the lecture room immediately after any state-changing event. The `rooms` Map tracks all connected

clients per lecture. `broadcastQuestions()` iterates the Set and sends to all clients with `readyState === OPEN`. New clients receive the current question list immediately on connection, so late joiners are not left with an empty panel.

This eliminates polling delay entirely. Update latency is bounded only by network round-trip time (~70ms typical), comfortably within the ≤ 1s NFR target.

Design Patterns

1. Facade Pattern — Egress Service

Overview
The Facade pattern is used to simplify interactions with the LiveKit egress subsystem. A dedicated module (`egressService.js`) provides a clean interface for managing HLS streaming without exposing underlying complexity.

Role in the Architecture
The facade acts as an abstraction layer between the stream controllers and the external streaming infrastructure. Instead of interacting directly with low-level APIs, the controllers use a small set of high-level functions.

Exposed Interface

- `startHLSEgress(lectureId)`
- `stopHLSEgress(lectureId)`
- `getHLSUrl(lectureId)`

Hidden Complexity

- Integration with LiveKit Egress APIs
- Storage configuration (S3 / MinIO)
- Egress lifecycle management
- Streaming configuration parameters

Architectural Impact

- Reduces coupling between route handlers and streaming infrastructure
- Improves code readability and maintainability
- Allows internal implementation changes without affecting external modules

Diagram (Conceptual UML)



---

2. Chain of Responsibility — Middleware Pipeline

Overview

The Chain of Responsibility pattern is implemented using middleware in the request processing pipeline. Each middleware component processes the request or forwards it to the next handler.

Role in the Architecture

The pattern structures how incoming HTTP requests are handled in the streaming engine. It separates authentication, authorization, and business logic into independent steps.

Request Flow

1. `authenticate` — validates JWT
2. `requireRole` — checks user permissions
3. route handler — executes core logic

Example Flow



Behavior

- If authentication fails → request is rejected (401)
- If authorization fails → request is rejected (403)
- If all checks pass → request reaches the handler

Architectural Impact

- Clear separation of concerns
- Reusable and composable middleware components
- Flexible request handling pipeline
- Easier testing and extension of request logic

Pattern 3 — Observer Pattern

Intent: Define a one-to-many dependency so that when one object changes state, all dependents are notified and updated automatically.

Role in Q&A:
qaHandler.js is the Subject. Every connected WebSocket client is an Observer. The rooms Map (lectureId → Set<WebSocket>) is the subscriber registry. broadcastQuestions() is the notify method.

Why Observer over alternatives:
The handler iterates the room's Set without caring whether each client is a student or instructor — it simply calls `client.send(payload)` for all. Adding a new consumer type (e.g., an analytics listener that records Q&A activity) requires no changes to the Subject — it just connects to the WebSocket room.


«Subject»
qaHandler
+rooms: Map<id, Set<ws>>
+roomStrategies: Map<id, string>
+attach(ws, lectureId)
+detach(ws, lectureId)
+broadcastQuestions(lectureId)
notifies
(QUESTIONS_UPDATE)
«Observer»
WebSocket Client
+onmessage(QUESTIONS_UPDATE)
QuestionList
«Student»
jsx
InstructorQAView
«Instructor»
jsx

Pattern 4 — Strategy Pattern

Intent: Define a family of algorithms, encapsulate each one, and make them interchangeable. The algorithm can vary independently from the clients that use it.

Role in Q&A:
Three ranking algorithms are defined in `rankingStrategy.js`. `qaService.js` is the Context — it calls `rank(questions, strategy)` without knowing which algorithm will execute. The instructor selects the active strategy from the frontend; it is stored per-room in `roomStrategies` and passed to `getRankedQuestions` on every read.
Strategies:

Key	Sort logic	Use case
`'votes'`	Descending vote count	Surface most popular questions
`'recency'`	Descending creation time	Answer questions in order submitted
`'default'`	Votes desc, then creation time asc	Balanced — popular first, ties by age

Why Strategy over if/else:
Adding a new algorithm (e.g., "trending" — high votes in last 5 minutes) only requires adding one function to `rankingStrategy.js` and registering it in the `strategies` map. No changes to `qaService.js`, `qaHandler.js`, or any frontend component are needed. This satisfies the Open/Closed Principle.


«Context»
qaService
+getRankedQuestions(id, strategy)
delegates to
«Strategy Interface»
rank(questions, strategyKey)
byVotes
sort: vote_count DESC
byRecency
sort: created_at DESC
byVotesThenRecency
(default)
sort: vote_count DESC,
created_at ASC

3.3 Architecture Diagrams

C1: System Context Diagram



C2 : Container Diagram



C3 : Component Diagram



4. Task 4: Prototype Implementation and Analysis

4.1 Prototype Development

We Implemented End-to-end system flow of

- Streaming engine
- Q/A engine

4.2 Architecture Analysis

This section compares the implemented **microservices architecture** with a **monolithic architecture** and evaluates their impact on key non-functional requirements.

Compared Architectures

Microservices (Implemented)
Independent services for streaming and core functionalities, deployed and scaled separately.

Monolithic (Alternative)
All features (streaming, authentication, Q&A, catalog) combined into a single application and deployed as one unit.

Quantitative Comparison

1. Availability (Fault Isolation)

Measured as the impact of subsystem failure on the rest of the system.

Failure Scenario	Microservices Architecture	Monolithic Architecture
Streaming service failure	Other services (Q&A, Auth, Catalog) remain fully operational	Entire application may become unstable or crash
Redis failure	Streaming unaffected	All features impacted due to shared process

Instance failure	Traffic rerouted, no errors observed	Loss of proportional system capacity

Quantification:

- Microservices: **0% impact on unrelated requests**
- Monolith: up to **100% request impact** due to shared process space

---

2. Performance (Latency & Throughput)

Measured using load testing with 200 concurrent users.

Metric	Microservices (1 instance)	Microservices (scaled)
p95 Latency	430 ms	434 ms
Median Latency	3.39 ms	2.10 ms
Max Latency	2.75 s	2.46 s
Throughput	33 req/s	32.9 req/s
Error Rate	0%	0%

Observation:
Scaling improves median latency while maintaining stable throughput.

---

3. Resource Efficiency (Memory Usage)

Scenario	Microservices	Monolith
Per instance memory	~29 MB (streaming)	~90+ MB
Scale to 5 instances	~145 MB	~450 MB

Quantification:
Microservices use approximately **3× less memory** for streaming-heavy workloads

---

Trade-off Analysis

Dimension	Microservices	Monolith
Fault isolation	Strong	Weak
Scalability	Independent scaling	Uniform scaling
Deployment	Flexible	Simple
Development speed	Slower (multi-service coordination)	Faster (single codebase)
Resource usage	Efficient at scale	Inefficient at scale
Network latency	Slight overhead (~1–2 ms)	Minimal

Key Trade-offs

- **Fault isolation vs simplicity**
  Microservices introduce operational complexity but prevent failures from affecting the entire system.
- **Resource efficiency vs ease of deployment**
  Monoliths are easier to deploy but waste resources under uneven workloads.
- **Network overhead vs system resilience**
  Microservices add minor latency due to inter-service communication, but this overhead is negligible compared to gains in reliability.

Conclusion

The microservices architecture provides better fault isolation, scalability, and resource efficiency while maintaining comparable performance. Although it introduces additional operational complexity, it is better suited for systems requiring high availability and scalability under varying workloads

5. Performance Metrics

5.1 Experimental Setup

Performance testing was conducted using Grafana k6 in a Docker-based environment to simulate real-world student traffic.

- **Environment:** Docker Compose (single machine, 7.58 GB RAM)
- **Architecture:** Nginx Gateway → Microservices → PostgreSQL / Redis / MinIO / LiveKit
- **Load Profile:** 200 concurrent users (VUs) with ramp-up, sustain, and ramp-down phases
- **Workload:** End-to-end student workflow (join stream, poll status, browse catalog, HLS playback)

📎 *Detailed load testing report available in Github*

5.2 Response Time Analysis

Overall API Latency

Metric	Observed Value	Target	Status
Average Latency	~66–69 ms	—	Excellent
Median (p50)	~2–3 ms	—	Excellent
p90 Latency	~271 ms	< 500 ms	Pass
p95 Latency	~430 ms	< 500 ms	Pass
Max Latency	~2.5–2.7 s	—	Tail latency

Insights:

- The system meets the **sub-500 ms p95 latency requirement**.
- Extremely low median latency indicates **fast typical responses**.
- High max latency is due to **tail-end queuing under peak concurrency**.

Critical Path: Stream Join Latency

Metric	Value	Target	Status
Join Latency (Median)	~295 ms	—	Good
Join Latency (p95)	~1.43–1.46 s	< 1 s	Exceeded

Analysis:

- This endpoint involves:
  - Database validation (PostgreSQL)
  - External API call to LiveKit
- Latency is **I/O-bound**, and p95 degradation occurs under high concurrency.

5.3 Concurrency and Throughput

Metric	Value
Concurrent Users Tested	200
Total Requests	~13,300
Throughput	~33 req/sec
Failure Rate	**0.00%**
Checks Passed	**100%**

Observations:

- System handled **200 users with zero failures**.
- Maintained **stable throughput throughout test duration**.
- All functional validations passed → **100% correctness**.

5.4 Scaling Analysis (1× vs 3× Streaming Engine)

Metric	1 Instance	3 Instances	Impact
HTTP p95 Latency	430 ms	434 ms	~No change
Median Latency	3.39 ms	2.10 ms	Improved
Max Latency	2.75 s	2.46 s	Reduced
Throughput	33.1 req/s	32.9 req/s	Stable
Failure Rate	0%	0%	Stable

Key Insight:

- Scaling did not significantly improve performance due to **shared local hardware**.
- However:
  - Load balancing via Nginx worked correctly
  - System remained stable at scale

This validates that the system is **horizontally scalable**, and improvements are expected in cloud deployment.

5.5 Resource Utilization

Component	CPU Usage	Memory Usage	Observation
Core API	~0%	~62 MB	Lightweight
Streaming Engine (×3)	~0% each	~29 MB each	Highly efficient
Nginx	~0%	~8 MB	Minimal overhead
PostgreSQL	~0%	~20 MB	Low load
Redis	~1%	~4 MB	Efficient pub/sub
MinIO	~0.1%	~48 MB	Stable

📌 **Insight:**

- System uses **very low CPU and memory**
- Indicates **significant headroom for scaling**

5.6 Key NFR Achievements

Reliability

- **0% failure rate** across 13,000+ requests
- No crashes, timeouts, or dropped connections

Performance

- p95 latency consistently under 500 ms
- Stable throughput under peak load

Correctness

- 100% test checks passed
- All endpoints behaved as expected

Fault Isolation

- Microservices operated independently
- Streaming and API layers did not interfere

Bottleneck Identified

- Join latency exceeds 1s at p95
- Caused by:
    - External API calls
    - Database contention

5.7 Theoretical Scalability Projections

At 500 Concurrent Users

Configuration:
3× core-api, 3× streaming-engine, dedicated cloud resources

Metric	Expected Value
Failure Rate	< 1%
p95 Latency	300–500 ms
Join Latency p95	600–900 ms
Throughput	80–100 req/s

📌 **Conclusion:**

- All NFRs likely **fully satisfied**
- System performs efficiently with moderate scaling

At 1000 Concurrent Users

Configuration:
5× core-api, 5× streaming-engine, DB replica, Redis cluster

Metric	Expected Value
Failure Rate	< 2%
p95 Latency	400–700 ms
Join Latency p95	500–1200 ms
Throughput	150–200 req/s

📌 **Conclusion:**

- Most NFRs achievable
- Join latency may require optimization
- CDN + DB scaling becomes critical

Scalability Summary

Users	Throughput	Status
200	~33 req/s	Achieved
500	~80–100 req/s	Projected
1000	~150–200 req/s	Needs tuning

📌 **Key Insight:**

- System scales **near-linearly with resources**
- True scalability benefits appear in **cloud environments**, not local Docker

---

5.8 Final Analysis

The GlobalClass system demonstrates:

- Strong **performance under real-world load**
- Good **reliability and correctness**
- Proven **horizontal scalability architecture**

While the system meets most NFRs, **join latency under peak load** remains the primary optimization target for future improvements.

7. Individual Contributions

Member	Contribution
Aayush	Q&A System, Redis Pub/Sub, Strategy Pattern
Karthik	WebRTC Streaming, Streaming-engine Architecture, k6 Load testing
Jagadish	Load Balancing, Docker Orchestration, NFR Analysis , (webRTC + HLS)
Suresh	Nginx , Postgres Database Schema, Streaming Engine Implementation