

```
In [ ]: import numpy as np
import matplotlib.pyplot as plt
from mpl_toolkits.mplot3d import Axes3D

from scipy.integrate import solve_ivp

from sir_model import *
```

```

In [ ]: # parameters
random_state = 12345
t_0 = 0
t_end = 1000
NT = t_end-t_0
# if these error tolerances are set too high, the solution will be qualitatively (!) wrong
rtol=1e-8
atol=1e-8

# SIR model parameters
beta=11.5
A=20
d=0.1
nu=1
b=0.01 # try to set this to 0.01, 0.020, ..., 0.022, ..., 0.03
mu0 = 10 # minimum recovery rate
mu1 = 10.45 # maximum recovery rate

# information
print("Reproduction number  $R_0$ =",  $R_0(\text{beta}, \text{d}, \text{nu}, \text{mu1})$ )
print('Globally asymptotically stable if  $\text{beta} \leq \text{d} + \text{nu} + \text{mu0}$ . This is',  $\text{beta} \leq \text{d} + \text{nu} + \text{mu0}$ )

# simulation
rng = np.random.default_rng(random_state)

SIM0 = rng.uniform(low=(190, 0, 1), high=(199,0.1,8), size=(3,))

time = np.linspace(t_0,t_end,NT)
sol = solve_ivp(model, t_span=[time[0],time[-1]], y0=SIM0, t_eval=time, args=(mu0, mu1, beta, A, d, nu, b), method=
'LSODA', rtol=rtol, atol=atol)

fig,ax = plt.subplots(1,3,figsize=(15,5))
ax[0].plot(sol.t, sol.y[0]-0*sol.y[0][0], label='1E0*susceptible');
ax[0].plot(sol.t, 1e3*sol.y[1]-0*sol.y[1][0], label='1E3*infective');
ax[0].plot(sol.t, 1e1*sol.y[2]-0*sol.y[2][0], label='1E1*removed');
ax[0].set_xlim([0, 500])
ax[0].legend();
ax[0].set_xlabel("time")
ax[0].set_ylabel(r"$S,I,R$")

```

```
ax[1].plot(sol.t, mu(b, sol.y[1], mu0, mu1), label='recovery rate')
ax[1].plot(sol.t, 1e2*sol.y[1], label='1E2*infective');
ax[1].set_xlim([0, 500])
ax[1].legend();
ax[1].set_xlabel("time")
ax[1].set_ylabel(r"$\mu, I$")

I_h = np.linspace(-0.,0.05,100)
ax[2].plot(I_h, h(I_h, mu0, mu1, beta, A, d, nu, b));
ax[2].plot(I_h, 0*I_h, 'r:')
#ax[2].set_ylim([-0.1,0.05])
ax[2].set_title("Indicator function h(I)")
ax[2].set_xlabel("I")
ax[2].set_ylabel("h(I)")

fig.tight_layout()
```

```

In [ ]: fig=plt.figure(figsize=(5,5))
ax=fig.add_subplot(111,projection="3d")
time = np.linspace(t_0,15000,NT)

cmap = ["BuPu", "Purples", "bwr"][1]

#SIM0 = [195.3, 0.052, 4.4] # what happens with this initial condition when b=0.022? -- it progresses VERY slowly.
#Needs t_end to be super large.
#sol = solve_ivp(model, t_span=[time[0],time[-1]], y0=SIM0, t_eval=time, args=(mu0, mu1, beta, A, d, nu, b), method
='DOP853', rtol=rtol, atol=atol)
#ax.plot(sol.y[0], sol.y[1], sol.y[2], 'r-');
#ax.scatter(sol.y[0], sol.y[1], sol.y[2], s=1, c=time, cmap='bwr');

SIM0 = [195.7, 0.03, 3.92] # what happens with this initial condition when b=0.022?
sol = solve_ivp(model, t_span=[time[0],time[-1]], y0=SIM0, t_eval=time, args=(mu0, mu1, beta, A, d, nu, b), method=
'DOP853', rtol=rtol, atol=atol)
ax.scatter(sol.y[0], sol.y[1], sol.y[2], s=1, c=time, cmap=cmap);

SIM0 = [193, 0.08, 6.21] # what happens with this initial condition when b=0.022?
sol = solve_ivp(model, t_span=[time[0],time[-1]], y0=SIM0, t_eval=time, args=(mu0, mu1, beta, A, d, nu, b), method=
'DOP853', rtol=rtol, atol=atol)
ax.scatter(sol.y[0], sol.y[1], sol.y[2], s=1, c=time, cmap=cmap);

ax.set_xlabel("S")
ax.set_ylabel("I")
ax.set_zlabel("R")

ax.set_title("SIR trajectory (unfinished)")
fig.tight_layout()

```

In []: