

Pausing the rollout process

Trigger a rollout by changing the image to `luksa/kubia:v4`, but then immediately (within a few seconds) pause the rollout:

```
kubectl set image deployment kubia nodejs=luksa/kubia:v4
```

```
deployment.apps "kubia" image updated
```

```
kubectl rollout pause deployment kubia
```

```
deployment.apps "kubia" paused
```

A single new pod should have been created, but all original pods should also still be running. Once the new pod is up, a part of all requests to the service will be redirected to the new pod. This way, you've effectively run a canary release.

```
kubectl get rs
```

NAME	DESIRED	CURRENT	READY	AGE
kubia-54c887cf4d	0	0	0	31m
kubia-5857d5f9ff	0	0	0	39m
kubia-6bb8b7b85c	1	1	1	52s
kubia-6fc8ff6566	3	3	3	57m

A canary release is a technique for minimizing the risk of rolling out a bad version of an application and it affecting all your users. Instead of rolling out the new version to everyone, you replace only one or a small number of old pods with new ones. This way only a small number of users will initially hit the new version. You can then verify whether the new version is working fine or not and then either continue the rollout across all remaining pods or roll back to the previous version.

```
while true; do curl 35.232.43.157:32229; done
```

```
This is v4 running in pod kuba-6bb8b7b85c-zhh9t
This is v1 running in pod kuba-6fc8ff6566-vh5zj
This is v1 running in pod kuba-6fc8ff6566-9j26j
^C
```

Once you're confident the new version works as it should, you can resume the deployment to replace all the old pods with new ones:

```
kubectl rollout resume deployment kuba
```

```
deployment.apps "kuba" resumed
```

```
kubectl get rs
```

NAME	DESIRED	CURRENT	READY	AGE
kuba-54c887cf4d	0	0	0	36m
kuba-5857d5f9ff	0	0	0	43m
kuba-6bb8b7b85c	3	3	3	5m

Obviously, having to pause the deployment at an exact point in the rollout process isn't what you want to do. In the future, a new upgrade strategy may do that automatically, but currently, the proper way of performing a canary release is by using two different Deployments and scaling them appropriately.

Pausing a Deployment can also be used to prevent updates to the Deployment from kicking off the rollout process, allowing you to make multiple changes to the Deployment and starting the rollout only when you're done making all the necessary changes. Once you're ready for changes to take effect, you resume the Deployment and the rollout process will start.

Note *If a Deployment is paused, the undo command won't undo it until you resume the Deployment.*