AegisGuard

Real-Time Transaction Fraud Prevention & Adaptive Authentication Engine

YouTube Video Demo Guide, Script & System Walkthrough
Created for Presenters, Video Explaners, and Hackathon Demonstrations

SUB-MILLISECOND (<15MS) LATENCY | 3-TIER ADAPTIVE DECISIONS | BEHAVIORAL BIOMETRICS | IMPOSSIBLE TRAVEL DETECTION | 100% EXPLAINABLE SIGNALS

🚀 Quick Guide for the Presenter (Start Here!)

Welcome! If you're recording the demo video for YouTube and are new to this project, **don't panic**. This document is written specifically for you. You don't need prior fraud-detection experience:

- **Section 1 & 2:** Gives you the background: why fraud detection is broken today and what makes AegisGuard revolutionary.
- **Section 3 & 4:** Explains how the engine works under the hood so you sound like an industry veteran.
- **Section 5:** Gives you the 2-minute terminal setup to run the app on your computer.
- **Section 6:** Provides a **word-for-word YouTube script** with exact click-by-click instructions!
- **Section 7 & 8:** Provides FAQs, YouTube tags, descriptions, and timestamps ready to paste into YouTube.

1. Problem Statement: Why Fraud Detection is Broken Today

In modern global commerce, over **$35 Trillion** in digital transactions occur every year. However, online merchants and financial institutions face a devastating dilemma known as the **Fraud-Friction Paradox**:

THE INDUSTRY CHALLENGE	WHY TRADITIONAL SOLUTIONS FAIL	DIRECT BUSINESS IMPACT
1. High Fraud Losses	Card-Not-Present (CNP) fraud, automated credential stuffing, and botnets steal $48 Billion annually. Attackers use headless browsers to test stolen credentials in seconds.	Direct chargebacks, processor fines, and lost merchandise.
2. Severe Cart Abandonment	To stop fraud, legacy systems force mandatory SMS/OTP codes or 3D-Secure prompts on *every single checkout*.	**15% to 25% cart abandonment**. Frustrated good customers give up and leave.
3. Opaque "Black-Box" ML	Modern AI models output an arbitrary fraud probability score (e.g., 0.87) with zero justification for why a customer was declined.	Customer support cannot help, compliance audits fail under FCRA/GDPR, and merchants don't trust the engine.
4. Slow Processing Latency	Asynchronous legacy risk engines take 300ms to 2,000ms to compute risk scores, causing sluggish checkouts.	Every 100ms delay drops e-commerce conversion rates by 1%.

💡 **The Core Question We Answer:**

"How can an online platform stop automated bot attacks and account takeovers in sub-15ms, reward trusted users with frictionless one-click payments, and explain 100% of its decision reasoning transparently?"

2. Why We Built AegisGuard: The Solution & Vision

AegisGuard was engineered from the ground up as a **real-time, cloud-native fraud scoring and adaptive step-up authentication microservice**. Instead of treating all checkouts with the same heavy-handed hurdles, AegisGuard dynamically measures silent telemetry and behavioural signals in the background.

The Four Architectural Pillars of AegisGuard:

1. **Zero-Friction Behavioral Telemetry:** Passively measures how the user interacts with the payment form—mouse movement curvature/jitter entropy, inter-keystroke timing intervals (cadence), dwell time, and clipboard paste detection. Human typing is naturally variable; automated bot scripts type with robotic, zero-variance speed or paste instant strings.
2. **Physical Impossible Travel Calculations (Haversine Formula):** Calculates geographic distance and elapsed time between the current transaction and the customer's previous authorized transaction. If a customer transacted in New York 10 minutes ago and suddenly checks out from Miami (1,750 km away), that requires an impossible physical speed of 10,500 km/h (Mach 8.5)—instantly triggering a challenge!
3. **Three-Tier Adaptive Decisions (ALLOW, CHALLENGE, BLOCK):**
   - `ALLOW (0 – 29)`: Instant approval in ~10–15ms. 95%+ of trusted customers experience zero hurdles.
   - `CHALLENGE (30 – 74)`: Step-up TOTP verification. Instead of blocking a user on a new device or travel VPN, we allow them to prove their identity safely. Successful verification registers the device as trusted.
   - `BLOCK (75 – 100)`: Automated immediate stoppage of botnets, blacklisted IP ranges, and brute-force attacks.
4. **100% Explainable Decision Weights:** Every decision returns the exact signals that contributed to the score, with normalized weights that add up precisely to the final risk number. No black boxes.

3. Under the Hood: Scoring Engine & Signal Weights

The evaluation pipeline executes in two high-speed stages configured in `server/src/config/weights.js`:

- **Stage 1 (Pre-Filters):** Fast-fail rules checking IP subnet blacklists and hard velocity violations.
- **Stage 2 (Weighted Pipeline):** Evaluates travel physics, hardware consistency, behavioral biometrics, and spend anomalies.

CATEGORY	SIGNAL FACTOR NAME	WEIGHT	CONDITION & BEHAVIORAL EVIDENCE
PRE-FILTER	`blacklisted_ip_or_subnet`	+50	IP address belongs to known commercial VPN, Tor exit node, or botnet CIDR.
PRE-FILTER	`hard_rate_limit_violation`	+60 / BLOCK	More than 5 checkout attempts from the same entity in under 60 seconds.
TRAVEL	`impossible_travel`	+40	Implied displacement speed exceeds **900 km/h** (commercial airliner speed).
TRAVEL	`rapid_displacement`	+25	Implied displacement speed between 500 km/h and 900 km/h.
DEVICE	`unrecognized_device`	+20	Canvas and WebGL browser hardware hash is not in customer's trusted registry.
DEVICE	`trusted_device`	-5	Hardware fingerprint matches a pre-verified device bound to the user profile.
DEVICE	`automated_browser_environment`	+35	Headless Chrome, Puppeteer, Selenium, or PhantomJS navigator flags detected.
BEHAVIOR	`clipboard_paste_sensitive_field`	+25	Direct paste event recorded on sensitive credit card number or CVV input.
BEHAVIOR	`superhuman_form_fill_speed`	+25	Total form dwell time is under 1,500 ms (impossible for human reading and typing).
BEHAVIOR	`zero_mouse_entropy`	+20	Mouse curvature and trajectory jitter score is ≤ 0.05 (straight-line bot script).
BEHAVIOR	`robotic_keystroke_cadence`	+25	Inter-keystroke interval standard deviation is < 15 ms (synthetic automated input).
BEHAVIOR	`typing_cadence_anomaly`	+10	Typing rhythm deviates by > 120 ms from customer's stored baseline mean.
AMOUNT	`severe_amount_anomaly`	+30	Transaction amount z-score is ≥ 3.0σ above historical customer average.
AMOUNT	`high_risk_merchant_category`	+15	High liquid conversion categories: cryptocurrency, gift cards, luxury goods.

🔒 **PCI-DSS Security Hygiene:** Sensitive 16-digit card numbers (PAN) and CVVs are *never* stored or logged to disk. The server extracts only the non-sensitive `card_last4` and generates a one-way `SHA-256` token hash for velocity indexing.

4. Application Architecture & The Two UIs

AegisGuard is divided into two intuitive operational views accessible from the top navigation bar:

🛒 Tab 1: Merchant Checkout Simulator

Simulates an e-commerce checkout page (e.g., luxury electronics store). Captures client telemetry in real time:

- **One-Click Personas:** Deterministic presets (Persona A, B, C) for instant demoing.
- **Live Telemetry Widget:** Live counter showing form dwell time, mouse jitter entropy, and paste flags.
- **Decision Modal:** Shows instantaneous ALLOW, CHALLENGE (with OTP input), or BLOCK with explainable signal breakdowns.
- **Custom Signal Playground:** Interactive sliders to modify signals and test any scenario on the fly.

📊 Tab 2: Risk Operations Console

Designed for fraud analysts and security operation teams:

- **Live Server-Sent Events (SSE) Stream:** Real-time streaming table showing transactions as they happen.
- **KPI Metric Cards:** Approval Rate, Challenge Rate, Block Rate, and sub-15ms Latency.
- **Interactive Recharts:** Risk score distribution histogram, top triggered factors, and decision breakdowns.
- ⚡ **Run Attack Simulation:** Fires a burst of 6 bot transactions to show live real-time detection.
- **Transaction Inspector Drawer:** Side drawer with deep-dive tabs: Factor Weights, Raw Telemetry, and Immutable Audit Trail.

5. How to Run the Application (2-Minute Setup)

Follow these quick commands in your terminal before recording your video:

Step 1: Seed the Database Baseline

```
npm run seed
```

This creates 5 diverse user profiles, verified hardware devices, and ~200 historical transactions in the local SQLite database.

Step 2: Start the Development Server

```
npm run dev
```

Starts both the Express API (Port 4000) and the React Vite client (Port 3000) concurrently.

Step 3: Open in Chrome

```
http://localhost:3000
```

Look at the top navbar: verify that the green **"● Live Stream Connected"** badge is visible. You're ready to record!

> 💡 **Quick Reset Tip:** If you ever make a mistake or want to re-record a scene, simply click the **"Reset Demo"** button in the top navigation bar. It instantly restores the database to its pristine demo state!

6. Complete YouTube Video Demo Script (Word-for-Word)

Follow this step-by-step roadmap during your video recording. Each step shows you **what to click on screen** and provides the **exact voiceover script** to speak. Aim for an upbeat, clear, and confident delivery. (Target length: ~4 to 5 minutes).

🎬 Scene 1: Introduction & The Problem (0:00 – 0:45)

🖥️ ACTION ON SCREEN

Start on `http://localhost:3000` on the **Merchant Checkout Simulator** tab. Have your webcam in the corner or full screen for the first 15 seconds, then cut to your screen.

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

*"Hi everyone! Today we are introducing **AegisGuard**: a sub-millisecond, real-time fraud scoring and adaptive authentication engine built for modern online checkout environments.*

In e-commerce, merchants face a painful trade-off: if you put high-friction SMS or OTP verification on every purchase, you lose up to 25% of good customers due to cart abandonment. But if you ease up, credential-stuffing bots and account takeover fraud can cost billions in chargebacks.

*AegisGuard solves this dilemma using **silent behavioral biometrics, impossible travel physics, and an explainable three-tier decision engine**: ALLOW, CHALLENGE, or BLOCK. Let's see it in action across three real-world personas!"*

🎬 Scene 2: Persona A — The Trusted Customer (ALLOW) (0:45 – 1:30)

🖥️ ACTION ON SCREEN

1. Click the green **"Persona A"** card at the top.
2. Point out customer name (**Alex Chen**), home city (**New York**), and trusted MacBook Pro.
3. Point out the product in Order Summary: **AuraPro Wireless Studio ANC Headphones ($74.50)**.
4. Point out the live telemetry metrics at the bottom of the card: dwell time ~14s, normal human mouse jitter (0.72), no paste.
5. Click the blue **"Authorize & Pay $74.50"** button.
6. The green **ALLOW** modal pops up in ~12 milliseconds.
7. Click **"Why this decision?"** to open the signal breakdown.

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

*"First, let's look at **Persona A**: Alex Chen, a returning legitimate customer. Alex is purchasing a pair of AuraPro Wireless ANC Headphones for $74.50 from his home in New York using his recognized MacBook Pro.*

Notice the client-side telemetry: his mouse jitter is 0.72, showing natural human curvature, and his typing cadence matches his historical profile.

*When I click 'Authorize & Pay'—look at that speed! In just **12 milliseconds**, AegisGuard approves the transaction with an instant **ALLOW** decision.*

*If we click 'Why this decision?', AegisGuard doesn't give us a vague AI score. It clearly explains that the device matched his verified hardware fingerprint—earning a negative risk bonus of minus 5 points—keeping his final risk score at **0 out of 100**. Zero friction, zero OTP hurdles, zero cart abandonment."*

🎬 Scene 3: Persona B — Suspicious VPN Hop & Impossible Travel (CHALLENGE) (1:30 – 2:45)

🖥️ ACTION ON SCREEN

1. Close the modal and click the amber **"Persona B"** preset.
2. Point out that Alex Chen transacted in New York 10 minutes ago, but this new request is coming from **Miami (~1,750 km away)** on an **unrecognized Windows PC**.
3. Point out the product in Order Summary: **SanDisk Extreme 1TB Portable NVMe SSD ($98.50)**.
4. Click **"Authorize & Pay $98.50"**.
5. The amber **CHALLENGE** modal appears with a 6-digit OTP prompt.
6. Highlight the signals: `impossible_travel (+40)` and `unrecognized_device (+20)`.
7. Point out the blue banner at the bottom: "*Hackathon Judge Demo Hint: Active TOTP code: 123456*".
8. Click the code or enter `123456` into the inputs.
9. Click **"Verify & Complete Payment"** → Modal turns green **"Payment Verified & Completed"**!

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

*"Now let's look at **Persona B**. Alex Chen completed an authorized transaction in New York just 10 minutes ago. Suddenly, a new $98.50 purchase attempt for a portable SSD arrives originating from Miami—over 1,750 kilometers away—on a completely new Windows browser.*

*When we submit this payment, AegisGuard calculates the geographic displacement velocity using the **Haversine formula**. Covering 1,750 kilometers in 10 minutes requires a physical speed of over **10,500 kilometers per hour**—which is physically impossible on commercial flights!*

*Instead of rigidly blocking a customer who might simply be on a corporate VPN, AegisGuard executes an **Adaptive Step-Up Challenge**. The risk score is 64 out of 100, driven by plus 40 for Impossible Travel and plus 20 for Unrecognized Device.*

*AegisGuard prompts for a 6-digit Time-based One-Time Password. We enter the one-time code `123456`, click 'Verify', and immediately the transaction upgrades to **CHALLENGE_PASSED**, payment completes, and the new device is securely bound to his account. Safe, adaptive, and customer-friendly!"*

🎬 Scene 4: Persona C — Automated Credential-Stuffing Bot (BLOCK) (2:45 – 3:45)

🖥️ ACTION ON SCREEN

1. Close the modal and click the red **"Persona C"** preset card.
2. Point out the product in Order Summary: **Ethereum Digital Asset Voucher (1.0 ETH) ($1,250.00)** under merchant *ApexCrypto Global Exchange*.
3. Highlight the telltale bot telemetry indicators locked in the diagnostics bar:
• IP Address: `45.154.255.89` (known botnet / datacenter CIDR)
• Mouse Jitter: `0.00` in bold red (zero human curve; straight robotic trajectory)
• Paste Detected: `TRUE` in bold red (automated clipboard injection into card field)
• Dwell Time: `420 ms` (superhuman script speed; <1 second)
4. Click **"Authorize & Pay $1,250.00"**.
5. The red **BLOCK** modal appears immediately with a Risk Score of **100 / 100**.
6. Walk through the four triggered factors that contribute to the block.

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

*"Now let's examine an actual cyber attack: **Persona C**, representing an automated credential-stuffing bot trying to purchase a $1,250 Ethereum Digital Asset Voucher with stolen card credentials.*

*Notice what our client-side telemetry captured before the submit button was even clicked: the IP belongs to a blacklisted bulletproof proxy subnet, the mouse jitter entropy is a dead flat **0.00**, the card number was pasted instantaneously, and the form dwell time started from a superhuman **420 milliseconds**.*

*We click 'Authorize & Pay', and AegisGuard hits it with an immediate, deterministic **BLOCK** at maximum risk score: **100 out of 100**.*

Looking at the transparent breakdown: Blacklisted Subnet (+50), Direct Clipboard Paste (+25), Superhuman Form Fill (+25), and Zero Mouse Entropy (+20). The bot script never stood a chance, and the merchant's capital is protected without human intervention."

🎬 Scene 5: Custom Signal Tweaker Sandbox (3:45 – 4:15)

🖥️ ACTION ON SCREEN

1. Close the modal and click the cyan **"Custom Mode"** button in the preset bar.
2. Show the interactive sliders: drag **Form Dwell Time**, toggle **Direct Clipboard Paste**, and adjust **Mouse Jitter Entropy**.
3. Explain that judges and developers can test any custom edge case live in the sandbox.

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

*"For judges and security auditors who want to experiment, AegisGuard includes an interactive **Custom Signal Playground**.*

You can freely adjust the form dwell time slider, simulate clipboard paste injections, tweak mouse jitter entropy, and pick different global IP locations to observe exactly how our weighted risk engine responds dynamically."

🎬 Scene 6: Risk Operations Console & Live Attack Simulation (4:15 – 5:30)

🖥️ ACTION ON SCREEN

1. Click the **"Risk Ops Console"** tab in the top navigation bar.
2. Point out the top KPI metric bar: Total Transactions, Approval Rate, Challenge Rate, Block Rate, and sub-15ms Latency.
3. Hover over the interactive Recharts: Risk Score Distribution histogram, Top Triggered Factors, and Decision Ratios.
4. Point out the Live Transaction Table streaming via **Server-Sent Events (SSE)**.
5. Click the high-impact button: **" ⚡ Run Attack Simulation"** in the top right.
6. Watch the live toast notifications and table rows populate in real time as 6 bot transactions are blocked.
7. Click on any transaction row to open the **Transaction Inspector Drawer**.
8. Click through the 3 drawer tabs: **Signal Breakdown**, **Raw Telemetry**, and **Immutable Audit Trail**.

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

*"Now, let's step into the shoes of a fraud analyst by opening the **Risk Operations Console**.*

*Everything here is connected via a persistent **Server-Sent Events (SSE) stream**. We see real-time KPIs: total volume, approval ratios, challenge pass rates, and an average engine latency of just **11 milliseconds**.*

Now watch what happens when an attacker targets our store: I'll click ' ⚡ Run Attack Simulation'.

Instantly, our background simulation fires a burst of 6 automated bot attacks. Watch the screen—live toast alerts fire, the score histogram updates dynamically, and every single attack is intercepted and blocked in real time!

*We can click any transaction row to slide out the **Transaction Inspector Drawer**. Here we have full regulatory compliance visibility: an exact breakdown of the mathematical signal weights, the raw browser hardware telemetry, and an **append-only immutable audit trail** recording every evaluation and state transition."*

🎬 Scene 7: Summary & Wrap-Up (5:30 – 6:00)

🖥️ ACTION ON SCREEN

Return to the full dashboard view or show the project GitHub README on screen.

🎙️ WHAT TO SAY (VOICEOVER SCRIPT)

"To wrap up: AegisGuard proves that modern security doesn't have to ruin the customer experience.

With sub-15ms processing, passive behavioral biometrics, impossible travel physics, and 100% transparent explainability, AegisGuard provides financial institutions with enterprise-grade protection that customers love.

The entire application is open source, cloud-ready with Docker, and tested end-to-end. Thank you so much for watching, and check out the GitHub link in the description below!"

7. Presenter Cheatsheet & Technical Glossary

If viewers or judges ask questions in comments or live Q&A, here are quick 1-sentence answers:

CONCEPT / TERM	SIMPLE PLAIN-ENGLISH EXPLANATION
Haversine Formula	A mathematical formula that calculates the great-circle spherical distance between two GPS coordinates on Earth. We divide distance by elapsed time to calculate velocity in km/h.
Mouse Jitter / Entropy	Humans move their mouse in natural curves with slight micro-tremors (jitter score > 0.40). Automated scripts use straight-line coordinate jumps or programmatic triggers (jitter ≤ 0.05).
Keystroke Cadence	Measures the mean delay and standard deviation between keystrokes. Humans have natural variation (~30–45ms std-dev). Bot scripts inject keys at rigid intervals (std-dev < 15ms) or 0ms.
Canvas / WebGL Fingerprint	Renders an invisible graphic in memory using the device's GPU and font engine. Because every GPU and driver renders pixels slightly differently, the resulting hash uniquely identifies hardware without cookies.
Server-Sent Events (SSE)	A lightweight, one-way HTTP streaming protocol (`GET /api/stream`) that pushes real-time transaction updates from the Node.js server directly to the React dashboard with sub-5ms overhead.
PCI-DSS Compliance	Sensitive 16-digit card numbers and CVVs are processed strictly in volatile memory. Only the last 4 digits and a one-way cryptographic SHA-256 hash are retained for velocity calculations.

8. YouTube Video Publishing Kit (Copy & Paste)

When uploading the video to YouTube, you can copy and paste the following metadata directly:

Recommended YouTube Video Titles (Choose One):

- **Option 1 (Recommended):** AegisGuard — Real-Time Fraud Prevention & Adaptive Authentication (Demo & Architecture)
- **Option 2:** Sub-Millisecond E-Commerce Fraud Scoring Engine: Behavioral Biometrics & Impossible Travel
- **Option 3:** Stopping Bots Without Ruining UX: Full Walkthrough of AegisGuard Fraud Microservice

Video Description & Timestamps:

```
🛡️ AegisGuard: Real-Time Transaction Fraud Scoring & Adaptive Step-Up Authentication

A deep-dive demonstration and architectural explanation of AegisGuard—a cloud-native microservice that eva

⏱️ TIMESTAMPS:
0:00 - Introduction & The Fraud-Friction Paradox
0:45 - Persona A: Trusted Customer (Instant ALLOW in 12ms)
1:30 - Persona B: Impossible Travel & Adaptive TOTP Challenge
2:45 - Persona C: Automated Bot Attack & Deterministic BLOCK
3:45 - Custom Signal Playground & Behavioral Sandbox
4:15 - Live Risk Operations Console (SSE Stream & Attack Simulation)
5:30 - System Architecture, Compliance Hygiene & Conclusion

🚀 KEY FEATURES:
• Sub-millisecond evaluation latency (<15ms)
• 3-Tier Adaptive Decisions: ALLOW, CHALLENGE (TOTP), BLOCK
• 100% Explainable risk factor weights (No black boxes!)
• Silent behavioral biometrics: Keystroke cadence, mouse entropy, paste detection
• Impossible travel detection via Haversine spherical displacement
• Real-time Risk Operations Console with Server-Sent Events (SSE)
• Zero PAN/CVV retention (PCI-DSS compliance)

💻 TECH STACK:
• Client: React, Vite, Tailwind CSS, Recharts, Lucide Icons
• Server: Node.js, Express, Helmet, CORS, SQLite (Swappable for Cloud SQL/Postgres)
• Cloud: Containerized with Docker, GCP Cloud Run ready
```

Video Tags / Keywords:

fraud prevention, cybersecurity, behavioral biometrics, machine learning fraud detection, stripe radar alternative, fintech demo, impossible travel algorithm, haversine formula, react vite, nodejs express, web application security, bot detection, TOTP authentication, hackathon project

---