

Nexora Corporate Knowledge Base: Environment Setup

Target Role: ENGINEERING | Version: Official | Published: 2026-09-25

1. Local Development Environment

Engineers use Docker Desktop or OrbStack to spin up local database, cache, and service dependencies via 'docker-compose up -d'. Standard package managers are Node (pnpm / npm), Go (go modules), and Python (uv / pip).

2. Secrets Management & Vault

Local development secrets must never be committed to repositories or shared in Slack. Secrets are fetched dynamically via HashiCorp Vault CLI or 1Password developer plugins.

3. Pre-Commit Hooks

All repositories configure 'pre-commit' hooks to run linter checks, GPG sign validation, and secret detection scans (TruffleHog) before code can be committed locally.

6. Workstation Provisioning

IT Ops provisions MacBook Pro or ThinkPad workstations with full-disk encryption before Day 1, consistent with the Security Policy device standards and the Remote Work equipment program.

7. VPN and Zero Trust Enrollment

Engineers enroll devices in the Zero-Trust VPN with posture compliance checks during onboarding week. Production JIT elevation is granted only from compliant, enrolled devices.

8. Keeping the Environment Current

Engineers pull updated base images and dependency lockfiles weekly. Stale environments older than 30 days are flagged in CI, since drift is a leading cause of works-on-my-machine defects.