

Nexora Corporate Knowledge Base: Git Workflow v1.2

Target Role: ENGINEERING | Version: Official | Published: 2026-09-25

1. Trunk-Based Development

Nexora engineering adheres strictly to Trunk-Based Development. Feature branches must be short-lived (maximum lifespan of 24-48 hours) and branched directly from 'main'.

2. Branch Naming Conventions

Branches must follow standard prefixes: feature/JIRA-123-short-desc, bugfix/JIRA-123-short-desc, hotfix/JIRA-123-short-desc, or chore/JIRA-123-short-desc.

3. Commit Hygiene & Mandatory Signing

All Git commits must be cryptographically signed using GPG or SSH keys verified in GitHub. Commit messages must follow the Conventional Commits specification (feat:, fix:, docs:, refactor:, test:, chore:).

4. Pull Request Requirements

Every Pull Request (PR) requires at least 1 peer approval from an engineer in the CODEOWNERS file. All automated CI checks (linters, unit tests, security vulnerability scans, build verification) must pass with zero errors before merge.

5. Merging Strategy

Use 'Squash and Merge' for feature branches to keep the main commit log clean and linear. Rebase on main prior to final merge.

6. Hotfix Branches

Emergency production fixes use hotfix/JIRA-123-short-desc branches cut directly from 'main'. They follow the same signing, review, and CI gates as features; only the deployment window differs, per the Deployment SOP out-of-band approval process.

7. Release Tagging

Each production deployment is tagged release-vX.Y.Z on main immediately after a successful canary rollout, so rollbacks and audits always reference an immutable artifact.

8. CODEOWNERS Maintenance

Every repository maintains a CODEOWNERS file mapping directories to owning teams. Ownership changes require a PR reviewed by both the outgoing and incoming owners.