

WEEK_8

```
File Edit Source Refactor Navigate Search Project Run Window Help
week8_3 - co3Application (1) [Spring Boot App] C:\Users\T.Karthik\Downloads\spring_tool_suite_4.24.0_RELEASE-e4.33.0.win32.x86_64_1\sts-4.26.0.RELEASE\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64.21.0.4.v20240802-1551\jre\bin\java.exe
Declaration Console
1 package
2
3 import
4
5 @Spring
6 public
7
8 pub
9
10
11 }
12
13 }

=====
:: Spring Boot :: (v4.1.1)

2026-09-15T22:19:05.869+05:30 INFO 27688 --- [week8_3] [ restartedMain] com.klu.co3Application : Starting co3Application using Java 21.0.4 with PID 27688 (C:\Users\T.Karthik\Downloads\spring_tool_suite_4.24.0_RELEASE-e4.33.0.win32.x86_64_1\sts-4.26.0.RELEASE\plugins\org.eclipse.justi.openjdk.hotspot.jre.full.win32.x86_64.21.0.4.v20240802-1551\jre\bin\java.exe)
2026-09-15T22:19:05.873+05:30 INFO 27688 --- [week8_3] [ restartedMain] com.klu.co3Application : No active profile set, falling back to 1 default profile: "default"
2026-09-15T22:19:05.926+05:30 INFO 27688 --- [week8_3] [ restartedMain] .e.DevToolsPropertyDefaultsPostProcessor : DevTools property defaults active! Set 'spring.devtools.add-properties' to 'true' to enable the DevTools property defaults. For additional web related logging consider setting the 'logging.level.org.springframework.boot.devtools.properties' log level.
2026-09-15T22:19:05.926+05:30 INFO 27688 --- [week8_3] [ restartedMain] .e.DevToolsPropertyDefaultsPostProcessor : For additional web related logging consider setting the 'logging.level.org.springframework.boot.devtools.properties' log level.
2026-09-15T22:19:06.733+05:30 INFO 27688 --- [week8_3] [ restartedMain] .s.d.r.c.RepositoryConfigurationDelegate : Bootstrapping Spring Data JPA repositories in DEFAULT mode.
2026-09-15T22:19:06.792+05:30 INFO 27688 --- [week8_3] [ restartedMain] .s.d.r.c.RepositoryConfigurationDelegate : Finished Spring Data repository scanning in 47 ms. Found 1 JPA repository.
2026-09-15T22:19:07.290+05:30 INFO 27688 --- [week8_3] [ restartedMain] o.s.boot.tomcat.TomcatWebServer : Tomcat initialized with port 8989 (http)
2026-09-15T22:19:07.310+05:30 INFO 27688 --- [week8_3] [ restartedMain] o.apache.catalina.core.StandardService : Starting service [Tomcat]
2026-09-15T22:19:07.313+05:30 INFO 27688 --- [week8_3] [ restartedMain] o.apache.catalina.core.StandardEngine : Starting Servlet engine: [Apache Tomcat/11.0.24]
2026-09-15T22:19:07.361+05:30 INFO 27688 --- [week8_3] [ restartedMain] b.w.c.s.WebApplicationContextInitializer : Root WebApplicationContext: initialization completed in 1433 ms
2026-09-15T22:19:07.544+05:30 INFO 27688 --- [week8_3] [ restartedMain] org.hibernate.orm.jpa : HHH000540: Processing PersistenceUnitInfo [name: default]
2026-09-15T22:19:07.602+05:30 INFO 27688 --- [week8_3] [ restartedMain] org.hibernate.orm.jpa : HHH000001: Hibernate ORM core version 7.4.5.Final
2026-09-15T22:19:08.121+05:30 INFO 27688 --- [week8_3] [ restartedMain] o.s.o.j.p.SpringPersistenceUnitInfo : No LoadTimeWeaver setup; ignoring JPA class transformer
2026-09-15T22:19:08.161+05:30 INFO 27688 --- [week8_3] [ restartedMain] com.zaxxer.hikari.HikariDataSource : HikariPool-1 - Starting...
2026-09-15T22:19:08.538+05:30 INFO 27688 --- [week8_3] [ restartedMain] com.zaxxer.hikari.pool.HikariPool : HikariPool-1 - Added connection com.mysql.cj.jdbc.ConnectionImpl@4418b...
2026-09-15T22:19:08.542+05:30 INFO 27688 --- [week8_3] [ restartedMain] com.zaxxer.hikari.pool.HikariPool : HikariPool-1 - Start completed.
2026-09-15T22:19:08.604+05:30 WARN 27688 --- [week8_3] [ restartedMain] org.hibernate.orm.deprecation : HHH90000025: MySQLDialect does not need to be specified explicitly using 'hibernate.dialect'
2026-09-15T22:19:08.622+05:30 INFO 27688 --- [week8_3] [ restartedMain] org.hibernate.orm.connections.pooling : HHH10001005: Database info:
Database JDBC URL [jdbc:mysql://localhost:3306/kluh]
Database driver: MySQL Connector/J
Database dialect: MySQLDialect
Database version: 8.0.46
Default catalog/schema: kluh/undefined
AutoCommit mode: undefined/unknown
Isolation level: REPEATABLE_READ [default REPEATABLE_READ]
JDBC fetch size: none
Pool: DataSourceConnectionProvider
Minimum pool size: undefined/unknown
Maximum pool size: undefined/unknown
2026-09-15T22:19:09.548+05:30 INFO 27688 --- [week8_3] [ restartedMain] org.hibernate.orm.core : HHH000489: No JTA platform available (set 'hibernate.transaction.jta.platform' to enable JTA transaction support)
Hibernate: alter table products modify column id bigint not null auto_increment
Hibernate: alter table products modify column description varchar(255)
2026-09-15T22:19:10.120+05:30 INFO 27688 --- [week8_3] [ restartedMain] o.s.d.j.e.query.QueryEnhancerFactories : Initialized JPA EntityManagerFactory for persistence unit 'default'
2026-09-15T22:19:10.206+05:30 INFO 27688 --- [week8_3] [ restartedMain] jpaBaseConfiguration$JpaWebConfiguration : Hibernate is in classpath; if applicable, HQL parser will be used.
2026-09-15T22:19:10.339+05:30 WARN 27688 --- [week8_3] [ restartedMain] jpaBaseConfiguration$JpaWebConfiguration : spring.jpa.open-in-view is enabled by default. Therefore, database queries may only be executed inside of an open transaction.
2026-09-15T22:19:10.870+05:30 INFO 27688 --- [week8_3] [ restartedMain] o.s.boot.tomcat.TomcatWebServer : Tomcat started on port 8989 (http) with context path '/'
2026-09-15T22:19:10.880+05:30 INFO 27688 --- [week8_3] [ restartedMain] com.klu.co3Application : Started co3Application in 5.54 seconds (process running for 6.53)
```

KARTHIK TALLA's Workspace

GET Get data

GET Get data

My Collection > Get data

GET http://localhost:8989/api/products

Send

Docs Params Authorization Headers 6 Body Scripts Tests Settings Cookies

Query Params

Key	Value	Description	Bulk Edit
Key	Value	Description	

Body Cookies Headers 5 Test Results 1/1

200 OK · 1.88 s · 416 B

Save Response

JSON Preview Visualize

```
1 [
2   {
3     "description": "Dell XPS 13",
4     "id": 1,
5     "name": "Laptop",
6     "price": 1200.0,
7     "quantity": 10
8   },
9   {
10    "description": "Samsung Galaxy S21",
11    "id": 2,
12    "name": "Smartphone",
13    "price": 999.0,
14    "quantity": 20
15  },
16  {
17    "description": "Apple iPad Pro",
18    "id": 3,
19    "name": "Tablet",
20    "price": 799.0,
21    "quantity": 15
22  }
23 ]
```

ENVIRONMENTS DOCUMENTS SPECS MOCKS FLOWS

Connect Git Terminal Console

The coast is clear!

Globals Vault Tools

Learning to use Postman

onboard-user I want to learn how to use Postman.

Here's a simple path to get hands-on:

1. Send your first request — Open a new request tab, enter a public URL (e.g. `https://jsonplaceholder.typicode.com/posts`), select GET, and hit Send.
2. Save it to a collection — Save the request to My Collection to keep it organized.
3. Add a test — In the Scripts tab of a request, write a simple test like `pm.test('Status is 200', () => pm.response.to.have.status(200));`
4. Use variables — Create an environment and store your base URL as a variable.

You currently have a request called Get data open in your workspace — that's a great place to start experimenting!

What would you like to do next?

Send my first request

Learn about Collections

Set up an Environment

Write my first test

Describe what you need. Press @ for context, / for Skills.

Auto

WEEK_8

The screenshot displays the Postman application interface. The top bar shows the workspace name "KARTHIK TALLA's Workspace" and a search bar. The left sidebar contains a "COLLECTIONS" panel with "My Collection" expanded, showing a "GET Get data" request. The main panel shows the details of this request: a GET method to the URL "http://localhost:8989/api/products/1". The "Body" tab is selected, showing a JSON response with a status of "200 OK", a response time of "276 ms", and a size of "237 B". The JSON response is as follows:

```
1 {
2   "description": "Banana",
3   "id": 1,
4   "name": "Fruit",
5   "price": 69.9,
6   "quantity": 10
7 }
```

The right sidebar features a "Learning to use Postman..." section with a "Send your first request" button and a "What would you like to do next?" section with links to "Send my first request", "Learn about Collections", "Set up an Environment", and "Write my first test".

WEEK_8

GET Get data | POST Get data

My Collection > Get data

POST http://localhost:8989/api/products

Body

```
1 {
2   "name": "Fruit",
3   "description": "Banana",
4   "price": 60.0,
5   "quantity": 10
6 }
```

Body Cookies Headers 5 Test Results 1/1

200 OK · 571 ms · 237 B

JSON

```
1 {
2   "description": "Banana",
3   "id": 4,
4   "name": "Fruit",
5   "price": 60.0,
6   "quantity": 10
7 }
```

Learning to use Postman...

Here's a simple path to get hands-on:

1. Send your first request — Open a new request tab, enter a public URL (e.g. <https://jsonplaceholder.typicode.com/posts>), select GET, and hit Send.
2. Save it to a collection — Save the request to **My Collection** to keep it organized.
3. Add a test — In the Scripts tab of a request, write a simple test like `pm.test("Status is 200", () => pm.response.to.have.status(200));`
4. Use variables — Create an environment and store your base URL as a variable.

You currently have a request called **Get data** open in your workspace — that's a great place to start experimenting!

What would you like to do next?

- Send my first request
- Learn about Collections
- Set up an Environment
- Write my first test

Describe what you need. Press @ for context, / for Skills.

Auto

GET Get data | PUT Get data

My Collection > Get data

PUT http://localhost:8989/api/products/1

Body

```
1 {
2   "name": "Fruit",
3   "description": "Banana",
4   "price": 60.0,
5   "quantity": 10
6 }
```

Body Cookies Headers 5 Test Results 1/1

200 OK · 505 ms · 237 B

JSON

```
1 {
2   "description": "Banana",
3   "id": 1,
4   "name": "Fruit",
5   "price": 60.0,
6   "quantity": 10
7 }
```

Learning to use Postman...

Here's a simple path to get hands-on:

1. Send your first request — Open a new request tab, enter a public URL (e.g. <https://jsonplaceholder.typicode.com/posts>), select GET, and hit Send.
2. Save it to a collection — Save the request to **My Collection** to keep it organized.
3. Add a test — In the Scripts tab of a request, write a simple test like `pm.test("Status is 200", () => pm.response.to.have.status(200));`
4. Use variables — Create an environment and store your base URL as a variable.

You currently have a request called **Get data** open in your workspace — that's a great place to start experimenting!

What would you like to do next?

- Send my first request
- Learn about Collections
- Set up an Environment
- Write my first test

Describe what you need. Press @ for context, / for Skills.

Auto

