Architecture of an Explorable Mathematics Microworld: Cognitive Engineering, Non-Gamified Visual Ergonomics, and Multilingual Systems for Primary Learners

Theoretical and Pedagogical Frameworks

Developmental Cognition and Representational Interlacing in Ten-Year-Old Learners

Children at ten years of age occupy a decisive developmental phase situated in the late stage of Jean Piaget's Concrete Operational Period[1]. Cognitively, children at this chronological threshold possess operational structures characterized by three primary mental capabilities: reversibility, decentration, and conservation[1]. Reversibility allows the learner to mentally trace an operational pathway backward, recognizing that an altered geometric form or numerical aggregate can be reconstituted into its original configuration without qualitative or quantitative loss[1]. Decentration allows the child to perceive and coordinate multiple dimensions simultaneously, freeing reasoning from the perceptual centration of early childhood where an increase in one parameter (such as vertical height) erroneously implies an increase in total magnitude[1]. Consequently, ten-year-olds demonstrate robust conservation of substance, area, and spatial properties across continuous physical permutations[1].

Developmental Dimension	Cognitive Operation	Digital Manipulation Modality	Mathematical Target Schema
Reversibility	Bidirectional mental tracking[1]	Dragging continuous sliders to reverse shape transformations[1]	Inverse operations: $a \times b = c \iff c$ [cite: 1, 2]
Decentration	Multi-feature coordinate analysis[1]	Real-time width compensation during area shearing[1]	Invariance of spatial area: $\text{Area} = b \times$ [cite: 1, 3]

Conservation	Invariance detection across states[1]	Continuous reassembly of polygonal planar meshes[1]	Conservation of planar surface magnitude[1]
Relational Schemas	Systemic structural comprehension[4]	Direct manipulatives linking variables dynamically[4]	Conceptual reasoning over procedural recall[2]

Despite these operational capabilities, ten-year-old learners encounter significant cognitive friction when forced to interact with purely abstract or ungrounded symbolic expressions[1]. When abstract formalisms are introduced without empirical anchors, working memory is expended on rote manipulation of arbitrary tokens rather than structural comprehension[1]. Jerome Bruner's instructional continuum resolves this friction through the Concrete-Pictorial-Abstract (CPA) sequence, corresponding to Enactive, Iconic, and Symbolic representations[4]. In computer-mediated environments, this pedagogical progression cannot be structured as an isolated, one-way sequence where physical or enactive models are abandoned once formal notations appear[4]. Instead, effective computational learning environments utilize an interlaced representational structure where enactive digital manipulation (tactile handling of dynamic elements), iconic forms (continuous geometric visuals and bar models), and symbolic notation (formal mathematical expressions) exist simultaneously on a shared reactive plane[3].

To ensure that learners do not form brittle associations between arbitrary graphical artifacts and mathematical laws, the learning architecture must implement Zoltan Dienes' Principle of Perceptual Variability[4]. Dienes posited that the structural invariants of a mathematical concept must be presented across diverse perceptual substrates[4]. When multiplication is presented solely as repeated addition or solely as an array of discrete icons, children fail to abstract the generalized operation[2]. Exposing learners to multiplication concurrently as discrete grouping grids, continuous Cartesian area manifolds, and scaling vectors ensures that irrelevant surface traits are stripped away, leaving only the invariant mathematical core[2]. This continuous multi-representational exposure cultivates what Richard Skemp categorized as relational understanding—a thorough grasp of what procedures accomplish and why they are mathematically valid—thereby preventing the superficial execution of memorized rules that characterizes instrumental understanding[2].

Cognitive Load Theory and the Elimination of Media Transience

Educational multimedia systems often rely on linear video explanations and auto-advancing instructional animations under the assumption that continuous motion guarantees comprehension. However, instructional analysis and empirical research reveal that dynamic audiovisual presentations often compromise conceptual mastery due to the Transient Information Effect[7]. John Sweller's Cognitive Load Theory demonstrates that human working

memory is severely limited in capacity and temporal persistence when processing novel information[9]. Fleeting auditory or animated presentations force the visual and phonological processors to capture dynamic information before it disappears, creating severe processing bottlenecks[7].

When exposed to continuous instructional animations, learners must continuously parse new spatial updates while simultaneously maintaining antecedent frames in working memory to interpret causal sequences[10]. This operational pattern imposes heavy extraneous cognitive load, depleting the mental resources needed to integrate information into long-term memory schemas[10]. In topics characterized by high intrinsic element interactivity—such as multi-step geometric proofs, fractional operations, or multi-component logic gates—transient presentations frequently cause comprehension to break down[10].

Cognitive Load Category	Media Manifestation	Architectural Countermeasure	Cognitive Mechanism
Extraneous Load	Transient dynamic media and non-interactive video[7]	User-scrubbed interactive systems and permanent visual residue[7]	Offloads historical state retention from working memory to visual field[7]
Extraneous Load	Seductive details, extraneous animations, and decorative UI[12]	Calm, functional design and stripped non-essential flair[12]	Prevents attentional fragmentation in children with maturing inhibitory control[13]
Intrinsic Load	High element interactivity in compound concepts[10]	Isolated-elements strategy and modular progression steps[11]	Deconstructs compound tasks into manageable structural components[11]
Germane Load	Passive media consumption lacking agency[12]	Tangible direct manipulation and real-time explorable systems[5]	Channels freed cognitive capacity directly into schema construction[4]

To eliminate the transient information effect, learning interfaces must discard passive video players in favor of learner-paced explorable explanations that leave a permanent visual residue[7]. Rather than watching autonomous animations, learners control changes via bidirectional scrubs, continuous spatial handles, and discrete state navigators[7]. As

transformations occur, ghosted trails and intermediate visual markers remain permanently visible on the workspace, relieving working memory from having to mentally reconstruct earlier states[7].

Furthermore, instructional interfaces must omit what Richard Mayer identified as seductive details—extraneous decorative artwork, background music, incidental cartoon characters, and celebratory animations[13]. Empirical evaluations establish that seductive details degrade conceptual performance, particularly in elementary school students whose executive inhibitory control is still maturing[13]. Spoken auditory narratives must be deployed according to the Modality Effect: spoken, natural narrative cues should accompany complex graphics rather than on-screen walls of visual text, offloading bandwidth from the visual channel to the auditory processor without inducing split-attention penalties[7].

Non-Gamified Visual Interface Ergonomics

Deconstructing Extrinsic Gamification and Dark Patterns

Commercial educational software commonly uses coercive engagement patterns adapted from mobile games, including artificial countdown timers, consumable energy units, daily progression streaks, virtual currencies, and competitive scoreboards[14]. While these mechanics stimulate artificial engagement metrics, empirical human-computer interaction studies establish that they act as coercive psychological patterns[15]. Extrinsic gamification alters a child's motivational orientation, replacing intrinsic epistemic curiosity with an external desire for synthetic rewards[14]. In time, children shift their behavior toward guessing tactics, superficial completion, and platform gaming rather than deliberate exploration and structural reasoning[2]. Furthermore, countdown timers and competitive leaderboards induce performance anxiety, directly reducing the working memory bandwidth required for concrete mathematical reasoning[12].

This architectural design eliminates extrinsic behavioral rewards, adopting Seymour Papert’s constructionist microworld philosophy and Bret Victor’s principles of explorable explanations. The application treats the learner as an investigator interacting with an active, mathematically consistent environment[4]. Engagement is sustained through interactive agency, clear visual feedback, and discovery rather than point-scoring loops[5]. Correctness is not communicated through cartoon popups, celebratory chimes, or badges; instead, correctness is intrinsically self-evident because the visual system operates within mathematically consistent rules[2]. When a child constructs an asymmetric division, an unaligned geometric shearing, or an invalid logic circuit, the model physically tips, slips, or misroutes items according to that error, providing clear spatial feedback that prompts independent cognitive recalibration[1].

Spatial Layout, Direct Manipulation, and Calm Visual Design

The visual design system adheres to calm technology principles, prioritizing spatial legibility, minimal visual noise, and tactile digital affordances suited to ten-year-old learners. The primary workspace uses an asymmetrical split-pane layout. The left viewport houses the interactive manipulation canvas, while the right viewport displays a persistent historical trace panel and linked symbolic equations. The canvas rests on warm neutral backgrounds, using deep slate

(#1E222A) for reduced glare or soft alabaster (#F8FAFC) for daylight reading, avoiding stark visual extremes that induce visual fatigue. Color is reserved entirely for mathematical meaning: contrasting hues highlight matching parameters, such as linking a polygon's base dimension to its corresponding factor in an algebraic equation.
Direct manipulation replaces abstract numerical input fields and dropdown menus. Mathematical entities are equipped with large, tangible grab points, edge rails, and rotational hinges designed for developing motor coordination. Interactive hit targets maintain a minimum size of $48 \times 48 \text{ dp}$, accompanied by subtle hover boundaries and elevation depth cues that clearly signal interactive affordances. Manipulating any visual control triggers instant mathematical recalculations across all active viewports at 60 to 120 frames per second, ensuring smooth sensory integration. As shapes mutate or values shift, antecedent states remain faintly visible as static vector outlines, providing reference marks that anchor cognitive reversibility and conservation without taxing working memory[1].

Interactive Conceptual Models for Core Mathematical Domains

Dynamic Spatial Geometry and Conservation Mechanics

Rather than presenting static Euclidean shapes accompanied by memorized formulas, the geometry engine models shapes as continuous physical assemblies governed by invariant geometric rules[1]. Learners investigate the area of a parallelogram by directly shearing the shape along its horizontal vector. As the user drags the top boundary, the internal vertical height (h) remains fixed between two subtle, parallel guide planes, while the base (b) maintains a fixed length. The child observes the interior surface area dynamically dissected into infinitesimal vertical pixel strips (or triangular end-caps) that seamlessly transpose across boundaries. The visual feedback explicitly shows that:

$$\text{Area} = \int_0^h b \, dy = b \times h$$

This demonstrates that while the perimeter stretches, the interior space occupied by the shape is strictly conserved[1].
Three-dimensional polyhedra are taught through interactive unrolling and kinematic transformations. Tapping a solid regular dodecahedron or prism triggers a spring-damped origami unfolding mechanic, unfurling its 3D polygonal boundaries into a flat, 2D planar net. The learner can drag an interactive continuity slider to watch the 2D planar net fold back into the 3D solid, observing how adjacent edges match and join. This mechanism reinforces spatial reversibility and deconstructs surface area into an intuitive composite sum of concrete 2D polygons[1].

Multiplicative Reasoning, Cartesian Area Matrices, and Partitioning

Dynamics

Multiplication and division are modeled through three distinct structural interpretations: discrete array grids, continuous Cartesian area manifolds, and physical conservation flow models[2].

The core multiplication engine utilizes an expandable Cartesian area matrix. Learners grab the lateral boundaries of a rectangular field to alter its dimensions (x, y). Rather than incrementing abstract numerical counters, dragging outward dynamically generates an array of unit blocks. When scaling up to larger double-digit factors (for example, 14×12), the interface introduces a dynamic cutting tool that bifurcates the factors into base-ten components:

$$(10 + 4) \times (10 + 2) = (10 \times 10) + (10 \times 2) + (4 \times 10) + (4 \times 2) = 100 + 20 + 40 + 8 =$$

Each sub-rectangle renders in an associated, harmonious hue, visually anchoring the distributive property of multiplication through physical spatial partition[2].

Division is framed through two complementary operations: fair-share partitioning (partitive division) and container-capacity grouping (quotative measurement division)[2]. In partitive mode, an initial volume of fluid units or discrete physical tokens is distributed evenly across a set of designated recipient basins, visually demonstrating equal distribution. In quotative mode, learners extract fixed-capacity measurement frames (such as groups of 4) from an initial mass of 24 units. A dynamic jump-line visualization maps each extraction as an inverse vector jump across a continuous number line, establishing division as the structural inverse of multiplication[1].

Set-Theoretic Structures, Fluid Containment, and Boolean Operations

Set theory is implemented as an interactive fluid ecosystem rather than a series of static circles drawn on a blackboard. The environment features a floating collection chamber containing geometric items that vary across specific properties, including shape, hue, internal pattern, and prime numerical values[2]. Learners construct Venn and Euler diagrams by dragging elastic, semi-permeable boundary enclosures onto the workspace, assigning conditional filter rules to each ring[2].

When released, the floating items are drawn toward their correct set positions via a real-time rigid-body physics simulation. Elements meeting a single criterion settle into that set's exclusive region, while elements satisfying multiple conditions ($A \cap$) are pulled into the overlapping intersection, reaching physical equilibrium[2]. Items failing all conditions are pushed out to the surrounding universal set region ($U \setminus (A \cup B)$)[2]. Learners can reposition the set boundaries relative to one another to observe topological shifts: separating the circles

illustrates disjoint sets ($A \cap B = \emptyset$), while pulling one circle entirely inside another visually demonstrates subsets ($A \subset B$). The interface links these spatial arrangements directly to Boolean logic, showing how set intersections map to logical AND, unions map to logical OR, and exterior regions map to logical NOT [2].

Mechanical Logic and Algorithmic Causality

To bridge concrete reasoning and formal computational logic without premature alphanumeric syntax, the logic module implements physical mechanical computation, inspired by the marble-driven architecture of the Turing Tumble[17].

Learners construct logic networks using tangible physical components placed on a pegboard grid[17]:

- Directional ramps guide descending marbles across the board, setting basic signal paths[17].
- Crossover tracks allow two paths to cross without interfering with each other[18].
- Bistable mechanical bits store binary states (0 and 1); when struck by a falling marble, a bit flips its direction, routing the current marble down one track while switching its internal memory state to divert subsequent marbles down the opposite path[17].
- Mechanical flippers act as directional triggers that divert marbles based on the entry angle[17].
- Interceptor blocks capture rolling marbles, halting circuit execution when an invalid condition occurs[17].

To evaluate a compound proposition such as:

$$(A \wedge B) \vee (\neg C)$$

the child places mechanical bits representing variables A, B, and C. Releasing a marble sends physical tokens down through the logic network. The marble travels through the mechanical gates, physically flipping states and following routes determined by the arrangement of parts[17]. If the logical circuit evaluates to True, the marble exits into a primary capture basin; if False, it routes into an alternate overflow basin. This mechanical visualization transforms invisible Boolean abstractions into observable causality[17]. The learner directly watches how state changes, feedback loops, and truth conditions propagate through physical space, developing an intuitive foundation for computational logic before ever seeing abstract symbolic code[17].

Multilingual Localization and Indic Script Engineering

Typographic Engineering and Complex Text Layout for Indic Scripts

Delivering an educational platform across English and major Indian languages (Hindi, Telugu, Bengali, Tamil) requires a specialized typographic pipeline. Indic scripts belong to the abugida writing system family, characterized by complex conjunct clusters, stacking consonants, and extensive non-linear vowel diacritics (*matras*) that extend substantially above the ascender line and below the descender line[21]. Standard Latin typographic metrics truncate or clip these complex conjuncts if implemented naively[21].

The platform integrates the open-source Google Noto Sans family, loading language-specific fonts: *Noto Sans Devanagari*, *Noto Sans Telugu*, *Noto Sans Bengali*, and *Noto Sans Tamil* alongside base *Noto Sans*[21]. Typographic tokens are customized to accommodate the distinct vertical dimensions of each script[21]. While Latin body copy operates effectively with line heights between $1.3\times$ and $1.5\times$ font size, Indic scripts require a minimum line-height multiplier of $1.8\times$[21]. This vertical clearance prevents vowel matras and conjunct descenders from overlapping adjacent text lines[21].

Text rendering relies on HarfBuzz compiled to WebAssembly (or platform-native OpenType layout engines) with comprehensive shaping tables enabled (liga, clig, akhn, rphf, blwf). This configuration ensures that multi-part conjuncts—such as the Devanagari ksha conjunct ($\text{क} + \text{◌्} + \text{ष} = \text{क्ष}$) or Bengali complex ligatures—render accurately without misplaced diacritics. Indic characters present intricate visual glyphs within identical pixel footprints[21]. Fonts must never render below a floor of $14\ \text{sp/px}$ on mobile screens, with a baseline body size set at $16\ \text{sp/px}$ [21]. The interface avoids ultra-thin or hairline weights, using medium (500) and semibold (600) weights to keep complex vowel loops legible on low-cost displays[21].

Managing Text Expansion and Elastic Layout Architecture

Localizing an interface from English to Indian regional languages results in structural text expansion[21]. Because translations often require explanatory phrasing or multisyllabic vocabulary, translated text strings commonly expand by 15% to 35% in physical length compared to their English counterparts[21].

Language	Script Family	Average Expansion Relative to English	Recommended Minimum Line-Height	Layout Vulnerability Points
English	Latin	Base (0%)	$1.4\times$ [cite: 22]	Baseline standard[22]
Hindi	Devanagari	$+15\%$ to $+$	$1.8\times$	Top matras cut

		[cite: 21]	[cite: 21, 22]	off by tight container boundaries[21]
Bengali	Eastern Nagari	$+20\%$ to $+$	$1.8\times$ [cite: 21]	High ascenders on dependent vowel signs
Telugu	Southern Brahmic	$+25\%$ to $+$	$1.85\times$ [cite: 22]	Circular vowel bases with wide horizontal footprint[22]
Tamil	Dravidian	$+20\%$ to $+$	$1.75\times$ [cite: 22]	Wide glyph loops requiring generous character margins

To maintain layout integrity across language switches, the user interface rejects fixed-dimension containers in favor of flexible layouts using CSS Flexbox and CSS Grid. Text containers use dynamic dimensions and adaptive padding, allowing UI elements to expand smoothly without breaking screen alignments. When horizontal text expansion exceeds viewport limits, control bars transition automatically from inline rows to vertical stacks. Truncation ellipses are strictly prohibited on pedagogical explanations and interactive prompts. Indic script lines wrap using locale-sensitive dictionary boundaries (Intl.Segmenter for word and grapheme segmentation), ensuring multi-syllable compound words break only at valid linguistic morpheme boundaries.

Bilingual Register Architecture and National Education Policy (NEP 2020) Alignment

India's National Education Policy (NEP 2020) stresses the cognitive benefits of mother-tongue and regional-language instruction in primary education, while recognizing the value of transitional bilingual frameworks[25]. A common barrier for learners moving through multilingual education systems is the abrupt shift from regional vernacular expressions to formal English scientific and mathematical terminology[26].

The application addresses this pedagogical challenge by implementing a dual-register conceptual bridge[26]. New mathematical concepts are introduced first through familiar, everyday conversational metaphors in the chosen regional tongue, anchoring understanding in daily life rather than dry formal translations[29]. This conversational introduction is paired directly with the standardized regional academic term (such as *क्षेत्रफल* in Hindi, *பரப்பளவு* in Tamil, or

వైశాల్యం in Telugu).

Alongside the regional terms, the system displays the international English equivalent (*Area*, A) and standard mathematical syntax ($A = b \times$), supported by optional native-language audio narrations on demand[3]. This tri-part approach grounds abstract concepts in the child's primary language while steadily building familiarity with global mathematical conventions, easing future transitions into secondary STEM education[4].

Technical Architecture, Performance, and Data Privacy

Client-Side Simulation Architecture and Hardware Acceleration

To deliver a compelling learning experience without relying on superficial game mechanics, every interaction must feel responsive, smooth, and physically tactile[5]. Any frame drops or visual lag during direct manipulation breaks the illusion of handling real physical objects, weakening the learning experience[5]. The runtime architecture operates on an offline-first progressive web model, executing all simulations and state computations entirely on the user's local device without server-side processing dependencies.

The physics and vector computation pipeline runs on a lightweight 2D rigid-body engine—such as Rapier2D compiled to WebAssembly (Wasm) or Matter.js[30]. WebAssembly provides deterministic performance across low-cost mobile processors, ensuring smooth physics calculations at 60 FPS without garbage collection interruptions[30]. Rendering is offloaded to hardware-accelerated Canvas2D and WebGL contexts. Geometric transformations, such as polygon shearing and polyhedral unfolding, are executed via vector matrix shaders on the GPU, avoiding Document Object Model (DOM) reflows and keeping the interface responsive under rapid touch interactions.

Regulatory Compliance with India's DPDP Act 2023 and Data Minimization

Educational technology products frequently face legal and ethical scrutiny for harvesting student behavioral data to drive engagement algorithms[31]. The application architecture adheres strictly to India’s Digital Personal Data Protection Act (DPDP Act 2023), which establishes strict protections for minors under 18 years of age[32].

DPDP Act 2023 Statutory Requirement	Statutory Mandate under Section 9	App Architectural Implementation
Parental Verification	Verifiable parental consent before processing any minor's data[32]	Out-of-band guardian authorization flow using SMS/email identity tokens; guest mode bypass[34]

Behavioral Profiling Ban	Absolute prohibition on tracking or behavioral monitoring of children[32]	Complete exclusion of analytics SDKs, session replay trackers, clickstream recorders, and telemetry[32]
Targeted Advertising Ban	Absolute prohibition on targeted advertising directed at children[32]	Zero advertising infrastructure; completely free, ad-free educational distribution[32]
Data Minimization	Processing restricted exclusively to necessary functional data[31]	Localized device storage (IndexedDB); zero collection of biometric, facial, audio, or demographic data[32]
Harm Prevention	Absolute ban on processing likely to cause detrimental effects to a child[33]	Omission of dark patterns, streak penalties, compulsive engagement loops, and social ranking screens[15]

The application functions with zero remote telemetry[33]. All user states, workspace parameters, and module progress are stored strictly in the client's local sandboxed storage via IndexedDB[32]. No personal profiles, unique device identifiers, facial recognition feeds, or biometric information are collected, transmitted, or processed[32]. If an optional multi-device synchronization feature is enabled by an adult, all transmissions require end-to-end encryption with verifiable parental consent managed via parent portals, keeping the application safe from commercial surveillance and fully compliant with data privacy regulations[32].

Architectural Synthesis

The strategic implementation matrix below cross-references each mathematical module with its pedagogical theory, interactive mechanic, localization requirements, and technical validation criteria.

Mathematical Domain	Underlying Cognitive Operation	Interactive Canvas Implementation	Dynamic Scaffolding & Visual Residue	Indic Translation Strategy	Technical Architecture
Dynamic Spatial	Reversibility and area	Dragging parallelogra	Ghost trace of previous	Visual pairing of	WebGL vector

Geometry	conservation under shearing transformations[1]	m vertices within parallel boundary guides; polygon folding/unfolding[1]	boundary configurations retained on canvas[7]	*Kshetraphal* / *Parappalavu* with English *Area* and algebraic formula notation ($A = b \times$)[21]	mesh transformation pipeline; HarfBuzz Wasm font shaping[21]
Multiplicative Reasoning	Partitive/quotative division; distributive area decomposition[2]	Expandable Cartesian grid matrices with dynamic cutting tools and jump lines[2]	Color-coded area partitions persist alongside dynamic equation components[2]	Conversational grouping terminology backed by formal academic registers (*Gunana* / *Bhagahar*)[29]	Canvas2D coordinate matrix math engine; zero layout thrashing
Set-Theoretic Structures	Decentration; logical classification by multiple overlapping criteria[1]	Movable Euler/Venn boundaries with interactive fluid physics and attractor nodes[2]	Static logic truth tables update dynamically beside fluid containers[7]	Direct visual mapping of set intersection ($A \cap$) to regional equivalents for "common ground"[29]	2D rigid-body particle simulation with equilibrium constraints[30]
Mechanical Computational Logic	Algorithmic state updates and Boolean variable evaluation[17]	Pegboard simulation with functional ramps, bistable bits, and	Output basins display physical marble counts matching	Action-oriented labeling for gate components (Pass/Block/	WebAssembly-compiled deterministic physics engine (Rapier2D)[3]

		flippers[17]	logical truth values[7]	Flip) alongside Boolean notation[29]	0

The blueprint synthesizes cognitive developmental psychology, non-extractive visual ergonomics, multilingual script engineering, and privacy-first software development. Replacing passive, transient video streams with interactive, learner-paced explorable explanations allows young learners to build solid, intuitive mental models of mathematical ideas[4]. Removing manipulative gamification mechanics and unnecessary visual clutter creates a calm, focused environment where children can think deeply[13]. Supported by a culturally aware, bilingual typographic system and an offline-first, private-by-design technical base, the platform offers an immersive learning experience that respects the child's mind, agency, and innate capacity for mathematical reasoning[1].

Works cited

1. (PDF) Concrete Operational Stage - ResearchGate, https://www.researchgate.net/publication/392722012_Concrete_Operational_Stage
2. What is the CPA approach? | White Rose Education, https://whiteroseeducation.com/latest-news/what-cpa-approach
3. The 'CPA' approach - HFL Education, https://www.hfleducation.org/blog/cpa-approach
4. Concrete Pictorial Abstract (CPA): A Maths Teaching Guide, https://www.structural-learning.com/post/concrete-pictorial-abstract-approaches-in-the-classroom
5. Jerome Bruner Theory of Cognitive Development - Simply Psychology, https://www.simplypsychology.org/bruner.html
6. CPA Approach Explained | Concrete Pictorial Abstract in Maths, https://mathsnoproblem.com/en/approach/concrete-pictorial-abstract
7. 21 - The Transient Information Principle in Multimedia Learning, https://www.cambridge.org/core/books/cambridge-handbook-of-multimedia-learning/transient-information-principle-in-multimedia-learning/670D96C3B9520320CE558AA855A49EE9
8. What is the Transient Information Effect? | InnerDrive, https://www.innerdrive.co.uk/blog/transient-information-effect/
9. Cognitive load theory, the transient information effect and e-learning, https://researchers.mq.edu.au/en/publications/cognitive-load-theory-the-transient-information-effect-and-e-lear/
10. Strategies for facilitating processing of transient information in ... - PMC, https://pmc.ncbi.nlm.nih.gov/articles/PMC9610327/
11. (PDF) The Effects of Transient Information and Element Interactivity, https://www.researchgate.net/publication/334008492_The_Effects_of_Transient_I

nformation_and_Element_Interactivity_on_Learning_from_Instructional_Animations
12. What is Cognitive Load Theory? Types and Examples - Medium, https://medium.com/octet-design-journal/what-is-cognitive-load-theory-types-and-examples-45ae581ae0ac
13. Cognitive load theory, the transient information effect and e-learning, https://www.researchgate.net/publication/272786898_Cognitive_load_theory_the_transient_information_effect_and_e-learning
14. Gamification in Learning Apps: Strategies & Benefits - Aimprosoft, https://www.aimprosoft.com/blog/gamification-in-learning-apps/
15. Gamification: Dark Patterns, Light Patterns, and Psychology - Medium, https://medium.com/@neil_62402/gamification-dark-patterns-light-patterns-and-psychology-9442d49f8b56
16. A Gamified Exploration of Deceptive Design Awareness for Children, https://arxiv.org/abs/2506.23017
17. Turing Tumble - Educator Guide - Upper Story, https://upperstory.com/turingtumble/assets/ed-guide-full-eng.pdf
18. Board Games That Teach AI Concepts (No Screen Required), https://www.kidsaitools.com/en/articles/board-games-teach-ai-concepts-no-screen
19. Case Study: Turing Tumble - Programming with Marbles, https://katiesteckles.co.uk/casestudies/CS_Turing-Tumble.html
20. (PDF) On the use of a Mechanical Computer Simulator Board-game, https://www.researchgate.net/publication/410951790_On_the_use_of_a_Mechanical_Computer_Simulator_Board-game_to_Teach_Computational_Thinking
21. Typography | UX4G Design System 3.0, https://ux4g.gov.in/foundations/typography
22. Typography - Style - Material Design, https://m1.material.io/style/typography.html
23. Noto Sans Display - Google Fonts, https://fonts.google.com/noto/specimen/Noto+Sans+Display
24. Typography in UI Design: 10 Rules That Will Instantly Improve Your, https://medium.com/@atnoforuiuxdesigning/typography-in-ui-design-10-rules-that-will-instantly-improve-your-interfaces-60604c8cb825
25. NEP 2020 Language Policy Explained: A Must-Read for Educators, https://www.edumerge.com/blog/nep-2020-language-policy-for-educators
26. What does NEP, 2020 state about languages?, Pg 8 - SuperKalam, https://superkalam.com/current-affairs/10-03-2025/what-does-nep-2020-state-about-languages-pg-8-c1cad1bf-fb3c-4a61-8331-e046be6ec4bb
27. Three Language Formula in India by NEP 2020 - LEAD School, https://leadschool.in/blog/three-language-formula/
28. Promotion of Mother Tongue-based Education - PIB, https://www.pib.gov.in/PressReleasePage.aspx?PRID=2291329
29. MULTILINGUALISM AND THE NATIONAL EDUCATION POLICY 2020, https://www.jmc.ac.in/uploads/staticfiles/jmcreview/vol7/1_Amrita%20Sastry_Nivedita%20Ghosh%20The%20JMC%20Review%202023.pdf

30. Matter.js - a 2D rigid body JavaScript physics engine - brm·io, https://brm.io/matter-js/
31. Navigating the DPDP Act: What It Means for EdTech and the Future, https://dalberg.com/our-ideas/navigating-the-dpdp-act-what-it-means-for-edtech-and-the-future-of-digital-learning/
32. DPDP Act Compliance for EdTech & Schools in India, https://ksandk.com/data-protection-and-data-privacy/dpdp-act-compliance-for-edtech-schools/
33. Legal Protection of Children's Data under India's Digital Personal, https://ijassonline.in/HTMLPaper.aspx?Journal=International%20Journal%20of%20Advances%20in%20Social%20Sciences;PID=2025-13-4-2
34. DPDP Act for Schools and EdTech: Handling Children's Data | Drema, https://www.drema.in/blog/dpdp-act-for-schools-edtech-childrens-data
35. Schools - Home - dpdpact.co.in, https://dpdpact.co.in/schools/