In [1]:
```
25
```
Out[1]: 25

Framework

In [2]:
```
sqrt(25)
```
```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
Cell In[2], line 1
----> 1 sqrt(25)

NameError: name 'sqrt' is not defined
```

In [9]:
```
import math #math module has many function
math.sqrt(25)
```
Out[9]: 5.0

In [5]:
```
math.floor(3.5)
```
Out[5]: 3

In [6]:
```
math.ceil(3.5)
```
Out[6]: 4

In [7]:
```
math.floor(4.9)
```
Out[7]: 4

In [8]:
```
math.ceil(4.9)
```
Out[8]: 5

In [11]:
```
math.pow(3,2) #it is sqareroot
```
Out[11]: 9.0

In [12]:
```
math.pow(2,3)
```
Out[12]: 8.0

In [13]:
```
m.floor(2,3)
```
```
---------------------------------------------------------------------------
TypeError                                 Traceback (most recent call last)
Cell In[13], line 1
----> 1 m.floor(2,3)

TypeError: math.floor() takes exactly one argument (2 given)
```

import math as m # import and as a keyword m.floor(3.4)

In [5]:
```
import math as m # import and as a keyword
print(m.floor(3.4))
print(m.ceil(3.4))
print(m.pow(3,4))
print(m.sqrt(10))
```

```
3
4
81.0
3.1622776601683795
```

In [6]:
```
from math import pow, floor, ceil, sqrt #import all function at one, it can under

print(m.floor(3.4))
print(m.ceil(3.4))
print(m.pow(3,4))
```

```
3
4
81.0
```

In [12]:
```
from math import * # print all math module inbuilt function waht ever user want th

print(floor(3.4))
print(ceil(3.4))
print(pow(3,4))
```

```
3
4
81.0
```

In [16]:
```
import math
math.sqrt(25)
```

Out[16]: 5.0

input

In [17]:
```
print(math.pi)
```

```
3.141592653589793
```

In [18]:
```
print(math.e)
```

```
2.718281828459045
```

In [19]:
```
import math as m
```

In [21]:
```
import math as m
m.sqrt(10)
```

Out[21]: 3.1622776601683795

In [22]:
```
round(pow(2,3))
```

Out[22]: 8

In [23]:
```
x2 = int(input('Enter the 1st number'))
y2 = int(input('Enter the 2nd number'))
z2 = x2 + y2
z2
```

Out[23]: 123

In [24]:
```
ch = input('enter an char')
print(ch)
```

print(ch[0])

In [25]:
```
print(ch[0])
```

p

In [26]:
```
print(ch[2])
```

i

In [30]:
```
result = eval(input('enter an expr'))
print(result)
```

343

In [ ]: