

3. Tech Coding

Attempted: 0/1

Input Specification:

input1 : A string S, representing the value and the currency of money.

Output Specification:

Return the value of the currency in Rupees.

Example 1:

input1 : 120 D

Output : 8400

Explanation:

120 D represents 120 Dollars, we first must convert this to rupees using the conversion table.

- $120 \text{ D} = 120 * 70 = 8400$
- $8400 \% 10000007 = 8400$

Therefore, 8400 is returned as the output.

Example 2:

input1 : 240 P

Output : 24000

Explanation:

Mettl Online Assessment © 2021-2031

Need Help?

CPP

```
1 #include<
2 #include<
3 // Read
4
5 int m
6 {
7
8
9
10
```

3. Tech Coding

Attempted: 0/1

Example 1:

input1 : 120 D

Output : 8400

Explanation:

120 D represents 120 Dollars, we first must convert this to rupees using the conversion table.

- $120 \text{ D} = 120 * 70 = 8400$
- $8400 \% 10000007 = 8400$

Therefore, **8400** is returned as the output.

Example 2:

input1 : 240 P

Output : 24000

Explanation:

240 P represents 240 Pounds, we first must convert this to rupees using the conversion table.

- $240 \text{ P} = 240 * 100 = 24000$
- $24000 \% 10000007 = 24000$

Therefore, **24000** is returned as the output.

CPP

```
1 #include<stdio.h>
2 #include<string.h>
3 // Read only rep
4
5 int moneyConve
6 {
7     // Read
8     // Wri
9     throw
10 }
```



3. Tech Coding

Example 1:

input1 : 120 D

Output : 8400

Explanation:

120 D represents 120 Dollars, we first must convert this to rupees using the conversion table.

- $120 \text{ D} = 120 * 70 = 8400$
- $8400 \% 10000007 = 8400$

Therefore, **8400** is returned as the output.

Example 2:

input1 : 240 P

Output : 24000

Explanation:

240 P represents 240 Pounds, we first must convert this to rupees using the conversion table.

- $240 \text{ P} = 240 * 100 = 24000$
- $24000 \% 10000007 = 24000$

Therefore, **24000** is returned as the output.

CPP

Compiler: g++ 5.4.0

```
1 #include<stdio.h>
2 #include<string.h>
3 // Read only region start
4
5 int moneyConversion(char* input1)
6 {
7     // Read only region end
8     // Write code and remove
9     throw "Function moneyCo
10 }
```