

ULIP Integration Document

Version No.: 3.0

Date: 24/03/2026

Project Name: ULIP

This document contains proprietary information of NLDSL. Unauthorized access, copying and replication are prohibited. This document must not be copied in whole or part by any means, without the written authorization of NLDSL, New Delhi, India.

Revision History

Version	Date	Author	Reviewer	Significant Changes
1.0	03/03/2025	Ayush Arya	Nayab Ali	Baseline Version
2.0	08/01/2026	Hasan Mhad Khan	Nayab Ali	Payload Update for BPCL/02
3.0	24/03/2026	Gaurav Tyagi	Pranab Manna	Update

Table of Contents

Contents

Introduction.....	4
1.1 Purpose	4
The Overall Description	4
1.2 Data Integration between BPCL System and ULIP application	4
1.3 BPCL/01	4
1.3.1 Technical Approach	6
1.4 BPCL/02	10
1.4.1 Technical Approach	12
1.5 Data Transmission & Authentication Mechanism	18

Introduction

1.1 Purpose

The purpose of this document is to define and provide details for accessing API for BPCL system information (information about oil and natural gas stations based on StateCode or geographical location (longitude, latitude, and radius) value from ULIP system

This document details the following points:

1. **Data Integration between BPCL and ULIP web service:** Identification of operational points where data integration between **BPCL** and ULIP web service will be needed.
2. **Technical Approach** for performing Data Integration

The Overall Description

Users will need to share their State Code or geographical location (longitude, latitude, and radius) to access the list of public petroleum and natural gas stations through the rest API.

Here are some points to keep in mind when accessing BPCL API data information:

- The API will only share data that is based on the user's provided information.
- ULIP will expose an API for getting data from the BPCL API.
- The BPCL/01 API will take the user information from the user to register that user. And the user will receive ReferenceNo in response, from this ReferenceNo user will be able to access the BPCL/02 API.
- The BPCL/02 API will take ReferenceNo and State Code or geographical location (longitude, latitude, and radius) to give information about petroleum and natural gas stations to the user.

1.2 Data Integration between BPCL System and ULIP application

The ULIP system will receive information from the user and provide data in return.

1.3 BPCL/01

This API is designed to register the user to the BPCL system based on user information. The user will provide their information, and once the user successfully registers, they will get the reference number in the response.

Please note that when making a request, **all of the JSON keys are mandatory in the payload**

```
{
  "customerName": "Ayush",
  "address": "Aligarh UP", "district":
  "Gautam Bhuda Nagar",
  "stateName": "Uttar Pradesh",
  "email": "test@paytm.com",
  "monthlyFuelConsumption":
  "10000", "userId": "test",
  "userIP": "193.2.2.2",
```

	Field Name	Field Description	Format	Required/Not – Required	Length
1	customerName	Customer Name	^[a-zA-Z\s]{2,20}\$	Required	2-20
2	Address	Address	^[a-zA-Z0-9\s,.-]{2,49}\$	Required	2-49
3	District	District	^[a-zA-Z\s]{2,20}\$	Required	2-20
4	StateCode	State Name	^[a-zA-Z\s]{1,30}\$	Required	1-30
5	Email	Email	[A-Za-z0-9\._%+~]+@[A-Za-z0-9\._-]+\.[A-Za-z]{2,}	Required	
6	monthlyFuelConsumption	Monthly fuel consumption	^\d{1,10}\$	Required	1-10
7	userId	User ID	^[a-zA-Z][a-zA-Z0-9\s._@]{1,20}\$	Required	2-20
8	userIP	User IP	^(?:\d{1,3}.){3}\d{1,3}\$	Required	
9	mobileNo	Mobile number	^[6-9]\d{9}\$	Required	10

1.3.1 Technical Approach

1. All the data will be shared through REST web services.
2. The user will share the input for which information is required.
3. BPCL API will share details of BPCL API information that exists in the system in JSON format.
4. The ULIP system will provide the data in JSON Object format in the response body.
5. When we hit the BPCL/01, and the user successfully registers, the user will get a reference number in return.

Request:

The request must be of the following format: **user information** is passed within the URL post request body in JSON format.

For staging -

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/BPCL/01>

```
{
  "customerName": "Ayush",
  "address": "Aligarh UP",
  "district": "Gautam Bhuda Nagar",
  "stateName": "Uttar Pradesh",
  "email": "test@paytm.com",
  "monthlyFuelConsumption": "10000",
  "userId": "test",
  "userIP": "193.2.2.2",
  "mobileNo": "9161999629"
}
```

Curl URL

```
curl --location 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/BPCL/01' \
--header 'Authorization: Bearer eyshbGciqiJlazmxMiJ8.eyJzdWliOiJ1bGwliwiaWF0ljoXNzI2NTU2ODk4LCJhcHBzIjoZGF0YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8Irg\
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data-raw '{
```

```
{
  "customerName": "Ayush",
  "address": "Aligarh UP",
  "district": "Gautam Bhuda Nagar",
  "stateName": "Uttar Pradesh",
  "email": "test@paytm.com",
  "monthlyFuelConsumption": "10000",
  "userId": "test",
  "userIP": "193.2.2.2",
  "mobileNo": "9161999629"
}
```

For production -

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/BPCL/01>

```
{
  "customerName": "Ayush",
  "address": "Aligarh UP",
  "district": "Gautam Bhuda Nagar",
  "stateName": "Uttar Pradesh",
  "email": "test@paytm.com",
  "monthlyFuelConsumption": "10000",
  "userId": "test",
  "userIP": "193.2.2.2",
  "mobileNo": "9161666615"
}
```

Curl URL

```
curl --location 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/BPCL/01' \
--header 'Authorization: Bearer eyshbGciqiJlazmxMiJ8.eyJzdWliOiJ1bGwliwiaWF0IjoxNzI2NTU2ODk4LCJhcHBzljoiZGF0YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8Irg' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data-raw '{
  "customerName": "Ayush",
  "address": "Aligarh UP",
  "district": "Gautam Bhuda Nagar",
  "stateName": "Uttar Pradesh",
  "email": "test@paytm.com",
  "monthlyFuelConsumption": "10000",
}
```

```
"userId": "test",  
"userIP": "193.2.2.2",  
"mobileNo": "9161666615"  
}
```

For obtaining an authentication token, refer to [Section 1.5](#)

Response

To acknowledge the above request, ULIP will send the below response -

In case of an invalid format

1. Invalid email

```
{  
  "response": null,  
  "error": "true",  
  "code": "400 BAD_REQUEST",  
  "message": "Data format failed OR wrong value entered at: email. Format  
should follow [A-Za-z0-9\\._%+\\-]+@[A-Za-z0-9\\.\\-]+\\. [A-Za-z]{2,}"  
}
```

2. Invalid userIP format

```
{  
  "response": null,  
  "error": "true",  
  "code": "400 BAD_REQUEST",  
  "message": "Data format failed OR wrong value entered at: userIP. Format  
should follow ^(?:\\d{1,3}.){3}\\d{1,3}$"  
}
```

3. Invalid mobile format

```
{  
  "response": null,  
  "error": "true",  
  "code": "400 BAD_REQUEST",  
  "message": "Data format failed OR wrong value entered at: mobileNo. Format should  
follow ^[6-9]\\d{9}$"  
}
```

1. In case BPCL API data user information already exists in the BPCL system

```
{
  "response": [
    {
      "response": {
        "ReferenceNo": null,
        "Status": 0,
        "Reason": "Mobile No. already exists"
      },
      "responseStatus": "ERROR"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

2. In case the BPCL API data user information does not exist in the BPCL system

```
{
  "response": [
    {
      "response": {
        "ReferenceNo": "9161666616",
        "Status": 1,
        "Reason": "Data Inserted Successfully."
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

Status Code 200: BPCL API data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: The server is not responding.

1.4 BPCL/02

This API is designed to retrieve information about petroleum and natural gas stations. It can be used by providing either the take State Code or the geographical location (longitude, latitude, and radius) of the desired location.

BPCL merchant(outlet) details are updated weekly, and retail selling prices (RSP) are updated daily to ensure users always see the latest and accurate information.

Please note that when making a request, **all of the JSON keys are mandatory in the payload**. First, the user must enter the reference number. If this reference number exists on the BPCL side, the user can then enter either the State Code or the geographical location (longitude, latitude, and radius). The reference number can be obtained when they hit the BPCL/01 API.

If you choose to use the State Code to access BPCL API data, then the geographical location (longitude, latitude, and radius) fields should be left empty.

Use the state code from the table below to inquire about the BPCL outlet in the respective state.

Serial no.	State Code	State Name
1	AN	Andaman & Nicobar
2	AP	Andhra Pradesh
3	ARP	Arunachal Pradesh
4	AS	Assam
5	BH	Bihar
6	CD	Chandigarh
7	CSG	Chhatisgarh
8	DDH	UT OF D&NH AND D&D
9	DDH	UT OF D&NH AND D&D
10	DEL	Delhi
11	GDD	Goa
12	GJ	Gujarat
13	HP	Himachal Pradesh
14	HR	Haryana
15	JK	Jammu & Kashmir
16	JRK	Jharkhand
17	KAR	Karnataka
18	KER	Kerala
19	LAK	Lakshwadeep
20	LDK	Ladakh
21	MAH	Maharashtra

22	MGL	Meghalaya
23	MNP	Manipur
24	MP	Madhya Pradesh
25	MZ	Mizoram
26	NZ	Nagaland
27	OR	Odisha
28	PB	Punjab
29	PY	Pondicherry
30	RJ	Rajasthan
31	SK	Sikkim
32	TG	Telangana
33	TN	Tamil Nadu
34	TRP	Tripura
35	UP	Uttar Pradesh
36	UTK	Uttarakhand
37	WB	West Bengal

```
{
  "referenceNo":"9161666615
  ",
  "stateCode":"DEL",
  "longitude": "",
  "latitude": "",
  "radius": ""
}
```

If you choose to use the geographical location to access BPCL API data, then State code field should be left empty.

```
{
  "referenceNo":"9161666615
  ",
  "stateCode": "",
  "longitude": "13.080487",
  "latitude": "80.267044",
  "radius": "10"
}
```

	Field Name	Field Description	Format	Required/Not – Required	Length
1	referenceNo	Reference number	^[0-9]\d{9}\$	Required	10

2	StateCode	State Name	^[A-Z]{1,6}\$	Required	1-6
4	longitude	Longitude	^[0-9]{2}\.{0,1}[0-9]{2,15} [0-9]{0,2}\$	Required	0-18
5	latitude	Latitude	^[0-9]{2}\.{0,1}[0-9]{2,15} [0-9]{0,2}\$	Required	0-18
6	radius	Radius	^\d{0,3}(\.\d{1,10})?\$	Required	1-10

1.4.1 Technical Approach

1. All the data will be shared through REST web services.
2. The user will share the input for which information is required.
3. BPCL API will share details of BPCL API station information that exists in the system in JSON format.
4. The ULIP system will provide the data in JSON Object format in the response body.

Request:

The request must be of the following format, where **State Code or geographical location (longitude, latitude, and radius)** are passed within the URL post request body in JSON format.

For staging -

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/BPCL/02>

```
{
  "referenceNo":"9161666748",
  "stateCode": "WB",
  "longitude": "",
  "latitude": "",
  "radius": ""
}
```

Curl URL

```
curl --location 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/BPCL/02' \  
--header 'Authorization: Bearer  
eyshbGciqiJlazmxMiJ8.eyJzdWliOiJ1bGlwliwiaWF0IjoxNzI2NTU2ODk4LCJhcHBzIjoiZGF0  
YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-  
9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8Irg\  
--header 'Content-Type: application/json' \  
--header 'Accept: application/json' \  
--data '{  
  "referenceNo": "9161666748",  
  "stateCode": "WB",  
  "longitude": "",  
  "latitude": "",  
  "radius": ""  
}'
```

For production -

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/BPCL/02>

```
{  
  "referenceNo": "9161666615",  
  "stateCode": "",  
  "longitude": "13.080487",  
  "latitude": "80.267044",  
  "radius": "10"  
}
```

Curl URL

```
curl --location 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/BPCL/02' \  
--header 'Authorization: Bearer  
eyshbGciqiJlazmxMiJ8.eyJzdWliOiJ1bGlwliwiaWF0IjoxNzI2NTU2ODk4LCJhcHBzIjoiZGF0  
YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-  
9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8Irg\  
--header 'Content-Type: application/json' \  
--header 'Accept: application/json' \  
--data '{  
  "referenceNo": "9161666615",  
  "stateCode": "",  
  "longitude": "13.080487",  
  "latitude": "80.267044",  
  "radius": "10"  
}'
```

For obtaining an authentication token, refer to [Section 1.5](#)

Response

To acknowledge the above request, ULIP will send the following response -

In case of an invalid format

1. Invalid referenceNo

```
{
  "response": null, "error":
  "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered at:      referenceNo.
Format should follow ^[0-9]\\d{9}$"
}
```

2. Invalid latitude or longitude format

```
{
  "response": null, "error":
  "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: longitude. Format should
follow ^[0-9]{2}\\.\\{0,1}[0-9]{2,15}|[0-9]{0,2}$"
}
```

3. Invalid radius format

```
{
  "response":
  null, "error":
  "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: radius. Format
should follow ^\\d{0,3}(\\.\\d{1,10})?$"
```

4. Invalid StateCode format

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered at: stateName. Format
should follow ^[a-zA-Z\\s]{1,30}$"
}
```

5. In case the BPCL API referenceNo number does not exist in the BPCL system

```
{
  "response": {
    "response": {
      "errorMsg": "referenceNo is not
valid", "errorCode":
      "PAYLOAD_ERROR"
    },
    "responseStatus": "ERROR"
  },
  "error": "false",
  "code": "200 OK",
  "message": "Success"
}
```

6. In case BPCL API data exists

```
{
  "response": [
    {
      "response": [
        {
          "CUSTOMER_CODE": 383051,
          "CUSTOMER_NAME": "RANJAN SERVICE CENTRE",
          "ADDRESS": "INDIAN OIL RETAIL OUTLET,Plot No 406 407 408,Other",
          "PIN_CODE": 711404,
          "LONGITUDE": 88.14868,
          "LATITUDE": 22.66246,
          "STATE_CODE": "WB",
          "STATE_NAME": "West Bengal",
          "DISTRICT_CODE": "WB009",
          "DISTRICT_NAME": "HOWRAH",
          "PRODUCT_NAMES": null,
          "FACILITIES": "FREE AIR FACILITY,CLEAN DRINKING
WATER,WASHROOM,AUTOMATED OUTLET,RESTROOM FOR MEN AND WOMAN",
          "PRODUCT_DETAILS": [
            {

```

```
"EFFECTIVE_DATE": "24-03-2026",
"PRODUCT_NAME": "HSD",
"PRICE": 92.04
},
{
  "EFFECTIVE_DATE": "24-03-2026",
  "PRODUCT_NAME": "MS",
  "PRICE": 105.43
}
]
},
{
  "CUSTOMER_CODE": 383106,
  "CUSTOMER_NAME": "SRO ASANSOL - VINAY ENTERPRISE",
  "ADDRESS": "NH2- BYPASS JUBILEE MORE KANYAPUR,ASANSOL,Asansol",
  "PIN_CODE": 713341,
  "LONGITUDE": 86.953191,
  "LATITUDE": 23.71638,
  "STATE_CODE": "WB",
  "STATE_NAME": "West Bengal",
  "DISTRICT_CODE": "WB023",
  "DISTRICT_NAME": "PASCHIM BARDHAMAN",
  "PRODUCT_NAMES": "Petrol,XP95,Xtra Green",
  "FACILITIES": "FREE AIR FACILITY,CLEAN DRINKING
WATER,WASHROOM,AUTOMATED OUTLET,XTRAPOWER,XTRAREWARD,RESTROOM FOR
MEN AND WOMAN",
  "PRODUCT_DETAILS": [
    {
      "EFFECTIVE_DATE": "24-03-2026",
      "PRODUCT_NAME": "HSD",
      "PRICE": 92.25
    },
    {
      "EFFECTIVE_DATE": "24-03-2026",
      "PRODUCT_NAME": "XP95",
      "PRICE": 115.2
    },
    {
      "EFFECTIVE_DATE": "24-03-2026",
      "PRODUCT_NAME": "XG",
      "PRICE": 96.03
    },
    {
      "EFFECTIVE_DATE": "24-03-2026",
```

```
        "PRODUCT_NAME": "MS",
        "PRICE": 105.66
    }
  ],
  {
    "CUSTOMER_CODE": 349620,
    "CUSTOMER_NAME": "HOQUE FUEL STATION",
    "ADDRESS": "Vill & PO: Singimari,PS: Maynaguri,Singimari",
    "PIN_CODE": 735302,
    "LONGITUDE": 88.785774,
    "LATITUDE": 26.610614,
    "STATE_CODE": "WB",
    "STATE_NAME": "West Bengal",
    "DISTRICT_CODE": "WB010",
    "DISTRICT_NAME": "JALPAIGURI",
    "PRODUCT_NAMES": "Petrol,XP95,Xtra Green",
    "FACILITIES": "FREE AIR FACILITY,CLEAN DRINKING
WATER,WASHROOM,AUTOMATED OUTLET,RESTROOM FOR MEN AND WOMAN",
    "PRODUCT_DETAILS": [
      {
        "EFFECTIVE_DATE": "24-03-2026",
        "PRODUCT_NAME": "MS",
        "PRICE": 105.54
      },
      {
        "EFFECTIVE_DATE": "24-03-2026",
        "PRODUCT_NAME": "XP95",
        "PRICE": 115.08
      },
      {
        "EFFECTIVE_DATE": "24-03-2026",
        "PRODUCT_NAME": "XG",
        "PRICE": 95.91
      },
      {
        "EFFECTIVE_DATE": "24-03-2026",
        "PRODUCT_NAME": "HSD",
        "PRICE": 92.13
      }
    ],
    "responseStatus": "SUCCESS"
  }
],
```

```
"error": "false",  
"code": "200",  
"message": "Success"
```

7. In case the BPCL API data does not exist

```
{  
  "response": [  
    {  
      "response": [],  
      "responseStatus": "SUCCESS"  
    }  
  ],  
  "error": "false",  
  "code": "200",  
  "message": "Success"  
}
```

Status Code 200: BPCL API data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: The server is not responding.

1.5 Data Transmission & Authentication Mechanism

All data exchanges will be securely done with HTTPS. ULIP's system will request data from BPCL through a URL with the following format:

For staging - <https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/BPCL/01>

Body:

```
{  
  "customerName": "Ayush",  
  "address": "Aligarh UP",  
  "district": "Gautam Bhuda Nagar",  
  "stateName": "Uttar Pradesh",  
  "email": "test@paytm.com",  
  "monthlyFuelConsumption": "10000",  
  "userId": "test",  
  "userIP": "193.2.2.2",  
  "mobileNo": "9161999629"  
}
```

To access the data exchange URL, you would need to use a security mechanism that is implemented by the ULIP system. The process is as follows:

- First time access: you will require a username and password. The username and password would be shared with you beforehand. Once you enter the valid username and password, the ULIP system will return a basic authorization token to you. You can use this token to communicate with the ULIP system until the token gets expired.

In brief, HTTP Basic Authentication works as follows:

When you hit the ULIP secured API for the first time, you need to provide a username and password to get an access token.

```
curl --location 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/user/login' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--data -raw '{
  "username": "xxxx",
  "password": "xxxx"}'
```

Authorization:

Bearer
eyJshbGciqjJlazmxMiJ8.eyJzdWliOiJ1bGlwliwiaWF0IjoxNzI2NTU2ODk4LCJhcHBzljoiZGF0YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8lrg

After successfully authenticating, the user will be logged into the ULIP system and obtain an access token. This token will be used by the user to communicate with the ULIP system. The token has an expiry time that represents the user session, which is typically set to 24 hours. After 24 hours, the session (token) will expire, and the user will need to re-authenticate.

Using the above token, the user can request the ULIP system for the BPCL API for details as follows

```
curl --location 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/BPCL/01' \
--header 'Authorization: Bearer eyJshbGciqjJlazmxMiJ8.eyJzdWliOiJ1bGlwliwiaWF0IjoxNzI2NTU2ODk4LCJhcHBzljoiZGF0YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8lrg' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data -raw '{
  "customerName": "Ayush",
  "address": "Aligarh UP",
  "district": "Gautam Bhuda Nagar",
  "stateName": "Uttar Pradesh",
  "email": "test@paytm.com",
}
```

```
{
  "monthlyFuelConsumption": "10000",
  "userId": "test",
  "userIP": "193.2.2.2",
  "mobileNo": "9161999629"
}
```

For production –

```
curl --location 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/user/login' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--data -raw '{
  "username": "xxx",
  "password": "xxx"
}'
```

Authorization:

Bearer

eyshbGciqiJlazmxMiJ8.eyJzdWliOiJ1bGlwliwiaWF0ljoXNzI2NTU2ODk4LCJhcHBzljoiZGF0YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8lrg

Upon successful authentication, the user would be logged into the ULIP system and get an access token. Though this token user can communicate with ULIP. This token has an expiry time that represents the user session. The session time out for the same to be fixed hour generally it is for 24 hours. After 24 hours, the session (token) will expire, and the user needs to reauthenticate.

Using the above token, the user can request the ULIP system for details as follows -

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/BPCL/01>

```
curl --location 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/BPCL/01' \
--header 'Authorization: Bearer
eyshbGciqiJlazmxMiJ8.eyJzdWliOiJ1bGlwliwiaWF0ljoXNzI2NTU2ODk4LCJhcHBzljoiZGF0YXB1c2gifQ.dqXUxA7agKxu9w961sr-QNG1g-9TWWpQQLUX6CsUO5drkwmny9hU4hlf6cOr8CXHIJ67Nv-HdGNtHtr2bH8lrg' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--data -raw '{
  "customerName": "Ayush",
  "address": "Aligarh UP",
  "district": "Gautam BhudaNagar",
  "StateCode": "Uttar Pradesh",
  "email": "test@paytm.com",
  "monthlyFuelConsumption": "10000",
  "userId": "test",
  "userIP": "193.2.2.2",
  "mobileNo": "9161666616"
}'
```