

ULIP Integration Requirement Document

Version No.: 4.0

Date: 08/11/2021

Project Name: ULIP

This document contains proprietary information of NLDSL. Unauthorized access, copying and replication are prohibited. This document must not be copied in whole or part by any means, without the written authorization of NLDSL, Noida, India.

Revision History

Version	Date	Author	Reviewer	Significant Changes
1.0	08/11/2021	Hasan Mhad Khan	Nayab Ali	Baseline Version
2.0	01/10/2024	Girish Chander	Nayab Ali	Updated
3.0	09/05/2025	Hasan Mhad Khan	Nayab Ali	New API details added
4.0	03/02/2025	Sudhanshu Singh	Nayab Ali	Regex Updated for Input Parameter for Icegate 13

Table of Contents

Introduction	4
1.1 Purpose	4
The Overall Description	4
1.2 Data Integration between ICEGATE System and ULIP application.....	5
1.3 ICEGATE/01.....	5
1.3.1 Technical Approach.....	5
1.4 ICEGATE/02.....	9
1.4.1 Technical Approach.....	9
1.5 ICEGATE/03.....	13
1.5.1 Technical Approach.....	13
1.6 ICEGATE/04.....	16
1.6.1 Technical Approach.....	17
1.7 ICEGATE/05.....	21
1.7.1 Technical Approach.....	21
1.8 ICEGATE/06.....	25
1.8.1 Technical Approach.....	25
1.9 ICEGATE/07.....	29
1.9.1 Technical Approach.....	29
1.10 ICEGATE/08	33
1.10.1 Technical Approach	33
1.11 ICEGATE/09	38
1.11.1 Technical Approach	39
1.12 ICEGATE/10	43
1.12.1 Technical Approach	43
1.13 ICEGATE/11	47
1.13.1 Technical Approach	48
1.14 ICEGATE/12	55
1.14.1 Technical Approach	56
1.15 ICEGATE/13	60
1.15.1 Technical Approach	60
1.16 Data Transmission & Authentication Mechanism	64

Introduction

1.1 Purpose

The purpose of this document is to define and provide details for accessing API for the ICEGATE (Indian Customs Electronic Data Interchange (EDI) Gateway) system information (e-filing services) from the ULIP system.

This document details the following points:

1. **Data Integration between ICEGATE and ULIP web service:** Identification of operational points where data integration between ICEGATE and ULIP web service will be needed.
2. **Technical Approach** for Performing Data Integration

The Overall Description

User will share the information such as **EGM number, BE number and shipping bill number** based on data send by user ULIP system will call respective **ICEGATE** API for accessing information.

Following are the point for accessing vehicle information: -

This API will share data based on information provided by user. ULIP will expose API for getting data from ICEGATE API.

1. **ICEGATE/01** API will take IGM and IGM date number from user and get data from ICEGATE API.
2. **ICEGATE/02** API will take BE number and date from user and get data from ICEGATE API.
3. **ICEGATE/03** API will take BE number and date from user and get data from ICEGATE API.
4. **ICEGATE/04** API will take Site id, IMO code, Vessel code, arrival data from user and get data from ICEGATE API.
5. **ICEGATE/05** API will take shipping bill number & date from user and get data from ICEGATE API.

6. **ICEGATE/06** API will take shipping bill number & date from user and get data from ICEGATE API.
7. **ICEGATE/07** API will take the IGM number and IGM date from the user and get data from the ICEGATE API.
8. **ICEGATE/08** API will take the EGM number and EGM date from the user and get data from the ICEGATE API.
9. ICEGATE/09 will provide MAWB details when Location and MAWB details are entered as input
10. ICEGATE/10 will provide MAWB details when the Master Bill Number and House Airway Bill no are entered as input
11. ICEGATE/11 will provide Air Export General Manifest & Air Import General Manifest Job Status Details
12. ICEGATE/12 will provide Manual/Courier/Postal SB details
13. ICEGATE/13 will provide e-Seal details

1.2 Data Integration between the ICEGATE System and the ULIP application

The user will share information with the ULIP system based on data shared ULIP will provide data to the user.

1.3 ICEGATE/01

This API will take **VCN number** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	igmNo	vessel call number as available in ICEGATE system.	[0-9]{1,7}	Required	Min 1 Max 7
2	igmDt	IGM date	[0-9]{8}	Required	Max 8

1.3.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **IGM number** for which detail is required.
3. ICEGATE API will share details of vessel information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

IGM number **2001362** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01>

```
{"igmNo":"2001362","igmDt":"11102018"}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 62dad653-e293-dbff-983e-388f64ae1cd8' \
-d '{"igmNo":"2001362","igmDt":"11102018"}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01>

```
{"igmNo":"2001362","igmDt":"11102018"}
```

Curl URL

```
curl -X POST \
```

```
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 62dad653-e293-dbff-983e-388f64ae1cd8' \
-d '{"igmNo":"2001362","igmDt":"11102018"}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid igm number

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: igmNo.
Format should follow [0-9]{1,10}"
}
```

2. Invalid date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered
at: igmDt. Format should follow [0-9]{8}"
}
```

b) In case of igm number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "voyageNo": null,
        "vesselType": null,
        "containerNo": null,
        "expDtOfArrival": null,
        "portOfArrival": null,
        "imoCodeOfVessel": null,
        "igmDt": null,
        "igmNo": null,
        "vesselCode": null,
        "totalNoOfLines": null,
        "masterName": null
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case IGM number exist

```
{
  "response": [
    {
      "response": {
        "voyageNo": "NILLL",
        "vesselType": "C",
        "containerNo": [
          "MLCU1234567",
          "TRLU1234567",
          "TTNU1234567",
          "YMLU1234567"
        ],
        "expDtOfArrival": "12102018",
        "portOfArrival": "INCCU1",

```

```

        "imoCodeOfVessel": "-",
        "igmDt": "11102018",
        "igmNo": 2001362,
        "vesselCode": "394137",
        "totalNoOfLines": 4,
        "masterName": "."
    },
    "responseStatus": "SUCCESS"
},
{
    "error": "false",
    "code": "200",
    "message": "Success"
}

```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.4 ICEGATE/02

This API will take **BE number** and **BE date** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	beNo	Bill of Entry Number as available in ICEGATE system.	[0-9]{1,7}	Required	7
2	beDt	BE date	[0-9]{8}	Required	8

1.4.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **BE number** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

BE number **2002892** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/02>

```
{"beNo": "2002892", "beDt": "16072011"}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/02 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TExp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: d0fa9f41-ec93-2b83-9b90-754b6ad24395' \
-d '{"beNo": "2002892", "beDt": "16072011"}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/02>

```
{"beNo": "2002892", "beDt": "16072011"}
```

Curl URL

```
curl -X POST \
```

```
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/02 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TExp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: d0fa9f41-ec93-2b83-9b90-754b6ad24395' \
-d '{"beNo":"2002892","beDt":"16072011"}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid BE number

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered
at: beNo. Format should follow [0-9]{7}"
}
```

2. Invalid date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered
at: beDt. Format should follow [0-9]{8}"
}
```

b) In case of BE number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "boeDetails": []
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case BE number exist

```
{
  "response": [
    {
      "response": {
        "boeDetails": [
          {
            "imoCode": "1000000",
            "containerNo": [
              "MSCU7786602"
            ],
            "unitOfQt": "MTS",
            "igmDt": "04072011",
            "natureOfCargo": "C",
            "countryOrig": "BR",
            "grossWt": 25.99,
            "totNoPkg": 56
          }
        ]
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
}
```

```
"message": "Success"
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.5 ICEGATE/03

This API will take **shipping bill number** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	beNo	Shipping Bill number as available in ICEGATE system.	[0-9]{1,7}	Required	7
2	beDt	BE date	[0-9]{8}	Required	8

1.5.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **BE number** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

BE number **6330973** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/03>

```
{"beNo": "6330973", "beDt": "22032012"}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/03 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TExp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{"beNo": "6330973", "beDt": "22032012"}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/03>

```
{"beNo": "6330973", "beDt": "22032012"}
```

Curl URL

```
curl -X POST \
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/03 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TExp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{"beNo": "6330973", "beDt": "22032012"}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid BE number

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: beNo. Format
should follow [0-9]{7}"
}
```

2. Invalid date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered
at: beDt. Format should follow [0-9]{8}"
}
```

b) In case of BE number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "oocNo": null,
        "oocDt": null
      },
      "responseStatus": "SUCCESS"
    }
  ]
}
```

```
}  
],  
"error": "false",  
"code": "200",  
"message": "Success"  
}
```

c) In case BE number exist

```
{  
  "response": [  
    {  
      "response": {  
        "oocNo": 2004296615,  
        "oocDt": "26032012"  
      },  
      "responseStatus": "SUCCESS"  
    }  
  ],  
  "error": "false",  
  "code": "200",  
  "message": "Success"  
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.6 ICEGATE/04

This API will take **shipping bill number** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	siteld	Site ID as available in ICEGATE system.	[0-9]{6}	Required	6

2	imoCode	Unique identifier for ships / registered ship management companies.	[A-Z0-9]{1,25}	Required	Min 1 Max 25
3	vesselCode	Vessel Code as available in ICEGATE system.	[A-Z0-9]{1,25}	Required	Min 1 Max 25
4	arrivalDate	The date when ship is estimated to arrive at the port of Call.	DATE (DDMMYYYY)	Required	8

1.6.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **data (site id, IMO code ,vessel code and arrival date)** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

site id, IMO code, vessel code and arrival date is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/04>

```
{
  "siteId": "INBOM1",
  "imoCode": "9241205",
  "vesselCode": "DCNT2",
  "arrivalDate": "15012020"
}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/04 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "siteId": "INBOM1",
  "imoCode": "9241205",
  "vesselCode": "DCNT2",
  "arrivalDate": "15012020"
}
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/04>

```
{
  "siteId": "INBOM1",
  "imoCode": "9241205",
  "vesselCode": "DCNT2",
  "arrivalDate": "15012020"
}
```

Curl URL

```
curl -X POST \
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/04 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
```

```
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \  
-d ' {  
  "siteId": "INBOM1",  
  "imoCode": "9241205",  
  "vesselCode": "DCNT2",  
  "arrivalDate": "15012020"  
}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid site id

```
{  
  "response": null,  
  "error": "true",  
  "code": "400",  
  "message": "Data format failed OR wrong value entered at:  siteId. Format  
should follow [A-Z0-9]{6}"  
}
```

2. Invalid IMO code

```
{  
  "response": null,  
  "error": "true",  
  "code": "400",  
  "message": "Data format failed OR wrong value entered  
at:  imoCode. Format should follow [A-Z0-9]{1,25}"  
}
```

3. Invalid vessel code

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered
at: vesselCode. Format should follow [A-Z0-9]{1,25}"
}
```

4. Invalid date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered
at: arrivalDate. Format should follow [0-9]{8}"
}
```

b) In case of data does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {},
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case data exist

```
{
  "response": [
```

```

{
  "response": {
    "shippingLineCode": "MSC",
    "shippingAgentCode": "JMB01",
    "rotationNumber": "1000045",
    "rotationDt": "24012020"
  },
  "responseStatus": "SUCCESS"
},
"error": "false",
"code": "200",
"message": "Success"
}

```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.7 ICEGATE/05

This API will take **shipping bill number** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	sbNo	Shipping Bill number as available in ICEGATE system.	[0-9]{7}	Required	7
2	sbDt	date	[0-9]{8}		8

1.7.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **shipping Bill number** and date for which detail is required.
3. ICEGATE API will share information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

Shipping Bill number **4164154** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/05>

```
{
  "sbNo": "6845161",
  "sbDt": "02042016"
}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/05 \
-H 'accept: application/json' \
-H 'authorization: Bearer eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh dGFwdXNoIn0.-FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838 uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "sbNo": "6845161",
  "sbDt": "02042016"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/05>

```
{
  "sbNo": "6845161",
  "sbDt": "02042016"
}
```

Curl URL

```
curl -X POST \
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/05 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "sbNo": "6845161",
  "sbDt": "02042016"
}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid shipping bill number

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: sbNo. Format
should follow [0-9]{1,7}"
}
```

2. Invalid shipping bill date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: sbDt. Format
should follow [0-9]{8}"
}
```

b) In case of shipping bill number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "sbNo": null,
        "unitOfQt": null,
        "natureOfCargo": null,
        "noOfPkgs": null,
        "portOfDest": null,
        "sbDt": null,
        "grossQt": null
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case SB number exist

```
{
  "response": [
    {
      "response": {
```

```

        "sbNo": "6845161",
        "unitOfQt": "null",
        "natureOfCargo": "C",
        "noOfPkgs": 287,
        "portOfDest": "LKCMB",
        "sbDt": "02042016",
        "grossQt": null
    },
    "responseStatus": "SUCCESS"
}
],
"error": "false",
"code": "200",
"message": "Success"
}

```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid json syntax, invalid json key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.8 ICEGATE/06

This API will take **shipping bill number** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	sbNo	Shipping Bill number as available in ICEGATE system.	[0-9]{7}	Required	7
2	sbDt	date	[0-9]{8}	Required	8

1.8.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **shipping Bill number** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

Shipping Bill number **5444772** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/06>

```
{
  "sbNo": "5444772",
  "sbDt": "16092011"
}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/06 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "sbNo": "5444772",
  "sbDt": "16092011"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/06>

```
{
  "sbNo": "5444772",
  "sbDt": "16092011"
}
```

Curl URL

```
curl -X POST \
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/06 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "sbNo": "5444772",
  "sbDt": "16092011"
}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid shipping bill number

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: sbNo. Format
should follow [0-9]{1,7}"
}
```

2. Invalid shipping bill date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at: sbDt. Format
should follow [0-9]{8}"
}
```

b) In case of shipping bill number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "leoDt": null
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case SB number exist

```
{
  "response": [
    {
      "response": {
        "leoDt": "23092011"
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
}
```

```

    "message": "Success"
  }

```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.9 ICEGATE/07

This API will take **IGM number** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	igmNo	Import General Manifest Number as available in ICEGATE system.	[0-9]{1,7}	Required	Min 1 Max 10
2	igmDt	IGM date	[0-9]{8}	Required	Max 8

1.9.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **IGM number and IGM date** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

IGM **2000690** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/07>

```
{
  "igmNo": "2000690",
  "igmDt": "31012014"
}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/07 \
-H 'accept: application/json' \
-H 'authorization: Bearer eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh dGFwdXNoIn0.-FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838 uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "igmNo": "2000690",
  "igmDt": "31012014"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/07>

```
{
  "igmNo": "2000690",
  "igmDt": "31012014"
}
```

Curl URL

```
curl -X POST \
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/07 \
-H 'accept: application/json' \
```

```
-H 'authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh  
dGFwdXNoIn0.-  
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAxp6vb838  
uxtet63g' \  
-H 'cache-control: no-cache' \  
-H 'content-type: application/json' \  
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \  
-d '{  
  "igmNo": "2000690",  
  "igmDt": "31012014"  
}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid IGM number

```
{  
  "response": null,  
  "error": "true",  
  "code": "400",  
  "message": "Data format failed OR wrong value entered at: beNo. Format  
should follow [0-9]{7}"  
}
```

2. Invalid IGM date

```
{  
  "response": null,  
  "error": "true",  
  "code": "400",  
  "message": "Data format failed OR wrong value entered at: igmDt. Format  
should follow [0-9]{8}"  
}
```

b) In case of IGM number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "imoCodeOfVessel": null,
        "vesselCode": null,
        "voyageNo": null,
        "portOfDest": null,
        "portOfShipment": null,
        "importerName": null,
        "modeOfTransport": null,
        "containerDetails": null
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case IGM number exist

```
{
  "response": [
    {
      "response": {
        "imoCodeOfVessel": "12345",
        "vesselCode": "TETS1",
        "voyageNo": "03",
        "portOfDest": "INBOM1",
        "portOfShipment": "INPAV1",
        "importerName": "HINDUSTAN CARGO",
        "modeOfTransport": "T",
        "containerDetails": [
          {
            "containerNo": "MMAU1162485",
            "totNoPkg": 1
          }
        ]
      }
    }
  ]
}
```

```
    },  
    "responseStatus": "SUCCESS"  
  },  
  ],  
  "error": "false",  
  "code": "200",  
  "message": "Success"  
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.10 ICEGATE/08

This API will take **EGM number**, **EGM date** and connect with ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	egmNo	Export General Manifest Number as available in ICEGATE system.	[0-9]{7}	Required	7
2	egmDt	EGM date	[0-9]{8}	Required	8

1.10.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide **EGM number and EGM date** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. ULIP system will provide the data in JSON Object format in response body.

Example:

EGM number **21889** and date **20112008** is shared by ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/08>

```
{
  "egmNo": "103978",
  "egmDt": "29032016"
}
```

Curl URL

```
curl -X POST \
https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/08 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh
dGFwdXNoIn0.-
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TAXp6vb838
uxtet63g' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \
-d '{
  "egmNo": "103978",
  "egmDt": "29032016"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/08>

```
{
  "egmNo": "103978",
```

```
"egmDt": "29032016"  
}
```

Curl URL

```
curl -X POST \  
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/08 \  
-H 'accept: application/json' \  
-H 'authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsIm1hdCI6MTYyNTczMzQ0NCwiYXBwcyI6ImRh  
dGFwdXNoIn0.-  
FTXGNLmro8bXz45XsfCWkz05u4fdnxpIYXK7HZ7ufbAtbXejm0rsYiv8rzjiUr0bjg1TExp6vb838  
uxtet63g' \  
-H 'cache-control: no-cache' \  
-H 'content-type: application/json' \  
-H 'postman-token: 74f68893-0e56-f20f-8581-827680413bb4' \  
-d '{  
  "egmNo": "103978",  
  "egmDt": "29032016"  
}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid shipping bill number

```
{  
  "response": null,  
  "error": "true",  
  "code": "400",  
  "message": "Data format failed OR wrong value entered at: beNo. Format  
should follow [0-9]{7}"  
}
```

2. Invalid EGM date

```
{
  "response": null,
  "error": "true",
  "code": "400",
  "message": "Data format failed OR wrong value entered at:  egmDt. Format
should follow [0-9]{8}"
}
```

b) In case of EGM number does not exist in ICEGATE system

```
{
  "response": [
    {
      "response": {
        "egmNo": null,
        "egmDt": null,
        "sbNo": null,
        "portOfDest": null,
        "noOfPckgs": null,
        "containerNo": null
      },
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

c) In case EGM number exist

```
{
  "response": [
    {
      "response": {
        "sbDetails": [
          {
            "containerNo": [
              "GESU5599051"
            ],
            "sbNo": 6825667,

```

```
        "noOfPckgs": 25,  
        "portOfDest": "SAJED"  
    },  
    {  
        "containerNo": [  
            "TCKU1732080"  
        ],  
        "sbNo": 6828170,  
        "noOfPckgs": 33,  
        "portOfDest": "GBCHD"  
    },  
    {  
        "containerNo": [  
            "APHU6684925"  
        ],  
        "sbNo": 6832965,  
        "noOfPckgs": 127,  
        "portOfDest": "USPXX"  
    },  
    {  
        "containerNo": [  
            "APZU3219840"  
        ],  
        "sbNo": 6833000,  
        "noOfPckgs": 186,  
        "portOfDest": "GBCHD"  
    },  
    {  
        "containerNo": [  
            "APHU4645318"  
        ],  
        "sbNo": 6833796,  
        "noOfPckgs": 52,  
        "portOfDest": "GBNWX"  
    },  
    {  
        "containerNo": [  
            "APHU4645318"  
        ],  
        "sbNo": 6834068,  
        "noOfPckgs": 1,  
        "portOfDest": "GBNWX"  
    },  
    {  
        "containerNo": [  
            "APZU4319058"  
        ],  
    },
```

```
        "sbNo": 6887160,  
        "noOfPckgs": 5225,  
        "portOfDest": "GBNWY"  
      },  
      {  
        "containerNo": [  
          "APZU3330134"  
        ],  
        "sbNo": 6887578,  
        "noOfPckgs": 1218,  
        "portOfDest": "GBNWY"  
      },  
      {  
        "containerNo": [  
          "CRXU3001523"  
        ],  
        "sbNo": 6887587,  
        "noOfPckgs": 1218,  
        "portOfDest": "USCHI"  
      }  
    ],  
    "egmNo": 21889,  
    "egmDt": "20112008"  
  },  
  "responseStatus": "SUCCESS"  
}  
],  
"error": "false",  
"code": "200",  
"message": "Success"  
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.11 ICEGATE/09

This API will provide MAWB details when the Location and MAWB details are entered as input

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	mawbNumber	MASTER AIRWAY BILL NUMBER	^[0-9]{1,20}	Required	7
2	custSite	location	^[A-Za-z0-9]{6}	Required	8

1.11.1 Technical Approach

1. All the data will be shared through REST web services.
2. The ULIP system will provide the mawb number and location, which is required for details.
3. ICEGATE API will share details of cargo information that exists in the ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in the **response** key in the response body.
5. The ULIP system will provide the data in JSON Object format in the response body.

Example:

Mawb number 06536234962 is shared by the ULIP system, then ICEGATE-integration will request the ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/09>

```
{  
  "mawbNumber": "06536234962",  
  "custSite": "INDEL42iio2oo21"  
}
```

Curl URL

```
curl -L -X POST 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/09' -H
'Authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:
application/json' --data-raw '{
  "mawbNumber": "06536234962",
  "custSite": "INDEL4"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/09>

```
{
  "mawbNumber": "06536234962",
  "custSite": "INDEL4"
}
```

Curl URL

```
curl -L -X POST 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/09'
-H 'Authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:
application/json' --data-raw '{
  "mawbNumber": "06536234962",
  "custSite": "INDEL4"
}'
```

For obtaining an authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the following response -

a) In case of invalid format**1. Invalid mawb number**

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered a
t: mawbNumber. Format should follow  ^[0-9]{1,20}$"
}
```

2. Invalid custSite

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered a
t: custSite. Format should follow  ^[A-Za-z0-9]{6}$"
}
```

b) In case the mawb number & custSite does not exist in the ICEGATE system

```
{
  "response": [
    {
      "response": {
        "errCode": "ERROR0004",
        "errMsg": "No Records Available"
      },
      "responseStatus": "ERROR",
      "message": null
    }
  ],
  "error": "false",
}
```

```
{
  "code": "200",
  "message": "Success"
}
```

c) In case the mawb number exists

```
{
  "response": [
    {
      "response": [
        {
          "grossWeight": "100",
          "flightDate": "15022025 12:02",
          "igmRtn": "71074",
          "dateOfIntegration": null,
          "mawbNumber": "06536234962",
          "totalPackage": "100",
          "igmDate": "25022025 12:02",
          "custSite": "INDEL4",
          "remarks": null,
          "flightNumber": "SV758",
          "status": "C"
        }
      ],
      "responseStatus": "SUCCESS",
      "message": null
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorised

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.12 ICEGATE/10

This API will take the **MAWB number** and connect with the ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	mawbNumber	MASTER AIRWAY BILL NUMBER	^[0-9]{1,20}	Required	20 max
2	hawbNumber	HOUSE AIRWAY BILL NUMBER	^[A-Za-z0-9]{1,15}	Required	15 max

1.12.1 Technical Approach

1. All the data will be shared through REST web services.
2. ULIP system will provide the **mawb number and hawb number** for which detail is required.
3. ICEGATE API will share details of cargo information that exists in the ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in the **response** key in the response body.
5. The ULIP system will provide the data in JSON Object format in the response body.

Example:

The MAWB and HAWB number are shared by the ULIP system, then ICEGATE integration will request the ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/10>

```
{  
  "mawbNumber": "15754138070",  
  "hawbNumber": "15751033332m23322"  
}
```

Curl URL

```
curl -L -X POST 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/10' -H
'Authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:
application/json' --data-raw '{
  "mawbNumber": "15754138070",
  "hawbNumber": "1575103333"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/10>

```
{
  "mawbNumber": "15754138070",
  "hawbNumber": "1575103333"
}
```

Curl URL

```
curl -L -X POST 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/10'
-H 'Authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:
application/json' --data-raw '{
  "mawbNumber": "15754138070",
  "hawbNumber": "1575103333"
}'
```

For obtaining an authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the following response -

a) In case of invalid format

1. Invalid mawb number

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered a
t: mawbNumber. Format should follow ^[0-9]{1,20}$"
}
```

2. Invalid hawbNumber

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered a
t: hawbNumber. Format should follow ^[A-Za-z0-9]{1,15}$"
}
```

b) In case the mawb number & hawb Number do not exist in the ICEGATE system

```
{
  "response": [
    {
      "response": {
        "errCode": "ERROR0004",
        "errMsg": "No Records Available"
      }
    }
  ]
}
```

```
    },
    "responseStatus": "ERROR",
    "message": null
  }
],
"error": "false",
"code": "200",
"message": "Success"
}
```

c) In case the mawb number and hawb number exist

```
{
  "response": [
    {
      "response": {
        "icdBlStatusResponseDto": {
          "subLineNo": "1",
          "voyageNo": "null",
          "mawbDT": "25052019",
          "portDest": "INJJK6",
          "uqc": "KGS",
          "igmDT": "31072019",
          "beLoc": "4",
          "containerDtlsResponseDtos": [
            {
              "subLineNo": "1",
              "lineNo": "1",
              "igmRTN": "2001935",
              "errCode": "40|41",
              "contNo": "MAEU4698704",
              "contStatus": "FCL",
              "arrDT": "null",
              "arrStatus": "null"
            },
            {
              "subLineNo": "1",
              "lineNo": "1",
              "igmRTN": "2001935",

```

```
        "errorCode": "100",
        "contNo": "MAEU4698704",
        "contStatus": "FCL",
        "arrDT": "null",
        "arrStatus": "null"
      }
    ],
    "getewayPort": "1",
    "grossWeight": "21200",
    "hawbDT": "25052019",
    "lineNo": "1",
    "igmRTN": "2001935",
    "packageCode": "PCS",
    "descOfGoods": "ROLLED WORK",
    "totalPackage": "2",
    "inwDT": "31072019",
    "vesselCode": "null",
    "cargoMovement": "LC"
  }
},
"responseStatus": "SUCCESS",
"message": null
}
],
"error": "false",
"code": "200",
"message": "Success"
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorised

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.13 ICEGATE/11

This API will provide Air Export General Manifest & Air Import General Manifest Job Status Details.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	location	Location	^[A-Za-z0-9]{6}	Required	6
2	flightDt	Flight Date	^((0[1-9] [12][0-9] 3[01])(0[1-9] 1[012])\\d{4})	Required	8
3	flightNo	Flight number	^[A-Za-z0-9]{1,30}	Required	1-30
4	flag	Flag	^[A-Za-z0-9]{1,15}	Required	1-15

1.13.1 Technical Approach

1. All the data will be shared through REST web services.
2. The ULIP system will provide the **flight number and other information** for which detail is required.
3. ICEGATE API will share details of cargo information that exists in the ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in the **response** key in the response body.
5. The ULIP system will provide the data in JSON Object format in the response body.

Example:

Flight number and other information are shared by the ULIP system, then ICEGATE-integration will request the ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/11>

```
{
  "location": "IMMUN1",
```

```
"flightDt": "15042025",  
"flightNo": "123G",  
"flag": "EGM"  
}
```

Curl URL

```
curl -L -X POST 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/11' -H  
'Authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdhcSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3  
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3  
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:  
application/json' --data-raw '{  
  "location": "IMMUN1",  
  "flightDt": "15042025",  
  "flightNo": "123G",  
  "flag": "EGM"  
'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/11>

```
{  
  "location": "IMMUN1",  
  "flightDt": "15042025",  
  "flightNo": "123G",  
  "flag": "EGM"  
}
```

Curl URL

```
curl -L -X POST 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/11'  
-H 'Authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdhcSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3  
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
```

```
F2gbl2fwTGdfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept: application/json' --data-raw '{
  "location": "IMMUN1",
  "flightDt": "15042025",
  "flightNo": "123G",
  "flag": "EGM"
}'
```

For obtaining an authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the following response -

a) In case of invalid format

1. Invalid location

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered at: location. Format should follow ^[A-Za-z0-9]{6}$"
}
```

2. Invalid flight date (flightDt)

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered at: flightDt. Format should follow ^((0[1-9]|[12][0-9]|3[01])(0[1-9]|1[012])\\d{4})$"
}
```

```
}
```

3. Invalid flight number (flightNo)

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data_format failed OR wrong value entered a
t: flightNo. Format should follow  ^[A-Za-z0-9]{1,30}$"
}
```

4. Invalid flag

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data_format failed OR wrong value entered a
t: flag. Format should follow  ^[A-Za-z0-9]{1,15}$"
}
```

b) In case the flight number does not exist in the ICEGATE system

```
{
  "response": [
    {
      "response": {
```

```

        "errCode": "ERROR0004",
        "errMsg": "No Records Available"
    },
    "responseStatus": "ERROR",
    "message": null
}
],
"error": "false",
"code": "200",
"message": "Success"
}

```

c) In case the flight number exists

```

{
  "response": [
    {
      "response": [
        {
          "ackSentTime": null,
          "flightDate": "19012022",
          "ackReceivedTime": null,
          "receivedTime": "20/01/2025 12:06",
          "sentTime": "20032025 12:03",
          "customLocation": "INDEL4",
          "flightNumber": "KU332",
          "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
        },
        {
          "ackSentTime": null,
          "flightDate": "19012022",
          "ackReceivedTime": null,
          "receivedTime": "17/01/2025 17:14",
          "sentTime": "17032025 05:03",
          "customLocation": "INDEL4",
          "flightNumber": "KU332",
          "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
        },
        {
          "ackSentTime": null,

```

```
"flightDate": "19012022",
"ackReceivedTime": null,
"receivedTime": "29/01/2025 15:40",
"sentTime": "29012025 03:01",
"customLocation": "INDEL4",
"flightNumber": "KU332",
"status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "27/01/2025 13:07",
      "sentTime": "27012025 01:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
      "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "24/01/2025 17:21",
      "sentTime": "24012025 05:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
      "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "23/01/2025 15:49",
      "sentTime": "23012025 03:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
      "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "23/01/2025 15:48",
```

```
"sentTime": "23012025 03:01",
"customLocation": "INDEL4",
"flightNumber": "KU332",
"status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "22/01/2025 12:25",
      "sentTime": "22012025 12:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
      "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "14/01/2025 16:28",
      "sentTime": "14012025 04:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
      "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "13/01/2025 10:12",
      "sentTime": "13012025 10:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
      "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    },
    {
      "ackSentTime": null,
      "flightDate": "19012022",
      "ackReceivedTime": null,
      "receivedTime": "10/01/2025 13:09",
      "sentTime": "10012025 01:01",
      "customLocation": "INDEL4",
      "flightNumber": "KU332",
```

```

        "status": "Inserted Successfully in Database. Sent to ICE
S for validation."
    }
    ],
    "responseStatus": "SUCCESS",
    "message": null
  }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}

```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorised

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.14 ICEGATE/12

This API will take the **shipping bill number** and connect with the ICEGATE API to get data.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	location	Location	^[A-Za-z0-9]{6}	Required	6
2	sbNo	Shipping Bill Number	^[0-9]{7}	Required	7
3	sbDate	Shipping Bill Date	^((0[1-9] [12][0-9] 3[01])(0[1-9] 1[012])\\d{4})	Required	8

1.14.1 Technical Approach

1. All the data will be shared through REST web services.
2. The ULIP system will provide **SB number** for which detail is required.
3. ICEGATE API will share details of cargo information which exist in ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in **response** key in response body.
5. The ULIP system will provide the data in JSON Object format in response body.

Example:

The SB number is shared by the ULIP system, then ICEGATE-integration will make a request to ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/12>

```
{
  "sbNo": "1340721",
  "sbDate": "23102024",
  "location": "INCCU5"
}
```

Curl URL

```
curl -L -X POST 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/12' -H
'Authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
F2gb12fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:
application/json' --data-raw '{
  "sbNo": "1340721",
  "sbDate": "23102024",
  "location": "INCCU5"
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/12>

```
{
  "sbNo": "1340721",
  "sbDate": "23102024",
  "location": "INCCU5"
}
```

Curl URL

```
curl -L -X POST 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/11'
-H 'Authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:
application/json' --data-raw '{
  "sbNo": "1340721",
  "sbDate": "23102024",
  "location": "INCCU5"
}'
```

For obtaining an authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the following response -

a) In case of invalid format

1. Invalid SB number

```
{
  "response": null,
```

```
"error": "true",
"code": "400 BAD_REQUEST",
"message": "Data format failed OR wrong value entered at: sbNo. Format should follow ^[0-9]{7}$"
}
```

2. Invalid sb date

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered at: sbDate. Format should follow ^((0[1-9]|[12][0-9]|3[01])(0[1-9]|1[012])\\d{4})$"
}
```

3. Invalid location

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered at: location. Format should follow ^[A-Za-z0-9]{6}$"
}
```

b) In case the sb number does not exist in the ICEGATE system

```
{
  "response": [
    {
      "response": {
```

```
        "errCode": "ERROR0004",
        "errMsg": "No Records Available"
    },
    "responseStatus": "ERROR",
    "message": null
}
],
"error": "false",
"code": "200",
"message": "Success"
}
```

c) In case the SB number exists

```
{
  "response": [
    {
      "response": {
        "expName": "Ni****ay",
        "sbType": "F",
        "egmNo": "3063019",
        "egmDt": "28102024",
        "iec": "AM****7A",
        "leoDt": "28102024",
        "chaNo": "SE****01"
      },
      "responseStatus": "SUCCESS",
      "message": null
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorised

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.15 ICEGATE/13

This API will provide e-Seal details.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	esealNumber	Shipping Bill number as available in ICEGATE system.	^{1,20}\$	Required	20 max
2	containerNumber	BE date	^[A-Za-z0-9]{1,10}	Required	15 max

1.15.1 Technical Approach

1. All the data will be shared through REST web services.
2. The ULIP system will provide an **e-seal number** for which detail is required.
3. ICEGATE API will share details of cargo information that exists in the ICEGATE system in JSON format.
4. ICEGATE Integration will add JSON in the **response** key in the response body.
5. The ULIP system will provide the data in JSON Object format in the response body.

Example:

E seal number and other information are shared by the ULIP system, then ICEGATE-integration will request the ICEGATE API.

Request:

The request must be of the following format

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/13>

```
{
  "esealNumber": "000000000045",
  "containerNumber": "TU679"
```

```
}
```

Curl URL

```
curl -L -X POST 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/13' -H  
'Authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3  
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3  
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:  
application/json' --data-raw '{  
  "esealNumber": "000000000045",  
  "containerNumber": "TU679"  
}'
```

For Staging:

<https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/13>

```
{  
  "esealNumber": "000000000045",  
  "containerNumber": "TU679"  
}
```

Curl URL

```
curl -L -X POST 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/13'  
-H 'Authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJhcHBzIjoiYXBpR2F0ZXdheSIsInN1YiI6InVsaXAiLCJpYXQiOiJlE3  
NDY3ODIyODN9.jdfwyGaBeVMDxX1zNQPLxnMESZbnVJ_4_Kwwlc4QHekC5tezrjWQE0sr4gwn8TA3  
F2gbl2fwTGDfT8MqctzUoQ' -H 'Content-Type: application/json' -H 'Accept:  
application/json' --data-raw '{  
  "mawbNumber": "15754138070",  
  "hawbNumber": "1575103333"  
}'
```

For obtaining authentication token, refer [Section 1.6](#)

Response

To acknowledge the above request, ULIP will send the following response -

a) In case of invalid format

1. Invalid e-seal Number

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered a
t: es sealNumber. Format should follow  ^[0-9]{1,20}$"
}
```

2. Invalid container Number

```
{
  "response": null,
  "error": "true",
  "code": "400 BAD_REQUEST",
  "message": "Data format failed OR wrong value entered a
t: containerNumber. Format should follow  ^[A-Za-z0-
9]{1,10}$"
}
```

b) In case the e seal number & container number does not exist in ICEGATE system

```
{
  "response": [
    {
```

```
        "response": {
            "errCode": "ERROR0004",
            "errMsg": "No Records Available"
        },
        "responseStatus": "ERROR",
        "message": null
    }
],
"error": "false",
"code": "200",
"message": "Success"
}
```

c) In case the e-seal number & container number do exist in the ICEGATE system

```
{
    "response": [
        {
            "response": {
                "esealNumber" : "0000000000045",
                "containerNumber" : "TU679",
                "sealDateTime" : "12042021 12:34",
                "sbNumber" : "2323134",
                "sbDate" : "12042021",
                "truckNumber" : "UP16380",
                "portCode" : null,
                "esealStatus" : "null",
                "verificationTime": "null"
            },
            "responseStatus": "SUCCESS",
            "message": null
        }
    ],
    "error": "false",
    "code": "200",
    "message": "Success"
}
```

Status Code 200: vehicle data response

Status Code 400: Bad request (Invalid JSON syntax, invalid JSON key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.16 Data Transmission & Authentication Mechanism

All data exchange would be done over secure HTTP (HTTPS). Request from ULIP's system would be made in the ICEGATE system through a data exchange URL that has the following form:

For Production:

<https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01>

Body:

```
{"igmNo":"1234","igmDt":"25102021"}
```

Access to the data exchange URL will be authorised through a security mechanism implemented by the ULIP system. The process is as follows:

- **First-Time Access:** Users will need a username and password, which will be provided in advance. Once the user enters a valid username and password, the ULIP system will return a basic authorisation token. This token will allow the user to communicate with the ULIP system until it expires.

Here is a summary of HTTP Basic Authentication:

During the initial access, the user will submit their username and password to the ULIP secured API to obtain an access token.

```
curl -X POST
'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/user/login'
-H 'accept: application/json'
-H 'content-type: application/json'
-data '{"username":"xxxxxx","password":"xxxxxx"} '
```

Authorization:

Bearer

eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJpbmRlcmNvbnQiLCJpYXQiOiJlODU1NjYyMzcsImFwcHMiOiJkYXRhcHVzaCJ9.jb-23Dbkwpz-3ptsuuZofzH-ce7jd0xR5WLkFfBPO_Dzjop01dSx90amqsjsGUARYLUPtUDiMX07oHG4L2AfFQ

Upon successful authentication, the user will be logged into the ULIP system and receive an access token. This token allows the user to communicate with ULIP. The token has an expiry time that represents the duration of the user session. **The session timeout is typically set for 24 hours from the time the token is generated.**

Using the above token, the user can request the ULIP system for vehicle details as follows -

```
curl -X POST \
  https://www.ulip.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01 \
  -H 'accept: application/json' \
  -H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsImIhdCI6MTYyNTIzMDQyNywiYXBwcyI6ImRh
dGFwdXNoIn0.rhumwWJ8BWeeHe9CYmIV1UKyJk-kLHA_ovX5Zi20wxEv-td-
KpxnfbKDI_8FZs0oggqx3AL-Du1y2qMoUD7uzA' \
  -H 'cache-control: no-cache' \
  -H 'content-type: application/json' \
  -H 'postman-token: 8e8a19a4-ea1e-6373-f616-e2e4af9a1338' \
  -d '{"igmNo": "1234", "igmDt": "25102021"}'
```

For Staging:

```
curl -X POST
  'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/user/login
  -H 'accept: application/json'
  -H 'content-type: application/json'
  -data '{"username": "xxxxxx", "password": "xxxxxx"}'
```

Authorization:**Bearer**

eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJpbmRlcmNvbnQiLCJpYXQiOiJlODU1NjYyMzcsImFwcHMiOiJkYXRhcHVzaCJ9.jb-23Dbkwpz-3ptsuuZofzH-ce7jd0xR5WLkFfBPO_Dzjop01dSx90amqsjsGUARYLUPtUDiMX07oHG4L2AfFQ

Upon successful authentication, the user will be logged into the ULIP system and receive an access token. This token allows the user to communicate with ULIP. The token has an expiry time that represents the duration of the user session. **The session timeout is typically set for 24 hours from the time the token is generated.**

Using the above token, the user can request the ULIP system for vehicle details as follows -

```
curl -X POST \
  https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/ICEGATE/01 \
  -H 'accept: application/json' \
  -H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsImIhdCI6MTYyNTIzMDEyNywiYXBwcyI6ImRh
dGFwdXNoIn0.rhumwWJ8BWeeHe9CYmIV1UKyJk-kLHA_ovX5Zi2OwxEv-td-
KpxnfbKDI_8FZsOoggqx3Al-Du1y2qMoUD7uzA' \
  -H 'cache-control: no-cache' \
  -H 'content-type: application/json' \
  -H 'postman-token: 8e8a19a4-ea1e-6373-f616-e2e4af9a1338' \
  -d '{"igmNo":"1234","igmDt":"25102021"}'
```