

ULIP Integration Document

Version No.: 2.0

Date: 18/05/2026

Project Name: ULIP

This document contains proprietary information of NLDSL. Unauthorized access, copying and replication are prohibited. This document must not be copied in whole or part by any means, without the written authorization of NLDSL, Noida, India.

ULIP Integration Document

Revision History

Version	Date	Author	Reviewer	Significant Changes
1.0	09/01/2025	Girish Chander	Nayab Ali	Baseline Version
2.0	18/05/2026	Gaurav Tyagi	Pranab Manna	Updated

Table of Contents

Introduction	4
1.1 Purpose	4
1.2 Data Integration between other system and ULIP application	4
1.3 NOENTRY/01	4
1.3.1 Technical Approach.....	4
1.4 Data Transmission & Authentication Mechanism	8

Introduction

1.1 Purpose

The purpose of this document is to define and provide details for getting no entry data based on state code from ULIP system.

This document details the following points:

1. **Data Integration between Other System and ULIP web service:** Identification of operational points where data integration between other system and ULIP web service will be needed.
2. **Technical Approach** for performing Data Integration

1.2 Data Integration between other system and ULIP application

Users will share information to ULIP system based on data shared ULIP will provide data (toll plaza rate) to the user.

1.3 NOENTRY/01

This API will take **stateCode** and based on the user input data, ULIP System will find the no entry data for the state code and send back the response to the user.

S. No.	Field Name	Field Description	Format	Required/Not – Required	Length
1	stateCode	State code for the particular state	^d{1,5}\$	Required	Max 5 digit

1.3.1 Technical Approach

1. All the data will be shared through rest web services.
2. ULIP system will provide data (toll rate) for which data is shared.
3. ULIP system will provide the data in JSON Object format in response body.

Request: The request must be of the following format, where **stateCode** is passed within the request body in JSON format.

ULIP Integration Document

Below is the list of the state codes we are taking.

State Code	State Name
1	JAMMU AND KASHMIR
2	HIMACHAL PRADESH
3	PUNJAB
4	CHANDIGARH
5	UTTARAKHAND
6	HARYANA
7	DELHI
8	RAJASTHAN
9	UTTAR PRADESH
10	BIHAR
11	SIKKIM
12	ARUNACHAL PRADESH
13	NAGALAND
14	MANIPUR
15	MIZORAM
16	TRIPURA
17	MEGHALAYA
18	ASSAM
19	WEST BENGAL
20	JHARKHAND
21	ORISSA
22	CHHATTISGARH
23	MADHYA PRADESH
24	GUJARAT
26	Dadra & Nagar Haveli and Daman & Diu
27	MAHARASHTRA
29	KARNATAKA
30	GOA
31	LAKSHADWEEP
32	KERALA
33	TAMIL NADU
34	PUDUCHERRY
35	ANDAMAN AND NICOBAR
36	TELANGANA
37	ANDHRA PRADESH
38	Ladakh

For Production: <https://www.ulip.dpiit.gov.in/ulip/v1.0.0/NOENTRY/01>

```
{"stateCode":"21"}
```

Curl URL

```
curl --location --request POST 'https://www.ulip.dpiit.gov.in/ulip /v1.0.0/NOENTRY/01' \  
--header 'Content-Type: application/json' \  
--header 'Authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ1bGlwliwiaWF0IjoxNjU3NzAzMjMyLCJhcHBzIjoZGF0YXB  
1c2gifQ.woK64SnrOZKvW5Jevd-eJI6PtetLBQ5WNfumvG_bu-  
XyX3AdgAzau6Cy0jzqmZcPZpMWNHPzpPadB82bVLAg0g' \  
--header 'Accept: application/json' \  
--data-raw '{"stateCode":"21"}'
```

For Staging: <https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/NOENTRY/01>

```
{"stateCode":"13"}
```

Curl URL

```
curl --location --request POST 'https://www.ulipstaging.dpiit.gov.in/ulip /v1.0.0/NOENTRT/01' \  
--header 'Content-Type: application/json' \  
--header 'Authorization: Bearer  
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ1bGlwliwiaWF0IjoxNjU3NzAzMjMyLCJhcHBzIjoZGF0YXB  
1c2gifQ.woK64SnrOZKvW5Jevd-eJI6PtetLBQ5WNfumvG_bu-  
XyX3AdgAzau6Cy0jzqmZcPZpMWNHPzpPadB82bVLAg0g' \  
--header 'Accept: application/json' \  
--data-raw '{"stateCode":"21"}'
```

For obtaining authentication token, refer Section [1.4](#)

Response

To acknowledge the above request, ULIP will send the below response -

a) In case of invalid format

1. Invalid data

```
{  
  "response": null,  
  "error": "true",  
  "code": "400",  
  "message": "Data format failed OR wrong value entered at: stateCode. Format should follow  
^d{1,5}$ }"
```

b) In case of valid data sent by the user

```
{
  "response": [
    {
      "response": [
        {
          "noEntryTime": "8.00 AM to 10.00 PM",
          "districtCode": 1,
          "districtName": "UPD- BBSR",
          "stateName": "Odisha",
          "areaName": "NH-203 Bypass Pandara Chowk to Rasulgarh Vla\nGGP Colony",
          "stateCode": 21
        },
        {
          "noEntryTime": "8.00 AM to 10.00 PM",
          "districtCode": 1,
          "districtName": "UPD- BBSR",
          "stateName": "Odisha",
          "areaName": "NH-203 Bypass Kesura Square to Jharpada",
          "stateCode": 21
        },
        {
          "noEntryTime": "8.00 AM to 10.00 PM",
          "districtCode": 1,
          "districtName": "UPD- BBSR",
          "stateName": "Odisha",
          "areaName": "Van,ibihar Square to Airport Square via Master\nCanteen Square",
          "stateCode": 21
        },
        {
          "noEntryTime": "8.00 AM to 10.00 PM",
          "districtCode": 1,
          "districtName": "UPD- BBSR",
          "stateName": "Odisha",
          "areaName": "Acharya Vihar Square to Sur Company Square V' Et\nAG Square",
          "stateCode": 21
        }
      ],
      "responseStatus": "SUCCESS"
    }
  ],
  "error": "false",
  "code": "200",
  "message": "Success"
}
```

Status Code 200: corporate data response

Status Code 400: Bad request (Invalid json syntax, invalid json key)

Status Code 401 or 403: Unauthenticated or Unauthorized

Status Code 500: Some internal server error occurred

Status Code 502: Server is not responding.

1.4 Data Transmission & Authentication Mechanism

All data exchange would be done over secure HTTP (HTTPS). Request from ULIP's system would be made in IWAI system through a data exchange URL that has following form:

For Production: <https://www.ulip.dpiit.gov.in/ulip/v1.0.0/NOENTRY/01>

Body:

```
{"stateCode":"13"}
```

Access to above data exchange URL would be authorized by use of a security mechanism implemented by the ULIP system. It is as follows:

- First time access: It would require a username and password [which would be shared with user beforehand]. Once user hit with valid user id and password, ULIP system will return a basic authorization token to user, using that token user will communicate with ULIP system until token will not get expired.

Summary of HTTP Basic Authentication is as follows:

First time when User will hit ULIP secured API through username and password for access token as follow-

```
curl --location --request POST 'https://www.ulip.dpiit.gov.in/ulip/v1.0.0/user/login' \  
  --header 'Accept: application/json' \  
  --header 'Content-Type: application/json' \  
  --data-raw '{  
    "username": "xxxx",  
    "password": "xxxx@123"}'
```

Authorization:

Bearer

```
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsImhhdCI6MTYyNTIzMDQyNywiYXBwcyI6ImRhdGFwdXN0In0.rhumwWJ8BWeeHe9CYmIV1UKyJk-kLHA_ovX5Zi2OwxEv-td-KpxnfbKDI_8FZsOoggqx3AI-Du1y2qMoUD7uzA'
```

Upon successful authentication, the user would be logged into the ULIP system and get an access token. Though this token user can communicate with ULIP. This token has expiry time which represent user session. The session time out for the same to be fixed hour, generally it is for 30 minutes. If there is no request coming from user for 30 minutes, then session (token) will be expired, and user need to re authenticate.

Using The above token, user can request ULIP system for CIN details as follow -

```
curl -X POST \  
  https://www.ulip.dpiit.gov.in/ulip/v1.0.0/NOENTRY/01
```

```
\
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsImhhdCI6MTYyNTIzMDQyNywiYXBwcyI6ImRhdGFwdXNoIn0.rhumwWJ8BWeeHe9CYmIV1UKyJk-kLHA_ovX5Zi2OwxEv-td-KpxnfbKDI_8FZsOoggqx3AI-Du1y2qMoUD7uzA' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 8e8a19a4-ea1e-6373-f616-e2e4af9a1338' \
-d '{}'
```

For Staging:

```
curl --location --request POST 'https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/user/login' \
--header 'Accept: application/json' \
--header 'Content-Type: application/json' \
--data-raw '{
"username": "xxxx",
"password": "xxxx@123"}'
```

Authorization:**Bearer**

```
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsImhhdCI6MTYyNTIzMDQyNywiYXBwcyI6ImRhdGFwdXNoIn0.rhumwWJ8BWeeHe9CYmIV1UKyJk-kLHA_ovX5Zi2OwxEv-td-KpxnfbKDI_8FZsOoggqx3AI-Du1y2qMoUD7uzA'
```

Upon successful authentication, the user would be logged into the ULIP system and get an access token. Though this token user can communicate with ULIP. This token has expiry time which represent user session. The session time out for the same to be fixed hour, generally it is for 30 minutes. If there is no request coming from user for 30 minutes, then session (token) will be expired, and user need to re authenticate.

Using The above token, user can request ULIP system for CIN details as follow -

```
curl -X POST \
https://www.ulipstaging.dpiit.gov.in/ulip/v1.0.0/NOENTRY/01 \
-H 'accept: application/json' \
-H 'authorization: Bearer
eyJhbGciOiJIUzUxMiJ9.eyJzdWIiOiJ0ZXN0MSIsImhhdCI6MTYyNTIzMDQyNywiYXBwcyI6ImRhdGFwdXNoIn0.rhumwWJ8BWeeHe9CYmIV1UKyJk-kLHA_ovX5Zi2OwxEv-td-KpxnfbKDI_8FZsOoggqx3AI-Du1y2qMoUD7uzA' \
-H 'cache-control: no-cache' \
-H 'content-type: application/json' \
-H 'postman-token: 8e8a19a4-ea1e-6373-f616-e2e4af9a1338' \
-d '{}'
```