

# Lecture 17 – Cybersecurity Fundamentals: CIA Triad, Hashing, Vulnerabilities, Threats, and AAA Model

---

## ▲ 1. CIA Triad

### ■ Definition:

The **CIA Triad** is the **core model of cybersecurity** that defines three main principles — **Confidentiality, Integrity, and Availability**. It provides the **framework for building secure systems** and **protecting data**.

---

### ✚ A. Confidentiality

#### ◆ Meaning:

Only **authorized people** should have access to sensitive information. It ensures **data privacy** and prevents **unauthorized disclosure**.

#### ◆ Example:

- Your bank account details should only be visible to you and your bank.
- Company confidential files should not be accessible to outsiders.

#### ◆ How to Achieve:

- **Encryption:** Converts data into unreadable format.
- **Access Control Lists (ACLs):** Restrict user access.
- **Multi-Factor Authentication (MFA):** Verifies identity using password + OTP.

#### ◆ Tools & Techniques:

- AES (Advanced Encryption Standard)
- VPN for secure transmission
- File permissions in OS

## ✖ B. Integrity

### ◆ Meaning:

Ensures that **data has not been changed or modified** without permission. Data must remain **accurate, complete, and trustworthy**.

### ◆ Example:

If a salary report or exam result file is altered without approval, data integrity is lost.

### ◆ How to Achieve:

- Use **Hashing algorithms** (MD5, SHA1, SHA256, etc.).
- **Digital Signatures** to verify authenticity.
- **Checksums** for file verification.

### ◆ Tool:

- **Hash Calculators**
  - [MD5File.com](https://md5file.com)
  - [VirusTotal.com](https://www.virustotal.com)
  - [Pelock Hash Calculator](https://pelock.com/hash-calculator)

These sites can calculate the **hash value** of files or text to verify their integrity.

---

## ✖ C. Availability

### ◆ Meaning:

Authorized users must have **timely and reliable access** to data and systems whenever needed.

### ◆ Example:

If your company's website is down due to a DDoS attack, availability is lost.

### ◆ How to Achieve:

- Use **Redundant Servers** and **Backups**.
- Apply **Disaster Recovery Plans**.

- Maintain **updated hardware** and **network security**.
- 

### ✅ CIA Triad Summary

| Principle       | Purpose              | How It's Maintained                 |
|-----------------|----------------------|-------------------------------------|
| Confidentiality | Keep data private    | Encryption, MFA                     |
| Integrity       | Keep data unmodified | Hashing, digital signatures         |
| Availability    | Keep data accessible | Backup, redundancy, DDoS protection |

---

## ⚙️ 2. Hash Value and Integrity Verification

### ◆ Definition:

A **hash value** is a **unique numeric or alphanumeric code** generated by applying a **hash function** to a file or text.

It represents the **content's fingerprint** — even a tiny change in the file changes the hash completely.

### ◆ Purpose:

- To **verify data integrity**.
- To **detect tampering or corruption**.
- To **authenticate** downloaded files.

### ◆ Example:

If a file has this original hash:

5d41402abc4b2a76b9719d911017c592

and after download it changes to:

7c6a180b36896a0a8c02787eeafb0e4c

It means the file was **modified** or **corrupted**.

---

### ◆ Common Hash Algorithms:

| Algorithm Full Form |                               | Bit Size    | Description                                 |
|---------------------|-------------------------------|-------------|---|
| MD5                 | Message Digest 5              | 128-bit     | Fast but weak (not secure for cryptography) |
| SHA-1               | Secure Hash Algorithm 1       | 160-bit     | More secure than MD5 but now outdated       |
| SHA-2               | Secure Hash Algorithm 2       | 256/512-bit | Currently used for modern systems           |
| SHA-512             | Secure Hash Algorithm 512-bit | 512-bit     | Very strong and secure                      |

---

### ⚠ Important Concept:

“Downloading a file does not cause harm — installing or executing it does.”

- Malware only activates **when the file is executed**.
- That’s when its **code runs** and starts performing malicious activity.

---

## ✿ 3. Vulnerability

### ◆ Definition:

A **vulnerability** is a **weakness or flaw** in software, hardware, or human behavior that can be **exploited** by an attacker.

### ◆ Example:

- Unpatched operating systems
  - Weak passwords
  - Misconfigured firewalls
  - Phishing-prone employees
-

## ◆ Types of Vulnerabilities:

### 1. Technical Vulnerabilities

Found in systems, software, or configurations.

- SMB (Server Message Block) protocol vulnerabilities
- RDP (Remote Desktop Protocol) exposure
- Outdated antivirus or software
- Unpatched operating systems

#### **Solution:**

Regular updates, system hardening, and patch management.

### 2. Human Vulnerabilities

Caused by user actions or negligence.

- Clicking phishing links
- Sharing passwords
- Disgruntled employees leaking data

#### **Solution:**

Security awareness training and strict access policies.

---

## 4. Threat

### ◆ Definition:

A **threat** is a potential event or person that can **exploit a vulnerability** and cause **damage** to data or systems.

### ◆ Example:

- A hacker launching a DDoS attack.
  - An insider stealing sensitive company data.
-

◆ **Common Threat Types:**

- **Remote attacks** – attacker gains unauthorized system access.
  - **Malware attacks** – viruses, worms, ransomware, trojans.
  - **DDoS attacks** – flooding network to make it unavailable.
- 

◆ **Common Threat Actors & Their Motivations:**

| Threat Actor     | Motivation                      | Example                            |
|------------------|---------------------------------|------------------------------------|
| Cyber Criminals  | Financial profit                | Ransomware, phishing               |
| Nation States    | Political or military advantage | Government-backed attacks          |
| Terrorist Groups | Ideological violence            | Attacks on critical infrastructure |
| Thrill Seekers   | Fun or challenge                | Website defacement                 |
| Insiders         | Revenge or dissatisfaction      | Disgruntled employee leaking data  |
| Hacktivists      | Political/social message        | Anonymous hacking groups           |

---

⚖️ **5. Risk**

◆ **Definition:**

**Risk** is the **probability and potential impact** of a negative incident happening due to a threat exploiting a vulnerability.

◆ **Formula:**

**Risk = Threat × Vulnerability**

### ◆ Example:

If a company has:

- Weak RDP password (**vulnerability**) and
- Hackers trying to brute-force it (**threat**),

then the **risk** of unauthorized access is high.

### ◆ Risk Management Process:

1. **Identify** vulnerabilities and threats.
2. **Assess** risk level (high, medium, low).
3. **Mitigate** using security controls.
4. **Monitor** continuously.

---

## 🔒 6. AAA Model (Authentication, Authorization, Accounting)

### 📘 Definition:

The **AAA Framework** is used to **control and track user access** in network and system security.

---

### 🔗 A. Authentication

#### ◆ Meaning:

Verifying **who the user is**.

It confirms the user's identity before granting access.

#### ◆ Example:

- Username + Password
  - OTP (One-Time Password)
  - Biometric login
-

## ✖ B. Authorization

### ◆ Meaning:

Defines **what the authenticated user can do**.

It decides the **level of access** or **permissions** for each user.

### ◆ Example:

- Admin can install software.
  - Employee can only read or modify documents.
- 

## ✖ C. Accounting

### ◆ Meaning:

Tracks **what users do** in the system after they log in.

Helps in **auditing, monitoring, and reporting**.

### ◆ Example:

- Login logs
  - File access logs
  - Command history
- 

## ✅ AAA Example in Real Life:

1. You log into your company network → **Authentication**
  2. You access only your department folder → **Authorization**
  3. System logs your activity → **Accounting**
- 

## 📄 7. IT Asset Disposal (Scraping in Companies)

When IT teams remove old or faulty hardware, they perform **scraping (secure disposal)** to ensure **confidential data doesn't leak**.

### ◆ Items to be Scrapped Securely:

- **Papers or documents** (shredded)



- **Toner cartridges**
- **RAM and Hard Drives (HDD/SSD)**
- **Network devices** (e.g., L3 Switches)

◆ **Reason:**

- To prevent sensitive company information from going outside.
- To comply with data protection regulations (like ISO certification).

---

✚ **Summary Chart**

| Concept              | Description              | Example                                   |
|----------------------|--------------------------|---|
| <b>CIA Triad</b>     | Security framework       | Confidentiality, Integrity, Availability  |
| <b>Hashing</b>       | Verify data integrity    | MD5, SHA256                               |
| <b>Vulnerability</b> | Weakness in system       | Outdated OS, weak password                |
| <b>Threat</b>        | Potential attack         | Hacker, malware, insider                  |
| <b>Risk</b>          | Threat × Vulnerability   | Data breach risk                          |
| <b>AAA Model</b>     | Access control framework | Authentication, Authorization, Accounting |

---

✅ **Final Takeaway:**

- **CIA Triad** defines *what* to protect.
- **Hashing** ensures *data integrity*.
- \**Vulnerability + Threat = Risk*.
- **AAA** defines *how* to control access.
- **Scrapping** ensures *data doesn't leak* after device disposal.