

✓ **How to Feed IOCs into a SIEM (Simple Steps)**

1 **Prepare the IOC List**

Your IOCs can come from:

- Threat intel platforms (VirusTotal, MISP, AlienVault OTX)
- SOC teams
- CERT alerts
- Vendor intelligence feeds
- Pentesting / Red team reports

Format it into a simple file:

type, value, description

IP, 45.77.12.32, Known malicious IP

Domain, badsite.com, Phishing domain

MD5, 098f6bcd4621d373cade4e832627b4f6, Malware hash

✓ **Import IOCs into SIEM**

Method A: Manual Upload (CSV/File Upload)

Most SIEMs allow uploading via:

- CSV
- JSON
- STIX/TAXII feeds

Example (Generic Steps):

1. Go to **Threat Intelligence / Indicators** section
2. Click **Import / Upload**
3. Upload IOC CSV/JSON
4. Map fields (IP, Domain, Hash, etc.)
5. Save and enable alerting rules

Used in: **Splunk ES, Sentinel, QRadar, ArcSight, Elastic SIEM**

3. Use API to Push IOCs

If you have automated feeds.

Example (Sentinel API):

POST <https://management.azure.com/.../indicators>

```
{
  "kind": "indicator",
  "properties": {
    "patternType": "ipv4-addr",
    "pattern": "[ipv4-addr:value = '45.77.12.32']",
    "description": "Malicious IP"
  }
}
```

Used in:

- MS Sentinel
- Splunk
- QRadar
- Elastic

4. Add IOCs using TAXII/STIX Feeds

Threat intel platforms provide **automatic feeds**.

Example sources:

- MISP
- AlienVault OTX
- Anomali
- IBM X-Force

Example steps:

1. Add **TAXII server URL**

2. Add **API key or credentials**
3. Select collection (e.g., otx-iocs)
4. Enable scheduled pulling



☑️ Add IOCs into Lookup Tables / Reference Sets Splunk (Lookup Table Method)

Upload IOC list:

Settings → Lookups → Lookup table files → Upload CSV

Query detection:

```
search src_ip IN [| inputlookup malicious_ips.csv]
```

QRadar (Reference Set Method)

Add an IP:

```
/opt/qradar/bin/ReferenceSetUtil.sh add "Malicious_IPs" 45.77.12.32
```



RULE CREATION (VERY IMPORTANT)

After uploading IOCs, create rules like:

IF

Any log → IP/Domain/Hash matches IOC list

THEN

Generate high severity alert



COMMON IOC TYPES YOU CAN FEED

IOC Type	Example
----------	---------

IP Address	192.168.10.5
------------	--------------

Domain	badsite.com
URL	http://phish.example.com/login
File Hash	md5: xxxxx
File Path	C:\Windows\temp\abc.exe
Registry Key	HKCU\Software\Malware