

✓ Top Nmap Scripts You Must Know

📋 No.	📄 Script Name	🧠 Purpose
1	smb-enum-shares	Lists SMB shares (both anonymous and authenticated)
2	smb-enum-users	Enumerates valid users via SMB
3	smb-os-discovery	Detects OS version via SMB
4	smb-vuln-ms17-010	Checks for EternalBlue vulnerability (WannaCry)
5	ftp-anon	Checks if anonymous FTP login is allowed
6	ftp-bounce	Detects FTP bounce scan vulnerability
7	http-title	Shows webpage titles for quick web app identification
8	http-enum	Enumerates common web directories (like /admin, /login)
9	http-vuln-cve2017-5638	Checks Apache Struts RCE vulnerability
10	http-headers	Displays security headers (HSTS, CSP, etc.)
11	http-methods	Finds HTTP methods enabled (e.g., PUT, DELETE)
12	dns-brute	Performs DNS subdomain brute-forcing
13	dns-zone-transfer	Attempts zone transfer (misconfig)
14	ssl-cert	Retrieves SSL certificate info
15	ssl-enum-ciphers	Lists supported SSL/TLS ciphers (for weak cipher detection)
16	mysql-empty-password	Checks MySQL login with no password
17	mysql-users	Attempts to guess MySQL usernames
18	ms-sql-info	Enumerates Microsoft SQL server info
19	vulners (external)	Integrates Nmap with Vulners API to list known CVEs
20	snmp-info	Gathers device/system info via SNMP

📘 How to Use an Nmap Script:

General format:

```
nmap -p <port> --script <script-name> <target>
```

Example 1: Check for EternalBlue on port 445

```
nmap -p 445 --script smb-vuln-ms17-010 192.168.1.10
```

Example 2: Run multiple SMB scripts

```
nmap -p 445 --script smb-enum* 192.168.1.10
```

Example 3: Subdomain brute-forcing

```
nmap --script dns-brute -Pn -n -T4 -v example.com
```

How to List All Available Scripts:

ls /usr/share/nmap/scripts/

Or from Nmap itself:

```
nmap --script-help
```

Bonus: Categories of Nmap Scripts

Category Examples

auth ssh-auth-methods, mysql-empty-password

broadcast broadcast-dhcp-discover, broadcast-netbios-master-browser

default Scripts run with -sC flag

discovery ftp-anon, dns-brute, snmp-info

exploit smb-vuln*, http-vuln-cve*

safe Scripts that won't crash services

vuln Vulnerability checks (e.g., http-vuln*)

version Scripts used with -sV scan