Problem 1

myDisplayImageGrey.m

myDisplayTwoImage.m

```
function myDisplayTwoImage(img1,img2)
figure('Position', [100, 100, 1200, 600]);
subplot(1,2,1);
myDisplayImageGrey(img1,"Original Image");
subplot(1,2,2);
myDisplayImageGrey(img2,"Sharpened Image");
end
```

myLinearContrastStretching.m

```
function contrastImg = myLinearContrastStretching(input)
    c = size(input,3);
    contrastImg = zeros(size(input));
    input = double(input);
    for l=1:c
        maxIntensity = max(max(input(:,:,I)));
        minIntensity = min(min(input(:,:,I)));
        contrastImg(:,:,I) = (input(:,:,I) - minIntensity) * double(255) /
(maxIntensity - minIntensity);
```

end end

myMainScript.m

```
%% MyMainScript
tic;
%% Super Moon Crop
imageData = load('../data/superMoonCrop.mat');
image = imageData.imageOrig;
stretchedImage = myLinearContrastStretching(image);
sharpImage = myUnsharpMasking(image,1.1,9,1.1);
sharpImage = myLinearContrastStretching(sharpImage);
myDisplayTwoImage(stretchedImage,sharpImage);
%% Lion Crop
imageData = load('../data/lionCrop.mat');
image = imageData.imageOrig;
stretchedImage = myLinearContrastStretching(image);
sharpImage = myUnsharpMasking(image, 1.1, 9, 1.6);
sharpImage = myLinearContrastStretching(sharpImage);
myDisplayTwoImage(stretchedImage,sharpImage);
toc;
```

myUnsharpMasking.m

```
function fiteredImage = myUnsharpMasking(input, sigma, windowSize,
scale)
     fiteredImage = input -
scale*imfilter(input,fspecial('log',windowSize,sigma));
end
```

Problem 2

end

myBilateralFiltering.m

function filteredImage = myBilateralFiltering(input, sigmaSpace, sigmaIntensity,windowSize)

```
% create pre defined filter gaussian space
filter = fspecial('gaussian',2*windowSize+1,sigmaSpace);
[len,wid] = size(input);
filteredImage = zeros([len,wid]);
for i = 1:len
for j = 1:wid
x = max(i-windowSize,1);
X = min(i+windowSize,len);
y = max(j-windowSize,1);
Y = min(j+windowSize,wid);
window = input(x:X,y:Y);
x1 = max(2+windowSize-i,1);
X1 = min(2*windowSize+1,len-i+windowSize+1);
y1 = max(2+windowSize-j,1);
Y1 = min(2*windowSize+1,wid-j+windowSize+1);
intensity = \exp(-((window-input(i,j)).^2)/(sigmaIntensity^2));
singleTerm = filter((x1:X1),(y1:Y1)).*intensity;
individualSum = window.*singleTerm;
filteredImage(i,j) = sum(individualSum(:))/sum(singleTerm(:));
end
end
```

myDisplayImageGrey.m

```
function myDisplayImageGrey(img,title1)
     imshow (mat2gray(img));
     title(title1);
  colormap(gray(200));
  axis on;
  colorbar;
myDisplayThreelmage.m
function myDisplayThreeImage(img1,img2,img3)
     figure('Position', [100, 100, 1200, 600]);
     subplot(1,3,1);
     myDisplayImageGrey(img1,"Original Image");
     subplot(1,3,2);
     myDisplayImageGrey(img2,"Corrupted Image");
     subplot(1,3,3);
     myDisplayImageGrey(img3,"Filtered Image");
end
myMainScript.m
%% MyMainScript
tic;
%% Barbara
imageData = load('../data/barbara.mat');
image = imageData.imageOrig;
[len, wid] = size(image);
corruptedImage = image +
0.05*(max(max(image))-min(min(image)))*randn(len);
```

```
sigmaSpace = 1.6;
sigmaIntensity = 13.5;
windowSize = 4;
out = myBilateralFiltering(corruptedImage, sigmaSpace, sigmaIntensity,
windowSize);
rmsd = myRmsd(out,image);
display(rmsd);
myDisplayThreeImage(image,corruptedImage,out);
out1 = myBilateralFiltering(corruptedImage, 0.9*sigmaSpace,
sigmaIntensity, windowSize);
rmsd1 = myRmsd(out1,image);
display(rmsd1);
out2 = myBilateralFiltering(corruptedImage, 1.1*sigmaSpace,
sigmaIntensity, windowSize);
rmsd2 = myRmsd(out2,image);
display(rmsd2);
out3 = myBilateralFiltering(corruptedImage, sigmaSpace,
0.9*sigmaIntensity, windowSize);
rmsd3 = myRmsd(out3,image);
display(rmsd3);
out4 = myBilateralFiltering(corruptedImage, sigmaSpace,
1.1*sigmaIntensity, windowSize);
rmsd4 = myRmsd(out4,image);
display(rmsd4);
figure;
filter = fspecial('gaussian',2*windowSize+1,sigmaSpace);
imshow(filter,'InitialMagnification','fit');
```

```
title("Spatial Gaussian Mask")
colormap(gray(200));
axis on;
colorbar;
%% Grass
image = im2double(imread('../data/grass.png'));
[len, wid] = size(image);
corruptedImage = image +
0.05*(max(max(image))-min(min(image)))*randn(len);
sigmaSpace = 0.71;
sigmaIntensity = 0.31;
windowSize = 2;
out = myBilateralFiltering(corruptedImage, sigmaSpace, sigmaIntensity,
windowSize);
rmsd = myRmsd(out,image);
display(rmsd);
myDisplayThreeImage(image,corruptedImage,out);
out1 = myBilateralFiltering(corruptedImage, 0.9*sigmaSpace,
sigmaIntensity, windowSize);
rmsd1 = myRmsd(out1,image);
display(rmsd1);
out2 = myBilateralFiltering(corruptedImage, 1.1*sigmaSpace,
sigmaIntensity, windowSize);
rmsd2 = myRmsd(out2,image);
display(rmsd2);
out3 = myBilateralFiltering(corruptedImage, sigmaSpace,
0.9*sigmaIntensity, windowSize);
rmsd3 = myRmsd(out3,image);
```

```
display(rmsd3);
out4 = myBilateralFiltering(corruptedImage, sigmaSpace,
1.1*sigmaIntensity, windowSize);
rmsd4 = myRmsd(out4,image);
display(rmsd4);
figure;
filter = fspecial('gaussian',2*windowSize+1,sigmaSpace);
imshow(filter,'InitialMagnification','fit');
title("Spatial Gaussian Mask")
colormap(gray(200));
axis on;
colorbar;
%% Honey Comb Real
image = im2double(imread('../data/honeyCombReal.png'));
[len, wid] = size(image);
corruptedImage = image +
0.05*(max(max(image))-min(min(image)))*randn(len);
sigmaSpace = 0.82;
sigmaIntensity = 0.27;
windowSize = 3;
out = myBilateralFiltering(corruptedImage, sigmaSpace, sigmaIntensity,
windowSize);
rmsd = myRmsd(out,image);
display(rmsd);
myDisplayThreeImage(image,corruptedImage,out);
out1 = myBilateralFiltering(corruptedImage, 0.9*sigmaSpace,
sigmaIntensity, windowSize);
rmsd1 = myRmsd(out1,image);
```

```
display(rmsd1);
out2 = myBilateralFiltering(corruptedImage, 1.1*sigmaSpace,
sigmaIntensity, windowSize);
rmsd2 = myRmsd(out2,image);
display(rmsd2);
out3 = myBilateralFiltering(corruptedImage, sigmaSpace,
0.9*sigmaIntensity, windowSize);
rmsd3 = myRmsd(out3,image);
display(rmsd3);
out4 = myBilateralFiltering(corruptedImage, sigmaSpace,
1.1*sigmaIntensity, windowSize);
rmsd4 = myRmsd(out4,image);
display(rmsd4);
figure;
filter = fspecial('gaussian',2*windowSize+1,sigmaSpace);
imshow(filter,'InitialMagnification','fit');
title("Spatial Gaussian Mask")
colormap(gray(200));
axis on;
colorbar;
toc;
myRmsd.m
function rsmdVal = myRmsd(img1,img2)
     [len, wid] = size(img1);
     rsmdVal = sqrt(sum(sum((img1-img2).^2))/(len*wid));
end
```

Problem 3

myDisplayImageGrey.m

```
function myDisplayImageGrey(img,title1)
     imshow (mat2gray(img));
     title(title1);
  colormap(gray(200));
  axis on;
  colorbar;
myDisplayThreeImage.m
function myDisplayThreeImage(img1,img2,img3)
     figure('Position', [100, 100, 1200, 600]);
     subplot(1,3,1);
     myDisplayImageGrey(img1,"Original Image");
     subplot(1,3,2);
     myDisplayImageGrey(img2,"Corrupted Image");
     subplot(1,3,3);
     myDisplayImageGrey(img3,"Filtered Image");
end
myMainScript.m
%% MyMainScript
tic;
%% Filtering Barbara image
load('../data/barbara.mat');
```

imageOrig = imgaussfilt(imageOrig,0.66);

```
imageOrig = imresize(imageOrig,0.5);
[len, wid] = size(imageOrig);
imgCorrupt = imageOrig +
0.05*(max(max(imageOrig))-min(min(imageOrig)))*randn(len);
h = 1.26;
patchSize = [9,9];
windowSize = [25,25];
out = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h);
rsmd0 = myRsmd(out,imageOrig);
display(rsmd0);
myDisplayThreeImage(imageOrig,imgCorrupt,out);
out1 = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h*0.9);
rsmd1 = myRsmd(out1,imageOrig);
display(rsmd1);
out2 = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h*1.1);
rsmd2 = myRsmd(out2,imageOrig);
display(rsmd2);
figure;
gaussianFilter = fspecial('gaussian', patchSize, double(patchSize(1))/6);
imshow(gaussianFilter,'InitialMagnification','fit');
title("Mask for Isotropic Patches")
colormap(gray(200));
axis on;
colorbar;
%% Filtering Grass image
imageOrig = im2double(imread('../data/grass.png'));
[len, wid] = size(imageOrig);
```

```
imgCorrupt = imageOrig +
0.05*(max(max(imageOrig))-min(min(imageOrig)))*randn(len);
h = 0.000109;
patchSize = [9,9];
windowSize = [25,25];
out = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h);
rsmd0 = myRsmd(out,imageOrig);
display(rsmd0);
myDisplayThreeImage(imageOrig,imgCorrupt,out);
out1 = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h*0.9);
rsmd1 = myRsmd(out1,imageOrig);
display(rsmd1);
out2 = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h*1.1);
rsmd2 = myRsmd(out2,imageOrig);
display(rsmd2);
figure;
gaussianFilter = fspecial('gaussian', patchSize, double(patchSize(1))/6);
imshow(gaussianFilter,'InitialMagnification','fit');
title("Mask for Isotropic Patches")
colormap(gray(200));
axis on;
colorbar;
%% Filtering Honey Comb image
imageOrig = im2double(imread('../data/honeyCombReal.png'));
[len, wid] = size(imageOrig);
imgCorrupt = imageOrig +
0.05*(max(max(imageOrig))-min(min(imageOrig)))*randn(len);
```

```
h = 0.00013;
patchSize = [9,9];
windowSize = [25,25];
out = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h);
rsmd0 = myRsmd(out,imageOrig);
display(rsmd0);
myDisplayThreeImage(imageOrig,imgCorrupt,out);
out1 = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h*0.9);
rsmd1 = myRsmd(out1,imageOrig);
display(rsmd1);
out2 = myPatchBasedFiltering(imgCorrupt, patchSize, windowSize, h*1.1);
rsmd2 = myRsmd(out2,imageOrig);
display(rsmd2);
figure;
gaussianFilter = fspecial('gaussian', patchSize, double(patchSize(1))/6);
imshow(gaussianFilter,'InitialMagnification','fit');
title("Mask for Isotropic Patches")
colormap(gray(200));
axis on;
colorbar;
toc;
myPatchBasedFiltering.m
function filterImg = myPatchBasedFiltering(img, patchSize, windowSize, h)
  [len, wid] = size(img);
  paddedImage = padarray(img, [(patchSize(1)-1)/2, (patchSize(2)-1)/2],
'symmetric', 'both');
```

```
gaussianFilter = fspecial('gaussian', patchSize, double(patchSize(1))/6);
  gaussianFilter = gaussianFilter/(sum(gaussianFilter(:)));
  gaussianFilterVector = gaussianFilter(:);
  featureImage = im2col(paddedImage, patchSize);
  featureImage = bsxfun(@times, featureImage, gaussianFilterVector);
  % Feature Image is of the same size as of the original image with last
dimension equal to feature dimension
  featureImage = permute(reshape(featureImage,
[patchSize(1)*patchSize(2), len, wid]), [2,3,1]);
  constant1 = (windowSize(1)-1)/2;
  constant2 = (windowSize(1)+1)/2;
  filterImg = zeros(size(img));
  for i=1:len
      for j=1:wid
            minI = (i-constant1);
            maxl = (i+constant1);
            minJ = (i-constant1);
            maxJ = (j+constant1);
            if i < constant2
                  minI = 1;
            elseif i > (len-constant1)
                  maxl = len;
            end
            if i < constant2
                  minJ = 1;
            elseif j > (wid-constant1)
                  maxJ = wid;
            end
```

```
patch = featureImage(minI:maxI, minJ:maxJ, :);
           sumSquareDiffernce = sum(bsxfun(@minus, patch,
featureImage(i,j,:)).^2, 3);
           expSumSquareDiffernce = exp(sumSquareDiffernce*(-1.0/h));
           dotWiseMult = img(minI:maxI,
minJ:maxJ).*expSumSquareDiffernce;
           filterImg(i,j) =
sum(dotWiseMult(:))/sum(expSumSquareDiffernce(:));
      end
  end
end
myRsmd.m
function rsmdVal = myRsmd(img1,img2)
     [len, wid] = size(img1);
     rsmdVal = sqrt(sum(sum((img1-img2).^2))/(len*wid));
end
```