

JavaScript Objects

Object Practice Set • 15 Questions • Easy → Hard

📁 Level 1 — Object Access

Q1. Basic Object Access

Ek `student` object banao jisme `name`, `age`, `course` aur `college` properties ho. Dot notation aur bracket notation dono ka use karke different properties print karo.

Hint: `student.name` aur `student["age"]` dono try karo.

Q2. Update Object Properties

Given:

```
let student = {  
  name: "Kartik",  
  age: 20,  
  course: "BTech"  
};
```

Student ki `age` ko update karo aur `course` ko bhi change karo. Updated object print karo.

Hint: Existing property ko new value assign kar sakte ho.

Q3. Dynamic Property Access

Given:

```
let student = {  
  name: "Kartik",  
  age: 20,  
  course: "BTech"  
};
```

```
let key = "course";
```

`key` variable ka use karke object ki corresponding value print karo.

Hint: Yahan dot notation nahi, bracket notation lagega.

Q4. Computed Property 📁

Ek variable `key = "city"` banao aur us variable ka use karke object ke andar dynamically `city` property create karo.

Hint: Object banate waqt `[key]` syntax observe karo.

📁 Level 2 — Nested Objects

Q5. Access Nested Object

Given:

```
let student = {  
  name: "Kartik",  
  address: {  
    city: "Gurugram",  
    state: "Haryana"  
  }  
};
```

Student ka `city` aur `state` print karo.

Hint: Object ke andar object hai, so multiple levels access karne honge.

Q6. Update Nested Property

Given upar wale object me `city` ko `"Delhi"` se replace karo aur updated nested object print karo.

Hint: Nested property ko directly access karke update karo.

Q7. Optional Chaining

Given:

```
let user = {  
  name: "Kartik",  
  address: {  
    city: "Gurugram"  
  }  
};
```

Optional chaining ka use karke `user.address.city` aur `user.address.pincode` safely access karo.

Goal: Missing property par error nahi aana chahiye.

□ Level 3 — Destructuring

Q8. Object Destructuring

Given:

```
let user = {  
  name: "Kartik",  
  age: 20,  
  city: "Gurugram"  
};
```

Object destructuring ka use karke `name` aur `city` ko separate variables me nikalo aur print karo.

Hint: Object ke property names ko directly destructure kar sakte ho.

Q9. Nested Destructuring

Given:

```
let user = {  
  name: "Kartik",  
  address: {  
    city: "Gurugram",  
    state: "Haryana"  
  }  
};
```

Destructuring ka use karke directly `name`, `city` aur `state` variables create karo.

Hint: Nested object ko bhi destructure karna hai.

Level 4 — Object Iteration

Q10. `for...in`

Given:

```
let student = {  
  name: "Kartik",  
  age: 20,  
  course: "BTech"  
};
```

`for...in` ka use karke object ki saari keys print karo.

Hint: `for...in` me variable kya represent karta hai, observe karo.

Q11. Keys + Values

Given kisi object ki saari keys aur unki corresponding values print karo.

Expected format:

name : Kartik

age : 20

course : BTech

Hint: `for...in` + bracket notation.

Q12. `Object.keys()` vs `Object.entries()`

Given:

```
let user = {  
  name: "Kartik",  
  age: 20,  
  city: "Gurugram"  
};
```

1. `Object.keys()` se saari keys print karo.
2. `Object.entries()` se key-value pairs print karo.

Goal: Dono methods ka output difference clearly samajhna.

Level 5 — Copying & Combining Objects

Q13. Spread vs `Object.assign()`

Given:

```
let user = {  
  name: "Kartik",  
  age: 20  
};
```

```
let extra = {  
  city: "Gurugram",  
  role: "Developer"  
};
```

Dono objects ko combine karke ek new object banao:

1. Spread operator se
2. `Object.assign()` se

Goal: Dono approaches ka practical difference samajhna.

Q14. Shallow Copy vs Deep Clone 💀

Given:

```
let user = {  
  name: "Kartik",  
  address: {  
    city: "Gurugram"  
  }  
};
```

1. Is object ki shallow copy banao.
2. Is object ki deep clone banao.
3. Nested `city` ko copy ke through change karo.
4. Observe karo original object me kya change hota hai.

Goal: Shallow copy aur deep clone ka actual behavior samajhna, sirf definition nahi.

Q15. 💀 Final Object Challenge

Given:

```
let user = {  
  name: "Kartik",  
  age: 20,  
  skills: {  
    frontend: "JavaScript",  
    backend: "Node.js"  
  },  
  location: {  
    city: "Gurugram",  
    country: "India"  
  }  
};
```

Program likho jo:

1. Dot notation se `name` print kare.
2. Bracket notation se `age` print kare.
3. Nested object se `frontend` print kare.
4. Destructuring se `name` aur `city` nikale.
5. `for...in` se `location` ki properties print kare.
6. `Object.keys()` se user ki keys nikale.
7. Spread operator se user ki copy banaye.
8. Optional chaining se `user.social?.instagram` safely access kare.
9. Computed property ka use karke object me dynamically `"github"` property add kare.

Rule: Isme tumhe khud decide karna hai ki kis step ke liye kaunsa Object concept use hoga. 🐱📄