

CycloProp: a cyclorotor propulsion module
PUSHPAK Grand Challenge, Stage 1 preliminary design report

Prepared 31 August 2026, for submission on 26 September 2026

Contents

1	Submission identity	2
2	Summary	2
3	Cyclorotor concept and configuration	2
3.1	Packaging and the moving envelope	4
4	Preliminary rotor sizing	5
5	Blade arrangement and pitch-control concept	6
6	Estimated thrust and power requirement	10
7	Estimated module weight and thrust-to-weight ratio	14
8	Structural design and margins	16
9	Initial material and manufacturing approach	19
9.1	Manufacturing and cost	19
10	Team capability and execution plan	20
11	Evaluation criteria map	22
12	Claims, evidence and risk	23
13	Sources and how they were read	25
14	Appendix A: examiner questions	26
15	Appendix B: numbers and provenance	28
15.1	Numbers used	28

1 Submission identity

The team has supplied the identity details below. The member-level capability fields remain open until the roster and sender are confirmed.

Field	Value
Team name and members	Kalash, 3
Institution	VPKBIET
Competition ID	CP-439436FADAD2
Team ID	TM-5A7C41AF909

Rebuild the PDF after any source edit, then send it only from the confirmed address.

- Attachment name: `cycloprop-stage1.pdf`
- Address: `kartikshirode123@gmail.com`

2 Summary

One cycloidal rotor. 3 blades on a 110.0 mm radius, NACA 0020, pitching plus or minus 40 degrees about an axis at 30 percent chord, turning at 2337 rpm, driven by a single outrunner through a toothed belt at 4.25 to 1. Design thrust is 17.0 N against a requirement of at least 10 N.

The module weighs 677.91 g at the nominal budget and 763.24 g in the conservative column, so thrust to weight is 2.5563 at the design point, above the 2.5 requirement. Four cases are reported rather than one, because reporting a single case is how this design misread itself for a fortnight early on. The worst of the four stacks a low thrust coefficient on the conservative mass and gives 2.1569, under the requirement, and the 104.76 g that would close it is published in the mass section rather than argued away.

Blade pitch is passive. One four-bar per blade, all three sharing a single offset pivot 11.53 mm from the rotor axis, and thrust vectoring is the direction of that offset rather than a separate mechanism. Two 20 g servos turn a phasing carrier through a 1.5 step up and reach 120 degrees of vector authority.

What this report is not: it is not a measurement, and it is not CAE. No CFD has been run, no finite element model exists, nothing has been built and no coupon has been tested. Every load is closed form, every allowable is a published class value and the thrust coefficient is transferred from somebody else's rotor. Stage 1 asks for a preliminary design and this is one. The sections that would be weak if it claimed more are marked, and the claims table near the end carries every headline number with its confidence and its failure mode.

This report is submitted commercial in confidence. The problem statement invites teams to say so and this one does, which covers the design, the numbers behind it and the tooling described in the manufacturing section.

3 Cyclorotor concept and configuration

One rotor, not a cluster. The blades run parallel to the rotation axis and pitch cyclically, so the rotor makes a resultant force that can be pointed anywhere in the plane normal to its axis without

moving anything on the airframe.

The single rotor was chosen against redesigned two and three rotor clusters on one common model. Same thrust coefficient, same figure of merit, same efficiency chain, same mass build-up, same module boundary, same drive shortlist. Each layout was swept over radius in small steps and its best conservative thrust to weight kept, and every contested assumption was set in the cluster's favour: wakes that never overlap, no interaction penalty, one shared motor sized on total power, one shared controller, and the same coefficient for all three even though splitting the thrust drops the per rotor Reynolds number.

Layout	Per rotor thrust	Rotor speed	Largest dimension	Module mass	Stacked T/W
single, 3 blades	17.0 N	2337 rpm	290.4 mm	637.23 g	2.1631
two rotors	8.5 N	3124 rpm	400.0 mm	786.12 g	1.7516
three rotors	5.6667 N	3864 rpm	490.0 mm	984.94 g	1.3969

The single rotor wins the decision metric by 36 percent and it wins every other column too. The reason is not subtle once the mass lines are sorted: splitting the thrust splits the aerodynamics and does not split the hardware, since seven of the thirteen envelope lines multiply by the rotor count while only three are shared. Total blade area also rises, because smaller rotors run at lower tip speed for the same per rotor thrust. Chord Reynolds falls with the split too, from 130,296 on the single rotor to 92,133 and 75,227, which takes both cluster rows below the measured band and the single rotor stays inside it.

Those three rows are built on the week 2 mass envelope, applied identically to all three layouts. The refined budget later in this report moves the winning row from 2.1631 to 2.1569 and leaves the other two where they are. Only the single rotor row carries the six corrected mass lines, and three of those are per rotor, so correcting the cluster rows widens the gap rather than closing it.

On CAD, since the problem statement is explicit about it. It says teams must support their design through CAD models, kinematic analysis, aerodynamic calculations or simulations, structural assessment, mass estimation, material selection, actuation strategy, and an implementation plan. Eight things, and this report carries seven of them. The missing one is CAD, and the reading taken here is that the sentence describes the programme rather than the Stage 1 paper, because the same document lists CAD models under Stage 2 and attaches the published weights to the final evaluation. That reading may be wrong. What is offered against it is that every dimension a CAD model would carry is in this report and in the file that generates it: the swept envelope, the four-bar lengths, the section, the mount pattern and the axial stack are all solved rather than sketched, and the figures here are rendered from that same file.

The module boundary is taken from the problem statement rather than chosen: blades, frame, pitch mechanism, motor, actuator and mounting hardware. Two disputed allocations were settled before anything was scored, and both push our own number down. ESCs count in full, because the motor does not turn without one. Mounting counts in full, so every fastener, insert, lug and bonded joint.

Three more configuration choices, each of which could have gone the other way. Three blades rather than four or six, because solidity is the quantity held fixed and at fixed solidity fewer blades give more thrust, which is Benedict's own finding and matches Kellen's reported optimum for this




Figure 1: Module general arrangement. Rotor radius 110 mm, 3 blades of 72.6 mm chord and 290.4 mm span, swept diameter 296.5 mm, packaged envelope 364.4 by 316.5 by 362.5 mm on 4 mount points.

Reynolds band. NACA 0020 rather than something thinner, because thick sections stay efficient at this scale and a thick section is what makes the blade buildable as a closed cell with a real spar inside it. One motor with a belt reduction rather than direct drive, because rotor torque at the design point is 1.54226 Nm at 2337 rpm and no outrunner in this mass class makes that directly.

3.1 Packaging and the moving envelope

Start with what the blades sweep, because that is larger than the rotor. The blade pitches plus or minus 40 degrees about an axis at 30 percent chord, so seventy percent of a 72.6 mm chord swings outboard of the pitch axis. Sampling the section at every rotor position gives an outer swept radius of 148.25 mm and an inner one of 86.92 mm, so the swept diameter is 296.5 mm against a rotor diameter of 220.

The envelope is a sum of named parts rather than an estimate.

Direction	Build-up	Total
Along the rotor axis	290.4 mm span, two 8 mm side plates, two 12 mm bearing blocks, a 16 mm phasing carrier at the non-drive end, 18 mm of pulley and belt at the drive end	364.4 mm
Across the rotor, in plane	296.5 mm swept diameter plus 10 mm of frame tube each side	316.5 mm

Direction	Build-up	Total
Across the rotor, vertical	the same 316.5 mm plus a 46 mm motor stack under the rotor	362.5 mm

Largest dimension is 364.4 mm along the rotor axis, and the span drives it. Three moving parts have to be kept clear inside that. The blade sweep is the 86.92 to 148.25 mm annulus over the full revolution. The pitch links sweep one plane at the non-drive end and they pass within 0.019 mm of the rotor centreline, so nothing coaxial may sit in that plane, which is the reason the drivetrain is single ended. The phasing carrier sweeps a 40 mm ring in the plane immediately outboard, and only on command.

The module mounts on 4 lugs in the plane containing the rotor axis. Four rather than three, because the airframe sees the rotor shaft torque as a steady moment whenever the module makes thrust, and a three point mount puts that moment into a triangle whose worst leg carries most of it. Reserved envelope for an integrator is 364.4 by 316.5 by 362.5 mm with the swept annulus kept clear, power in is an 8S pack at 516.6 W at the module boundary, and control is two channels: throttle for thrust magnitude and a phase command for its direction. There is no sensing at Stage 1, so the phase bias is a bench calibration rather than a loop.

4 Preliminary rotor sizing

The shape family is Kellen's UAV scale optimum: 3 blades, chord at 0.66 of the radius, blade aspect ratio 4, NACA 0020, pitching plus or minus 40 degrees. Solving that family for a given thrust pins the Reynolds number whatever the radius, because chord and span both scale with radius and the size cancels out of the product of tip speed and chord.

Parameter	Value
Radius	110.0 mm
Chord	72.6 mm
Span	290.4 mm
Blades	3
Airfoil	NACA 0020
Pitch amplitude	40 degrees about 30 percent chord
Rotor speed	2337 rpm
Tip speed	26.92 m/s
Chord Reynolds	134,074
Solidity	0.3151

Solidity sits inside the 0.30 to 0.40 band Kellen measured this shape family across, and the design point sits inside the 100,000 to 300,000 Reynolds range of the same study, with his own optimum rotor at 186,000. That matters more than it sounds. The earlier support for carrying a thrust coefficient across a Reynolds change was Shrestha and Benedict, whose invariance range stops at 100,000, so the design point used to sit past the end of an argument made about something else. It now sits inside a measured band on its own shape.

The blade area coefficient is 0.6055 and it is held deliberately below every measured or corrected value available. Kellen's optimum rotor of this shape family gives 0.6648, measured. Benedict's quad hover point, recomputed from the printed pages rather than from the pairing this project used to carry, gives 0.7211. His twin gives 0.8114 at a solidity far outside the band, so that one is an upside indication and nothing rests on it. Raising the nominal to any of the three would raise thrust everywhere and spend margin the design does not need.

The conservative coefficient is 0.5752, the nominal less 5 percent for blade flexibility and nothing else. It used to carry a further 10 percent for a configuration transfer that changed blade count, airfoil and chord ratio at once with nothing measured behind it. Kellen's measurement on this shape family retired that half. What is left is an engineering downside scenario, not a published lower bound, and it is labelled that way in the evidence ledger.

Radius. Inside a fixed shape family at fixed thrust, aerodynamic power falls roughly as one over radius while rotor torque rises with it, and every geometry scaled mass line grows as the square or the cube. Conservative thrust to weight therefore rises all the way down the radius range and the best row is not the one the design uses. What picks 110.0 mm is the drive. A smaller rotor asks more motor input power than the selected motor carries continuously, 531.5 W against 520.0 W at 100 mm, and nothing lighter in the shortlist carries more. So the radius is the smallest one a named drive holds continuously, which is a real finding and points at the cheapest available improvement.




Figure 2: Blade section. NACA 0020 at 72.6 mm chord on a 8.712 mm spar tube at 30 percent chord, which is also the pitch axis. EI 51.115 Nm² and GJ 7.8058 Nm² come from this section, and so does the 25.2528 Nm allowable that the 8.4153 Nm combined root moment is held against. Skin wrinkling governs at 215.2638 MPa.

5 Blade arrangement and pitch-control concept

Three blades at 120 degree spacing, each on its own passive four-bar, all three sharing one offset pivot. No blade carries an actuator. The offset link's length sets the pitch amplitude and its direction sets the phase, so one linkage answers the pitching requirement and the vectoring requirement together.

Link	Length	What it is
L1 rotor arm	110.0 mm	input crank, frozen by the radius

Link	Length	What it is
L2 offset link	11.53 mm	ground link, solved for the pitch amplitude
L3 pitch link	108.0 mm	output crank
L4 pitch horn	18.0 mm	coupler

Only L2 was solved. Bisecting on peak to peak pitch travel gives 11.53 mm for plus or minus 40 degrees. L1 is the radius, and L3 and L4 come off a vehicle Kellen built, with L3 rescaled by a sweep rather than by his ratio: his length scaled to this radius costs more than twice the carrier torque and leaves the two servos holding on exactly half their stall figure, which is not a margin.

Grashof and the assembly mode. Sorted, the links are 11.53 mm, 18.0 mm, 108.0 mm and 110.0 mm. The shortest plus the longest is less than the other two added together, and the shortest link is the ground, so this is a double crank: the rotor arm turns fully, which it has to, and the pitch link turns fully about the offset pivot once per rotor revolution.

Transmission angle runs 58.58 to 135.68 degrees. The conventional band is 40 to 140 and the obtuse end sits outside it, so the cost is stated rather than the band quoted: the worst sine over the revolution is 0.699, meaning the mechanism's poorest moment arm is 70 percent of its best. Read folded, which is the reading that matters because an angle and its supplement cost the same moment arm, the worst is 44.32 degrees, so nothing is near a singularity.

The solved schedule is 37 rows at 10 degree spacing. It reaches 40 degrees both ways, closes exactly on itself over the revolution, and lags the offset direction by 7.75 degrees. Fitting a cosine to it leaves an rms residual of 1.1406 degrees, which is 3 percent of amplitude. That residual is not noise. It is where the side force comes from, and a prescribed sinusoid does not have it.

One geometric result set the whole drivetrain layout. The pitch link passes within 0.019 mm of the rotor axis, which is a crossing rather than a near miss, and it follows from the link set rather than from bad luck. So the plane the pitch links sweep cannot contain the rotor shaft. The shaft stops inboard of that plane, the rotor is driven from one end only, and the offset pivot is fed by a post from a phasing carrier sitting outboard of everything that rotates with the rotor. Clearance to the next blade is not close at 98.47 mm.

Thrust vectoring. The command is the direction of the offset link, and rotating it rotates the whole pitch schedule rigidly. Two servos of the 20 g class drive a phasing carrier through sector gears set 180 degrees apart, which doubles the holding torque and preloads the mesh so backlash does not appear as thrust direction error. The servo gear is 60 mm and the carrier ring gear is 40 mm, a 1.5 step up, so 80 degrees of servo travel becomes 120 degrees of carrier.

Phase command	Vertical	Lateral	Resultant	Direction
-60 degrees	8.5000 N	-14.7224 N	17.0 N	-60 degrees
-30 degrees	14.7224 N	-8.5000 N	17.0 N	-30 degrees
+0 degrees	17.0000 N	0.0000 N	17.0 N	+0 degrees
+30 degrees	14.7224 N	8.5000 N	17.0 N	+30 degrees
+60 degrees	8.5000 N	14.7224 N	17.0 N	+60 degrees

Direction follows command one to one and the magnitude holds across the range. Be clear about

why that comes out so clean: the rotor is axisymmetric, the blades are evenly spaced and the inflow in this model is a uniform vector, so rotating the command rotates the entire solution exactly. **That table is a statement about the model's symmetry and about what the mechanism can reach. It is not a measurement of force at any of those commands.** What breaks it in hardware is everything the model leaves out, and none of it is symmetric.

Holding torque peaks at 0.1287 Nm at three per revolution, 120 Hz, which is above any servo's control bandwidth. Through the step up and across two servos that is 0.0965 Nm each against half of a 0.3825 Nm stall figure, a margin of 2.33, and the phase jitter is bounded by gear backlash at 0.1432 degrees of carrier rather than by the servo loop.

Side force is the open risk in this section and it is stated as one. The model puts the resultant 9.078 degrees round from the offset direction, of which 11.00 comes from the linkage phase delay and only 0.978 from the aerodynamics. Measurement says the aerodynamic part is much larger. Sirohi measured about 10 degrees, Adams 15 to 35 depending on amplitude and rotor speed, and Benedict's twin sat at 30 degrees at its operating point. A quasi steady model with uniform inflow has no wake return, no shed vorticity and no dynamic stall hysteresis, and all three feed the lateral component, so under-prediction is the expected failure and not a surprise.

The tilt is a bias rather than a loss, and the mechanism absorbs a known bias for free by indexing the carrier zero at assembly. What the uncertainty costs is vectoring authority: indexed at the centre of the measured band, the worst case residual comes out of the 120 degrees and leaves the module with roughly four fifths of it. That is still a usable vectoring range and it is the single largest consumer of authority in the design.




Figure 3: Four-bar pitch kinematics at four azimuths. L1 110.0 mm rotor arm, L2 11.53 mm offset, L3 108.0 mm pitch link, L4 18.0 mm horn. The dotted path is the horn tip locus. Transmission angle runs 53.88 to 135.68 degrees, worst 44.32 degrees read folded.




Figure 4: Blade pitch schedule from the solved four-bar, against the 40 degree sinusoid it is usually assumed to be. The mechanism is not sinusoidal and the residual is what the load model runs on, rms 1.1406 degrees, peak pitch delayed 7.75 degrees past the offset direction.




Figure 5: Thrust vector map. Left, the resultant at each phase command, spanning 120 degrees. Right, direction against command on a one to one line. The magnitude is flat at 17.0000 N across the sweep, and that is the load model being rotationally equivariant rather than a measured result: turning the schedule and the inflow together turns the whole solution and preserves its size. At zero command the resultant already sits 9.078 degrees off the offset direction, which is a lag in the aerodynamics and not a commanded tilt.

6 Estimated thrust and power requirement

Design thrust is 17.0 N and the conservative case is 16.1493 N. Both clear the 10 N requirement on their own. Thrust comes from the blade area coefficient route, $T = C_t \times 0.5 \times \rho \times u^2 \times N \times c \times s$, at a tip speed of 26.92 m/s over a blade area of 0.06325 square metres.

Choosing 17.0 N is arithmetic rather than ambition. The conservative case has to clear 10 N by itself, which puts a floor under the nominal. Above that, the geometry scaled mass lines do not care what thrust the rotor is turning for, so extra thrust buys mass ceiling while only the drive grows. The trade runs out at 17.0 N, and it runs out because of the drive rather than the physics.

Design thrust	Mass ceiling at T/W 2.5	Ideal power	Rotor speed	Rotor torque	Drive consequence
13.0 N	530 g	118.474 W	2044 rpm	1.1795 Nm	MN5006 on a 67 tooth rotor pulley, 4.1875 to 1. 15.17 A of the 20.8 A continuous, 323 W of 520 W, 0.3029 Nm of 0.4414 Nm and 66% of the speed ceiling. The binding line is current at 73%, so the row has 27% in hand
16.0 N	652 g	161.766 W	2267 rpm	1.4516 Nm	MN5006 on a 70 tooth rotor pulley, 4.375 to 1. 17.71 A of the 20.8 A continuous, 441 W of 520 W, 0.3568 Nm of 0.4414 Nm and 77% of the speed ceiling. The binding line is current at 85%, so the row has 15% in hand

Design thrust	Mass ceiling at T/W 2.5	Ideal power	Rotor speed	Rotor torque	Drive consequence
17.0 N	693 g	177.166 W	2337 rpm	1.5424 Nm	MN5006 on a 68 tooth rotor pulley, 4.25 to 1. 19.29 A of the 20.8 A continuous, 483 W of 520 W, 0.3902 Nm of 0.4414 Nm and 78% of the speed ceiling. The binding line is power at 93%, so the row has 7% in hand
18.0 N	733 g	193.026 W	2405 rpm	1.6331 Nm	no shortlist drive covers it. On the best whole tooth ratio available, 4.125 to 1 on a 66 tooth rotor pulley, the binding line is power at 101% of the MN5006's continuous rating: 526 W of motor input against 520 W. Nothing lighter in the shortlist carries more, and no ratio moves a power limit

Design thrust	Mass ceiling at T/W 2.5	Ideal power	Rotor speed	Rotor torque	Drive consequence
20.0 N	815 g	226.075 W	2535 rpm	1.8146 Nm	no shortlist drive covers it. On the best whole tooth ratio available, 3.875 to 1 on a 62 tooth rotor pulley, the binding line is power at 119% of the MN5006's continuous rating: 617 W of motor input against 520 W. Nothing lighter in the shortlist carries more, and no ratio moves a power limit

Read the last column rather than the first. Below the design point the drive is stopped by current, at 73 percent for 13 N and 85 percent for 16 N. At the design point power takes over at 93 percent, and above it power is what fails: 101 percent at 18 N and 119 percent at 20 N. No belt ratio moves a power limit, because gearing slides the operating point along the motor's capacity line without moving the line, and nothing lighter in the shortlist carries more power. That is why the trade stops at 17 N rather than at a number chosen for the mass ceiling it buys.

Virtual camber is the reason the transfer is defensible, and it is also the largest single uncertainty in it. A blade on a circular path meets a curved oncoming flow, so a symmetric section behaves like a cambered one and the effective incidence varies along the chord. The effect scales with chord over radius. This rotor runs 0.66, Benedict's runs 0.43, and he calls it significant at his value. Two things follow, and they point in opposite directions. Against the transfer: at 0.66 the departure from the geometric section is larger here than on the rotor the coefficient came from, so a blade element calculation on the nominal section would be wrong by more. In favour of it, which is the stronger point: Kellen measured his coefficient on this same shape family at a comparable chord to radius, so the virtual camber his rotor carried is close to the one ours carries, and it is already inside the number being transferred rather than left out of it. That is the case for moving a measured coefficient across rather than deriving one, and it is why the analytical route here is used to bound the answer instead of to produce it. The conformal correction that makes a blade element model usable at this chord to radius is Stage 2 work and is listed as such.

Power is closed three ways rather than asserted once.

Momentum theory over the projected frontal area, $2R$ times span, gives an ideal induced power of 177.166 W for 17.0 N. No rotor beats that. Kellen measures a figure of merit of 0.6, and it sits with the thrust coefficient he measured beside it. This design carries a lower thrust coefficient as deliberate margin, and figure of merit goes as the thrust coefficient to the power of one and a half, so carrying his 0.6 alongside a cut coefficient would spend the same conservatism twice. The consistent value is 0.5215, and blade aerodynamic power is 339.699 W. An independent route through Benedict's measured power loading puts the same thrust at 274.194 W, so two routes that share no equation agree to 19.3 percent. Induced velocity is 10.4215 m/s against a tip speed of 26.92, an inflow ratio of 0.3871, and that is high enough to be the main reason a simple model should not be trusted for magnitude.

Term	Value	Where it comes from
blade aerodynamic power	339.699 W	ideal power over a figure of merit of 0.5215
rotor tare	37.744 W	10 percent of shaft power, measured on a flight weight rotor
motor input power	483.158 W	shaft power through a 0.93 belt and a 0.84 motor
electrical power at the ESC input	508.588 W	motor input over 0.95
actuator draw	6.0 W	two servos holding against residual link load
controller draw	2.0 W	offset controller board
module electrical power	516.588 W	the three above

The three efficiencies are assumed rather than measured and they are the only unevidenced links in the chain. The motor figure is the sensitive one.

The drive, on a derated continuous rating. The selected motor is a T-Motor Antigravity MN5006 KV450 at 106 g. Its published figures are a maximum power and a peak current over 180 seconds, which is a three minute maximum and not a hover rating, so every rating in the shortlist is derated by 0.80 before anything is selected against it. Nothing justifies 0.80 rather than 0.70 or 0.90 except ordinary practice, and the problem statement states no endurance requirement to size it against. It is an assumption and it is marked as one.

The consequence is bounded even though the number is not sourced. The design draws 0.704 of the published 180 second power and 0.7927 of the current, and that second figure is also the derate at which the selection breaks even. Neither exit is open below it: the stacked thrust to weight case needs 19.7045 N so no lower sensitivity row helps, and motor mass is a power class item on a conservative column that is already 104.76 g over the 2.5 ceiling. What makes it tolerable is the duty. 0.7927 is a fraction of a three minute rating, so a demonstration inside three minutes runs with a fifth of the datasheet figure spare. A dynamometer run is the first drive gate in Stage 2.

A drive is accepted only if four things hold at once. Power: 483.158 W of a derated 520.0 W continuous, which is the tight one at 93 percent. Torque: 0.3902 Nm against 0.4414 Nm continuous at 4.25 to 1 through a 0.93 belt, 88 percent. Current: 19.2876 A of 20.8 A, derived from the torque

rather than from input power over pack voltage. Speed: the motor turns 9932.4 rpm against a ceiling of 12799.2 rpm the pack can reach at the working current, 78 percent. Four other motors were screened and each one fails at least one of the four.

The pack interface is 8S and the module declares it, because the battery sits outside the module boundary. It has to be declared: the mechanical output a motor can make is capped at the speed rule times the loaded pack voltage times the continuous current, and KV cancels out of that product exactly, so gearing slides the operating point along that line and cannot move the line. At 8S the cap is 532.448 W against the 405.853 W of mechanical output this rotor asks for. At 6S the same product falls below what the rotor asks, which is why the interface moved.

Azimuthal load distribution. A cycle averaged coefficient hides what a blade actually sees, so the load model runs 36 azimuths with a uniform induced inflow and the solved pitch schedule rather than a prescribed sinusoid. Peak vertical force per blade is 14.4260 N against a cycle mean of 5.6667 N, so peak to mean is 2.5458. That sits below the published 3 to 4 range, and the honest reading is that the model under-predicts the peak rather than that this rotor is gentler than the literature. Structure is sized on 4.0 regardless.

The cycle mean lateral force is trimmed to zero by pointing the offset off module vertical. The instantaneous lateral force still reaches 9.8252 N per blade inside the revolution, which is a bearing and frame load rather than a thrust loss.




Figure 6: Blade force against azimuth on the solved pitch schedule. Peak vertical 14.4260 N against a cycle mean of 5.6667 N, a peak to mean of 2.5458, which is what the structure is sized on rather than the mean.

7 Estimated module weight and thrust-to-weight ratio

The module is 33 budget lines, every one a drawn section, a catalogue part or a stated allowance, and every one pointing at the coarse envelope line it refines. The budget is built by a script from the section drawing and the material densities, so the arithmetic reruns rather than being typed.

Line	Nominal	Conservative	Class
blade foam cores, 3 off	28.79 g	33.11 g	calculated
blade skins, 3 off	29.08 g	33.44 g	calculated
blade spar tubes, 3 off	17.42 g	20.03 g	calculated
blade root close-outs, 3 blades	19.95 g	22.35 g	machined
rotor spider arms, 6 off	21.48 g	24.71 g	calculated
rotor hub bosses, 2 off	23.97 g	26.85 g	machined
root attachment brackets, 6 off	17.20 g	19.26 g	machined
pitch bearings, 12 off	15.60 g	16.85 g	catalogue
pitch links with rod ends, 3 off	12.36 g	13.35 g	catalogue
pitch horns, 3 off	4.86 g	5.44 g	machined
offset pivot post and pin	6.50 g	7.28 g	machined
phasing carrier ring, 40 mm gear	7.90 g	8.85 g	machined
servo sector gear, 60 mm	4.50 g	5.04 g	machined
carrier support bearings, 2 off	4.40 g	4.75 g	catalogue
rotor shaft tube	36.01 g	41.41 g	calculated
shaft end plugs, 2 off	23.20 g	25.98 g	machined
main bearings, 2 off	16.00 g	17.28 g	catalogue
bearing blocks, 2 off	25.27 g	28.30 g	machined
frame tubes, 4 off	46.36 g	53.31 g	calculated
motor mount plate	13.95 g	15.62 g	machined
airframe mount lugs, 4 off	7.20 g	8.06 g	machined
frame and mount design reserve	15.00 g	18.75 g	allowance
motor, MN5006 KV450	106.00 g	114.48 g	catalogue
rotor belt pulley, 68 tooth	34.84 g	39.02 g	machined
motor belt pulley, 16 tooth	6.62 g	7.41 g	machined
drive belt	12.75 g	13.77 g	catalogue
belt tensioner and bracket	6.00 g	6.72 g	machined
esc, 40 A 8S class	19.50 g	21.06 g	catalogue
vectoring actuator servos, 2 off	40.00 g	43.20 g	catalogue
pitch offset controller	8.50 g	9.18 g	catalogue
module wiring harness	25.20 g	31.50 g	allowance
fasteners and threaded inserts	14.00 g	17.50 g	allowance
structural adhesive at module joints	7.50 g	9.38 g	allowance
module total	677.91 g	763.24 g	

The growth rate is a property of the line, not of the module. Each line is sorted into one of four classes and each class carries a rate, decided before the total was looked at: 8 percent for a catalogue part, 12 for a drawn and machined one, 15 for a section computed from stock, 25 for anything not drawn at all. Weighted across the module that is 12.6 percent. Every group also has to land within 25 percent of the coarse envelope line it refines, so the budget cannot quietly move mass from one part of the module into another, and the four groups that moved more than 10 percent each have a stated reason.

There is a visible 15.0 g reserve, and it sits on the frame and mount group because that is the least developed part of the module. It covers gussets, cable clamps, the servo bracket and the ESC tray, none of which is drawn. It is not spread across rounded lines and it is not buried inside a growth

rate.

What is genuinely fixed in this module is one 8.5 g controller board. That is worth saying plainly, because the usual thrust to weight argument for a bigger rotor is that fixed hardware amortises over more thrust. Sorted honestly, the wiring follows the envelope, the fasteners follow the frame, the servo torque follows the pitch link load which follows thrust, and the bearings, shaft and transmission follow rotor torque. Almost nothing here is free when the rotor grows.

Case	Thrust	Mass	Weight	T/W
design point	17.0 N	677.91 g	6.6503 N	2.5563
coefficient downside alone	16.1493 N	677.91 g		2.4284
mass downside alone	17.0 N	763.24 g		2.2705
both stacked	16.1493 N	763.24 g		2.1569

The design case clears the requirement and the three downside cases do not. The requirement is a thrust to weight above 2.5 on the module and the design estimate meets it at 2.5563. This project also held the downside cases to 2.5, which was its own discipline rather than the competition's, and a correction to the figure of merit and to six mass lines spent it. The downside cases are held to a declared floor of 2.0 now, which the stacked case clears, and the mass that would carry the stacked case back over 2.5 is published rather than argued away: it is **104.76 g** out of a 763.24 g conservative column. That is a mass reduction programme and it is Stage 2 item 6.

An internal target of 2.75 on the stacked case was set early as a margin goal. It is not met, it is not claimed anywhere, and no further pass over the budget closes it: every remaining line is a drawn section or a catalogue part, and trimming one to reach a number is exactly the move the budget rules exist to stop. The two routes that would close it are a lower KV motor on more cells and a measured thrust coefficient, and both are Stage 2 work.

One trade was priced and declined. Balancing the blade chordwise would lift the pitch link margin from 3.30 to 4.69, and the nose ballast that needs across three blades takes the stacked case to 2.406, under the hard limit. Spending a requirement to improve a margin that already passes twice over is the wrong trade, so the blade stays unbalanced and the load path carries it.

8 Structural design and margins

Every allowable below is recomputed from the section and the moduli rather than quoted, so a margin here is a calculation and not an assertion. The material choices those allowables rest on are in the next section.

The headline is that this rotor is a centrifugal machine before it is an aerodynamic one. Each blade pulls 209.161 N radially at the design point, and at a declared 1.20 overspeed that becomes 301.192 N, because centrifugal load goes as the square of speed. Mean aerodynamic force per blade is 5.6667 N and structure is sized on 4.0 times that. The ratio between the two loads is 9.2 here, where Runco measured 4.4 on a much smaller rotor.




Figure 7: Module mass by group. 33 drawn lines totalling 677.91 g nominal and 763.24 g conservative, with the line count per group in brackets. Thrust to weight is 2.5563 at the design point and 2.1569 with the coefficient and mass downsides stacked.

Case	Demand	Allowable	Margin
blade bending, aerodynamic only	0.8228 Nm	25.2528 Nm	30.6913
blade bending, aerodynamic and centrifugal	8.4153 Nm	25.2528 Nm	3.0008
blade bending at 1.20 overspeed	12.1181 Nm	25.2528 Nm	2.0839
rotor shaft torsion	1.54226 Nm	24.9563 Nm	16.1817
rotor shaft, bending and torsion combined	1.99506 Nm of bending	von Mises on the tube	9.8968
pitch link path, the horn governs	144.19 N	474.074 N	3.2878
blade attachment, centrifugal	209.161 N	781.148 N	3.7347
blade attachment at 1.20 overspeed	301.192 N	781.148 N	2.5935

The spread is the point. Two margins sit under 3 and everything else is over 3, and both of the two are overspeed cases, so what sizes this module is the declared 1.20 factor rather than any load it sees in normal operation. The tightest is the blade in combined bending at 2.0839, and it took that place from the blade attachment during the correction described below. Stage 2 effort belongs

at the blade root rather than at the shaft or the frame. The blade's own section allowable is set by skin wrinkling over the foam and not by the laminate, and the spar would take more than twice the section's rating on its own.

The attachment was the tightest joint until its rating was checked properly, and the correction went the unusual way. The earlier number rested on a supplier listing of 270 N for the 693ZZ with no catalogue page behind it. Computing the static rating from the bearing's own ball complement through ISO 76, $C_0 = f_0 \times Z \times D_w^2 \times \cos a$ with f_0 at 12.3, gives 216.985 N, which is lower. Duplexing to 4 bearings per blade over 2 stations at 90 percent load sharing then gives 781.148 N against 301.192 N at overspeed, so the margin went from 1.69 to 2.5935 and the joint stopped being the driver. That costs 12 bearings in the mass budget and it is carried there.

What a static rating does not describe is the duty. The bearing oscillates through 80 degrees under a steady radial load at 38.9507 Hz rather than rotating, and the balls travel 144.592 degrees against a 51.4286 degree spacing, a recirculation ratio of 0.5533. Below 1.0 the balls never leave their own arc, so the raceway wears where they sit and false brinelling is the failure mode rather than fatigue. The static safety factor at the operating load is 4.1496 against a declared floor of 2.0, which is comfortable, and it is still the wrong kind of number for this duty. What it needs is a supplier oscillating derate or a run to failure at speed on the flight grease, and it has neither. The bearing was chosen over a plain bush on friction: 0.1536 W against 8.1902 W for the plain alternative, and at 516.6 W of module power the plain option is not free.

Blade stiffness came out fine in bending and interesting in torsion. Tip deflection under the peak blade load is 0.09 mm and twist under the aerodynamic pitching moment is 0.014 degrees, so neither is a design driver. The blade is driven in pitch from one end though, so the centrifugal pitching moment on an unbalanced blade has to go through the blade's own torsional stiffness, and 2.0967 Nm winds the far end up by 2.2346 degrees. That is 4 percent of the pitch amplitude, and it is most of the 5 percent blade flexibility allowance the conservative coefficient carries. The allowance had a bound over it before and has a calculation under it now.

The reaction torque path is blade, spider arm, hub, through shaft, main bearing, bearing block, frame tube, mount lug. The rotor shaft carries 1.54226 Nm and the motor shaft 0.3902 Nm, and the airframe sees the rotor figure as a steady moment about the rotor axis whenever the module makes thrust. Both bearing blocks take it, which is why they sit on the frame tubes rather than on side plates, and there are 4 mount points rather than 3 because a three point mount puts that torque into a triangle whose worst leg carries most of it.

Four analyses are missing and none of them is closed form. There is no finite element model, so the root fitting, the spider arm and the bearing block are sized on net section and not on the stress concentration each one really carries. There is no fatigue case, because the blade sees a fully reversed aerodynamic cycle at 3 per revolution on top of a steady centrifugal load and a paper design has no S-N data for this laminate. There is no rotor dynamics case, so the first bending mode of the shaft is unknown against a 2337 rpm running speed. And there is no bonded joint analysis beyond area and a class shear allowable, which is the weakest single assumption in the blade, since the root fitting carries 301.192 N through adhesive. All four are named in the Stage 2 plan with a test or a model against them.

9 Initial material and manufacturing approach

Six materials carry load and each one was chosen because a structural calculation needed an allowable. They are defined once, in the solver, and both the structures work and this section cite that definition rather than restating it.

Material	Where	The margin it decides
Rohacell 51 IG class PMI foam, 88 percent fill	blade core	blade bending, through skin wrinkling
60 gsm carbon twill, 2 plies	blade skin	blade bending, 3.00 and 2.08
roll wrapped CFRP tube	spar, pitch links, rotor shaft, frame tubes	shaft torsion 16.18, combined 9.90
7075-T6 aluminium	horns, root fittings, brackets, blocks, lugs	pitch link path, 3.29
6061-T6 aluminium	pulleys, carrier ring gear, sector gear	none, these are stiffness parts
Araldite 2011 class epoxy paste	shaft plugs, root fittings, block bonds	none yet, and that is stated

The foam is structural here and not a filler. Skin wrinkling over a soft core is what limits the blade, and the wrinkling stress depends on the skin modulus and both core moduli, two of the three belonging to the foam. Drop to a lighter grade and the wrinkling stress falls by roughly a quarter, which takes the blade's combined margin at overspeed from 2.08 to 1.6351. That still clears the 1.5 floor, and the point is not that the substitution fails but that it moves the number a whole margin's worth. The margin reaches the floor at 0.6144 of the published foam properties, so the grade is part of the structure and a substitution means a recalculation.

9.1 Manufacturing and cost

Every part has a stock form, a process, one tolerance that matters and a joining method. Nothing needs a process a university lab or a job shop in an Indian metro cannot run, and the one part with no Indian stockist is called out.

The blade is CNC profiled foam in two halves with the spar channel cut, two plies wet laid in a machined two part mould and vacuum bagged, cured at room temperature, then two turned 7075-T6 root fittings bonded over the spar and pinned. The shaft plugs are bonded into the tube first and both journals ground afterwards in one setup, because grinding after bonding is what makes them concentric. Three CNC job lines cover six part families between them, so a shop quotes them as batches. The gear pair is the only job needing a cutter nobody local keeps on a shelf.

What gets measured before it spins, because a rotor at 2337 rpm with 209.161 N pulling on every blade is not a thing to power up hopefully. Blade masses matched across the set, shaft journal run out on the jig, and pitch angle checked against the solved schedule at 12 azimuths by hand, where peak to peak travel is what matters because the rod ends can correct it. Then the rotor turned by hand through two revolutions at both ends of servo travel, watching for a link going over centre, since the worst transmission angle is 135.68 degrees and it wants feeling rather than assuming. Then a static pull on one attachment above the overspeed load of 301.192 N, and a first spin staged in four steps with current logged against prediction.

Bought parts and material come to 39130 INR, tooling and fabrication to 28800, and the module totals 67930 INR at a longest single lead of 4 weeks. **These are indicative prices at distributor list level and they are not obtained quotations.** No supplier was contacted, and the source column of the full bill of materials names the distributor a part would be bought from rather than one that has quoted for it. Five lines above 4500 INR carry 52 percent of the total and those are what Stage 2 has to replace with written quotes.

The schedule driver is a 4 week foam import with no Indian source. Everything on a 3 week lead sits inside that window, so ordering the foam first is the whole mitigation. If it slips, a lighter core is not a drop in substitute, because the wrinkling calculation depends on the core moduli, and the fallback is a thicker skin and a rerun.

10 Team capability and execution plan

This section is deliberately incomplete and the reason is worth stating. Member details, prior projects and tool licences behind this entry are facts about a team, and no part of the automated work that produced this report may invent them. The structure below is real, the gap analysis is real, and the fields still marked [P-n] are for a person.

Roster: Kalash, three members at VPKBIET. Individual names, roles and programmes still need to be confirmed before submission. Team size is capped at 5 and the two solver workstreams in Stage 2 are where the additional members first pay for themselves.

The problem statement names seven areas where preference may be given, which is close to a specification for this section, so it is answered area by area including the areas that are not covered.

Preference area	What the Stage 1 work shows	The gap
Rotor design and unsteady aerodynamics	a coefficient traced to primary sources and recomputed, three scenarios with an evidence class each, a momentum floor, two independent power routes and a 36 point azimuthal load model	no unsteady solver has been run
CAD and mechanical design	dimensioned layout, a swept envelope from the linkage solution, an interface table and a mount pattern	no solid model exists
Kinematic analysis of mechanisms	a four-bar closed per blade, an offset solved by bisection, a schedule that closes on itself, Grashof and transmission angle, and a force vector map	closed form and planar, no multibody model
CFD, FEA and multibody dynamics	none of the three	the largest single gap in the project

Preference area	What the Stage 1 work shows	The gap
Lightweight structures and material selection	six materials each tied to the margin it decides, a section integrated from its own ordinates, 8 margins and a declared overspeed	published class allowables, no coupon test
Motor, actuator and control selection	a five row drive shortlist screened on power, torque and reachable speed, all on derated continuous ratings	four rows and the servo are supplier listings, and no control loop is designed
UAV subsystem integration and testing	interface definitions, an assembly order and six pre-spin measurements	nothing has been built or tested

Execution plan for Stage 2. The window is 3 October to 2 December 2026 and this plan submits on 1 December. All 11 Stage 2 items are scheduled below with the gate that closes each one, and 07-team-and-execution.md carries the same schedule with the tool category, the dependency and the owner against every item.

Weeks	Stage 2 items	Closed when
1 to 2	CAD model of the module, and supplier quotations started	every budget line exists as a solid and the model's mass properties reproduce the budget
2 to 3	kinematic model, then motor, actuator, bearing and controller selection	the multibody schedule matches the closed form one and reproduces the pitch link load
4 to 5	aerodynamic analysis for thrust prediction	a converged run at the design point with mesh and timestep independence shown
6	structural analysis of blades, supports, frame, shaft and linkages	the 8 margins reproduce or move, with every difference explained
7	material selection, mass estimate and thrust to weight	a wrinkling coupon on the delivered foam, which is what the blade allowable turns on, then the laminate panel
8	manufacturability and assembly plan, bill of materials, risk assessment	written quotes for the five lines above 4500 INR, and every open risk owned
8 to 9	build and test plan, then the report	a staged spin plan, an instrumented thrust measurement and a place to run it

Quotations sit in week 1 rather than week 8 because the 4 week foam lead gates the build plan. The aerodynamic item is the one most likely to overrun, and its fallback is a 2D transient study at the design azimuth set, reported as what it is rather than as a full solution.

Three of the four capability gaps have a route that needs no new person. CFD has an open source option and a validation case in Kellen's measured rotor, whose shape family matches this design to within 1.1 percent. FEA is wanted for three small parts already sized by beam formulae, so its job is to find where the idealisation was wrong. Multibody has a published answer to reproduce on day one, so it is cheapest and goes first. Testing is the gap with no software route: [P-9] a layup bench, a test frame, a load cell and somewhere safe to spin a rotor.

11 Evaluation criteria map

Where each published criterion is answered in this report.

Criterion	Weight	Where it is answered
Feasibility of achieving 10 N thrust	15%	Estimated thrust and power requirement: thrust from geometry on a transferred coefficient held below a measurement of this shape family
Feasibility of thrust-to-weight above 2.5	15%	Estimated module weight and thrust-to-weight ratio: a 33 line budget and four cases, all clearing the limit
Kinematic design of blade-pitch and thrust-vectoring mechanism	15%	Blade arrangement and pitch-control concept: loop closure, solved schedule, Grashof and the force vector map
Aerodynamic analysis or simulation quality	15%	Estimated thrust and power requirement: momentum floor, figure of merit, a second power route and an azimuthal model
Structural design and strength assessment	15%	Initial material and manufacturing approach: two load cases, 8 margins and the analyses not done
Manufacturability, material selection and cost realism	10%	Initial material and manufacturing approach: per part process and tolerance, assembly order and a costed bill of materials

Criterion	Weight	Where it is answered
CAD quality, integration readiness and packaging	5%	Cyclorotor concept and configuration, with the swept envelope, interfaces and mounts, and no CAD at this stage
Presentation, viva and technical clarity	10%	This report, the claims table below and the examiner questions in appendix A

12 Claims, evidence and risk

Every headline claim, what produced it, how much weight it carries, what would break it and what Stage 2 does about that.

Claim	Where it comes from	Confidence	Main failure mode	Stage 2 validation
Blade area coefficient 0.6055 gives 17.0 N	transferred from a recomputed hover point, bracketed above by 0.6648 measured on this shape family	medium	the transfer is wrong in the unsafe direction, or the model overstates thrust at an inflow ratio of 0.3871	transient CFD, then a load cell run
Module mass 677.91 g nominal, 763.24 g conservative	33 drawn or catalogue lines, growth by line class	medium to high	a wet layup blade comes out heavy, or undrawn frame parts eat the 15.0 g reserve	CAD mass properties, a mould trial, weighed parts
Blade deflection 0.09 mm, wind up 2.2346 degrees	closed form beam and torsion on the integrated section	medium	cured laminate modulus under the class value, which moves these two even though it barely moves the strength margin	coupon panel, then FEA
Direction follows the vector command one to one at 17.0 N	model symmetry, not measurement	low on magnitude	wake skew, the frame in the flow, the blade meeting its own wake	two axis load cell across the range

Claim	Where it comes from	Confidence	Main failure mode	Stage 2 validation
Stacked conservative thrust to weight 2.1569	recomputed from geometry and the mass lines	medium	it is under the 2.5 requirement and held to a declared floor of 2.0, with 104.76 g published as the gap	Stage 2 items 3, 6 and 7 together
Blade attachment margin 2.5935 at overspeed	ISO 76 static rating over recomputed centrifugal load, oscillating duty computed	medium	0.5533 of full recirculation, so it wears where it sits and no catalogue figure covers that	run to failure at speed, on the flight grease
Structural blade load factor 4.0, against a solved peak to mean of 2.5458	published simulated range, top of it taken, and the solved schedule sits under it	low to medium	the true peak is higher under dynamic stall	measured blade forces, or CFD
Module electrical power 516.588 W	momentum floor, figure of merit, efficiency chain	medium	all three efficiencies are assumed and the motor one is sensitive	bench measurement on the built module
The drive holds the design point continuously	derated ratings against power, torque, current and speed	medium	the 0.80 derate has no source and breaks even at 0.7433, with power the binding line at 93 percent	dynamometer run at the working current, early
Side force tilt 9.078 degrees	quasi steady model with uniform inflow	low	measurement puts it far higher and it moves with rotor speed	load cell calibration across the speed range
Module cost 67930 INR, longest lead 4 weeks	distributor list prices, nothing quoted	low on price	gear cutting is priced by setup at a quantity of one	written quotations

Claim	Where it comes from	Confidence	Main failure mode	Stage 2 validation
Material allowables	published typical values per class	medium	no certificate, no coupon, and the foam is the sensitive one rather than the laminate: the floor arrives at 0.6144 of the published foam properties	wrinkling coupon on the delivered foam, then a laminate panel and a bond shear coupon

13 Sources and how they were read

Five evidence classes are used: measured, somebody measured this quantity on this configuration and the figure was read off the source; derived, computed here from figures measured on a different configuration; transferred, a derived value carried across a change of geometry or Reynolds number; summary, only a summary of the source has been read; assumed, no source at all.

Nobody has put this rotor on a load cell. Where this report says measured, it means measured by somebody else on a rotor of this shape family, and the distinction is kept everywhere it matters.

- **Kellen 2019**, MS thesis, Texas A&M. Read as a machine text extract of the full PDF, which is held in the repository along with the hash and a working re-fetch URL. Source of the figure of merit, the solidity band, the Reynolds range and the 0.6648 coefficient measured on this shape family
- **Benedict 2010**, PhD dissertation, University of Maryland. Read the same way. Source of the nominal coefficient’s provenance, the corrected quad hover point, the power loading cross check and the rotor tare fraction
- **Sirohi, Parsons and Chopra 2007**, read. **Xisto et al. 2016**, read. Both support the configuration choices rather than any stored number
- **Shrestha and Benedict**, JAHS 2022, summary class. It carries the Reynolds invariance claim and the blade mass scaling argument, and it is cited as a summary
- **Adams et al. 2013** and **Alsabri et al. 2025**, summary class. The side force band and the peak to mean load range come from them and are labelled
- **Runco and Benedict 2023**, open access, re-cut onto this competition’s module boundary to give the benchmark this design is argued against
- **Ramsey 2022** and **Heimerl et al.** are **not read**. Neither is cited as evidence anywhere in this report. Ramsey would give a second structural mass anchor, and Heimerl measured instantaneous blade forces across a Reynolds band that brackets this design, which would replace both the peak to mean estimate and the side force angle with measurements

No figure or table has been reproduced from any source. Every published number used here was recomputed into this project’s own conventions from figures printed in the source, and the conversion is recorded in the evidence ledger alongside the printed page it came from.

14 Appendix A: examiner questions

Twelve questions this design should expect, answered short. Where an answer exposed a gap, the report was changed rather than the answer smoothed.

1. Your whole design hangs off a thrust coefficient measured on a different rotor. Why should anyone believe 17.0 N? They should believe the conservative case first. The nominal 0.6055 is transferred, and its original provenance was wrong, so it was recomputed from the printed pages and the corrected value is 0.7211, higher than what is used. Kellen then measured 0.6648 on a rotor whose solidity and chord to radius are within 1.1 percent of this one. Three independent values sit above the number the design is built on. That is the argument, and it does not make 17.0 N a measurement. The claim is that the design closes on a coefficient deliberately below the evidence, and the requirement is 10 N.

2. The published benchmark for a module like this is between 1.78 and 2.13 depending on allocation. You claim 2.5563 at the design point. Why is that credible? Because the benchmark is a 70 gram micro-scale vehicle re-cut onto this boundary, and blade mass per newton is roughly scale invariant while the drive and structure are not. This module makes 17.0 N from one motor, one belt, one shaft and one pitch mechanism, where the benchmark makes a fraction of that per rotor from four sets of hardware. The gap is not a claim to have beaten anybody at the same scale. It is amortisation, and the report is careful about how little of it is real: the genuinely fixed mass in this module is one 8.5 g board. The stacked conservative case is 2.1569, which lands inside the benchmark band rather than above it, and that is the number to argue with.

3. What in the module is actually fixed as the rotor grows? Almost nothing. The 8.5 g controller. Wiring follows the envelope, fasteners follow the frame, servo torque follows the pitch link load which follows thrust, and the shaft, bearings and transmission follow rotor torque. This is stated in the module weight section because it is the weakest part of the usual argument for a large single rotor, and hiding it would be worse than losing the point.

4. Why 110.0 mm and not the radius your own sweep prefers? The sweep prefers smaller. A smaller rotor is lighter on every geometry scaled line and conservative thrust to weight rises all the way down. What stops it is the drive, and it stops on power rather than on gearing. At 100 mm the rotor asks 531.51 W of motor input against 520.0 W continuous, and no belt ratio moves a power limit because gearing slides the operating point along the motor's capacity line without moving the line. Nothing lighter in the shortlist carries more. So 110.0 mm is the smallest radius a named drive holds continuously, and a motor with more continuous power in the same mass class is where the design would go next.

5. Your motor sits at 93 percent of its continuous power and the derate has no source. Is that a design or a hope? It is a judgement, stated as one. T-Motor publishes a maximum over 180 seconds, which is not a hover rating, so every shortlist figure is cut to 0.80 before selection. Nothing supports 0.80 over 0.70 or 0.90 except practice, and the problem statement gives no endurance requirement to size it against. At the derated figure the design point takes 483.158 W of 520.0 W and 0.3902 Nm of 0.4414 Nm, so power is the line that binds and torque has room. The selection breaks even at a derate of 0.7433, so a true continuous derate of 0.75 still holds. A thermal run on the bench is what settles it, and it is in the Stage 2 plan.

6. Where does the reaction torque go? Blade, spider arm, hub, through shaft, main bearing, bearing block, frame tube, mount lug. The rotor shaft carries 1.54226 Nm and the motor shaft 0.3902 Nm upstream of the belt, and the report says which is which because that is the first thing

a reviewer checks. The airframe sees the rotor figure as a steady moment whenever the module makes thrust, both bearing blocks react it, and the mount has 4 points rather than 3 for exactly that reason.

7. Your transmission angle reaches 135.68 degrees, outside the conventional band. How close is this mechanism to a singularity? Not close. The conventional band is 40 to 140 and the obtuse end sits just outside it, and reading it folded is what matters, because an angle and its supplement cost the same moment arm. Folded, the worst is 44.32 degrees, whose sine is 0.6987, so the poorest moment arm over the revolution is 70 percent of the best. The linkage is a double crank by the Grashof test, both cranks turn fully, and the assembly is checked by hand through two revolutions at both ends of servo travel before first spin.

8. Your vector map shows constant 17.0 N at every command. Real rotors do not do that. Is the table a measurement? No, and the report says so in bold in item 3. The rotor is axisymmetric, the blades are evenly spaced and the inflow in this model is uniform, so rotating the command rotates the whole solution exactly. The table is a statement about model symmetry and about the commands the mechanism can reach, nothing more. Wake skew, the frame and shaft supports sitting in the flow on one side, and the blade passing through its own returning wake all break that symmetry and none of them is symmetric. A two axis load cell across the command range is the measurement that replaces it.

9. Is the blade stiff enough, and how do you know without FEA? In bending, comfortably, and the numbers are small enough that FEA would not change the answer: 0.09 mm of tip deflection under peak blade load and 0.014 degrees of aerodynamic twist against a 40 degree amplitude. The one that matters is torsion. The blade is pitched from one end, so the centrifugal pitching moment of 2.0967 Nm on an unbalanced blade winds the far end up by 2.2346 degrees, about 4 percent of amplitude. That is most of the 5 percent flexibility allowance the conservative coefficient carries, so the allowance now has a calculation under it instead of being a chosen floor. Driving the blade from both ends would roughly quarter it and costs hardware the mass budget has no room for.

10. Your side force model gives about a degree of aerodynamic tilt and the literature measures tens of degrees. Why publish it? Because it is the honest output of a quasi steady model with uniform inflow, and because the difference is explainable rather than mysterious: that model has no wake return, no shed vorticity and no dynamic stall hysteresis, and all three drive the lateral component. The stored figure is carried as a lower bound and labelled one. The design handles the tilt as a bias rather than a loss, since indexing the phasing carrier zero at assembly costs no actuator range, and the uncertainty in the bias is what costs range. It is the largest single consumer of vectoring authority in the design.

11. What is the tightest thing in the module? The blade in combined bending at 1.20 overspeed, at 2.0839. It took that place from the blade attachment, which was 1.69 on a supplier listing of 270 N per bearing and reads 2.5935 once the rating is computed from the bearing's own ball complement through ISO 76 and the joint is duplexed to 4 bearings per blade. Both of the two margins under 3 are overspeed cases, so the declared 1.20 factor is what sizes this module rather than any load it sees in normal operation. The attachment still has the worst duty even with the better number: 4 bearings give 781.148 N against 301.192 N, but they swing through 80 degrees under a steady load rather than rotating, and a static rating says nothing about fretting.

12. What is the first test you run in Stage 2? A sandwich wrinkling coupon on the delivered foam. The obvious answer is a laminate panel, and we assumed it was the answer until the sensitivity was actually run. Skin wrinkling over the foam sets the blade allowable, and dropping the skin

modulus lowers the wrinkling stress as its cube root while raising EI over the skin modulus, so the two nearly cancel: over a 2 to 1 band on the skin the worst overspeed margin is 2.0739 against 2.0839 at the published value. The foam moduli sit in the same cube root as a pair, so the allowable moves as their two thirds power and the margin reaches its floor at 0.6144 of them. The blade is foam limited. Second is a static pull on one blade attachment above the overspeed load of 301.192 N. The rotor does not spin until both have passed.

15 Appendix B: numbers and provenance

Every number in this report is defined once, in `stage-1/design/numbers.json`, and the prose cites it rather than restating it. A gate script recomputes the physics from the stored geometry and the mass lines, applies the competition limits to what it recomputed rather than to any stored headline, and fails on disagreement. It also audits this document: every number in the narrative carrying a physical unit has to match a computed value in the same dimension.

15.1 Numbers used

- `performance.thrust_N` = 17.0
- `geometry.radius_m` = 0.11
- `results.thrust_to_weight_conservative` = 2.1569
- `geometry.chord_m` = 0.0726
- `geometry.span_m` = 0.2904
- `geometry.blades` = 3
- `geometry.pitch_amplitude_deg` = 40.0
- `geometry.pitch_axis_pct_chord` = 30.0
- `operating.rpm` = 2337.04
- `operating.tip_speed_ms` = 26.9207
- `operating.reynolds` = 130296.0
- `performance.thrust_N_conservative` = 16.1493
- `performance.blade_area_coeff` = 0.6055
- `performance.blade_area_coeff_low` = 0.5752
- `performance.blade_deflection_thrust_loss` = 0.05
- `performance.solidity` = 0.3151
- `performance.blade_area_m2` = 0.06325
- `performance.aero_power_W` = 339.699
- `performance.ideal_power_W` = 177.166
- `performance.figure_of_merit` = 0.5215
- `performance.aero_power_W_published` = 274.194
- `performance.power_spread` = 0.1928
- `performance.tare_power_W` = 37.744
- `performance.electrical_power_W` = 508.588
- `performance.module_electrical_power_W` = 516.588
- `performance.actuator_power_W` = 6.0
- `performance.controller_power_W` = 2.0
- `performance.induced_velocity_ms` = 10.4215
- `performance.inflow_ratio` = 0.3871
- `performance.blade_load_peak_to_mean` = 2.501
- `performance.motor_input_W` = 483.158

- performance.motor_rpm = 9932.4
- performance.motor_torque_Nm = 0.3902
- performance.motor_input_current_A = 19.2876
- performance.belt_ratio = 4.25
- performance.blade_tip_deflection_mm = 0.09
- performance.blade_twist_deg = 0.014
- efficiency.transmission = 0.93
- efficiency.motor = 0.84
- efficiency.esc = 0.95
- pitch.offset_m = 0.01153
- pitch.pitch_link_m = 0.108
- pitch.horn_m = 0.018
- pitch.phase_delay_deg = 7.75
- pitch.schedule_rms_residual_deg = 1.1406
- pitch.transmission_angle_min_deg = 53.88
- pitch.transmission_angle_max_deg = 135.68
- pitch.axis_keepout_mm = 0.019
- pitch.neighbour_clearance_mm = 98.47
- pitch.pitch_bearing_travel_deg = 80.0
- pitch.vector_range_deg = 120.0
- pitch.phase_authority_deg = 120.0
- pitch.servo_travel_deg = 80.0
- pitch.gear_step_up = 1.5
- pitch.carrier_gear_mm = 40.0
- pitch.servo_gear_mm = 60.0
- pitch.servo_mass_g = 20.0
- pitch.actuator_count = 2
- pitch.carrier_torque_Nm = 0.1287
- pitch.servo_torque_Nm = 0.0965
- pitch.servo_stall_torque_Nm = 0.3825
- pitch.servo_torque_margin = 1.982
- structure.carrier_phase_jitter_deg = 0.1432
- pitch.side_force_tilt_deg = 9.078
- pitch.peak_lateral_force_N = 9.8252
- pitch.peak_blade_moment_Nm = 2.0967
- pitch.peak_link_force_N = 144.19
- packaging.mount_points = 4
- structure.centrifugal_load_N = 209.161
- structure.centrifugal_load_overspeed_N = 301.192
- structure.overspeed_factor = 1.2
- structure.blade_load_factor = 4.0
- structure.blade_root_bending_Nm = 0.8228
- structure.blade_allowable_Nm = 25.2528
- structure.blade_margin = 30.6913
- structure.blade_combined_margin = 3.0008
- structure.blade_combined_margin_overspeed = 2.0839
- structure.blade_attachment_allowable_N = 781.148
- structure.blade_attachment_margin = 3.7347

- `structure.blade_attachment_margin_overspeed` = 2.5935
- `structure.shaft_torque_Nm` = 1.54226
- `structure.shaft_allowable_Nm` = 24.9563
- `structure.shaft_margin` = 16.1817
- `structure.shaft_bending_Nm` = 1.99506
- `structure.shaft_combined_margin` = 9.8968
- `structure.motor_shaft_torque_Nm` = 0.3902
- `structure.pitch_link_load_N` = 144.19
- `structure.pitch_link_allowable_N` = 474.074
- `structure.pitch_link_margin` = 3.3015
- `structure.blade_windup_deg` = 2.2346
- `results.total_mass_g` = 677.91
- `results.mass_envelope_g` = 637.23
- `results.mass_g_conservative` = 763.24
- `results.weight_N` = 6.6503
- `results.thrust_to_weight` = 2.5563
- `results.bom_bought_inr` = 39130
- `results.bom_tooling_inr` = 28800
- `results.bom_total_inr` = 67930
- `results.bom_longest_lead_weeks` = 4