

1. :has()

Year: 2025 (Full cross-browser support)

Syntax:

```
div:has(img)
```

Purpose:

Parent selector.

Example:

```
.card:has(img) {  
  border: 2px solid blue;  
}
```

Browser Support: Chrome, Safari, Firefox, Edge

Reference: Selectors Level 4

2. @layer

Year: 2025 (Full baseline support)

Syntax:

```
@layer utilities {  
  .btn { padding: 10px; }  
}
```

Purpose:

Controls cascade priority via layers.

Example:

```
@layer base, theme, utilities;
```

Browser Support: All major browsers

Reference: CSS Cascade Level 5

3. subgrid

Year: 2025 (Fully supported)

Syntax:

```
grid-template-columns: subgrid;
```

Purpose:

Allows nested grids to inherit track sizing.

Example:

```
.parent {  
  display: grid;  
  grid-template-columns: 1fr 1fr;  
}
```

```
.child {  
  display: grid;  
  grid-template-columns: subgrid;  
}
```

Browser Support: All modern browsers

Reference: CSS Grid Level 2

4. container-type (Container Queries)

Year: 2025 (Fully supported)

Syntax:

```
.container {  
  container-type: inline-size;  
}
```

Purpose:

Enables styling based on the size of a container rather than viewport.

Example:

```
.card {  
  container-type: inline-size;  
}  
@container (min-width: 400px) {  
  .card-title {  
    font-size: 1.5rem;  
  }  
}
```

Browser Support: All modern browsers (Chrome, Safari, Firefox, Edge)

Reference: MDN – Container Queries

5. Container Query Units (cqw, cqh, cqi, cqb)

Year: 2025

Syntax:

```
width: 50cqw;
```

Purpose:

Responsive sizing based on container dimensions.

Example:

```
.box {  
  width: 50cqw;  
  height: 30cqh;  
}
```

Browser Support: All modern browsers (2025+)
Reference: W3C CSS Containment Module Level 3

6. @scope

Year: 2025 (Widely supported)

Syntax:

```
@scope ( ) {  
  /* scoped styles */  
}
```

Purpose:

Limits CSS rules to a specific DOM subtree, preventing style leakage.

Example:

```
@scope (.card) {  
  h2 {  
    color: darkblue;  
  }  
}
```

Browser Support: Chrome 118+, Safari 17+, Firefox 120+

Reference: MDN Web Docs – CSS @scope Rule

7. @property

Year: 2025 (Baseline)

Syntax:

```
@property --name {  
  syntax: "";  
  inherits: false;  
  initial-value: 0px;  
}
```

Purpose:

Defines typed custom properties with validation and animation support.

Example:

```
@property --box-size {  
  syntax: "";  
  initial-value: 100px;  
  inherits: false;  
}  
.box {  
  width: var(--box-size);  
}
```

```
}
```

Browser Support: Chrome, Edge, Safari, Firefox

Reference: MDN – CSS @property

8. color-mix()

Year: 2025 (Widely supported)

Syntax:

```
color-mix(in srgb, red 50%, blue 50%)
```

Purpose:

Blends two colors dynamically.

Example:

```
.button {  
  background: color-mix(in srgb, blue 70%, white);  
}
```

Browser Support: All major browsers (2025+)

Reference: CSS Color Module Level 5

9. light-dark()

Year: 2025

Syntax:

```
color: light-dark(lightColor, darkColor);
```

Purpose:

Automatically switches color based on color scheme.

Example:

```
body {  
  color: light-dark(black, white);  
}
```

Browser Support: Chrome 120+, Safari 17+, Firefox 121+

Reference: CSS Color Module Level 5

10. scrollbar-gutter

Year: 2025 (Baseline)

Syntax:

```
scrollbar-gutter: stable both-edges;
```

Purpose:

Prevents layout shift when scrollbars appear.

Example:

```
body {  
  scrollbar-gutter: stable;  
}
```

Browser Support: All modern browsers

Reference: MDN – scrollbar-gutter

11. text-box

Year: 2025

Syntax:

```
text-box: trim;
```

Purpose:

Controls inline text metrics trimming.

Example:

```
h1 {  
  text-box: cap alphabetic;  
}
```

Browser Support: Chrome 121+, experimental in others

Reference: CSS Inline Layout Module Level 3

12. animation-timeline

Year: 2025

Syntax:

```
animation-timeline: scroll();
```

Purpose:

Links animation to scroll progress.

Example:

```
.box {  
  animation: fade 1s linear;  
  animation-timeline: scroll();  
}
```

Browser Support: Chrome, Safari 17+, Firefox in progress

Reference: Scroll-Linked Animations Spec

13. view-transition-name

Year: 2025

Syntax:

```
view-transition-name: hero;
```

Purpose:

Enables animated page transitions.

Example:

```
.hero {  
  view-transition-name: hero;  
}
```

Browser Support: Chrome, Edge; partial Safari

Reference: CSS View Transitions Module

14. scroll-state() Query

Year: 2025

Syntax:

```
@container scroll-state(stuck: top)
```

Purpose:

Applies styles when container enters specific scroll states.

Example:

```
@container scroll-state(stuck: top) {  
  header {  
    background: black;  
  }  
}
```

Browser Support: Chrome (experimental)

Reference: CSS Scroll-Driven Animations Module

15. ::target-text

Year: 2025

Syntax:

```
::target-text
```

Purpose:

Styles highlighted text targeted via URL fragment.

Example:

```
::target-text {  
  background: yellow;  
}
```

Browser Support: Chrome 120+, Safari 17+, Firefox 121+

Reference: Selectors Level 4

16. anchor-name

Year: 2026 (Emerging)

Syntax:

```
anchor-name: --tooltip-anchor;
```

Purpose:

Defines an anchor for positioned elements.

Example:

```
.button {  
  anchor-name: --btn;  
}
```

Browser Support: Chrome 121+ (experimental)

Reference: CSS Anchor Positioning Module

17. position-anchor

Year: 2026

Syntax:

```
position-anchor: --btn;
```

Purpose:

Positions element relative to an anchor element.

Example:

```
.tooltip {  
  position-anchor: --btn;  
}
```

Browser Support: Chrome (experimental), others in progress

Reference: CSS Anchor Positioning Draft

18. position-area

Year: 2026

Syntax:

```
position-area: top center;
```

Purpose:

Specifies anchor alignment area.

Example:

```
.tooltip {  
  position-area: bottom center;  
}
```

Browser Support: Experimental (Chrome)

Reference: CSS Anchor Positioning Level 1

19. @custom-media

Year: 2026

Syntax:

```
@custom-media --small (max-width: 600px);
```

Purpose:

Reusable media query variables.

Example:

```
@media (--small) {  
  body {  
    font-size: 14px;  
  }  
}
```

Browser Support: Experimental / partial support

Reference: Media Queries Level 5

20. timeline-scope

Year: 2026

Syntax:

```
timeline-scope: --myTimeline;
```

Purpose:

Defines animation timeline scope.

Example:

```
.container {  
  timeline-scope: --section;  
}
```

Browser Support: Experimental

Reference: CSS Scroll Animations Level 1