

taining materials that are susceptible to contact, water damage and/or air flow are more likely to result in fibers being released. Only approved testing methods can determine whether asbestos is present, and at what levels.

- (c) Employees shall not perform any construction, maintenance or repairs in areas where there is a potential exposure to Presumed Asbestos Containing Material (PACM) or Asbestos Containing Material (ACM) in excess of the Personal Exposure Limits or in regulated areas in the normal scope of their work without first receiving the proper training and personal protective equipment for the type or class of work to be performed. If any employee is asked to enter such areas they shall first contact their supervisor for instructions, before entering the areas. Employees shall not, under any circumstances intentionally disturb, remove or clean up asbestos containing material without first contacting their supervisor.
- (d) **CAUTION** when drilling in doors that you suspect contain asbestos, special training and work practices are required. Contact your supervisor.

14.8 Flammable Liquids and Solvents

- (a) ONLY NON-FLAMMABLE PVC GLUE SHALL BE USED FOR BONDING SECTIONS OF IN-GROUND PVC HYDRAULIC JACK LINERS.
- (b) When using paints, solvents and chemicals, read the warning labels, appropriate MSDSs and follow instructions.
- (c) Avoid getting solvent on clothing. If clothing becomes contaminated, it shall be changed immediately.
- (d) Flames, sparks or any other ignition source shall be kept away from flammable liquids and their vapors. Smoking is prohibited in areas where such materials are used or stored, and "No Smoking" signs shall be posted in these areas.