

## Disentangled Recurrent Wasserstein Autoencoder

While learning of disentangled representations leads to better interpretability, only a handful of works explore unsupervised sequential representations. The work introduces recurrent Wasserstein Autoencoder (R-WAE), which disentangles representation of an input sequence into static and dynamic factors. R-WAE minimizes an upper bound of a penalized of the Wasserstein distance between model and sequential distributions, and simultaneously maximizes the mutual information between input data and different disentangled factors. R-WAE is further extended to learn categorical latent representations in the case of weak supervision. Empirical evaluation of R-WAE on video generation and disentanglement demonstrates improved performance in comparison to prior methods.

A sequence  $x_{1:T}$  is disentangled into static part  $z^c$  and dynamic part  $\{z_t^m\}$ . The primary component behind this procedure is the optimal transport  $W(P_D, P_G)$  between the data distribution  $P_D$  and latent code distribution  $P_G$  with respective sequential variables  $X_{1:T}$ . In practice,  $W(P_D, P_G)$  corresponds to a penalized form of a Wasserstein distance which the method minimizes for disentangling representations. This is achieved by utilizing scaled MMD penalties for latents  $Z^C$  and  $Z^m$  which are more expressive in comparison to scaled Jensen-Shannon penalties. In case the number of motions in the sequential data are available, the framework incorporates categorical latent variables  $a$  to enhance the disentanglement of the dynamic latent codes of motions. From an information theoretic perspective, R-WAE minimizes a lower bound on Mutual Information which is superior to the bound of a VAE due to the presence of two KL terms with each corresponding to static and dynamic factors.

The R-WAE framework, in comparison to prior generative and sequential disentangling frameworks, demonstrates improved performance. R-WAE achieves better EER for static and dynamic latents on the TIMIT speech dataset and classification errors on Sprites and moving MNIST. Qualitatively, R-WAE suitably captures motion and static components which are further utilized across different subjects. Additionally, the framework presents apt sample quality among generated video frames. Perhaps a natural question arises of how does the minimization of R-WAE lower bound quantitatively compare to that of VAE? The answer would help further understand the superiority of R-WAE to a sequential VAE.

The framework of sequential disentanglement using a Wasserstein metric presents two novel directions for future research. Firstly, the work poses an important question of what other metrics can be utilized to capture more complex latent components in videos? And secondly, R-WAE could be further extended to larger temporal span wherein the length of the video is significantly large and sequential prediction errors may compound over the course of inference.

The work presented R-WAE, a sequential framework for disentangling representations into static and dynamic factors. R-WAE minimizes a penalized Wasserstein metric and simultaneously maximizes a lower bound on Mutual Information which is superior to that of a sequential VAE. On a range of challenging video datasets, R-WAE successfully depicts disentangling of representations and generation of video frames while improving over prior methods.