

Augmenting Physical Models with Deep Networks for Complex Dynamics Forecasting

Accurate prediction and forecasting of dynamical processes under partial knowledge is a challenging problem. Data-driven approaches often result in insufficient context and non-negligible errors. To address these challenges, the work introduces a principled approach for augmenting incomplete physical dynamics governed by differential equations with deep data-driven models. The novel APHYNITY framework decomposes dynamics into a physical component with prior knowledge, and a data-driven component with accounting for errors in the model. The learning problem aims to utilize the data-driven component for capturing information which is absent in the physical model. The decomposition results in unique set formulations leading to interpretability and generalization. The APHYNITY framework augments incomplete physical models for identification and forecasting of unknown dynamics. Dynamics corresponding to a system are decomposed into two components: a physical component F_p which accounts for prior knowledge, and a data-driven component F_a which accounts for model errors. In order to utilize the data-driven dynamics for only capturing information which is absent in the physical model, a general-purpose optimization objective is constructed which minimizes the contribution of F_a constrained on the decomposed dynamics. APHYNITY leverages model-based knowledge by augmenting it using neurally parameterized dynamics. The decomposition results in a unique formulation by virtue of Chebyshev sets. This provisions interpretability and generalization with respect to each of model's components. Upon utilizing deep neural networks as parametric decompositions, the work introduces an adaptive constrained optimization method. Optimization introduces an increasing sequence of Lagrange multipliers λ_j such that the successive minima converge to a solution. Iterates are optimized using gradient descent.

The APHYNITY framework, when evaluated on 3 diverse differential equation processes, demonstrates improved performance and reduced error rates in comparison to prior neural differential equation and parameteric prediction methods. Additionally, the framework is found consistent across complete and incomplete physics dataset highlighting generalization in complex scenarios. Qualitative comparison of predictions and ablations further highlight the efficacy of decomposition under varying dynamics. On the other hand, the framework could be further improved with regards to its decomposition design. Minimizing the data-driven contribution F_a may result in inaccurate predictions wherein the physics model is complete but inaccurate. Sampling from the model may potentially result in challenging trajectories. To this end, the question which remains unanswered is *what other decompositions could be utilized to address the limitations of model and data jointly?*

Provision of a model-based and data-driven abstraction of dynamics provides two new directions for future research. Firstly, the work could be extended to incorporate more sophisticated decomposition schemes which would efficaciously explain the limitations of model under complex dynamics. And secondly, evaluation of APHYNITY on multi-object interaction dynamics such as a spring-mass system would further aid in understanding generalization.

The paper introduced APHYNITY framework which decomposes dynamics governed by differential equations into physical and data-driven components. Dynamic abstractions are approximated using deep neural networks with an auxiliary objective to minimize the data-driven contribution. Constrained adaptive optimization provides an increasing sequence of multipliers which enforce trajectory constraints. APHYNITY demonstrates improved performance and generalization in the presence of complete and incomplete physics with ablations validating the decomposition scheme.