Comparison and Performance Analysis of Standard and LVM Based Disk Partitioning

Aswin Babu K

College of Engineering Trivandrum

16th September 2018

► Computers use secondary storage for permanent data storage

- ► Computers use secondary storage for permanent data storage
- ► File Systems specify the format for read/write tasks

- ► Computers use secondary storage for permanent data storage
- ► File Systems specify the format for read/write tasks
- Examples: ext4, XFS, FAT32, NTFS

- ► Computers use secondary storage for permanent data storage
- ► File Systems specify the format for read/write tasks
- Examples: ext4, XFS, FAT32, NTFS
- Partitions are containers on which file systems are created

- ► Computers use secondary storage for permanent data storage
- ► File Systems specify the format for read/write tasks
- Examples: ext4, XFS, FAT32, NTFS
- Partitions are containers on which file systems are created
- Partitions need not be the entire size of the drive


- ► Computers use secondary storage for permanent data storage
- ► File Systems specify the format for read/write tasks
- Examples: ext4, XFS, FAT32, NTFS
- Partitions are containers on which file systems are created
- Partitions need not be the entire size of the drive
- Creating multiple partitions is the norm

- ► Computers use secondary storage for permanent data storage
- ► File Systems specify the format for read/write tasks
- Examples: ext4, XFS, FAT32, NTFS
- Partitions are containers on which file systems are created
- Partitions need not be the entire size of the drive
- Creating multiple partitions is the norm
- Each partition need not have the same file system

▶ The process of creating partitions

- ► The process of creating partitions
- Entirely logical process

- ▶ The process of creating partitions
- Entirely logical process
- Partition utilities include fdisk, parted and diskutil



Why multiple Partitions?

Separate user data from system files

Why multiple Partitions?

- Separate user data from system files
- ▶ Run multiple Operating Systems

Why multiple Partitions?

- Separate user data from system files
- ▶ Run multiple Operating Systems
- Organize personal data

► Stores information about the partitions

- Stores information about the partitions
- ► Several formats exist, eg. APM, MBR, GUID, diskLabel

- Stores information about the partitions
- Several formats exist, eg. APM, MBR, GUID, diskLabel
- Most of the older PCs use Master Boot Record

- Stores information about the partitions
- Several formats exist, eg. APM, MBR, GUID, diskLabel
- ▶ Most of the older PCs use Master Boot Record
- Newer PCs use GUID Partition Table




Figure 1: A typical partition table

Mounted partitions cannot be manipulated

- Mounted partitions cannot be manipulated
- ▶ Partitions can use only adjacent free space during resize

- Mounted partitions cannot be manipulated
- ▶ Partitions can use only adjacent free space during resize
- You cannot extend a partition to cover two physical drives

► An abstraction on top of an abstraction

- ► An abstraction on top of an abstraction
- Creates logical volumes, on top of existing partitions

- An abstraction on top of an abstraction
- Creates logical volumes, on top of existing partitions
- Existing partitions are called Physical Volumes (PV)

- An abstraction on top of an abstraction
- Creates logical volumes, on top of existing partitions
- Existing partitions are called Physical Volumes (PV)
- One or more physical volumes form Volume Groups (VG)

- ► An abstraction on top of an abstraction
- Creates logical volumes, on top of existing partitions
- Existing partitions are called Physical Volumes (PV)
- One or more physical volumes form Volume Groups (VG)
- Logical Volumes (LV) are created on top of VGs

- ► An abstraction on top of an abstraction
- Creates logical volumes, on top of existing partitions
- Existing partitions are called Physical Volumes (PV)
- One or more physical volumes form Volume Groups (VG)
- Logical Volumes (LV) are created on top of VGs
- Device Mapper acts as middle man between LVM and Linux




Figure 2: A typical LVM setup

Features of LVM

▶ Mounted volumes can be manipulated

- Mounted volumes can be manipulated
- ▶ Partitions can span more than one physical drive

- Mounted volumes can be manipulated
- ▶ Partitions can span more than one physical drive
- Creation of snapshots while system is up

- Mounted volumes can be manipulated
- ▶ Partitions can span more than one physical drive
- Creation of snapshots while system is up
- Allows creating striped volume

Redundant Array of Independant Disks

- Redundant Array of Independant Disks
- ► RAID allows combining drives for reliability, performance

- Redundant Array of Independant Disks
- ► RAID allows combining drives for reliability, performance
- ► Eight standard modes RAID level 0 to 7

- Redundant Array of Independant Disks
- ► RAID allows combining drives for reliability, performance
- Eight standard modes RAID level 0 to 7
- ▶ RAID Level 5 and up gives Striping + Parity

- Redundant Array of Independant Disks
- RAID allows combining drives for reliability, performance
- Eight standard modes RAID level 0 to 7
- ▶ RAID Level 5 and up gives Striping + Parity
- Higher performance than LVM striping

- Redundant Array of Independant Disks
- RAID allows combining drives for reliability, performance
- ► Eight standard modes RAID level 0 to 7
- RAID Level 5 and up gives Striping + Parity
- ► Higher performance than LVM striping
- ► RAID 5 requires at least three drives

- Redundant Array of Independant Disks
- ► RAID allows combining drives for reliability, performance
- Eight standard modes RAID level 0 to 7
- ▶ RAID Level 5 and up gives Striping + Parity
- ► Higher performance than LVM striping
- ▶ RAID 5 requires at least three drives
- All drives must be of same capacity
- ▶ (10-¿Spanned volumes not possbile

- Redundant Array of Independant Disks
- RAID allows combining drives for reliability, performance
- Eight standard modes RAID level 0 to 7
- RAID Level 5 and up gives Striping + Parity
- ► Higher performance than LVM striping
- ▶ RAID 5 requires at least three drives
- All drives must be of same capacity
- Does not offer snapshots
- ▶ (10-¿Spanned volumes not possbile

- Redundant Array of Independant Disks
- RAID allows combining drives for reliability, performance
- Eight standard modes RAID level 0 to 7
- RAID Level 5 and up gives Striping + Parity
- ► Higher performance than LVM striping
- ▶ RAID 5 requires at least three drives
- All drives must be of same capacity
- Does not offer snapshots
- ▶ (10-¿Spanned volumes not possbile

- Redundant Array of Independant Disks
- RAID allows combining drives for reliability, performance
- Eight standard modes RAID level 0 to 7
- RAID Level 5 and up gives Striping + Parity
- Higher performance than LVM striping
- ▶ RAID 5 requires at least three drives
- All drives must be of same capacity
- Does not offer snapshots
- ▶ (10-¿Spanned volumes not possbile
- Mounted partitions cannot be manipulated

Only supported under Linux

- Only supported under Linux
- Drive failure while using striped volume cause data loss

- Only supported under Linux
- Drive failure while using striped volume cause data loss

- Only supported under Linux
- ▶ Drive failure while using striped volume cause data loss
- Lower performance than standard partitioning

LVM Performance

LVM Performance

▶ On average, LVM is 5% slower than standard partitioning

LVM Performance

- ▶ On average, LVM is 5% slower than standard partitioning
- ▶ LVM based machines takes around 20% more time to boot

Conclusion

Conclusion

▶ LVM greatly eases the task of system administration

Conclusion

- ▶ LVM greatly eases the task of system administration
- ▶ Performance penality is mostly negligible

Source Code

 $https://github.com/karuvally/lvm_seminar.git$