Web Technology Practical Assignments

Second Year MCA • Questions 1–13 with answers and execution instructions

Note: Save HTML programs with the .html extension and open them in a browser. For PHP programs, save files inside C:\xampp\htdocs\practical\, start Apache in XAMPP, and open them using http://localhost/practical/filename.php. Bootstrap, AngularJS and jQuery CDN examples need internet access.

Question 1: Create a static HTML page displaying the given output using frames.

Answer / procedure: The sample has a website heading, profile heading, left navigation links, and Name/Contact Number textboxes. Modern HTML no longer supports the old <frameset> element, so this code recreates the required frame-style layout using CSS.

```
<!DOCTYPE html>
<html>
<head>
<title>My Website</title>
<style>
body { font-family: "Times New Roman", serif; }
.container { width: 580px; height: 285px; border: 1px solid black; margin: 30px auto; }
.header { height: 53px; border-bottom: 1px solid black; padding: 5px 10px; }
.header h3 { margin: 0; }
.header p { text-align: center; margin: 2px 0; font-size: 18px; }
.content { display: flex; height: 225px; }
.menu { width: 190px; border-right: 1px solid black; padding: 15px 10px; }
.menu a { display: block; color: black; font-weight: bold; margin: 20px 0 40px; }
.details { padding: 45px 15px; }
.row { display: flex; align-items: center; gap: 10px; margin-bottom: 22px; font-size: 18px; }
input { width: 145px; height: 35px; border: 1px solid black; border-radius: 8px; } </style>
</head>
<body>
<div class="container">
  <div class="header">
    <h3>MY WEBSITE</h3>
    <p>MY PROFILE</p>
  </div>
  <div class="content">
    <div class="menu">
      <a href="#home">Home</a>
      <a href="#profile">My Profile</a>
    </div>
    <div class="details">
      <div class="row"><label>Name: -</label><input type="text" name="name"></div>
      <div class="row"><label>Contact No.: -</label><input type="text" name="contact"></div>
    </div>
  </div>
</div>
</body>
</html>
```

Run: Save as question1.html (Save as type: All Files), then double-click it to open in Chrome.

Question 2: Design external CSS and link it to HTML: style headings, paragraphs with 13px font, text blue, and headings green.

Answer / procedure: Create two files in the same folder: question2.html and style.css.

File: question2.html

```
<!DOCTYPE html>
<html>
<head>
<title>External CSS Demo</title>
<link rel="stylesheet" href="style.css">
</head>
<body>
<h1>Welcome to My Website</h1>
<h2>About Us</h2>
<p>This paragraph uses a 13px font and blue text.</p>
</body>
</html>
```

File: style.css `h1, h2`

```
{          color:
green;
} p
{
    font-size: 13px;
    color: blue; }
```

Run: Save both files in the same folder and open question2.html in Chrome.

Question 3: Write JavaScript code for a Patient Master form and validate Patient ID, Patient Name, Address, City, Contact Number and Date of Birth.

Answer / procedure: This example checks required fields, numeric patient ID, 10-digit contact number, and a selected date.

```
<!DOCTYPE html>
<html>
<head><title>Patient Master</title></head> <body>
<h2>Patient Master Form</h2>
<form onsubmit="return validateForm()">
  Patient ID: <input id="pid"><br><br>
  Patient Name: <input id="pname"><br><br>
  Address: <input id="address"><br><br>
  City: <input id="city"><br><br>
  Contact Number: <input id="contact" maxlength="10"><br><br>
  Date of Birth: <input id="dob" type="date"><br><br>
  <button type="submit">Submit</button>
  <button type="reset">Reset</button>
</form> <script>
function validateForm() {
  let id = document.getElementById("pid").value.trim();   let
name = document.getElementById("pname").value.trim();   let
address = document.getElementById("address").value.trim();   let
city = document.getElementById("city").value.trim();   let
contact = document.getElementById("contact").value.trim();   let
dob = document.getElementById("dob").value;
```

```
  if (!id || !name || !address || !city || !contact || !dob) {
alert("All fields are required.");     return false;
  }   if (!/^[0-9]+$/.test(id)) {
alert("Patient ID must contain digits only.");
return false;
  }   if (!/^[A-Za-z ]+$/.test(name)) {     alert("Patient name
must contain letters and spaces only.");     return false;
  }   if (!/^[0-9]{10}$/.test(contact)) {
alert("Contact number must be exactly 10 digits.");
return false;
  }   if (new Date(dob) > new Date()) {
alert("Date of birth cannot be in the future.");
return false;
  }   alert("Patient form validated
successfully.");   return false; }
</script>
</body>
</html>
```

Run: Save as question3.html and open in Chrome. This validates in the browser; it does not store records in a database.

Question 4: Create a Bootstrap grid with a 50% split on small, medium and large devices.

Answer / procedure: Bootstrap uses a 12-column grid. col-sm-6, col-md-6 and col-lg-6 each take 6 of 12 columns (50%) at their breakpoint.

```
<!DOCTYPE html>
<html>
<head>
<title>Bootstrap Grid</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet"> </head>
<body>
<div class="container mt-4">
  <div class="row">
    <div class="col-6 col-sm-6 col-md-6 col-lg-6">
      <div class="p-3 border bg-light">Left Column (50%)</div>
</div>
    <div class="col-6 col-sm-6 col-md-6 col-lg-6">
      <div class="p-3 border bg-secondary text-white">Right Column (50%)</div>
    </div>
  </div>
</div>
</body>
</html>
```

Run: Save as question4.html and open in a browser with internet access for the Bootstrap CDN.

Question 5: Design a responsive webpage using HTML, CSS and Bootstrap.

Answer / procedure: The following example uses a responsive navbar and Bootstrap grid.

```
<!DOCTYPE html>
<html>
<head>
<title>Responsive Website</title>
<meta name="viewport" content="width=device-width, initial-scale=1">
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
</head>
```

```
<body>
<nav class="navbar navbar-expand-lg navbar-dark bg-dark">
  <div class="container">
    <a class="navbar-brand" href="#">My Website</a>
    <button class="navbar-toggler" type="button" data-bs-toggle="collapse" data-bs-target="#menu">
      <span class="navbar-toggler-icon"></span>
    </button>
    <div class="collapse navbar-collapse" id="menu">
      <ul class="navbar-nav ms-auto">
        <li class="nav-item"><a class="nav-link" href="#home">Home</a></li>
        <li class="nav-item"><a class="nav-link" href="#about">About</a></li>
        <li class="nav-item"><a class="nav-link" href="#contact">Contact</a></li>
      </ul>
    </div>
  </div>
</nav>
<div class="container my-4" id="home">
  <div class="p-4 bg-light rounded">
    <h1>Welcome</h1><p>This webpage adjusts to different screen sizes.</p>
</div>
  <div class="row mt-3">
    <div class="col-12 col-md-6"><div class="p-3 border">Section One</div></div>
<div class="col-12 col-md-6"><div class="p-3 border">Section Two</div></div>
  </div>
</div>
<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>
</body>
</html>
```

Question 6: Create a resume website in WordPress.

Answer / procedure: This is a practical setup task rather than a coding question. For a local installation, start Apache and MySQL in XAMPP, place WordPress in C:\xampp\htdocs\resume, create a database in phpMyAdmin, and complete the WordPress installer at http://localhost/resume.

Procedure:

1. Download and extract WordPress into C:\xampp\htdocs\resume.
2. Start Apache and MySQL in XAMPP Control Panel.
3. Open http://localhost/phpmyadmin and create a database named resume_db.
4. Open http://localhost/resume and follow the installation steps. Use the database name resume_db and local MySQL credentials configured for XAMPP.
5. Log in to WordPress, choose Appearance → Themes, install/activate a suitable resume or portfolio theme.
6. Create pages: Home, About Me, Education, Skills, Projects and Contact.
7. Set the navigation menu, add your resume information, preview the website and publish the pages.

Question 7: Build a navigation menu that highlights the selected entry using AngularJS directives.

Answer / procedure: This example uses ng-click and ng-class to highlight the selected menu item.

```
<!DOCTYPE html>
<html ng-app="menuApp">
<head>
<title>AngularJS Navigation</title>
```

```
<style>
.menu a { padding: 10px; display: inline-block; color: black; text-decoration: none; }
.active { background: green; color: white !important; }
</style>
<script src="https://ajax.googleapis.com/ajax/libs/angularjs/1.8.2/angular.min.js"></script> </head>
<body ng-controller="MenuController">
<h2>Navigation Menu</h2>
<div class="menu">
  <a href="" ng-click="selected='Home'" ng-class="{active:selected==='Home'}">Home</a>
  <a href="" ng-click="selected='About'" ng-class="{active:selected==='About'}">About</a>
  <a href="" ng-click="selected='Contact'" ng-class="{active:selected==='Contact'}">Contact</a>
</div>
<p>Selected: {{selected}}</p>
<script> angular.module("menuApp",
[])
.controller("MenuController", function($scope) {
  $scope.selected = "Home";
});
</script>
</body>
</html>
```

Run: Save as question7.html and open in Chrome with internet access for AngularJS.

Question 8: Create a Student Records application using AngularJS.

Answer / procedure: This basic example adds student records to an in-memory array. Data is lost when the page is refreshed; a database is needed for permanent storage.

```
<!DOCTYPE html>
<html ng-app="studentApp">
<head>
<title>Student Records</title>
<script src="https://ajax.googleapis.com/ajax/libs/angularjs/1.8.2/angular.min.js"></script> </head>
<body ng-controller="StudentController">
<h2>Student Records</h2>
<form ng-submit="addStudent()">
  Name: <input ng-model="newStudent.name" required>
  Roll No: <input ng-model="newStudent.roll" required>
  Class: <input ng-model="newStudent.class" required>
  <button type="submit">Add Student</button>
</form>
<br>
<table border="1" cellpadding="8">
<tr><th>Name</th><th>Roll No</th><th>Class</th><th>Action</th></tr>
<tr ng-repeat="s in students">
  <td>{{s.name}}</td><td>{{s.roll}}</td><td>{{s.class}}</td>
  <td><button ng-click="removeStudent($index)">Delete</button></td>
</tr>
</table> <script>
angular.module("studentApp", [])
.controller("StudentController", function($scope) {
  $scope.students = [];
  $scope.newStudent = {};
  $scope.addStudent = function() {
    $scope.students.push(angular.copy($scope.newStudent));
    $scope.newStudent = {};
  };
  $scope.removeStudent = function(index) {
```

```
    $scope.students.splice(index, 1);
  };
});
</script>
</body>
</html>
```

Question 9: Write a jQuery program to get the value of a textbox.

Answer / procedure: The .val() method reads the current value from an input field.

```
<!DOCTYPE html>
<html>
<head>
<title>Get Textbox Value</title>
<script src="https://code.jquery.com/jquery-3.7.1.min.js"></script>
</head>
<body>
<h2>Get Textbox Value</h2>
Enter your name: <input type="text" id="username">
<button id="show">Show Value</button>
<p id="result"></p>
<script>
$(document).ready(function() {
$("#show").click(function() {     var
value = $("#username").val();
    $("#result").text("Your name is: " + value);
  });
});
</script>
</body>
</html>
```

Run: Save as question9.html and open in Chrome with internet access for the jQuery CDN.

Question 10: PHP program to format user-entered text using chosen color, font and size, and save preferences in a cookie.

Answer / procedure: Save the following as question10.php. It displays the submitted text with selected styles and optionally stores style preferences in a cookie.

```
<?php
$color = $_POST['color'] ?? ($_COOKIE['color'] ?? 'blue');
$font = $_POST['font'] ?? ($_COOKIE['font'] ?? 'Arial');
$size = $_POST['size'] ?? ($_COOKIE['size'] ?? '16');
$text = $_POST['text'] ?? '';


$allowedColors = ['black','blue','red','green'];
$allowedFonts = ['Arial','Georgia','Times New Roman','Courier New']; $allowedSizes
= ['14','16','18','20','24'];


if (!in_array($color, $allowedColors)) $color = 'blue';
if (!in_array($font, $allowedFonts)) $font = 'Arial'; if
(!in_array($size, $allowedSizes)) $size = '16';
```

```
if ($_SERVER['REQUEST_METHOD'] === 'POST' && isset($_POST['save'])) {
setcookie('color', $color, time() + 30*24*60*60, '/');
setcookie('font', $font, time() + 30*24*60*60, '/');     setcookie('size',
$size, time() + 30*24*60*60, '/');
}
?>
<!DOCTYPE html>
<html><head><title>Text Formatter</title></head><body>
<h2>Text Formatter</h2>
<form method="post">
  <textarea name="text" rows="5" cols="40" placeholder="Enter text"><?php
echo htmlspecialchars($text, ENT_QUOTES, 'UTF-8');
  ?></textarea><br><br>
  Color: <select name="color">
    <?php foreach (['black','blue','red','green'] as $c) {       echo '<option
'.($color===$c?'selected':'').' value="'.$c.'">'.$c.'</option>';     } ?>
  </select>
  Font: <select name="font">
    <?php foreach (['Arial','Georgia','Times New Roman','Courier New'] as $f) {
echo '<option '.($font===$f?'selected':'').' value="'.$f.'">'.$f.'</option>';     }
?>
  </select>
  Size: <select name="size">
    <?php foreach (['14','16','18','20','24'] as $s) {       echo '<option
'.($size===$s?'selected':'').' value="'.$s.'">'.$s.'px</option>';     } ?>
  </select>
  <label><input type="checkbox" name="save" value="yes"> Save preferences</label>
  <button type="submit">Format Text</button>
</form>
<?php if ($text !== '') { ?>
<h3>Formatted Output</h3>
<div style="color:<?php echo $color; ?>;font-family:<?php echo htmlspecialchars($font, ENT_QUOTES, 'UTF-8');
?>;font-size:<?php echo $size; ?>px;">
<?php echo nl2br(htmlspecialchars($text, ENT_QUOTES, 'UTF-8')); ?>
</div>
<?php } ?> </body></html>
```

Note: Cookies must be set before any HTML output. The code sets cookies before the page markup. A cookie written on a POST request is normally available to the browser on the next request.

Question 11: Create a PHP form to capture Book Name, Author Name, Publisher Name, Category and Synopsis, with Reset and Submit buttons.

Answer / procedure: This version submits the form to the same PHP page and displays the captured values. It does not store them permanently in a database.

```
<!DOCTYPE html>
<html>
<head><title>Book Details</title></head>
<body>
<h2>Book Details Form</h2>
<form method="post">
  Book Name: <input type="text" name="book" required><br><br>
  Author Name: <input type="text" name="author" required><br><br>
  Publisher Name: <input type="text" name="publisher" required><br><br>
  Category: <input type="text" name="category" required><br><br>
  Synopsis:<br><textarea name="synopsis" rows="4" cols="35" required></textarea><br><br>
<button type="reset">Reset</button>
  <button type="submit" name="submit">Submit</button>
```

```
</form> <?php
if (isset($_POST['submit'])) {    echo '<h3>Submitted Book Details</h3>';    foreach
(['book'=>'Book    Name','author'=>'Author    Name','publisher'=>'Publisher    Name',
'category'=>'Category','synopsis'=>'Synopsis']   as   $key=>$label)   {            echo
'<p><b>'.$label.':</b> '.nl2br(htmlspecialchars($_POST[$key] ?? '', ENT_QUOTES, 'UTF-
8')).'</p>';   } } ?>
</body>
</html>
```

Run: Save as question11.php in the XAMPP practical folder and open through localhost. For permanent storage, add a MySQL table and INSERT query if your instructor requires it.

Question 12: Implement a PHP web service for a calculator application.

Answer / procedure: This version displays a calculator interface with two number fields and +, −, ×, ÷ buttons. PHP processes the selected operation and displays the result on the page. Save as q12.php in C:\xampp\htdocs and open http://localhost/q12.php with Apache running.

```
<?php
$result = ""; $error = ""; if
(isset($_POST["calculate"])) {
    $a = $_POST["num1"] ?? ""; $b = $_POST["num2"] ?? ""; $op = $_POST["operation"] ?? "";     if ($a === "" ||
$b === "" || !is_numeric($a) || !is_numeric($b)) { $error = "Please enter valid numbers."; }     else {
        $a = (float)$a; $b = (float)$b;         switch ($op) {             case "add": $result = $a + $b; break;
case "subtract": $result = $a - $b; break;             case "multiply": $result = $a * $b; break;
case "divide": if ($b == 0) { $error = "Cannot divide by zero."; } else { $result = $a / $b; } break;
default: $error = "Select a valid operation.";
        }
    }
} ?>
<!DOCTYPE html><html><head><title>PHP Calculator</title>
<style>body{font-family:Arial;background:#eee}.calculator{width:320px;margin:60px
auto;padding:24px;background:white;border:1px solid #ccc;border-
radius:10px;textalign:center}input[type=number]{width:90%;padding:10px;margin:8px 0;box-
sizing:borderbox}button{width:55px;padding:10px;margin:5px 2px;cursor:pointer}.result{margin-
top:18px;color:green;fontweight:bold}.error{margin-top:18px;color:red}</style></head><body>
<div class="calculator"><h2>PHP Calculator</h2><form method="post">
<input type="number" step="any" name="num1" placeholder="First number" value="<?php echo
htmlspecialchars($_POST['num1'] ?? ''); ?>" required>
<input type="number" step="any" name="num2" placeholder="Second number" value="<?php echo
htmlspecialchars($_POST['num2'] ?? ''); ?>" required><br>
<input type="hidden" name="operation" id="operation" value="add">
<button type="submit" name="calculate" value="1"
onclick="document.getElementById('operation').value='add'">+</button>
<button type="submit" name="calculate" value="1"
onclick="document.getElementById('operation').value='subtract'">−</button>
<button type="submit" name="calculate" value="1"
onclick="document.getElementById('operation').value='multiply'">×</button>
<button type="submit" name="calculate" value="1"
onclick="document.getElementById('operation').value='divide'">÷</button></form>
<?php if ($result !== "") { ?><div class="result">Result: <?php echo htmlspecialchars((string)$result);
?></div><?php } ?>
<?php if ($error !== "") { ?><div class="error"><?php echo htmlspecialchars($error); ?></div><?php } ?>
</div></body></html>
```

Run: Save as q12.php in C:\xampp\htdocs, start Apache, then open http://localhost/q12.php. MySQL is not required for Q12.

Question 13: Connect PHP to MySQL and store book details in a database.

Answer / procedure: This additional practice question extends Q11. Create a database and table in phpMyAdmin, then connect PHP to MySQL and insert submitted book details. Start Apache and MySQL in XAMPP.

Step 1 — Create the database and table

Open http://localhost/phpmyadmin, click SQL, and run the following commands. If college_db already exists, do not run CREATE DATABASE again; select it and create the table only if needed.

```
CREATE DATABASE college_db;
USE college_db; CREATE
TABLE books (
    id INT AUTO_INCREMENT PRIMARY KEY,
book_name VARCHAR(100) NOT NULL,
author_name VARCHAR(100) NOT NULL,
publisher_name VARCHAR(100) NOT NULL,
category VARCHAR(50) NOT NULL,     synopsis
TEXT NOT NULL
);
```

Step 2 — Save this program as q13.php in C:\xampp\htdocs\

```
<?php
$conn = new mysqli("localhost", "root", "", "college_db"); if ($conn-
>connect_error) { die("Connection failed: " . $conn->connect_error); }
$message = ""; if
(isset($_POST["submit"])) {
    $book = trim($_POST["book"] ?? ""); $author = trim($_POST["author"] ?? "");
    $publisher = trim($_POST["publisher"] ?? ""); $category = trim($_POST["category"] ?? "");
    $synopsis = trim($_POST["synopsis"] ?? "");     if ($book &&
$author && $publisher && $category && $synopsis) {
        $stmt = $conn->prepare("INSERT INTO books (book_name, author_name, publisher_name, category, synopsis)
VALUES (?, ?, ?, ?, ?)");
        $stmt->bind_param("sssss", $book, $author, $publisher, $category, $synopsis);
        $message = $stmt->execute() ? "Book saved successfully!" : "Error saving book."; $stmt->close();
} else { $message = "Please fill in all fields."; } } ?>
<!DOCTYPE html><html><head><title>Book Details</title></head><body><h2>Book Details Form</h2>
<form method="post">Book Name: <input name="book" required><br><br>
Author Name: <input name="author" required><br><br>
Publisher Name: <input name="publisher" required><br><br>
Category: <input name="category" required><br><br>
Synopsis: <textarea name="synopsis" required></textarea><br><br>
<button type="reset">Reset</button> <button type="submit" name="submit">Submit</button></form>
<p><?php echo htmlspecialchars($message); ?></p></body></html> <?php
$conn->close(); ?>
```

Step 3 — Run and verify

Save as C:\xampp\htdocs\q13.php. Start Apache and MySQL, then open http://localhost/q13.php. Submit a book record. Verify it in phpMyAdmin → college_db → books → Browse, or run SELECT * FROM books; in the SQL tab.

Connection note: This assumes MySQL is on localhost port 3306 with username root and a blank password. If your MySQL uses a password or a different port, update the connection settings.

Quick Revision: How to Run Each Program

- Q1, Q3, Q4, Q5, Q7, Q8 and Q9: save as .html and open in Chrome.
- Q2: save question2.html and style.css in the same folder; open the HTML file.
- Q6: install WordPress locally using XAMPP and a MySQL/MariaDB database.
- Q10, Q11 and Q12: save .php files in C:\xampp\htdocs\, start Apache, and open through http://localhost/filename.php. Q13 additionally requires MySQL and a database/table.
- If Bootstrap, AngularJS or jQuery does not load, check internet connectivity because these examples use CDN links.
- Database storage is not included in Q3 and Q8 because the supplied questions do not explicitly require it. Q13 demonstrates persistent storage using PHP and MySQL.

Important Exam Tips

- Use Save as type: All Files in Notepad to avoid accidentally saving files as .txt.
- PHP code will not execute by double-clicking the file; use localhost through XAMPP/WAMP.
- The Reset button clears the form controls; it does not delete records already stored in a database.
- For production systems, validate data on the server as well as in the browser and use prepared SQL statements for database operations.

Additional Notes: WordPress Resume Website Setup (Q6)

Aim: To create a two-page resume website using WordPress, PHP, MySQL and XAMPP.

Procedure

8. **Download WordPress:** Visit https://wordpress.org/download/ and download the WordPress ZIP file. Extract it.
9. **Create the website folder:** Open C:\xampp\htdocs, create a folder named resume, then copy all files and folders inside the extracted wordpress folder into C:\xampp\htdocs\resume. Ensure index.php is directly inside the resume folder.
10. **Start XAMPP:** Open XAMPP Control Panel and start Apache and MySQL. If MySQL fails because port 3306 is occupied, resolve the port conflict before continuing.
11. **Create the database:** Open http://localhost/phpmyadmin, click New, enter resume_db, and click Create.
12. **Run the installer:** Open http://localhost/resume. Select a language and enter the database name resume_db, username root, password blank only if the XAMPP root account has no password, database host localhost, and table prefix wp_. Click Submit and continue the installation.
13. **Set up the administrator:** Enter the site title My Resume Website, choose an administrator username and strong password, enter a valid email address, and click Install WordPress. Store the login details securely.
14. **Log in:** Open http://localhost/resume/wp-admin and log in with the administrator credentials.
15. **Create two pages:** Go to Pages → Add New Page. Create and publish Home (introduction, profile photo and short professional summary) and Resume (education, technical skills, projects and contact details).
16. **Choose a design:** Go to Appearance → Themes and activate a suitable theme. Use Appearance → Editor if available to customize the design and navigation.
17. **Add navigation and test:** Add Home and Resume links to the site navigation, publish the pages, and visit http://localhost/resume to check the website.

Result

A two-page resume website is created locally using WordPress and XAMPP.

Bro, in your practical document, Q12 is the PHP Calculator program, not the SOAP program. The calculator uses PHP and does not require MySQL. If your SOAP calculator is a separate question, follow the SOAP steps below.

How to run a SOAP program using XAMPP

Step 1: Start XAMPP

- Open XAMPP Control Panel.
- Start Apache.
- MySQL is not required for a basic SOAP calculator.

Step 2: Create the PHP file

1. Open `C:\xampp\htdocs`.
2. Create a file named `soap_server.php`.
3. Put your SOAP server code inside it.

Step 3: Check SOAP support

Open `C:\xampp\php\php.ini` in Notepad and find:

```
;extension=soap
```

Remove the starting semicolon:

```
extension=soap
```

Save the file and restart Apache.

Step 4: Run the program

Open your browser and visit:

```
http://localhost/soap_server.php
```