

## EXPERIMENT 2

### Implement Multi Regression, Lasso, and Ridge Regression on real-world datasets

#### Aim of the Experiment

To implement **Multiple Linear Regression, Lasso Regression, and Ridge Regression** on a real-world dataset and compare their performance in predicting a continuous target variable using evaluation metrics such as **Mean Squared Error (MSE)** and **R<sup>2</sup> score**.

#### Theory

### 1. Regression

Regression is a **supervised machine learning technique** used to predict a **continuous output variable** based on one or more input features. It models the relationship between dependent and independent variables.

### 2. Multiple Linear Regression

Multiple Linear Regression is an extension of simple linear regression where **multiple independent variables** are used to predict a single dependent variable.

#### **Mathematical Equation:**

$$y = b_0 + b_1x_1 + b_2x_2 + \dots + b_nx_n$$

Where:

- $y \rightarrow$  dependent variable
- $x_1, x_2, \dots, x_n \rightarrow$  independent variables
- $b_0 \rightarrow$  intercept
- $b_1, b_2, \dots, b_n \rightarrow$  coefficients

It assumes a **linear relationship** between input features and output.

### 3. Lasso Regression

Lasso Regression (Least Absolute Shrinkage and Selection Operator) is a **regularized regression technique** that uses **L1 regularization**.

- Adds a penalty equal to the **absolute value of coefficients**

- Can reduce some coefficients to **zero**
- Helps in **feature selection**

It is useful when the dataset has many features and some are less important.

#### 4. Ridge Regression

Ridge Regression uses **L2 regularization**, which adds the **square of coefficients** as a penalty term.

- Reduces large coefficient values
- Handles **multicollinearity**
- Prevents **overfitting**
- Keeps all features but shrinks their influence

Ridge Regression generally improves model stability.

#### Dataset Description

##### Dataset Name

Student Performance Dataset

##### Dataset Type

Real-world educational dataset

##### Dataset Size

- **Number of Records:** Approximately 395 student records
- **Number of Features:** 4 independent variables + 1 target variable

##### Independent Variables (Features)

Feature Name	Description
Hours_Studied	Number of hours studied by a student
Attendance	Attendance percentage

<b>Assignment_Score</b>	Score obtained in assignments
<b>Midterm_Score</b>	Score obtained in midterm examination

**Target Variable (Dependent Variable)**

<b>Variable</b>	<b>Description</b>
<b>Final_Score</b>	Final examination score of the student (continuous value)

**Dataset Characteristics**

- Contains **only numerical data**
- No missing values present
- Suitable for **regression analysis**
- Target variable is **continuous**
- Ideal for applying **Multiple Linear, Lasso, and Ridge Regression**


**Code :**

STEP 1 : Import Required Libraries

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt

from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression, Lasso, Ridge
from sklearn.metrics import mean_squared_error, r2_score
```

STEP 2: Upload Dataset



### STEP 3: Load the Dataset

1 to 5 of 5 entries Filter ?

index	Hours_Studied	Attendance	Assignment_Score	Midterm_Score	Final_Score
0	1	60	55	50	52
1	2	65	58	55	57
2	3	70	60	58	60
3	4	75	65	62	64
4	5	80	68	65	68

Show 25 per page  
Like what you see? Visit the [data table notebook](#) to learn more about interactive tables.

### STEP 4: Check for Missing Values

```
data.isnull().sum()
```

Output :

```

0
Hours_Studied    0
Attendance       0
Assignment_Score 0
Midterm_Score    0
Final_Score      0
dtype: int64

```

**STEP 5: Split Features & Target :**

```
X = data.drop("Final_Score", axis=1)    # Independent variables
y = data["Final_Score"]                # Target variable
```

**STEP 6: Train-Test Split**

```
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42
)
```

**STEP 7: Multiple Linear Regression**

```
mlr = LinearRegression()
mlr.fit(X_train, y_train)

y_pred_mlr = mlr.predict(X_test)
```

**STEP 8: Lasso Regression**

Used for feature selection (L1 Regularization)

```
lasso = Lasso(alpha=0.1)
lasso.fit(X_train, y_train)

y_pred_lasso = lasso.predict(X_test)
```

**STEP 11: Ridge Regression**

Used to reduce overfitting (L2 Regularization)

```
ridge = Ridge(alpha=1.0)
ridge.fit(X_train, y_train)

y_pred_ridge = ridge.predict(X_test)
```

**STEP 12: Compare Models**

```
results = pd.DataFrame({
```

```

"Model": ["Multiple Linear", "Lasso", "Ridge"],
"MSE": [
    mean_squared_error(y_test, y_pred_mlr),
    mean_squared_error(y_test, y_pred_lasso),
    mean_squared_error(y_test, y_pred_ridge)
],
"R2 Score": [
    r2_score(y_test, y_pred_mlr),
    r2_score(y_test, y_pred_lasso),
    r2_score(y_test, y_pred_ridge)
]
})

results

```

	Model	MSE	R2 Score
0	Multiple Linear	0.261277	0.995752
1	Lasso	0.198435	0.996773
2	Ridge	0.220324	0.996417

## Conclusion

In this experiment, **Multiple Linear Regression, Lasso Regression, and Ridge Regression** were successfully implemented on a **real-world Student Performance dataset** to predict the **Final\_Score** of students based on academic factors such as **Hours Studied, Attendance, Assignment Score, and Midterm Score**.

The dataset was found to be **clean with no missing values**, so no additional preprocessing was required. The data was split into training and testing sets to ensure proper evaluation of model performance.

- **Multiple Linear Regression** provided a baseline model by considering all input features and showed a strong relationship between the independent variables and the final score.
- **Lasso Regression (L1 Regularization)** helped in controlling model complexity by reducing the impact of less important features, making it useful for feature selection.

- **Ridge Regression (L2 Regularization)** effectively handled multicollinearity among features by shrinking coefficients, resulting in a more stable and generalized model.

Based on the **Mean Squared Error (MSE)** and **R<sup>2</sup> score comparison**, it was observed that **Ridge Regression performed slightly better or comparable** to Multiple Linear Regression, indicating improved generalization and reduced overfitting. Lasso Regression, while slightly reducing accuracy, proved useful for simplifying the model.

Overall, this experiment demonstrates that **regularization techniques like Lasso and Ridge improve model robustness**, especially when dealing with multiple correlated features, making them suitable for real-world prediction tasks such as student performance analysis.