

```
mysql> create database AirportManagement;  
Query OK, 1 row affected (0.07 sec)
```

```
mysql> use AirportManagement;  
Database changed
```

```
mysql> create table Airline(  
-> airline_id int,  
-> airline_name varchar(100),  
-> country varchar(50)  
-> );
```

```
Query OK, 0 rows affected (0.07 sec)
```

```
mysql> create table Flight(  
-> flight_id int,  
-> airline_id int,  
-> flight_number varchar(20),  
-> origin varchar(50),  
-> destination varchar(50),  
-> departure_time datetime,  
-> arrival_time datetime  
-> );
```

```
Query OK, 0 rows affected (0.09 sec)
```

```
mysql> create table Ticket(  
-> ticket_id int,  
-> flight_id int,  
-> ticket_price decimal(10,2),  
-> ticket_class varchar(20)  
-> );
```

```
Query OK, 0 rows affected (0.09 sec)
```

```
mysql> create table Passenger(  
-> passenger_id int,  
-> first_name varchar(50),  
-> last_name varchar(50),  
-> email varchar(100),  
-> age int,  
-> seat_number varchar(10),  
-> ticket_id int  
-> );
```

```
Query OK, 0 rows affected (0.09 sec)
```

```
mysql> insert into Airline(airline_id,airline_name,country)  
-> values  
-> (1,'SkyWinges','USA'),  
-> (2,'BlueBird Airways','UK'),  
-> (3,'Oceanic Air','Australia'),  
-> (4,'FalconFly','UAE'),  
-> (5,'GlobalJet','Germany');
```

```
Query OK, 5 rows affected (0.07 sec)
```

```

mysql> insert into Flight(flight_id,airline_id,flight_number,origin,destination,departure_time,arrival_time)
-> values
-> (1,1,'SW101','New York','Los Angeles','2025-08-01 08:00:00','2025-08-01 11:30:00'),
-> (2,2,'BB202','London','Paris','2025-08-02 09:00:00','2025-08-02 10:20:00'),
-> (3,3,'OA303','Sydney','Melbourne','2025-08-03 07:15:00','2025-08-03 08:45:00'),
-> (4,4,'FF404','Dubai','Mumbai','2025-08-04 14:00:00','2025-08-04 17:15:00'),
-> (5,5,'GJ505','Berlin','Rome','2025-08-05 10:00:00','2025-08-05 12:10:00');
Query OK, 5 rows affected (0.07 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> insert into Ticket(ticket_id,flight_id,ticket_price,ticket_class)
-> values
-> (1,1,199.99,'Economy'),
-> (2,2,89.50,'Business'),
-> (3,3,120.75,'Economy'),
-> (4,4,220.00,'First'),
-> (5,5,150.00,'Economy');
Query OK, 5 rows affected (0.07 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> insert into Passenger(passenger_id,first_name,last_name,email,age,seat_number,ticket_id)
-> values
-> (1,'John','Doe','john.doe@example.com',30,'12A',1),
-> (2,'Emily','Smith','emily.smith@example.com',27,'4B',2),
-> (3,'Carols','Garcia','carols.garcia@example.com',35,'8C',3),
-> (4,'aisha','Khan','aisha.khan@example.com',22,'1A',4),
-> (5,'Luca','Rossi','luca.rossi@example.com',40,'16D',5);
Query OK, 5 rows affected (0.04 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql> alter table Airline add rating decimal(3,1);
Query OK, 0 rows affected (0.09 sec)
Records: 0 Duplicates: 0 Warnings: 0

```

```
mysql>
mysql> alter table Passenger change seat_number seat_code;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual
  use near '' at line 1
mysql>
mysql>
mysql> alter table Passenger change seat_number seat_code varchar(10);
Query OK, 0 rows affected (0.04 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> alter table Ticket modify ticket_class varchar(50);
Query OK, 0 rows affected (0.07 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> alter table Passenger drop age;
Query OK, 0 rows affected (0.08 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> alter table Flight add status varchar(20);
Query OK, 0 rows affected (0.08 sec)
Records: 0  Duplicates: 0  Warnings: 0
```

```
mysql> create database Bookshop;  
Query OK, 1 row affected (0.07 sec)
```

```
mysql> use Bookshop;  
Database changed
```

```
mysql> create table Book(  
    -> ISBN varchar(20),  
    -> Name varchar(50),  
    -> Price int,  
    -> PublishDate date  
    -> );  
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> create table Author(  
    -> authorID int,  
    -> name varchar(50),  
    -> biography text  
    -> );  
Query OK, 0 rows affected (0.09 sec)
```

```
mysql> create table Customers(  
    -> customerID int,  
    -> name varchar(50),  
    -> email varchar(60),  
    -> address varchar (100)  
    -> );  
Query OK, 0 rows affected (0.10 sec)
```

```
mysql> create table Orders(  
    -> orderID int,  
    -> customerID int,  
    -> OrderDate date  
    -> );  
Query OK, 0 rows affected (0.10 sec)
```

```
mysql> create table Review(  
    -> reviewID int,  
    -> rating varchar(20),  
    -> comment text  
    -> );  
Query OK, 0 rows affected (0.09 sec)
```

```
-- comment text  
-> );
```

Query OK, 0 rows affected (0.09 sec)

```
mysql> insert into Book(ISBN,Name,Price,PublishDate)  
-> values  
-> ('0','beast',1000,'2025:08:22'),  
-> ('1','quest',2000,'2025:09:22'),  
-> ('2','doowa',2500,'2025:09:10'),  
-> ('3','bambo',2600,'2024:07:10'),  
-> ('4','strike',4600,'2022:03:14'),  
-> ('5','blood',1600,'2021:06:14'),  
-> ('6','nuwara',600,'2026:01:27'),  
-> ('7','ella',2600,'2021:12:24');
```

Query OK, 8 rows affected, 8 warnings (0.06 sec)

Records: 8 Duplicates: 0 Warnings: 8


```
mysql> insert into Author(authorID,name,biography)
-> values
-> (100,'yeha','best in the world'),
-> (101,'john','good author'),
-> (102,'wick','new author'),
-> (103,'sadewni','best poet'),
-> (104,'kash','bad author'),
-> (105,'tharu','karate expert'),
-> (106,'charith','normal writer');
Query OK, 7 rows affected (0.07 sec)
Records: 7  Duplicates: 0  Warnings: 0
```

```
mysql> insert into Customer(customerID,name,email,address)
-> values
-> (1,'kashmika','kash@gmail.com','112 panadura'),
-> (2,'nihara','niha@gmail.com','100 panadura'),
-> (3,'fernando','fer@gmail.com','105 panadura'),
-> (4,'yehashi','yeha@gmail.com','112 kaluthara'),
-> (5,'poorwa','poorwa@gmail.com','100 kaluthara'),
-> (6,'sadewni','sadewni@gmail.com','105 kaluthara'),
-> (7,'tharushka','tharu@gmail.com','105 nuwara'),
-> (8,'thadi','thadi@gmail.com','108 nuwara');
ERROR 1146 (42S02): Table 'bookshop.customer' doesn't exist
```

```
mysql>
```

```
mysql>
```

```
mysql> insert into Customers(customerID,name,email,address)
-> values
-> (1,'kashmika','kash@gmail.com','112 panadura'),
-> (2,'nihara','niha@gmail.com','100 panadura'),
-> (3,'fernando','fer@gmail.com','105 panadura'),
-> (4,'yehashi','yeha@gmail.com','112 kaluthara'),
-> (5,'poorwa','poorwa@gmail.com','100 kaluthara'),
-> (6,'sadewni','sadewni@gmail.com','105 kaluthara'),
-> (7,'tharushka','tharu@gmail.com','105 nuwara'),
-> (8,'thadi','thadi@gmail.com','108 nuwara');
Query OK, 8 rows affected (0.07 sec)
Records: 8  Duplicates: 0  Warnings: 0
```

```
mysql> insert into Orders(orderID,customerID,OrderDate)
-> values
-> (201,1,'2025:01:01'),
-> (202,2,'2025:02:03'),
-> (203,3,'2026:02:03'),
-> (204,4,'2026:02:04'),
-> (205,5,'2026:03:04'),
-> (206,6,'2022:03:04'),
-> (207,7,'2022:05:14'),
-> (208,8,'2026:02:14');
```

Query OK, 8 rows affected, 8 warnings (0.07 sec)

Records: 8 Duplicates: 0 Warnings: 8

```
mysql> insert into Review(reviewID,rating,comment)
-> values
-> (301,'good','good book'),
-> (302,'normal','normal book'),
-> (303,'best','best book'),
-> (304,'good','good adventure book'),
-> (305,'happy','good horror book'),
-> (306,'normal','sql book'),
-> (307,'best','best to learn'),
-> (308,'worst','too scary');
```

Query OK, 8 rows affected (0.07 sec)

Records: 8 Duplicates: 0 Warnings: 0

```
mysql> alter table Book add Genre varchar(50);
```

Query OK, 0 rows affected (0.08 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
mysql> alter table Customers add Phone varchar(15);
```

Query OK, 0 rows affected (0.09 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
mysql>  
mysql> alter table Orders change OrderDate PurchaseDate date;  
Query OK, 0 rows affected (0.08 sec)  
Records: 0 Duplicates: 0 Warnings: 0
```

```
mysql>  
mysql>  
mysql>  
mysql>  
mysql>  
mysql> create database puffycake;  
Query OK, 1 row affected (0.01 sec)
```

```
mysql> use puffycake;  
Database changed  
mysql> create table customer(  
-> customerID int,  
-> FirstName varchar(50),  
-> LastName varchar(60),  
-> email varchar(70),  
-> phone int,  
-> address varchar(100),  
-> city varchar(100),  
-> CreatedAt varchar(50)  
-> );  
Query OK, 0 rows affected (0.02 sec)
```



```
mysql>
```

```
mysql>
```

```
mysql> create table orders(
```

```
    -> orderID int,
```

```
    -> customerID int,
```

```
    -> OrderDate date,
```

```
    -> OrderTotal int,
```

```
    -> PaymentMethod varchar(50),
```

```
    -> OrderStatus varchar(60),
```

```
    -> notes text
```

```
    -> );
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> insert into customer(customerID,FirstName,LastName,email,phone,address,city,CreatedAt)
-> values
-> (101,'kashmika','fernando','kash@gmail.com',00000,'112 panadura','panadura','online'),
-> (102,'yehashi','sadewni','yeha@gmail.com',00001,'112 panadura','panadura','shop'),
-> (103,'tharu','fernando','tharu@gmail.com',00002,'112 galle','galle','shop'),
-> (104,'charith','fernando','chari@gmail.com',00003,'114 kaluthara','kaluthara','online'),
-> (105,'john','xavier','john@gmail.com',00004,'114 nuwara','nuwara','online'),
-> (106,'kashmi','fernando','kashmi@gmail.com',00005,'10 panadura','panadura','shop'),
-> (107,'dexter','mark','dexter@gmail.com',00006,'1 colombo','colombo','shop'),
-> (108,'brock','lesnar','brock@gmail.com',00007,'1 paris','london','shop'),
-> (109,'randy','orton','randy@gmail.com',00008,'1 mawatha','los vegas','shop'),
-> (110,'seth','rollins','seth@gmail.com',00009,'9 peta','sarngburg','online');
Query OK, 10 rows affected (0.01 sec)
Records: 10  Duplicates: 0  Warnings: 0
```