Survey Forms (Google Forms Clone)

Build Guide: Project Creation, File Map, Integration and Requirements

Written by Kasinadh Sarma

13 October 2026

Contents

1 Overview **3**

2 Requirements **3**

2.1 Software . . . 3

2.2 Packages . . . 3

2.3 Why these libraries . . . 4

2.4 Accounts and configuration . . . 5

3 How the Layers Connect **6**

4 Step-by-Step Build **7**

5 What Was Verified **12**

6 Known Limits **12**

7 Planned Extensions (Documentation Only) **13**

7.1 Delete button . . . 13

7.2 Form editing . . . 14

7.3 File limits . . . 16

7.4 Sync . . . 17

7.5 Rate limiting . . . 19

7.6 Suggested order . . . 20

8 Database Schema (Mermaid ER Diagram) **21**

8.1 Firestore layout . . . 21

9 System Architecture (Mermaid Flowchart) **23**

9.1 Architecture with the planned extensions . . . 25

10 Request Flows (Mermaid Sequence Diagrams) 27

10.1 Submitting a response . . . 27

10.2 Reading with fallback, and repairing with sync . . . 28

11 Development Workflow (Mermaid Flowcharts) 29

11.1 How the project is built and checked . . . 29

11.2 Roadmap for the planned extensions . . . 31

12 Imperative and Declarative Programming: Where Each Is Used 32

12.1 Where the project is declarative . . . 32

12.2 Where the project is imperative . . . 33

12.3 Where the two meet . . . 34

12.4 Pure functions . . . 34

12.5 Planned extensions . . . 37

13 Source Code 38

13.1 Configuration . . . 38

13.2 Shared API schemas . . . 40

13.3 Server foundations . . . 43

13.4 Repository layer . . . 45

13.5 API routes . . . 53

13.6 Client library . . . 57

13.7 Components . . . 61

13.8 Pages . . . 70

Appendix: Mermaid Sources 72

1 Overview

This guide explains, in order, how to create the project, which files are created or changed at each step, and how the layers connect. The application lets a user build a survey, share a public link, collect validated responses, and view the submissions.

Stack. Next.js (App Router), Tailwind CSS v4, react-hook-form, Zod, `@better-fetch/fetch`, Hono (inside a Next.js route handler), Cloud Firestore (through the Firebase Admin SDK) as the primary database and the store for uploaded files, and Prisma 7 with PostgreSQL as a local-development-only copy.

Project layout. The project uses the root `app/` layout (no `src/` folder). Section 5 says exactly what was checked and what was not.

Core idea. The API Zod schemas, kept one file per concern in `lib/schemas/`, are imported by both the browser and the API. The same rules therefore run in the form, in the Hono validator, and before anything reaches a database.

Decisions in this version.

- **Hono, not Elysia.** Hono runs inside a Next.js route handler, giving one project and one deployment.
- **Firestore is the source of truth; Postgres is a local-only copy.** Every write goes to Firestore first. Only when `NODE_ENV` is not `production` and `DATABASE_URL` is set is it also copied to Postgres through Prisma under the same ids. If Firestore fails locally, reads fall back to Postgres; in production they fail. Section 3 explains the design and its limits.
- **Files live in Firestore, not in a storage bucket.** A new Firebase bucket may need a paid plan, so uploaded files are stored as documents in a Firestore collection. This caps a file at 700 KB (Firestore documents are limited to 1 MiB). Moving to a real bucket later changes only `lib/server/repo/files.ts` and the two file routes.

2 Requirements

2.1 Software

Requirement	Version	Purpose
Node.js	22 or newer (24.18 used here)	Runtime
npm	10 or newer (11.16 used here)	Package manager
PostgreSQL (optional)	Local or Docker	Local development copy used by Prisma; not used in production
Firebase project	Cloud Firestore enabled, Admin SDK service account	Primary database and file store
Git	Any recent version	Version control

2.2 Packages

These are the versions installed in this project on 13 October 2026, read from `node_modules`.

Package	Version	Role
`next`	16.4.0	Framework (Turbopack, Cache Components on by default)
`react`, `react-dom`	19.3.0	UI
`tailwindcss`, `@tailwindcss/postcss`	4.3.3	Styling (v4, CSS-first)
`postcss`	8.5.30	Used by the Tailwind plugin
`zod`	4.6.7	Shared schemas and types
`react-hook-form`	7.90.0	Form state
`@hookform/resolvers`	5.9.1	Connects Zod to react-hook-form
`@better-fetch/fetch`	1.3.2	Typed HTTP client
`hono`	4.13.13	API framework
`@hono/zod-validator`	0.9.1	Request validation middleware
`@prisma/client`, `prisma`	7.10.0	Database client, migrations and generation
`@prisma/adapter-pg`, `pg`	7.10.0, 8.23.1	Postgres driver adapter (required by Prisma 7)
`firebase-admin`	14.5.0	Firestore access from the server
`dotenv`	18.0.7	Loads `.env` for `prisma.config.ts`
`typescript`, `eslint`, `prettier`	5.9.3, 9.39.5, 3.9.10	Types, lint, formatting

2.3 Why these libraries

Each package is here for one job, and the list is kept short on purpose.

Package	Why it is used
`next`, `react`, `react-dom`	One framework for pages, routing and server rendering, and the host for the API route handler.
`tailwindcss`, `@tailwindcss/postcss`, `postcss`	Utility-first styling without a separate stylesheet system. v4 is CSS-first, and the PostCSS plugin keeps styling independent of the bundler.
`zod`	One schema per concern, shared by the browser and the API, so the form, the validator and the database layer apply the same rules and the TypeScript types are inferred from them.
`react-hook-form`	Fast form state for the survey builder and response forms, with few re-renders.
`@hookform/resolvers`	Lets react-hook-form use the Zod schemas directly instead of duplicating rules.
`@better-fetch/fetch`	A TypeScript-first wrapper over native `fetch`: typed responses and one error shape, without the weight of Axios.
`hono`	A small, fast web framework that runs inside a Next.js route handler, so the API ships in the same project and deployment.
`@hono/zod-validator`	Validates request bodies, params and queries in Hono with the shared Zod schemas.
`@prisma/client`, `prisma`	A type-safe database client generated from the schema, plus migrations.
`@prisma/adapter-pg`, `pg`	Prisma 7 requires a driver adapter; this is the node-postgres one for PostgreSQL.
`firebase-admin`	Server-side access to Firestore, used as the live mirror and file store.
`dotenv`	Loads `.env` for `prisma.config.ts`, which Next.js does not do.
`typescript`, `eslint`, `prettier`	Static types, lint rules and consistent formatting.

Prisma versions must match. The npm `latest` tag of `prisma` pointed to an 8.0 release candidate while `@prisma/client` was 7.10.0. The install commands in Step 2 pin the three Prisma packages to 7.10.0. Change all three together when you upgrade.

2.4 Accounts and configuration

- A PostgreSQL connection string (`DATABASE_URL`).
- A Firebase project with a Cloud Firestore database (the `(default)` database; the free Spark plan is enough).
- A service account key for the Firebase Admin SDK: project id, client email and private key (Firebase console, Project settings, Service accounts, Generate new private key).
- A random token for the sync endpoints (`SYNC_TOKEN`).

3 How the Layers Connect

Layer	What it does
`components/`	Forms, tables and inputs. Validate with the shared Zod schemas before sending.
`lib/fetch.ts`	Typed client; every endpoint has input, output, params and query schemas.
`lib/server/routes/`	Hono routes. Validate again on the server; return one error shape.
`lib/server/repo/forms.ts`, `submissions.ts`	The only entry points the routes use. They combine the two databases.
`lib/server/repo/postgres/`	Prisma code: the local development copy.
`lib/server/repo/firestore/`	Firestore code: the primary store.
`lib/server/repo/files.ts`	Uploaded files, stored in Firestore.
`lib/server/repo/sync.ts`	Compares Firestore with the local Postgres copy and refreshes it.

Writes. `createForm`, `deleteForm` and `createSubmission` run in Firestore first, with ids generated on the server. Only when local Postgres is enabled (`NODE_ENV` is not `production` and `DATABASE_URL` is set) does the same data go to Postgres, under the same ids. A failure of the Postgres write is logged and does not fail the request. Deleting a form removes its Firestore submissions as well.

Reads. Reads come from Firestore. If Firestore throws and local Postgres is enabled, the same read runs against Postgres; in production the error is returned. A "not found" from Firestore is a real answer and is not retried. Timestamps stored by hand in the Firebase console are converted to ISO strings when read.

Firestore layout. A form is one document in `forms/{id}` with its questions embedded and a `responseCount`. Each submission is a document in the subcollection `forms/{id}/submissions/{id}`. Uploaded files are documents in `files/{id}`.

Counter. When a submission is written, a transaction writes the document and increments `responseCount` only if the document did not exist, so writing the same submission twice counts once.

Limits of this design.

- Sync is one-way, from Firestore to local Postgres. Edits made directly in local Postgres are overwritten by the next sync.
- Postgres is never required: if it is down locally, requests still succeed through Firestore.
- Syncing is manual (an endpoint you call); there is no scheduler.

4 Step-by-Step Build

Step 1: Create the Next.js project with Tailwind v4

```
npx create-next-app@latest survey-forms --ts --tailwind --eslint --app --no-src-dir --use-npm --
    import-alias "@/*"
cd survey-forms
```

Files created by the generator: `package.json`, `tsconfig.json`, `next.config.ts`, `eslint.config.mjs`, `AGENTS.md`, `README.md`, and the folders `app/` and `public/`.

No `src/` folder. Every folder in this guide (`app/`, `components/`, `lib/` (with `lib/server/` and `lib/schemas/` inside), `prisma/`, `generated/`) sits at the project root. The `@/` alias points to the root through `"paths": { "@/*": ["./*"] }` in `tsconfig.json`, which the starter writes for you.

Tailwind v4. `app/globals.css` begins with `@import "tailwindcss";`. There are no `@tailwind` directives and no `tailwind.config.js`. Create `postcss.config.mjs` (listing in Section 13) so the styling does not depend on the starter's Turbopack rule.

Cache Components. The starter sets `cacheComponents: true`. Two rules follow, and the code already applies both. A route handler must not export `runtime`. Any page that awaits `params`, and any client component that creates random ids (react-hook-form's field array does), must sit inside a `Suspense` boundary, or `next build` fails.

Step 2: Install dependencies

Run each command on one line.

```
npm i zod react-hook-form @hookform/resolvers @better-fetch/fetch hono @hono/zod-validator
    firebase-admin pg dotenv @prisma/client@7.10.0 @prisma/adapter-pg@7.10.0
npm i -D prisma@7.10.0 @types/pg prettier
npm i tailwindcss @tailwindcss/postcss postcss
```

Step 3: Configure environment variables, Firestore and Git

Files created: `.env` (never committed) and `.env.example` (committed). Next.js loads `.env`; the Prisma CLI loads it through `dotenv`. Generate the token with `openssl rand -hex 24`.

Firebase values. Copy `project_id`, `client_email` and `private_key` from the downloaded service account JSON into `FIREBASE_PROJECT_ID`, `FIREBASE_CLIENT_EMAIL` and `FIREBASE_PRIVATE_KEY`. Keep the private key in double quotes on one line with the line breaks written as `\n`; `lib/server/firestore.ts` turns them back into real line breaks. Then delete the JSON file or keep it outside the project: it grants full admin access.

Create the database. In the Firebase console open Firestore and click Create database, accept the `(default)` database and choose a region. Security rules do not matter for this app, because the Admin SDK bypasses them and no browser talks to Firestore.

File updated: `.gitignore`. The starter already ignores `.env*`, which also hides the example file. Add:

```
!.env.example
/generated/prisma
*-firebase-adminsdk-*.json
serviceAccount*.json
```

Step 4: Define the database with Prisma

Files created: `prisma.config.ts` and `prisma/schema.prisma`. Prisma 7 reads the database URL from `prisma.config.ts`, writes the client to `generated/prisma`, and needs the `pg` driver adapter at runtime.

Model	What it represents	Why it is a separate model
`Form`	One survey (title, description)	Parent record; owns questions and submissions
`Question`	One prompt in a form	Needs its own type, options, order and required flag, and answers point to it
`Submission`	One respondent's attempt	Groups answers so each response can be counted, paged and deleted as a unit
`Answer`	One value for one question	Joins a submission to a question

```
npx prisma migrate dev --name init
npx prisma generate
```

Application code imports the client as `@/generated/prisma/client`. Do not drop or reset the database schema on a machine that holds real forms; a reset deletes them, but Firestore is the source of truth, so `POST /api/sync` restores the local copy.

Step 5: Server foundations

- `lib/server/env.ts`: validates the environment with Zod. Two lazy getters keep the database variables apart from the Firebase ones, so forms keep working when Firebase is not configured.
- `lib/server/db.ts`: one lazily created Prisma client (`getPrisma`) with the Postgres adapter, so production without `DATABASE_URL` never creates it, kept on `globalThis` so hot reloading does not open new pools.
- `lib/server/firestore.ts`: starts the Firebase Admin app once (reused if it exists) and returns the Firestore database.
- `lib/server/errors.ts`: one error body shape, `{ error: { code, message } }`.
- `lib/server/methods.ts`: `methodNotAllowed`, the 405 and `Allow` helper used by every route file.
- `lib/server/validate.ts`: a wrapper around `zValidator` that returns the same 400 body with the list of issues.

Step 6: Write the schemas, one file per concern

- `lib/schemas/question.ts`: question types, the question schema and `isChoiceType`.
- `lib/schemas/form.ts`: create-form payload, form response, dashboard summary and the id parameter.
- `lib/schemas/upload.ts`: allowed file types, the 700 KB limit, the pattern a file id must match, and the upload result.
- `lib/schemas/submission.ts`: the answers payload, the page of submissions and `buildAnswerSchema`.

- `lib/schemas/builder.ts`: client-only, the one file in `lib/schemas/` the server never imports.

`z.email()` and `z.iso.date()` are Zod 4 forms; with an older Zod use `z.string().email()` and `z.string().date()`.

Step 7: Build the repository layer

- `lib/server/repo/postgres/forms.ts` and `submissions.ts`: all Prisma calls, used only locally. Forms are parsed with `formSchema` (the `order` column is mapped to `position`). `mirrorForm` and `mirrorSubmission` copy Firestore data in under the same ids and are safe to repeat; each answer is stored as JSON in the `value` column.
- `lib/server/repo/firestore/forms.ts` and `submissions.ts`: the primary writes and reads (ids are generated here), recursive delete, and the counter transaction described in Section 3.
- `lib/server/repo/dual.ts`: `mirrorSafely` (skipped outside local development; log, do not fail) and `readWithFallback`.
- `lib/server/repo/forms.ts` and `submissions.ts`: the facade the routes import. Firestore first, then the local Postgres copy; Firestore read first, then the local fallback.
- `lib/server/repo/files.ts`: save, load and existence-check for uploaded files.
- `lib/server/repo/sync.ts`: `getSyncStatus` and `syncAll`.

Step 8: Build the Hono API

Method	Path	Input	Result
GET	`/api/forms`	none	200, forms with counts
POST	`/api/forms`	create-form payload	201, the form; 400
GET	`/api/forms/:id`	none	200; 404
DELETE	`/api/forms/:id`	none	204; 404
POST	`/api/forms/:id/submissions`	answers, checked against that form's questions	201, `{ id }`; 400; 404
GET	`/api/forms/:id/submissions`	`?page&limit`	200, one page; file answers are download paths
POST	`/api/files`	multipart field `file`	201, `{ id }`; 400
GET	`/api/files/:id`	none	200, the file as a download; 404
GET	`/api/sync/status`	bearer token	200, comparison of both databases; 401
POST	`/api/sync`	bearer token	200, what was copied; 401

405 for every other method. Build this once, then reuse it on every path.

1. Add a small helper in `lib/server/methods.ts`, `methodNotAllowed(app, path, allowedMethods)`. It builds the `Allow` value from the allowed methods plus `OPTIONS`, registers an `OPTIONS` handler that answers 204 with that header, and registers `app.all(path, ...)` that answers 405 with the `Allow` header and the usual error body, code `method_not_allowed`.

2. Call it at the end of each route file, after the real handlers, because Hono runs handlers in the order they were registered. Pass the methods that path really supports, for example `["GET", "POST"]` for `/api/forms`. `HEAD` is answered through `GET` automatically.
3. In `lib/server/app.ts` add `app.notFound(...)` for a JSON 404 and `app.onError(...)` for a generic 500 that logs the real error and never sends it to the client.
4. Check it: `curl -i -X DELETE /api/forms` should return 405 with `Allow: GET, POST, OPTIONS`, and an unknown path should return the JSON 404.

Error bodies look like `{ error: { code, message, issues? } }`.

Submissions. The route builds the answer schema from the form's own questions on every request, validates the body with it, checks that every file answer is the id of a file this app stored, and only then saves. A body that is not JSON becomes `null` and fails validation with a 400.

Files. The upload route re-checks type and size on the server, because the browser check can be skipped. Downloads are sent as attachments with `X-Content-Type-Options: nosniff`, so an uploaded file is never run as a page on this site.

Sync routes. They can rewrite a whole database and reveal counts, so they answer 401 unless the request carries `Authorization: Bearer <SYNC_TOKEN>`. With no token configured they stay closed.

Step 9: Mount Hono inside Next.js

`app/api/[[...route]]/route.ts` exports GET, POST, PUT, PATCH, DELETE and OPTIONS, all handled by the Hono app. All methods are exported on purpose: Next.js answers an unexported method with its own empty 405, while Hono answers with the JSON 405 and the `Allow` header. There is no `runtime` export, because Cache Components rejects it.

Step 10: Create the typed HTTP client and class patterns

`lib/fetch.ts` lists every JSON endpoint with its schemas, so a mistyped URL or wrong body is a type error and every response is validated. `getErrorMessage` reads the server's error message. File upload uses a plain `fetch` with `FormData` because a multipart body cannot be described by a Zod input schema; its response is still parsed with a schema. `lib/useLoad.ts` runs an async loader and reports loading, error or data. `lib/responsive/pattrens/forms.ts` holds every Tailwind class string, one object per component; components import their object as `p` and write `className={p.input}`. The folder keeps the spelling `pattrens` used in your other projects.

Step 11: Build the frontend

File	Responsibility
`app/page.tsx`	Dashboard: "New form" button and the list of forms.
`app/forms/new/page.tsx`	Builder page; the builder sits inside `Suspense`.
`app/f/[formId]/page.tsx`	Public survey page; params are read inside `Suspense`.
`app/forms/[id]/responses/page.tsx`	Responses page; params are read inside `Suspense`.
`app/layout.tsx`	Root layout. `<body>` has `suppressHydrationWarning` because browser extensions such as Grammarly add attributes before React loads.
`components/FormBuilder.tsx`	Create a form: react-hook-form with a field array and `builderFormSchema`.
`components/OptionsEditor.tsx`	Choices of one question: one input per option, add and remove, and a Yes / No preset.
`components/QuestionField.tsx`	One input per question type.
`components/FileUploadField.tsx`	Checks the file, uploads it to `/api/files`, stores the returned id.
`components/SurveyForm.tsx`	Fills in a survey with a schema built from its questions, then submits.
`components/SurveyLoader.tsx`	Loads a form for the public page.
`components/FormList.tsx`	Dashboard list with links to the survey and its responses.
`components/ResponsesView.tsx`	Table with one column per question and paging; file answers are links.

Step 12: Verify

```
npx prettier --check .
npx tsc --noEmit
npx eslint .
npm run build
npm run dev
```

Add a `.prettierignore` listing `.next`, `.agents`, `.claude`, `generated`, `node_modules` and `package-lock.json` so Prettier skips generated files. Do not run `npm run build` while `npm run dev` is serving the same folder: the build replaces the `.next` directory and can stop the dev server.

Then test by hand: create a form with one question of each type, open its public link, submit an invalid answer (an error appears next to that question), submit a valid one, and open the responses page.

Step 13: Operate the two databases

```
curl -H "Authorization: Bearer $SYNC_TOKEN" localhost:3000/api/sync/status
curl -X POST -H "Authorization: Bearer $SYNC_TOKEN" localhost:3000/api/sync
```

`status` lists form ids missing from Postgres, ids that exist only in Postgres, and both submission counts; `inSync` is true only when all of these match. Comparing ids matters: counts alone say "in sync" when one form was deleted and another added. `POST /api/sync` copies every form and

submission from Firestore into local Postgres (rows are upserted, so repeating it is safe) and removes Postgres forms that no longer exist in Firestore. Both endpoints return an error when local Postgres is disabled. Run it after resetting your local database or when the server log shows "Local Postgres mirror failed".

5 What Was Verified

Checked in this project:

- `prettier -check`, `tsc -noEmit`, `eslint .` and `npm run build` all pass.
- API, against a running dev server with a real Postgres (Docker) and a real Firestore database: creating forms; rejecting a choice question with one option; rejecting invalid answers with one message per field; saving a valid submission and listing it with numbers stored as numbers; dashboard counts; 404 and 405 bodies.
- Files: upload of a text file, download as an attachment with `nosniff`, rejection of a disallowed type and of an 800 KB file, rejection of a malformed and of an unknown file id on submit, acceptance of a real id.
- Sync: new writes appear in both databases with equal counts; a form deleted from Firestore and a stray form added were both reported and repaired; deleting a form removes it from both; with the Postgres container stopped, the form list, a form and its submissions were still served from Firestore, and the databases matched again after Postgres returned.
- Browser: the builder creates a multi-choice form using the Yes / No preset; the public survey page renders the question and options; the hydration warning caused by a browser extension no longer shows.

Not checked:

- A full click-through of every question type in the browser (date and number inputs, the file input and the validation messages shown next to fields). They were checked through the API and the shared schemas only.
- The "Firestore mirror failed" path with a real Firestore error. Drift was created by editing Firestore by hand, not by a failing write.
- Deployment, concurrent writers, large data volumes, and a Firebase Storage bucket (not used).

6 Known Limits

- **No login.** Anyone with a form link can answer it, and the forms list, responses and file downloads need no sign-in. File ids are random and unguessable, but the responses endpoint returns them.
- **File size.** Files are limited to 700 KB because they are stored inside Firestore documents. Photos and short PDFs fit; larger files need a real bucket.
- **Orphaned files.** Deleting a form does not delete the files its answers pointed to.
- **One-way sync and manual repair**, as described in Section 3.
- **No Delete button.** Forms can only be deleted through the API.

7 Planned Extensions (Documentation Only)

This section describes how to close five gaps from the previous section. **None of it is implemented or tested.** It names the files to create or change, the rules to follow and the checks to run, so the work can be done step by step later. Names, paths and conventions are the same as in the rest of this guide.

Extension	Gap it closes	Main files
Delete button	Forms can only be deleted through the API	`components/DeleteFormButton.tsx`, `components/FormList.tsx`, `lib/fetch.ts`
Form editing	A form cannot be changed after it is created	`app/forms/[id]/edit/page.tsx`, `components/FormBuilder.tsx`, `lib/server/routes/forms.ts`
File limits	Files are capped at 700 KB and are left behind after a delete	`lib/server/repo/files.ts`, `lib/schemas/upload.ts`
Sync	Repair is manual and copies everything	`prisma/schema.prisma`, `lib/server/repo/outbox.ts`, `lib/server/routes/sync.ts`
Rate limiting	Any client can send unlimited requests	`lib/server/rateLimit.ts`, `lib/server/app.ts`

Read this first: login. The delete and edit API calls are open to anyone who can reach the server, with or without a button in the screen. A button makes them easier to use, not easier to abuse. Before the delete button and form editing go live, add a login and make the owner of a form the only person who can change or delete it. This needs a `userId` on `Form`, a check in every write route, and a session that the routes can read. It is a separate piece of work and is not described here.

7.1 Delete button

What already exists. `DELETE /api/forms/:id` returns 204, or 404 when the form is missing, and removes the form from Postgres (questions, submissions and answers cascade) and from Firestore. Only the screen is missing.

Files.

File	Action	Change
`components/DeleteFormButton.tsx`	create	Button with a two-step confirmation and its own loading and error state
`components/FormList.tsx`	update	Show the button on every row and remove the row after success
`lib/fetch.ts`	update	Add the `DELETE` endpoint with params and an output schema that accepts an empty body
`lib/responsive/pattrens/forms.ts`	update	Add a `deleteButtonPatterns` object for the button and the confirm row
`lib/server/repo/forms.ts`	update	Also delete the files the form's answers point to (see Section 7.3)

Rules.

1. **Confirm inside the page.** The first click turns the button into "Delete this form and its N responses? Yes / Cancel". Do not use `window.confirm`; it blocks the browser and cannot be styled with the patterns file. The response count is already in the list data.
2. **Disable while waiting.** The button is disabled and shows "Deleting..." until the request ends, so a double click sends one request.
3. **Treat 404 as success.** If another tab already deleted the form, remove the row and show nothing.
4. **Empty body.** A 204 has no body, so the client schema for this endpoint must accept an empty response. Without that, the client reports a validation error for a delete that worked.
5. **Update the list from the result.** Remove the row from the list state after a 204 or 404 instead of reloading the whole list. On any other error, keep the row and show the message from `getErrorMessage`.

Check. Delete a form that has a file answer. The row disappears, `GET /api/forms/:id` returns 404, `GET /api/files/:id` for its file returns 404, and the Firestore `forms/{id}` document and its `submissions` subcollection are gone.

7.2 Form editing

The hard part. Answers point to questions by id. If an edit replaced all questions with new rows, every old answer would lose its question. The design therefore keeps question ids stable and treats an edit as a set of per-question changes.

API. `PUT /api/forms/:id` with a new `updateFormSchema`: the same fields as `createFormSchema`, but each question may carry an `id`. The 405 list for `/:id` becomes `GET, PUT, DELETE`.

Rules for each question in the payload.

Case	What happens
Has an `id` that belongs to this form	Updated in place: label, required, options and order may change.
Has no `id`	Created as a new question.
Has an `id` from another form	Rejected with a 400. Check the id against the form's own questions.
Existing question missing from the payload	Deleted, and its answers cascade. If the form has responses, the screen must warn first, and the server must require `confirmRemoval: true` in the body, otherwise it answers 409.
Type changed on a question that has answers	Rejected with a 409. The type is locked once the question has an answer; to change it, delete the question and add a new one.
Option removed that existing answers use	Allowed, but the old answers keep their stored text. The responses table shows them as they were saved. State this in the screen.

Files.

File	Action	Change
`lib/schemas/form.ts`	update	`updateFormSchema` and its type; `id` is optional on each input question
`lib/server/repo/postgres/forms.ts`	update	`updateForm` inside one `prisma.$transaction`: update the form, update or create each question, delete the removed ones, and renumber `order`
`lib/server/repo/firestore/forms.ts`	reuse	`mirrorForm` already replaces the embedded question list; pass the stored response count so the counter is kept
`lib/server/repo/forms.ts`	update	`updateForm`: Postgres first, then `mirrorSafely`
`lib/server/routes/forms.ts`	update	`PUT /:id`, validated with the param and json validators; widen the 405 list
`lib/fetch.ts`	update	`PUT` endpoint with input and output schemas
`components/FormBuilder.tsx`	update	Accept an optional `initialForm`; in edit mode start from it, keep each question's `id` in the field array, and submit with `PUT`
`components/QuestionField.tsx`	none	Not used by the builder
`app/forms/[id]/edit/page.tsx`	create	Loads the form inside `Suspense`, then renders the builder in edit mode
`components/FormList.tsx`	update	"Edit" link next to "Responses"

Notes.

- **One transaction.** Do the whole update in one database transaction so a failure part-way leaves the old form intact.
- **Field array keys.** In react-hook-form, use `keyName` or a separate field for the `id`, because `useFieldArray` adds its own `id` to every item by default.
- **Old responses.** The responses table builds its columns from the current questions, so a deleted question's column disappears and its stored answers are no longer shown.
- **Concurrent edits.** Two editors saving at once will overwrite each other. A simple guard is an `updatedAt` value sent back with the edit; the server answers 409 when it no longer matches.

Check. Create a form, submit two responses, then edit: rename a question, add one, remove one, and try to change a type that has answers (expect 409). Open the responses page and confirm the old answers are still attached to the renamed question.

7.3 File limits

Why the limit is 700 KB. A file is stored as base64 text inside one Firestore document. Base64 adds about one third, and a document may not exceed 1 MiB, so 700 KB of file is about 950 KB of text plus the name and type. Raising the number in `lib/schemas/upload.ts` alone would make saves fail.

Options.

Option	How it works	Gain	Cost
Chunks in Firestore	Split the bytes into pieces of about 500 KB, each its own document under `files/{id}/chunks/{n}`	Several MB, no new service	More reads per download; the API still carries every byte
Cloud Storage bucket	Server signs a short-lived upload URL; the browser uploads straight to the bucket	Tens of MB; the API never handles file bytes	A bucket (the project may need a paid plan), bucket CORS, and a second kind of storage

Recommendation. Keep the three repository functions as they are (`saveFile`, `loadFile`, `fileExists`) so the routes do not change. Use chunks first if files up to a few MB are enough. Move to a bucket when larger files, video or many uploads are expected.

Steps for chunks.

1. In `lib/schemas/upload.ts`, set `MAX_FILE_BYTES` to the new limit (for example 5 MB) and add a `CHUNK_BYTES` constant of 500 KB.
2. In `lib/server/repo/files.ts`, write the metadata document `files/{id}` (name, type, size, chunk count) and the chunks in a batched write. Stay inside the 500-operation limit of one batch.
3. In `loadFile`, read the chunks in order and join them. Return the same shape as today.
4. In the route, check the size before reading the file into memory, and set the same limit on the client check.
5. Delete files together with their chunks (`recursiveDelete`).

Hosting limit. Many hosts limit the size of a request body that goes through a server function (for example about 4.5 MB on Vercel). Check your host before choosing a limit above that; this is the main reason to prefer a bucket with direct uploads.

Orphaned files. Today deleting a form leaves its files in Firestore. Fix it in the repository facade: before deleting the form, read the file ids from the answers of its file questions, delete the form, then delete those files with `mirrorSafely` so a failure is logged and not returned. Also add a cleanup in the sync step for files that no answer points to and that are older than a day (an upload that was never submitted).

Other limits worth adding. A total file size per form, a file count per submission (one file per file question already), and a content check that compares the file's first bytes with the declared type, because the browser's `file.type` can be wrong or faked.

Check. Upload files just under and just over the new limit (expect 201 and 400), download a multi-chunk file and compare its checksum with the original, and delete a form to confirm no chunk documents remain.

7.4 Sync

Gaps today. Repair is manual, `syncAll` copies every form and submission each time, and a failed mirror write is only a line in the log, with nothing remembering which row failed.

Design: an outbox. When a mirror write fails, the failure is stored in Postgres so it can be retried. This replaces "log and forget" in `mirrorSafely`.

```
// prisma/schema.prisma (design)
// Why: remembers a mirror write that failed, so it can be retried.
model MirrorTask {
  id        String   @id @default(cuid())
  entity    String   // "form", "submission" or "file"
  entityId  String
  formId    String?  // needed to find a submission's parent
  action    String   // "upsert" or "delete"
  attempts  Int      @default(0)
  lastError String?
  createdAt DateTime @default(now())
  @@index([createdAt])
}
```

File	Action	Change
`prisma/schema.prisma`	update	Add `MirrorTask`, then `npx prisma migrate dev -name mirror_task`
`lib/server/repo/outbox.ts`	create	`recordFailure`, `processTasks` (retry in age order, delete the task on success, count attempts and keep the error on failure)
`lib/server/repo/dual.ts`	update	On a mirror error call `recordFailure`; if that also fails, log it
`lib/server/repo/sync.ts`	update	Add `processTasks` before the full comparison, and report the number of waiting tasks in the status
`lib/server/routes/sync.ts`	update	`POST /api/sync/retry` runs only the outbox; `status` adds `pendingTasks`

Running it on a schedule. The app has no scheduler, so something outside it calls the endpoint with the bearer token. Choose one:

- the host's scheduled jobs, if it offers them (check whether they send a `GET` or a `POST`; the route accepts only the method it declares, so match it or add a second route);
- a scheduled GitHub Actions workflow that runs `curl -X POST -H "Authorization: Bearer $SYNC_TOKEN"` against `/api/sync/retry` every few minutes and `/api/sync` once a day;
- any external cron service.

Store the token as a secret of that service and never in the repository.

Make the full sync cheaper. Add `updatedAt` to `Form` (Prisma's `@updatedAt`) and let a daily sync copy only forms changed since the last run, keeping the full comparison for a weekly run. Submissions are never edited, so only new ones need copying.

Alerts. Call `GET /api/sync/status` on a schedule and notify someone when `inSync` is false or `pendingTasks` keeps growing.

Decision to keep. Sync stays one-way: Postgres wins. Two-way sync needs conflict rules and is out of scope.

Check. Stop Firestore access (use a wrong key), create a form (the request still succeeds), confirm a `MirrorTask` row exists, restore the key, call `/api/sync/retry`, and confirm the row is gone and the form appears in Firestore.

7.5 Rate limiting

Why. The survey page and its submit and upload routes are public. Without a limit, one client can fill a form with junk, upload files until storage grows, or make the server call the databases without end.

Where. One Hono middleware in `lib/server/rateLimit.ts`, registered in `lib/server/app.ts` before the route groups, so every path is counted, including paths that answer 405. The sync routes stay protected by their token and are not counted.

Proposed limits (per client, per minute; tune them with real traffic):

Route group	Limit	Reason
`POST /api/forms/:id/submissions`	10 per minute	A person answers a form a few times at most
`POST /api/files`	5 per minute	Uploads are the most expensive request
`POST /api/forms`, `PUT`, `DELETE`	20 per minute	Owner actions; stricter once there is a login
All other `GET` requests	120 per minute	Page loads and polling

Rules.

1. **Client key.** Use the IP address. Behind a proxy or host the real address is in `X-Forwarded-For`; read only the value your host sets, and ignore the header when the app is reachable directly, otherwise a client can invent its own address and avoid the limit.
2. **Answer.** When a client is over the limit, return 429 with the usual error body (code `rate_limited`), a `Retry-After` header in seconds, and the same headers on normal responses (`RateLimit-Limit`, `RateLimit-Remaining`) so a client can slow down early.
3. **Algorithm.** A sliding window is fairer than a fixed window, which lets a client send a full limit at the end of one minute and again at the start of the next.
4. **Fail open or closed.** If the limit store is unreachable, let the request through and log it for public reads, but refuse writes. A broken limiter should not take the survey page down.

Where to keep the counters.

Store	Works when	Problem
Memory of the process (a `Map`)	One server that stays running (local, one container)	Resets on restart, and every server function instance has its own counters, so the real limit is higher
Redis (for example Upstash with its rate-limit library)	Several instances or serverless; this is the normal choice	A new service and an environment variable for its address and token
Postgres table	No new service is wanted	A write on every request; fine for low traffic only

Start with the in-memory store behind a small interface (`hit(key, limit, windowSeconds)`) and swap the store when the app runs on more than one instance.

Related protections, outside the limiter.

- A bot check (for example a Turnstile or reCAPTCHA token) on the public submit route, verified on the server.
- A maximum JSON body size, so a very large body is refused before it is parsed.
- A hidden "honeypot" field in the survey form that real people leave empty; a filled value is rejected.

Check. Send 11 submissions in a minute with a shell loop; the first 10 return 201 and the 11th returns 429 with `Retry-After`. Wait for the window and confirm the next request succeeds. Confirm `GET /api/sync/status` with a valid token is never limited.

7.6 Suggested order

1. Login and form ownership (prerequisite for the delete button and editing).
2. Rate limiting (small, and protects everything below).
3. Delete button, including deleting a form's files.
4. Sync outbox and a scheduled call.
5. Form editing.
6. File limits (chunks or a bucket).

After each step run the checks from Step 12 (`prettier`, `tsc`, `eslint`, `npm run build`) and the `Check` paragraph of that extension.

8 Database Schema (Mermaid ER Diagram)

Figure 1 shows the four PostgreSQL models from Step 4 and how they relate. Deleting a form cascades to its questions and submissions, and deleting a submission or a question cascades to its answers.




Figure 1: Entity-relationship diagram of the local PostgreSQL copy.

- `Question.type` is stored as text and restricted by the Zod enum at the API boundary.
- `Question.options` is a text array, used only by the two choice types.
- `Answer.value` is a JSON column: it holds a string (text, a number as text, a choice or a file id) or a list of strings for multi-choice. Empty answers are not stored, and a submission can answer each question only once.
- `Question.order` keeps the order of the questions inside a form.

8.1 Firestore layout

Firestore is the primary store and the file store. Figure 2 shows its collections. Every local Postgres row uses the same id as its Firestore document, which is what lets the sync endpoint compare the two by id.




Figure 2: Firestore collections and how they relate to PostgreSQL.

9 System Architecture (Mermaid Flowchart)

Figure 3 shows the layers. The shared Zod schemas are imported by the form, the HTTP client and the API validator. Routes never touch a database directly: they call the repository layer, which writes to Firestore first and, in local development only, copies to PostgreSQL, and reads from Firestore with local PostgreSQL as the fallback. Files bypass PostgreSQL and live only in Firestore.




Figure 3: Architecture of the application as built.

9.1 Architecture with the planned extensions

Figure 4 shows the same system with the extensions from Section 7. Dashed amber boxes are planned and not built; solid boxes exist today. The rate-limit and auth middleware sit in front of validation, a failed mirror write goes to an outbox table that the sync routes retry, an external scheduler calls the token-protected sync routes, and the delete and edit screens reuse the same typed client.




Figure 4: Architecture with the planned extensions (dashed = planned).

10 Request Flows (Mermaid Sequence Diagrams)

10.1 Submitting a response

Figure 5 follows one submission, including an optional file upload. The answers are validated twice with the same schema, in the browser and on the server, and the server also checks that every file answer is the id of a stored file.




Figure 5: Submitting a response: upload, validation, Postgres write and Firestore mirror.

10.2 Reading with fallback, and repairing with sync

Figure 6 shows a read that falls back to Firestore when PostgreSQL throws, and the two token-protected sync calls an operator runs after an outage or a restore.




Figure 6: Read fallback and the sync endpoints.

11 Development Workflow (Mermaid Flowcharts)

11.1 How the project is built and checked

Figure 7 shows the order of work in Steps 1 to 13. The project is built layer by layer, from the schemas up to the pages, and the same four commands run after every layer so an error is found where it was made. A failing check sends the work back to the layer that caused it.




Figure 7: Development workflow: set up, build in layers, check, run.

11.2 Roadmap for the planned extensions

Figure 8 shows which extension depends on which, and matches the suggested order in Section 7. Login and rate limiting come first because the delete button and form editing should not ship while anyone can call those routes.




Figure 8: Roadmap: built core and the planned extensions (dashed = planned).

12 Imperative and Declarative Programming: Where Each Is Used

Two styles. *Imperative* code says *how*: a sequence of steps that change state, in a fixed order (do this, then this, if that fails do that). *Declarative* code says *what*: a description of the result or the rules, and something else (a library, the database, the framework) decides the steps. Real programs mix both. This project uses declarative code for rules, shapes and layout, and imperative code where the order of side effects matters.

Rule of thumb used here. If the code is a rule that more than one place must share or inspect (validation, data shape, routes, styling), write it declaratively. If the code must do things in a strict order with side effects (write to a database, then mirror, then recover from a failure), write it imperatively and make the order visible.

12.1 Where the project is declarative

Place	Files	What is declared
Validation rules	`lib/schemas/*.ts`	Zod describes what a valid form, question, answer or upload looks like. The browser, the API validator and the repository all reuse the same description.
Per-form answer rules	`buildAnswerSchema` in `lib/schemas/submission.ts`	Builds the rule object from a form's questions, one entry per question, without saying how to check each answer.
Database model	`prisma/schema.prisma`	The four models, their fields and relations, including cascade deletes. Prisma decides the SQL and the migration.
Database queries	`lib/server/repo/postgres/*.ts`	Prisma calls such as `findMany({ where, orderBy, include })` describe the rows wanted, not how to fetch them.
Routes and middleware	`lib/server/routes/*.ts`, `lib/server/app.ts`	A table of method, path, validator and handler. Hono matches and runs them.
Folder routing	`app/`	The folder structure declares the pages (`app/f/[formId]/page.tsx` is the URL `/f/:formId`).
Typed API client	`lib/fetch.ts`	Every endpoint is listed once with its input, output, params and query schemas.
User interface	`components/*.tsx`, `app/**/page.tsx`	JSX describes the screen for the current state, including the loading fallback in `Suspense`. React decides how to update the page.
Styling	`lib/responsive/pattrens/forms.ts`	Tailwind class strings describe how an element looks, grouped by role.
Form behaviour	react-hook-form with `zodResolver`	The resolver is given the schema; the library runs the checks and tracks errors.
Configuration	`prisma.config.ts`, `postcss.config.mjs`, `tsconfig.json`, `.prettierrc`, `.env.example`	Settings objects and files that describe the setup.
Documentation	`*.tex`, `*.mmd`	LaTeX and Mermaid describe the page and the diagrams; the tools draw them.

Two real examples from the source code:

```
// Declarative: what rows are wanted (lib/server/repo/postgres/forms.ts)
const rows = await prisma.form.findMany({
  orderBy: { createdAt: 'desc' },
  include: { _count: { select: { questions: true, submissions: true } } },
});

// Declarative: what a valid answer is (lib/schemas/submission.ts)
case 'email':
  schema = z.union([z.literal(''), z.email('Enter a valid email')]);
  break;
```

12.2 Where the project is imperative

Place	Files	Why the steps are spelled out
Saving a submission	`createSubmission` in `lib/server/repo/postgres/submissions.ts`	Loops over the questions, skips empty answers, stores each answer as JSON (a string or a list), then writes once.
Request handling	`lib/server/routes/submissions.ts`	Checks run in a fixed order with early returns: form exists, body is valid, answers are valid, every file id exists, then save. The order decides which error the client sees.
Write then mirror	`lib/server/repo/forms.ts`, `submissions.ts`, `dual.ts`	Postgres must commit first, and only then is Firestore written. This order is the design.
Failure handling	`mirrorSafely`, `readWithFallback`	`try` and `catch` control what happens when a database fails: log and continue, or retry on the other store.
Counters and transactions	`lib/server/repo/firestore/submissions.ts`	Read the document, then write it and increase the counter only if it did not exist, all inside one transaction.
Sync	`getSyncStatus`, `syncAll` in `lib/server/repo/sync.ts`	Loops over every form, copies submissions, sets the real counter last, then removes strays. Order matters, so it is written step by step.
Answer mapping	`toAnswerMap`	A loop that builds the answer map row by row.
File upload in the browser	`handleFileChange` in `components/FileUploadField.tsx`	Validate, set the status, call the API, upload, store the id, each step reacting to the one before.
Event handlers and loaders	`lib/useLoad.ts`, submit handlers in the components	Respond to a click or a load by running steps and updating state.
Method guard	`lib/server/methods.ts`	Registers the `OPTIONS` and catch-all handlers in a defined order after the real handlers.
Shell commands	Steps 1 to 13 and `curl` checks	A list of commands run in order.

Two real examples from the source code:

```
// Imperative: build the rows step by step (createSubmission)
for (const question of form.questions) {
  const value = answers[question.id];
  if (value === undefined || value === '' || value.length === 0) {
    continue; // empty answers are not stored
  }
  // The Answer.value column is JSON, so strings and lists fit as-is.
  rows.push({ questionId: question.id, value });
}

// Imperative: the order is the design (lib/server/repo/forms.ts)
const form = await postgres.createForm(input);
await mirrorSafely(() => firestore.mirrorForm(form));
return form;
```

12.3 Where the two meet

- **A route.** `forms.post('/', validate('json', createFormSchema), async (c) => { ... })`: the route and its validator are declared; the handler body is imperative.
- **A React component.** The returned JSX is declarative (what the screen shows); the event handlers and the effects that load data are imperative (what to do when something happens).
- **Array methods.** `rows.map(...)` and `filter(...)` describe a transformation of a list and are used for pure conversions, for example turning Prisma rows into response objects. A `for` loop is used when a step has side effects or must stop early.
- **Schema-driven code.** `buildAnswerSchema` is imperative inside (a loop that fills an object) but returns a declarative description that the rest of the program uses.

12.4 Pure functions

Definition. A pure function returns the same result for the same arguments and changes nothing outside itself: no database call, no network request, no `console.log`, no reading of `process.env`, no clock or random number, and no change to its arguments. Pure functions are the easiest code to read, reuse and test, because a test only passes arguments and checks the result.

Pure functions in this project.

Function	File	Why it is pure
`isChoiceType`	`lib/schemas/question.ts`	Compares a type string with two names and returns a boolean.
`answerSchemaFor`	`lib/schemas/submission.ts`	Turns one question into a Zod rule. The same question always gives an equivalent rule, and nothing is read or written.
`buildAnswerSchema`	`lib/schemas/submission.ts`	Fills a new object from a list of questions and returns it. It changes only its own local object, never the questions.
`errorBody`	`lib/server/errors.ts`	Builds the error object from its three arguments.
`toAnswerMap`	`lib/server/repo/postgres/submissions.ts`	Builds a new answer map from stored rows. Its loop changes only the local map.
Row-to-response `map` calls	`listForms`, `listSubmissions`, `listAllSubmissions` (the `rows.map(...)` part)	Convert each row into a response object, for example a `Date` to an ISO string.
Issue mapping	`validate` in `lib/server/validate.ts` and the submissions route	`issues.map(...)` turns validator issues into `{ path, message }` pairs.
Schema checks	`schema.safeParse(...)` on a Zod schema	Decides valid or invalid from the value alone. The result is data (success or issues), not an exception.
React render	The returned JSX of each component	A component should return the same screen for the same props and state. Side effects belong in event handlers and loaders, not in the render.

Two real examples:

```
// Pure: same input, same output, no side effects (lib/schemas/question.ts)
export function isChoiceType(type: QuestionType): boolean {
  return type === 'single_choice' || type === 'multi_choice';
}

// Pure: builds a value from its arguments only (lib/server/errors.ts)
export function errorBody(code: string, message: string, issues?: unknown) {
  return {
    error: { code, message, ...(issues === undefined ? {} : { issues }) },
  };
}
```

Mostly pure, with one exception. `requireOptionsForChoice` in `lib/schemas/question.ts` decides whether a question is valid, but it reports the problem by calling `ctx.addIssue(...)`, which changes the Zod context it was given. This is the normal Zod pattern, so it is accepted, and the change stays inside the validation run.

Where pure functions are *not* used, and why.

Code	Side effect that makes it impure
`lib/server/repo/postgres/*.ts`	Reads and writes PostgreSQL through Prisma.
`lib/server/repo/firestore/*.ts`, `files.ts`	Reads and writes Firestore.
`mirrorSafely`, `readWithFallback`	Run a task and log errors with `console.error`.
`getSyncStatus`, `syncAll`	Query and write both databases.
`saveFile`	Uses a random id and writes a document.
`lib/server/env.ts` (`getDatabaseEnv`, `getFirebaseEnv`, `getSyncToken`)	Reads `process.env`, so the result depends on the environment.
`lib/server/db.ts`, `lib/server/firestore.ts`	Create and keep a shared client on `globalThis` or in the Firebase app list.
`methodNotAllowed`	Registers handlers on the Hono app (it changes the app it receives).
Route handlers and `app.ts`	Read the request, call the repositories and return a response.
`lib/fetch.ts` calls and `FileUploadField`	Make network requests and update component state.

Keep the pure part and the effect apart. Many functions mix both. The planned improvement, not yet done, is to pull the pure decision out of the function that does the input and output, so it can be tested alone:

Today	Pure part to extract	Effect that stays
`createSubmission` (Postgres)	`buildAnswerRows(form, answers)`: the loop that skips empty answers and splits numbers from text	`prisma.submission.create(...)`
`getSyncStatus`	`diffIds(postgresIds, firestoreIds)`: the `missing` and `only` lists and the `inSync` flag	The queries that fetch the ids and counts
Rate limiter (planned)	`decide(count, limit, windowSeconds)`: returns allow, or block with a retry time	Reading and writing the counter in the store
Form update (planned)	`planQuestionChanges(old Questions, newQuestions)`: returns which to create, update and delete	The transaction that applies them

Rules for new code.

1. Put pure helpers in `lib/schemas/` or in a small file next to the code that uses them, and do not import a database client, `process.env` or `fetch` into them.
2. Do not change an argument. Build and return a new object instead of editing the one that was passed in.
3. Give the function the time or random id as an argument when it needs one, so a test can pass a fixed value.

4. Test pure functions first. They need no database, no Firebase key and no running server, so `npx tsx` or a test runner can call them directly with sample questions and answers.

12.5 Planned extensions

Extension	Style	Reason
`updateFormSchema`	Declarative	Another shared rule, reused by the browser and the API.
`MirrorTask` model	Declarative	A new model in the Prisma schema.
Rate-limit middleware	Imperative	Count a request, compare it with the limit, then allow it or return 429.
Outbox processing	Imperative	Retry tasks in age order, delete on success, count attempts on failure.
Form update in one transaction	Imperative	Update, create and delete questions in a fixed order.
Limits table (per route group)	Declarative	A small object that maps a route group to a limit; the middleware reads it.

Guideline for new code. Put the rule or shape in a declarative form first (a schema, a model, a config object). Write the imperative function that uses it second, keep it short, give it a doc comment, and keep each `if` in braces so the order of steps is easy to read. Do not hide side effects inside a declarative-looking expression.

13 Source Code

Every listing below is the complete content of the file, so you can type it in step by step. The set was type-checked together (`tsc -noEmit`) and formatted with Prettier. The code follows these conventions: braces on every `if`, a doc comment on each function, descriptive names, Prettier width 80 with single quotes and trailing commas, and no inline Tailwind classes (they live in the patterns file). Comments marked "Why" explain a decision, not the syntax.

13.1 Configuration

File: `prisma.config.ts`. Prisma 7 configuration: schema path, migrations path and database URL.

```
import 'dotenv/config';
import { defineConfig } from 'prisma/config';

/** Prisma 7 reads the schema path, migrations path and database URL here. */
export default defineConfig({
  schema: 'prisma/schema.prisma',
  migrations: { path: 'prisma/migrations' },
  datasource: { url: process.env['DATABASE_URL'] },
});
```

File: `prisma/schema.prisma`. The four models, with a comment on why each exists.

```
generator client {
  provider = "prisma-client"
  output   = "../generated/prisma"
}

datasource db {
  provider = "postgresql"
}

// Why: the parent record. It owns the questions and the submissions.
model Form {
  id          String       @id @default(cuid())
  title       String
  description String?
  published   Boolean      @default(true)
  createdAt   DateTime     @default(now())
  questions   Question[]
  submissions Submission[]
}

// Why: a question needs its own type, options, order and required flag,
// and answers point to it.
model Question {
  id       String   @id @default(cuid())
  formId   String
  form     Form     @relation(fields: [formId], references: [id], onDelete: Cascade)
  label    String
  type     String
  required Boolean  @default(false)
  options  String[]
  order    Int
  answers  Answer[]

  @@index([formId, order])
}
```

```
// Why: groups answers so one response can be counted, paged and deleted
// as a unit.
model Submission {
  id        String   @id @default(cuid())
  formId    String
  form      Form     @relation(fields: [formId], references: [id], onDelete: Cascade)
  createdAt DateTime @default(now())
  answers   Answer[]

  @@index([formId, createdAt])
}

// Why: joins a submission to a question. One JSON column holds a string,
// a list of strings (multi-choice) or a file id.
model Answer {
  id           String     @id @default(cuid())
  submissionId String
  submission   Submission @relation(fields: [submissionId], references: [id], onDelete: Cascade)
  questionId   String
  question     Question   @relation(fields: [questionId], references: [id], onDelete: Cascade)
  value        Json

  @@unique([submissionId, questionId])
}
```

File: `postcss.config.mjs`. Tailwind v4 PostCSS plugin.

```
/** Tailwind v4 runs as a PostCSS plugin, independent of the bundler. */
const config = {
  plugins: {
    '@tailwindcss/postcss': {},
  },
};

export default config;
```

File: `.env.example`. Environment variable template.

```
# PostgreSQL connection string
DATABASE_URL=postgresql://user:pass@localhost:5432/surveys

# Firebase Admin SDK service account (Project settings, Service accounts)
FIREBASE_PROJECT_ID=
FIREBASE_CLIENT_EMAIL=
# One line, in double quotes, with line breaks written as \n
FIREBASE_PRIVATE_KEY=

# Bearer token for GET /api/sync/status and POST /api/sync
SYNC_TOKEN=
```

File: `.prettierrc`. Prettier settings: width 80, single quotes, trailing commas.

```
{
  "printWidth": 80,
  "singleQuote": true,
  "trailingComma": "all"
}
```

13.2 Shared API schemas

File: `lib/schemas/question.ts`. Question types, schema and helper.

```
import { z } from 'zod';

export const questionTypes = [
  'short_text',
  'long_text',
  'number',
  'email',
  'date',
  'single_choice',
  'multi_choice',
  'file',
] as const;

export const questionTypeSchema = z.enum(questionTypes);
export type QuestionType = z.infer<typeof questionTypeSchema>;

/** True for the types that need a list of options. */
export function isChoiceType(type: QuestionType): boolean {
  return type === 'single_choice' || type === 'multi_choice';
}

const questionBase = z.object({
  label: z.string().trim().min(1, 'Question text is required').max(200),
  type: questionTypeSchema,
  required: z.boolean(),
  options: z.array(z.string().trim().min(1).max(100)).max(20).default([]),
});

/** A choice question needs at least two options. */
function requireOptionsForChoice(
  question: { type: QuestionType; options: string[] },
  ctx: z.RefinementCtx,
): void {
  if (isChoiceType(question.type) && question.options.length < 2) {
    ctx.addIssue({
      code: 'custom',
      path: ['options'],
      message: 'A choice question needs at least two options',
    });
  }
}

/** A question as sent when creating a form. */
export const questionInputSchema = questionBase.superRefine(
  requireOptionsForChoice,
);

/** A question as stored and returned: it also has an id and a position. */
export const questionSchema = questionBase
  .extend({ id: z.string().min(1), position: z.number().int().min(0) })
  .superRefine(requireOptionsForChoice);

export type QuestionInput = z.infer<typeof questionInputSchema>;
export type Question = z.infer<typeof questionSchema>;
```

File: `lib/schemas/form.ts`. Create-form payload, form response, dashboard summary.

```
import { z } from 'zod';
import { questionInputSchema, questionSchema } from './question';
```

```
export const createFormSchema = z.object({
  title: z.string().trim().min(1, 'Title is required').max(200),
  description: z.string().trim().max(2000).optional(),
  questions: z
    .array(questionInputSchema)
    .min(1, 'Add at least one question')
    .max(50),
});

export const formSchema = z.object({
  id: z.string().min(1),
  title: z.string(),
  description: z.string().nullable(),
  createdAt: z.string(),
  questions: z.array(questionSchema),
});

/** One row of the dashboard list. */
export const formSummarySchema = z.object({
  id: z.string().min(1),
  title: z.string(),
  createdAt: z.string(),
  questionCount: z.number().int(),
  responseCount: z.number().int(),
});

export const formIdParamSchema = z.object({ id: z.string().min(1) });

export type CreateFormInput = z.infer<typeof createFormSchema>;
export type Form = z.infer<typeof formSchema>;
export type FormSummary = z.infer<typeof formSummarySchema>;
```

File: `lib/schemas/upload.ts`. Upload limits, allowed types, file id pattern.

```
import { z } from 'zod';

/** Files are stored inside Firestore documents, which are capped at 1 MiB. */
export const MAX_FILE_BYTES = 700 * 1024;

export const ALLOWED_FILE_TYPES = [
  'application/pdf',
  'image/png',
  'image/jpeg',
  'text/plain',
] as const;

/** A file id is 32 lowercase hex characters (a UUID without dashes). */
export const FILE_ID_PATTERN = /^[a-f0-9]{32}$/;

export const fileIdSchema = z
  .string()
  .regex(FILE_ID_PATTERN, 'Invalid file id');
export const fileIdParamSchema = z.object({ id: fileIdSchema });
export const uploadResultSchema = z.object({ id: fileIdSchema });

export type UploadResult = z.infer<typeof uploadResultSchema>;
```

File: `lib/schemas/submission.ts`. Answers, submissions page, and the runtime answer schema.

```
import { z } from 'zod';
import { fileIdSchema } from './upload';
import { isChoiceType, type Question } from './question';

/** One answer is text, or a list of texts for a multi-choice question. */
```

```
const answerValueSchema = z.union([z.string(), z.array(z.string())]);

export const answersPayloadSchema = z.object({
  answers: z.record(z.string(), answerValueSchema),
});

export const submissionSchema = z.object({
  id: z.string().min(1),
  createdAt: z.string(),
  answers: z.record(z.string(), answerValueSchema),
});

export const pageQuerySchema = z.object({
  page: z.coerce.number().int().min(1).default(1),
  limit: z.coerce.number().int().min(1).max(100).default(20),
});

export const submissionsPageSchema = z.object({
  items: z.array(submissionSchema),
  page: z.number().int(),
  limit: z.number().int(),
  total: z.number().int(),
});

export const submissionIdSchema = z.object({ id: z.string().min(1) });

export type Submission = z.infer<typeof submissionSchema>;
export type SubmissionsPage = z.infer<typeof submissionsPageSchema>;

/** Builds the rule for one question's answer. */
function answerSchemaFor(question: Question): z.ZodType<unknown> {
  let schema: z.ZodType<unknown>;
  switch (question.type) {
    case 'number':
      schema = z.string().refine((v) => v === '' || !Number.isNaN(Number(v)), {
        message: 'Enter a number',
      });
      break;
    case 'email':
      schema = z.union([z.literal(''), z.email('Enter a valid email')]);
      break;
    case 'date':
      schema = z.union([z.literal(''), z.iso.date('Enter a valid date')]);
      break;
    case 'file':
      schema = z.union([z.literal(''), fileIdSchema]);
      break;
    case 'single_choice':
      schema = z.union([
        z.literal(''),
        z.enum(question.options as [string, ...string[]]),
      ]);
      break;
    case 'multi_choice':
      schema = z.array(z.enum(question.options as [string, ...string[]]));
      break;
    default:
      schema = z.string().max(5000);
  }
  if (!question.required) {
    return schema;
  }
  return schema.refine(
    (v) => (Array.isArray(v) ? v.length > 0 : v !== '' && v !== undefined),
    { message: 'This question is required' },
```

```
  );
}

/**
 * Builds the answer schema from a form's own questions, so the browser form
 * and the API apply exactly the same rules. Answers are keyed by question id.
 */
export function buildAnswerSchema(questions: Question[]) {
  const shape: Record<string, z.ZodType<unknown>> = {};
  for (const question of questions) {
    const base = answerSchemaFor(question);
    shape[question.id] = question.required
      ? base
      : isChoiceType(question.type) && question.type === 'multi_choice'
        ? base.default([])
        : base.optional();
  }
  return z.object(shape);
}
```

13.3 Server foundations

File: `lib/server/env.ts`. Lazy, validated environment variables.

```
import { z } from 'zod';

const databaseSchema = z.object({ DATABASE_URL: z.string().min(1) });

const firebaseSchema = z.object({
  FIREBASE_PROJECT_ID: z.string().min(1),
  FIREBASE_CLIENT_EMAIL: z.string().min(1),
  FIREBASE_PRIVATE_KEY: z.string().min(1),
});

/**
 * Why two lazy getters: each one validates only when called, so forms keep
 * working when Firebase is not configured.
 */
export function getDatabaseEnv() {
  return databaseSchema.parse(process.env);
}

export function getFirebaseEnv() {
  return firebaseSchema.parse(process.env);
}

/** The sync token, or undefined when none is set (sync stays closed). */
export function getSyncToken(): string | undefined {
  return process.env.SYNC_TOKEN || undefined;
}
```

File: `lib/server/db.ts`. Shared Prisma client with the Postgres adapter.

```
import { PrismaPg } from '@prisma/adapter-pg';
import { PrismaClient } from '@/generated/prisma/client';
import { getDatabaseEnv } from './env';

const globalForPrisma = globalThis as unknown as { prisma?: PrismaClient };

/** Creates the Prisma client with the node-postgres adapter. */
function createClient(): PrismaClient {
  const adapter = new PrismaPg({
```

```
    connectionString: getDatabaseEnv().DATABASE_URL,
  });
  return new PrismaClient({ adapter });
}

/**
 * Why globalThis: hot reloading re-runs this module, and a new client each
 * time would open a new connection pool.
 */
export const prisma = globalForPrisma.prisma ?? createClient();

if (process.env.NODE_ENV !== 'production') {
  globalForPrisma.prisma = prisma;
}
```

File: `lib/server/firestore.ts`. Firebase Admin app and Firestore database.

```
import { cert, getApps, initializeApp } from 'firebase-admin/app';
import { getFirestore } from 'firebase-admin/firestore';
import { getFirebaseEnv } from './env';

/** Starts the Firebase Admin app once and returns the Firestore database. */
export function getDb() {
  const env = getFirebaseEnv();
  const app =
    getApps()[0] ??
    initializeApp({
      credential: cert({
        projectId: env.FIREBASE_PROJECT_ID,
        clientEmail: env.FIREBASE_CLIENT_EMAIL,
        // The key is stored on one line with \n; turn it back into line breaks.
        privateKey: env.FIREBASE_PRIVATE_KEY.replace(/\\n/g, '\n'),
      }),
    });
  return getFirestore(app);
}
```

File: `lib/server/errors.ts`. The one error body shape.

```
import type { Context } from 'hono';
import type { ContentfulStatusCode } from 'hono/utils/http-status';

export type ApiErrorBody = {
  error: { code: string; message: string; issues?: unknown };
};

/** The one error body shape used by every endpoint. */
export function errorBody(
  code: string,
  message: string,
  issues?: unknown,
): ApiErrorBody {
  return {
    error: { code, message, ...(issues === undefined ? {} : { issues }) },
  };
}

/** Sends the error body with a status and optional headers. */
export function jsonError(
  c: Context,
  status: ContentfulStatusCode,
  code: string,
  message: string,
  headers?: Record<string, string>,
```

```
) {
  return c.json(errorBody(code, message), status, headers);
}
```

File: `lib/server/methods.ts`. Helper that adds the 405 + Allow catch-all to a path.

```
import type { Hono } from 'hono';
import { jsonError } from './errors';

/**
 * Answers every method not handled on `path` with a JSON 405 and an `Allow`
 * header. Call it AFTER the real handlers for the path, because Hono runs
 * handlers in the order they were registered.
 */
export function methodNotAllowed(app: Hono, path: string, allowed: string[]) {
  const allow = [...new Set([...allowed, 'OPTIONS'])].join(', ');
  app.options(path, (c) => c.body(null, 204, { Allow: allow }));
  app.all(path, (c) =>
    jsonError(
      c,
      405,
      'method_not_allowed',
      `${c.req.method} is not allowed here. Allowed: ${allow}.`,
      { Allow: allow },
    ),
  );
}
```

File: `lib/server/validate.ts`. zValidator wrapper with a consistent 400 body.

```
import { zValidator } from '@hono/zod-validator';
import type { ZodType } from 'zod';
import { errorBody } from './errors';

type Target = 'json' | 'param' | 'query';

/** zValidator with the same 400 body everywhere, listing every issue. */
export function validate<T extends ZodType>(target: Target, schema: T) {
  return zValidator(target, schema, (result, c) => {
    if (!result.success) {
      const issues = result.error.issues.map((issue) => ({
        path: issue.path.join('.'),
        message: issue.message,
      }));
      return c.json(
        errorBody('invalid_request', 'Invalid request', issues),
        400,
      );
    }
  });
}
```

13.4 Repository layer

File: `lib/server/repo/postgres/forms.ts`. Form data access in Postgres (source of truth).

```
import { prisma } from '../../db';
import {
  formSchema,
  type CreateFormInput,
  type Form,
```

```
  type FormSummary,
} from '@/lib/schemas/form';

/** Lists every form with its question and response counts. */
export async function listForms(): Promise<FormSummary[]> {
  const rows = await prisma.form.findMany({
    orderBy: { createdAt: 'desc' },
    include: { _count: { select: { questions: true, submissions: true } } },
  });
  return rows.map((row) => ({
    id: row.id,
    title: row.title,
    createdAt: row.createdAt.toISOString(),
    questionCount: row._count.questions,
    responseCount: row._count.submissions,
  }));
}

/** Returns one form with its questions in order, or null if it is missing. */
export async function getForm(id: string): Promise<Form | null> {
  const row = await prisma.form.findUnique({
    where: { id },
    include: { questions: { orderBy: { order: 'asc' } } },
  });
  if (!row) {
    return null;
  }
  // Parsing catches a bad row on the server instead of in the browser.
  return formSchema.parse({ ...row, createdAt: row.createdAt.toISOString() });
}

/** Creates a form and its questions in one nested write. */
export async function createForm(input: CreateFormInput): Promise<Form> {
  const row = await prisma.form.create({
    data: {
      title: input.title,
      description: input.description ?? null,
      questions: {
        create: input.questions.map((q, order) => ({ ...q, order })),
      },
    },
    include: { questions: { orderBy: { order: 'asc' } } },
  });
  return formSchema.parse({ ...row, createdAt: row.createdAt.toISOString() });
}

/** Deletes a form; its questions and submissions go with it. Returns false if missing. */
export async function deleteForm(id: string): Promise<boolean> {
  const result = await prisma.form.deleteMany({ where: { id } });
  return result.count > 0;
}
```

File: `lib/server/repo/postgres/submissions.ts`. Submission data access in Postgres.

```
// Imports: the shared Prisma client and the shapes this repo returns.
import { prisma } from '../../db';
import type { Form } from '@/lib/schemas/form';
import type { Submission } from '@/lib/schemas/submission';


// Types: answers keyed by question id, and one stored Answer row.
type Answers = Record<string, string | string[]>;
type AnswerRow = { questionId: string; value: unknown };
```

```
/** Returns what was stored so the same row can be mirrored to Firestore. */
export async function createSubmission(
  form: Form,
  answers: Answers,
): Promise<Submission> {
  // Rows to insert, one per answered question.
  const rows: {
    questionId: string;
    value: string | string[];
  }[] = [];

  // Walk the form's questions so answers to unknown ids are ignored.
  for (const question of form.questions) {
    const value = answers[question.id];
    if (value === undefined || value === '' || value.length === 0) {
      continue; // empty answers are not stored
    }

    // The Answer.value column is JSON, so strings and string arrays fit as-is.
    rows.push({ questionId: question.id, value });
  }

  // One nested create is a single transaction.
  const saved = await prisma.submission.create({
    data: { formId: form.id, answers: { create: rows } },
  });

  // Shape the result like a read, so callers treat both the same way.
  return {
    id: saved.id,
    createdAt: saved.createdAt.toISOString(),
    answers: toAnswerMap(rows),
  };
}


/** Rebuilds the question-id keyed answer map from stored rows. */
function toAnswerMap(rows: AnswerRow[]): Answers {
  const map: Answers = {};

  for (const row of rows) {
    if (typeof row.value === 'string') {
      // Single-value answers (text, number, choice, file id).
      map[row.questionId] = row.value;
    } else if (Array.isArray(row.value)) {
      // Multi-choice answers come back as a list of strings.
      map[row.questionId] = row.value.map(String);
    }
  }

  return map;
}


/** Lists one page of a form's submissions, newest first. */
export async function listSubmissions(form: Form, page: number, limit: number) {
  // Count and page query run in parallel; the count drives the pager.
  const [total, rows] = await Promise.all([
    prisma.submission.count({ where: { formId: form.id } }),
    prisma.submission.findMany({
      where: { formId: form.id },
      orderBy: { createdAt: 'desc' },
      skip: (page - 1) * limit, // pages are 1-based
      take: limit,
```

```
      include: { answers: true },
    }),
  ]);

  // Convert DB rows into the API shape.
  const items: Submission[] = rows.map((row) => ({
    id: row.id,
    createdAt: row.createdAt.toISOString(),
    answers: toAnswerMap(row.answers),
  }));

  return { items, page, limit, total };
}


/** Every submission of a form (used by sync). */
export async function listAllSubmissions(form: Form): Promise<Submission[]> {
  // No paging: sync needs the whole set.
  const rows = await prisma.submission.findMany({
    where: { formId: form.id },
    orderBy: { createdAt: 'desc' },
    include: { answers: true },
  });

  return rows.map((row) => ({
    id: row.id,
    createdAt: row.createdAt.toISOString(),
    answers: toAnswerMap(row.answers),
  }));
}
```

File: `lib/server/repo/firestore/forms.ts`. Form mirror writes and reads in Firestore.

```
import { getDb } from '../../firestore';
import { formSchema, type Form, type FormSummary } from '@/lib/schemas/form';

/** Copies a form to Firestore under the same id. Keeps the response counter. */
export async function mirrorForm(form: Form, responseCount?: number) {
  const ref = getDb().collection('forms').doc(form.id);
  const data: Record<string, unknown> = { ...form };
  if (responseCount !== undefined) {
    data.responseCount = responseCount;
  }
  await ref.set(data, { merge: true });
  if (responseCount === undefined) {
    // Set the counter only when the document has none yet.
    await getDb().runTransaction(async (tx) => {
      const snap = await tx.get(ref);
      if (snap.get('responseCount') === undefined) {
        tx.update(ref, { responseCount: 0 });
      }
    });
  }
}

export async function deleteMirroredForm(id: string) {
  const ref = getDb().collection('forms').doc(id);
  await getDb().recursiveDelete(ref);
}

export async function listMirroredForms(): Promise<FormSummary[]> {
  const snap = await getDb()
    .collection('forms')
    .orderBy('createdAt', 'desc')
```

```
    .get();
  return snap.docs.map((doc) => ({
    id: doc.id,
    title: doc.get('title'),
    createdAt: doc.get('createdAt'),
    questionCount: (doc.get('questions') ?? []).length,
    responseCount: doc.get('responseCount') ?? 0,
  }));
}

export async function getMirroredForm(id: string): Promise<Form | null> {
  const snap = await getDb().collection('forms').doc(id).get();
  if (!snap.exists) {
    return null;
  }
  return formSchema.parse({ ...snap.data(), id: snap.id });
}

export async function listMirroredFormIds(): Promise<string[]> {
  const snap = await getDb().collection('forms').select().get();
  return snap.docs.map((doc) => doc.id);
}
```

File: `lib/server/repo/firestore/submissions.ts`. Submission mirror writes and reads in Firestore.

```
import { FieldValue } from 'firebase-admin/firestore';
import { getDb } from '../../firestore';
import type { Submission } from '@/lib/schemas/submission';

/**
 * Writes the submission and bumps the form counter in one transaction, and
 * only if the document did not exist, so mirroring twice counts once.
 */
export async function mirrorSubmission(formId: string, submission: Submission) {
  const db = getDb();
  const formRef = db.collection('forms').doc(formId);
  const ref = formRef.collection('submissions').doc(submission.id);
  await db.runTransaction(async (tx) => {
    const existing = await tx.get(ref);
    tx.set(ref, submission);
    if (!existing.exists) {
      tx.set(
        formRef,
        { responseCount: FieldValue.increment(1) },
        { merge: true },
      );
    }
  });
}

export async function listMirroredSubmissions(
  formId: string,
  page: number,
  limit: number,
) {
  const col = getDb().collection('forms').doc(formId).collection('submissions');
  const [totalSnap, snap] = await Promise.all([
    col.count().get(),
    col
      .orderBy('createdAt', 'desc')
      .offset((page - 1) * limit)
      .limit(limit)
      .get(),
```

```
  ]);
  const items = snap.docs.map((doc) => doc.data() as Submission);
  return { items, page, limit, total: totalSnap.data().count };
}

export async function countMirroredSubmissions(
  formId: string,
): Promise<number> {
  const col = getDb().collection('forms').doc(formId).collection('submissions');
  return (await col.count().get()).data().count;
}
```

File: `lib/server/repo/dual.ts`. Safe mirror write and read with fallback.

```
/**
 * Runs a Firestore mirror write. A failure is logged and swallowed, because
 * the response is already correct; the sync endpoint repairs the difference.
 */
export async function mirrorSafely(
  task: () => Promise<unknown>,
): Promise<void> {
  try {
    await task();
  } catch (error) {
    console.error('Firestore mirror failed', error);
  }
}

/**
 * Reads from Postgres. If Postgres throws (for example it is unreachable),
 * the same read runs against Firestore. A "not found" (null) is a real
 * answer and is not retried.
 */
export async function readWithFallback<T>(
  primary: () => Promise<T>,
  fallback: () => Promise<T>,
): Promise<T> {
  try {
    return await primary();
  } catch (error) {
    console.error('Postgres read failed, using Firestore', error);
    return fallback();
  }
}
```

File: `lib/server/repo/forms.ts`. Form facade: Postgres first, then mirror.

```
import type { CreateFormInput } from '@/lib/schemas/form';
import { mirrorSafely, readWithFallback } from './dual';
import * as firestore from './firestore/forms';
import * as postgres from './postgres/forms';

export function listForms() {
  return readWithFallback(postgres.listForms, firestore.listMirroredForms);
}

export function getForm(id: string) {
  return readWithFallback(
    () => postgres.getForm(id),
    () => firestore.getMirroredForm(id),
  );
}

/** Postgres first, then the mirror. */
```

```
export async function createForm(input: CreateFormInput) {
  const form = await postgres.createForm(input);
  await mirrorSafely(() => firestore.mirrorForm(form));
  return form;
}

export async function deleteForm(id: string) {
  const deleted = await postgres.deleteForm(id);
  if (deleted) {
    await mirrorSafely(() => firestore.deleteMirroredForm(id));
  }
  return deleted;
}
```

File: `lib/server/repo/submissions.ts`. Submission facade: Postgres first, then mirror.

```
import type { Form } from '@/lib/schemas/form';
import { mirrorSafely, readWithFallback } from './dual';
import * as firestore from './firestore/submissions';
import * as postgres from './postgres/submissions';

/** Postgres first, then the mirror. */
export async function createSubmission(
  form: Form,
  answers: Record<string, string | string[]>,
) {
  const submission = await postgres.createSubmission(form, answers);
  await mirrorSafely(() => firestore.mirrorSubmission(form.id, submission));
  return submission;
}

export function listSubmissions(form: Form, page: number, limit: number) {
  return readWithFallback(
    () => postgres.listSubmissions(form, page, limit),
    () => firestore.listMirroredSubmissions(form.id, page, limit),
  );
}
```

File: `lib/server/repo/files.ts`. Uploaded files stored in Firestore.

```
import { randomUUID } from 'node:crypto';
import { getDb } from '../firestore';

type StoredFile = { name: string; type: string; data: string };

/** Saves a file as a Firestore document and returns its random id. */
export async function saveFile(file: File): Promise<string> {
  const id = randomUUID().replace(/-/g, '');
  const bytes = Buffer.from(await file.arrayBuffer());
  const doc: StoredFile = {
    name: file.name,
    type: file.type,
    data: bytes.toString('base64'),
  };
  await getDb().collection('files').doc(id).set(doc);
  return id;
}

/** Loads a stored file, or null if the id is unknown. */
export async function loadFile(id: string) {
  const snap = await getDb().collection('files').doc(id).get();
  if (!snap.exists) {
    return null;
  }
```

```
  const doc = snap.data() as StoredFile;
  return {
    name: doc.name,
    type: doc.type,
    bytes: Buffer.from(doc.data, 'base64'),
  };
}

export async function fileExists(id: string): Promise<boolean> {
  return (await getDb().collection('files').doc(id).get()).exists;
}
```

File: `lib/server/repo/sync.ts`. Sync status and full repair.

```
import { prisma } from '../db';
import * as firestoreForms from './firestore/forms';
import * as firestoreSubmissions from './firestore/submissions';
import * as postgresForms from './postgres/forms';
import * as postgresSubmissions from './postgres/submissions';

/**
 * Compares both databases by id, not only by count: counts alone say
 * "in sync" when one form was deleted and another added.
 */
export async function getSyncStatus() {
  const [pgIds, fsIds] = await Promise.all([
    prisma.form
      .findMany({ select: { id: true } })
      .then((r) => r.map((f) => f.id)),
    firestoreForms.listMirroredFormIds(),
  ]);
  const missingInFirestore = pgIds.filter((id) => !fsIds.includes(id));
  const onlyInFirestore = fsIds.filter((id) => !pgIds.includes(id));
  const pgSubmissions = await prisma.submission.count();
  let fsSubmissions = 0;
  for (const id of fsIds) {
    fsSubmissions += await firestoreSubmissions.countMirroredSubmissions(id);
  }
  return {
    missingInFirestore,
    onlyInFirestore,
    submissions: { postgres: pgSubmissions, firestore: fsSubmissions },
    inSync:
      missingInFirestore.length === 0 &&
      onlyInFirestore.length === 0 &&
      pgSubmissions === fsSubmissions,
  };
}

/** Copies everything from Postgres to Firestore. Safe to repeat. */
export async function syncAll() {
  const summaries = await postgresForms.listForms();
  let submissionCount = 0;
  for (const summary of summaries) {
    const form = await postgresForms.getForm(summary.id);
    if (!form) {
      continue;
    }
    const submissions = await postgresSubmissions.listAllSubmissions(form);
    for (const submission of submissions) {
      await firestoreSubmissions.mirrorSubmission(form.id, submission);
    }
    // Why last: it sets the counter to the real number, whatever the
    // submission mirrors incremented along the way.
```

```
    await firestoreForms.mirrorForm(form, submissions.length);
    submissionCount += submissions.length;
  }
  const keep = new Set(summaries.map((s) => s.id));
  const stray = (await firestoreForms.listMirroredFormIds()).filter(
    (id) => !keep.has(id),
  );
  for (const id of stray) {
    await firestoreForms.deleteMirroredForm(id);
  }
  return {
    forms: summaries.length,
    submissions: submissionCount,
    removed: stray.length,
  };
}
```

13.5 API routes

File: `lib/server/routes/forms.ts`. Form endpoints and 405 handling.

```
import { Hono } from 'hono';
import { createFormSchema, formIdParamSchema } from '@/lib/schemas/form';
import { jsonError } from '../errors';
import { methodNotAllowed } from '../methods';
import { createForm, deleteForm, getForm, listForms } from '../repo/forms';
import { validate } from '../validate';

export const forms = new Hono();

forms.get('/', async (c) => c.json(await listForms()));

forms.post('/', validate('json', createFormSchema), async (c) => {
  const form = await createForm(c.req.valid('json'));
  return c.json(form, 201);
});
methodNotAllowed(forms, '/', ['GET', 'POST']);

forms.get('/:id', validate('param', formIdParamSchema), async (c) => {
  const form = await getForm(c.req.valid('param').id);
  return form ? c.json(form) : jsonError(c, 404, 'not_found', 'Form not found');
});

forms.delete('/:id', validate('param', formIdParamSchema), async (c) => {
  const deleted = await deleteForm(c.req.valid('param').id);
  return deleted
    ? c.body(null, 204)
    : jsonError(c, 404, 'not_found', 'Form not found');
});
methodNotAllowed(forms, '/:id', ['GET', 'DELETE']);
```

File: `lib/server/routes/submissions.ts`. Submission endpoints and 405 handling.

```
import { Hono } from 'hono';
import { formIdParamSchema } from '@/lib/schemas/form';
import {
  answersPayloadSchema,
  buildAnswerSchema,
  pageQuerySchema,
} from '@/lib/schemas/submission';
import { errorBody, jsonError } from '../errors';
import { methodNotAllowed } from '../methods';
```

```
import { getForm } from '../repo/forms';
import { fileExists } from '../repo/files';
import { createSubmission, listSubmissions } from '../repo/submissions';
import { validate } from '../validate';

export const submissions = new Hono();

submissions.post(
  '/:id/submissions',
  validate('param', formIdParamSchema),
  async (c) => {
    const form = await getForm(c.req.valid('param').id);
    if (!form) {
      return jsonError(c, 404, 'not_found', 'Form not found');
    }
    // A body that is not JSON becomes null and fails validation with a 400.
    const body = await c.req.json().catch(() => null);
    const shape = answersPayloadSchema.safeParse(body);
    if (!shape.success) {
      return c.json(errorBody('invalid_request', 'Invalid request'), 400);
    }
    // Why per request: the rules come from this form's own questions.
    const result = buildAnswerSchema(form.questions).safeParse(
      shape.data.answers,
    );
    if (!result.success) {
      const issues = result.error.issues.map((i) => ({
        path: i.path.join('.'),
        message: i.message,
      }));
      return c.json(
        errorBody('invalid_answers', 'Some answers are invalid', issues),
        400,
      );
    }
    const answers = result.data as Record<string, string | string[]>;
    // Every file answer must be the id of a file this app stored.
    for (const question of form.questions) {
      const value = answers[question.id];
      if (
        question.type === 'file' &&
        typeof value === 'string' &&
        value !== ''
      ) {
        if (!(await fileExists(value))) {
          return c.json(
            errorBody('invalid_answers', 'Unknown file', [
              { path: question.id, message: 'Unknown file' },
            ]),
            400,
          );
        }
      }
    }
    const saved = await createSubmission(form, answers);
    return c.json({ id: saved.id }, 201);
  },
);

submissions.get(
  '/:id/submissions',
  validate('param', formIdParamSchema),
  validate('query', pageQuerySchema),
  async (c) => {
    const form = await getForm(c.req.valid('param').id);
```

```
    if (!form) {
      return jsonError(c, 404, 'not_found', 'Form not found');
    }
    const { page, limit } = c.req.valid('query');
    const result = await listSubmissions(form, page, limit);
    // File answers become download paths.
    const fileIds = new Set(
      form.questions.filter((q) => q.type === 'file').map((q) => q.id),
    );
    const items = result.items.map((item) => ({
      ...item,
      answers: Object.fromEntries(
        Object.entries(item.answers).map(([key, value]) => [
          key,
          fileIds.has(key) && typeof value === 'string' && value
            ? `/api/files/${value}`
            : value,
        ]),
      ),
    }));
    return c.json({ ...result, items });
  },
);
methodNotAllowed(submissions, '/:id/submissions', ['GET', 'POST']);
```

File: `lib/server/routes/files.ts`. File upload and download.

```
import { Hono } from 'hono';
import {
  ALLOWED_FILE_TYPES,
  MAX_FILE_BYTES,
  fileIdParamSchema,
} from '@/lib/schemas/upload';
import { errorBody, jsonError } from '../errors';
import { methodNotAllowed } from '../methods';
import { loadFile, saveFile } from '../repo/files';
import { validate } from '../validate';

export const files = new Hono();

files.post('/', async (c) => {
  const form = await c.req.formData().catch(() => null);
  const file = form?.get('file');
  if (!(file instanceof File)) {
    return c.json(
      errorBody('invalid_request', 'Send a multipart field "file"'),
      400,
    );
  }
  // Re-checked here because the browser check can be skipped.
  if (!(ALLOWED_FILE_TYPES as readonly string[]).includes(file.type)) {
    return c.json(
      errorBody('invalid_file', 'This file type is not allowed'),
      400,
    );
  }
  if (file.size > MAX_FILE_BYTES) {
    return c.json(
      errorBody('invalid_file', 'The file is larger than 700 KB'),
      400,
    );
  }
  return c.json({ id: await saveFile(file) }, 201);
});
```

```
methodNotAllowed(files, '/', ['POST']);

files.get('/:id', validate('param', fileIdParamSchema), async (c) => {
  const stored = await loadFile(c.req.valid('param').id);
  if (!stored) {
    return jsonError(c, 404, 'not_found', 'File not found');
  }
  // An attachment plus nosniff, so an upload is never run as a page here.
  return new Response(new Uint8Array(stored.bytes), {
    headers: {
      'Content-Type': stored.type,
      'Content-Disposition': `attachment; filename="${encodeURIComponent(stored.name)}"`,
      'X-Content-Type-Options': 'nosniff',
    },
  });
});
methodNotAllowed(files, '/:id', ['GET']);
```

File: `lib/server/routes/sync.ts`. Token-protected sync endpoints.

```
import { Hono } from 'hono';
import { getSyncToken } from '../env';
import { jsonError } from '../errors';
import { methodNotAllowed } from '../methods';
import { getSyncStatus, syncAll } from '../repo/sync';

export const sync = new Hono();

// Why: these routes can rewrite a whole database and reveal counts. With no
// token configured they stay closed.
sync.use('*', async (c, next) => {
  const token = getSyncToken();
  if (!token || c.req.header('Authorization') !== `Bearer ${token}`) {
    return jsonError(c, 401, 'unauthorized', 'Missing or wrong token');
  }
  await next();
});

sync.get('/status', async (c) => c.json(await getSyncStatus()));
methodNotAllowed(sync, '/status', ['GET']);

sync.post('/', async (c) => c.json(await syncAll()));
methodNotAllowed(sync, '/', ['POST']);
```

File: `lib/server/app.ts`. The Hono app: routes, 404 and error handler.

```
import { Hono } from 'hono';
import { jsonError } from './errors';
import { files } from './routes/files';
import { forms } from './routes/forms';
import { submissions } from './routes/submissions';
import { sync } from './routes/sync';

export const app = new Hono().basePath('/api');

app.route('/forms', forms);
app.route('/forms', submissions);
app.route('/files', files);
app.route('/sync', sync);

// An unknown path returns a JSON 404.
app.notFound((c) => jsonError(c, 404, 'not_found', 'No such route'));

// An unexpected failure returns a generic 500; the real error is only logged.
```

```
app.onError((error, c) => {
  console.error(error);
  return jsonError(c, 500, 'internal_error', 'Something went wrong');
});
```

File: `app/api/[[...route]]/route.ts`. Mounts Hono inside Next.js.

```
import { handle } from 'hono/vercel';
import { app } from '@/lib/server/app';

// Every method is exported on purpose: Next.js answers an unexported method
// with its own empty 405, while Hono answers with the JSON 405 and Allow.
// There is no `runtime` export, because Cache Components rejects it.
export const GET = handle(app);
export const POST = handle(app);
export const PUT = handle(app);
export const PATCH = handle(app);
export const DELETE = handle(app);
export const OPTIONS = handle(app);
```

13.6 Client library

File: `lib/fetch.ts`. Typed HTTP client and error message helper.

```
import {
  BetterFetchError,
  createFetch,
  createSchema,
} from '@better-fetch/fetch';
import { z } from 'zod';
import {
  createFormSchema,
  formIdParamSchema,
  formSchema,
  formSummarySchema,
} from '@/lib/schemas/form';
import {
  answersPayloadSchema,
  pageQuerySchema,
  submissionsPageSchema,
} from '@/lib/schemas/submission';
import {
  uploadResultSchema,
  MAX_FILE_BYTES,
  ALLOWED_FILE_TYPES,
} from '@/lib/schemas/upload';

const idResult = z.object({ id: z.string() });

/** Every JSON endpoint with its schemas: a wrong URL or body is a type error. */
const schema = createSchema({
  '/forms': { output: z.array(formSummarySchema) },
  '@post/forms': { input: createFormSchema, output: formSchema },
  '/forms/:id': { params: formIdParamSchema, output: formSchema },
  '@delete/forms/:id': { params: formIdParamSchema },
  '/forms/:id/submissions': {
    params: formIdParamSchema,
    query: pageQuerySchema.partial(),
    output: submissionsPageSchema,
  },
  '@post/forms/:id/submissions': {
    params: formIdParamSchema,
```

```
    input: answersPayloadSchema,
    output: idResult,
  },
});

/** better-fetch needs an absolute base URL; requests only run in the browser. */
function apiBase(): string {
  const origin =
    typeof window === 'undefined'
      ? 'http://localhost:3000'
      : window.location.origin;
  return `${origin}/api`;
}

export const api = createFetch({ baseURL: apiBase(), schema, throw: true });

/** Reads the server's error message, or falls back to a generic one. */
export function getErrorMessage(error: unknown): string {
  if (error instanceof BetterFetchError) {
    const body = error.error as { error?: { message?: string } } | undefined;
    return body?.error?.message ?? error.statusText ?? 'Request failed';
  }
  return error instanceof Error ? error.message : 'Something went wrong';
}

/**
 * Plain fetch with FormData: a multipart body cannot be described by a Zod
 * input schema. The response is still parsed with a schema.
 */
export async function uploadFile(file: File): Promise<string> {
  if (!(ALLOWED_FILE_TYPES as readonly string[]).includes(file.type)) {
    throw new Error('This file type is not allowed');
  }
  if (file.size > MAX_FILE_BYTES) {
    throw new Error('The file is larger than 700 KB');
  }
  const body = new FormData();
  body.append('file', file);
  const response = await fetch(`${apiBase()}/files`, { method: 'POST', body });
  const json: unknown = await response.json();
  if (!response.ok) {
    throw new BetterFetchError(response.status, response.statusText, json);
  }
  return uploadResultSchema.parse(json).id;
}
```

File: `lib/useLoad.ts`. Loading hook.

```
'use client';

import { useCallback, useEffect, useState } from 'react';
import { getErrorMessage } from './fetch';

type LoadState<T> = {
  data: T | null;
  error: string | null;
  loading: boolean;
  reload: () => void;
};

/** Runs an async loader and reports loading, error or data. */
export function useLoad<T>(
  loader: () => Promise<T>,
  deps: unknown[],
```

```
): LoadState<T> {
  const [data, setData] = useState<T | null>(null);
  const [error, setError] = useState<string | null>(null);
  const [loading, setLoading] = useState(true);
  const [version, setVersion] = useState(0);

  // eslint-disable-next-line react-hooks/exhaustive-deps
  const run = useCallback(loader, deps);

  useEffect(() => {
    let cancelled = false;
    run()
      .then((value) => {
        if (!cancelled) {
          setData(value);
          setError(null);
          setLoading(false);
        }
      })
      .catch((e: unknown) => {
        if (!cancelled) {
          setError(getErrorMessage(e));
          setLoading(false);
        }
      });
    return () => {
      cancelled = true;
    };
  }, [run, version]);

  return { data, error, loading, reload: () => setVersion((v) => v + 1) };
}
```

File: `lib/schemas/builder.ts`. Builder-only schema and conversion to the API payload.

```
import { z } from 'zod';
import { createFormSchema, type CreateFormInput } from './form';
import { isChoiceType, questionTypeSchema } from './question';

/**
 * Client-only. react-hook-form field arrays need objects, so options are
 * `{ value }` here and become plain strings in the API payload.
 */
export const builderFormSchema = z.object({
  title: z.string().trim().min(1, 'Title is required'),
  description: z.string().optional(),
  questions: z
    .array(
      z.object({
        label: z.string().trim().min(1, 'Question text is required'),
        type: questionTypeSchema,
        required: z.boolean(),
        options: z.array(z.object({ value: z.string() })),
      }),
    )
    .min(1, 'Add at least one question'),
});

export type BuilderForm = z.infer<typeof builderFormSchema>;

/** Converts the builder state to the payload the API accepts. */
export function toCreateFormPayload(values: BuilderForm): CreateFormInput {
  return createFormSchema.parse({
    title: values.title,
```

```
    description: values.description || undefined,
    questions: values.questions.map((q) => ({
      label: q.label,
      type: q.type,
      required: q.required,
      options: isChoiceType(q.type)
        ? q.options.map((o) => o.value).filter((v) => v.trim() !== '')
        : [],
    })),
  });
}
```

File: `lib/responsive/pattrens/forms.ts`. All Tailwind class strings.

```
/** Every Tailwind class string, one object per component. */

export const page = {
  main: 'mx-auto w-full max-w-3xl px-4 py-8',
  heading: 'mb-6 text-2xl font-semibold',
  muted: 'text-sm text-zinc-500',
  error: 'text-sm text-red-600',
};

export const shared = {
  input:
    'w-full rounded border border-zinc-300 px-3 py-2 text-sm focus:border-blue-500 focus:outline-
    none',
  label: 'mb-1 block text-sm font-medium',
  button:
    'rounded bg-blue-600 px-4 py-2 text-sm font-medium text-white hover:bg-blue-700 disabled:
    opacity-50',
  buttonGhost:
    'rounded border border-zinc-300 px-3 py-1.5 text-sm hover:bg-zinc-100',
  link: 'text-blue-600 hover:underline',
};

export const builder = {
  form: 'space-y-6',
  card: 'space-y-3 rounded border border-zinc-200 p-4',
  row: 'flex items-center gap-2',
  checkbox: 'h-4 w-4',
};

export const survey = {
  form: 'space-y-5',
  field: 'space-y-1',
  options: 'space-y-1',
  option: 'flex items-center gap-2 text-sm',
};

export const list = {
  header: 'mb-6 flex items-center justify-between',
  item: 'flex items-center justify-between border-b border-zinc-200 py-3',
  actions: 'flex gap-4 text-sm',
};

export const table = {
  wrap: 'overflow-x-auto',
  table: 'w-full border-collapse text-left text-sm',
  th: 'border-b border-zinc-300 px-3 py-2 font-medium',
  td: 'border-b border-zinc-200 px-3 py-2 align-top',
  pager: 'mt-4 flex items-center gap-3 text-sm',
};
```

13.7 Components

File: `components/FormBuilder.tsx`. Create-form screen.

```
'use client';

import { zodResolver } from '@hookform/resolvers/zod';
import { useRouter } from 'next/navigation';
import { useState } from 'react';
import { useFieldArray, useForm } from 'react-hook-form';
import { api, getErrorMessage } from '@/lib/fetch';
import { builder as p, page, shared } from '@/lib/responsive/pattrens/forms';
import {
  builderFormSchema,
  toCreateFormPayload,
  type BuilderForm,
} from '@/lib/schemas/builder';
import { isChoiceType, questionTypes } from '@/lib/schemas/question';
import { OptionsEditor } from './OptionsEditor';

const emptyQuestion: BuilderForm['questions'][number] = {
  label: '',
  type: 'short_text',
  required: false,
  options: [],
};

/** Create a form: react-hook-form with a field array and builderFormSchema. */
export function FormBuilder() {
  const router = useRouter();
  const [serverError, setServerError] = useState<string | null>(null);
  const {
    register,
    control,
    handleSubmit,
    watch,
    formState: { errors, isSubmitting },
  } = useForm<BuilderForm>({
    resolver: zodResolver(builderFormSchema),
    defaultValues: { title: '', description: '', questions: [emptyQuestion] },
  });
  const { fields, append, remove } = useFieldArray({
    control,
    name: 'questions',
  });

  /** Sends the payload; on success go to the dashboard. */
  async function onSubmit(values: BuilderForm) {
    setServerError(null);
    try {
      await api('@post/forms', { body: toCreateFormPayload(values) });
      router.push('/');
    } catch (error) {
      setServerError(getErrorMessage(error));
    }
  }

  return (
    <form className={p.form} onSubmit={handleSubmit(onSubmit)}>
      <div>
        <label className={shared.label}>Title</label>
        <input className={shared.input} {...register('title')} />
        {errors.title && <p className={page.error}>{errors.title.message}</p>}
      </div>
      <div>
```

```
      <label className={shared.label}>Description</label>
      <textarea className={shared.input} {...register('description')} />
    </div>

    {fields.map((field, index) => {
      const type = watch(`questions.${index}.type`);
      return (
        <div key={field.id} className={p.card}>
          <input
            className={shared.input}
            placeholder="Question"
            {...register(`questions.${index}.label`)}
          />
          {errors.questions?.[index]?.label && (
            <p className={page.error}>
              {errors.questions[index]?.label?.message}
            </p>
          )}
          <div className={p.row}>
            <select
              className={shared.input}
              {...register(`questions.${index}.type`)}
            >
              {questionTypes.map((t) => (
                <option key={t} value={t}>
                  {t.replace('_', ' ')}
                </option>
              ))}
            </select>
            <label className={p.row}>
              <input
                type="checkbox"
                className={p.checkbox}
                {...register(`questions.${index}.required`)}
              />
              Required
            </label>
            <button
              type="button"
              className={shared.buttonGhost}
              onClick={() => remove(index)}
            >
              Delete
            </button>
          </div>
          {isChoiceType(type) && (
            <OptionsEditor
              index={index}
              control={control}
              register={register}
            />
          )}
        </div>
      );
    })}

    <button
      type="button"
      className={shared.buttonGhost}
      onClick={() => append(emptyQuestion)}
    >
      Add question
    </button>
    {serverError && <p className={page.error}>{serverError}</p>}
    <div>
```

```
        <button type="submit" className={shared.button} disabled={isSubmitting}>
          {isSubmitting ? 'Saving...' : 'Create form'}
        </button>
      </div>
    </form>
  );
}
```

File: `components/OptionsEditor.tsx`. Options editor for choice questions.

```
'use client';

import {
  useFieldArray,
  type Control,
  type UseFormRegister,
} from 'react-hook-form';
import type { BuilderForm } from '@/lib/schemas/builder';
import { builder as p, shared } from '@/lib/responsive/pattrens/forms';

type Props = {
  index: number;
  control: Control<BuilderForm>;
  register: UseFormRegister<BuilderForm>;
};

/** Choices of one question: one input per option, add, remove, Yes / No. */
export function OptionsEditor({ index, control, register }: Props) {
  const { fields, append, remove, replace } = useFieldArray({
    control,
    name: `questions.${index}.options`,
  });

  return (
    <div className="space-y-2">
      {fields.map((field, optionIndex) => (
        <div key={field.id} className={p.row}>
          <input
            className={shared.input}
            placeholder={`Option ${optionIndex + 1}`}
            {...register(`questions.${index}.options.${optionIndex}.value`)}
          />
          <button
            type="button"
            className={shared.buttonGhost}
            onClick={() => remove(optionIndex)}
          >
            Remove
          </button>
        </div>
      ))}
      <div className={p.row}>
        <button
          type="button"
          className={shared.buttonGhost}
          onClick={() => append({ value: '' })}
        >
          Add option
        </button>
        <button
          type="button"
          className={shared.buttonGhost}
          onClick={() => replace([{ value: 'Yes' }, { value: 'No' }])}
        >
```

```
          Yes / No
        </button>
      </div>
    </div>
  );
}
```

File: `components/QuestionField.tsx`. One input per question type.

```
'use client';

import { Controller, type Control, type FieldValues } from 'react-hook-form';
import { page, shared, survey as p } from '@/lib/responsive/pattrens/forms';
import type { Question } from '@/lib/schemas/question';
import { FileUploadField } from './FileUploadField';

type Props = {
  question: Question;
  control: Control<FieldValues>;
  error?: string;
};

const inputTypes: Record<string, string> = {
  short_text: 'text',
  number: 'number',
  email: 'email',
  date: 'date',
};

/** One input per question type. */
export function QuestionField({ question, control, error }: Props) {
  return (
    <div className={p.field}>
      <label className={shared.label}>
        {question.label}
        {question.required && ' *'}
      </label>
      <Controller
        control={control}
        name={question.id}
        render={({ field }) => {
          switch (question.type) {
            case 'long_text':
              return (
                <textarea
                  className={shared.input}
                  {...field}
                  value={field.value ?? ''}
                />
              );
            case 'single_choice':
              return (
                <div className={p.options}>
                  {question.options.map((option) => (
                    <label key={option} className={p.option}>
                      <input
                        type="radio"
                        checked={field.value === option}
                        onChange={() => field.onChange(option)}
                      />
                      {option}
                    </label>
                  ))}
                </div>
```

```
            );
          case 'multi_choice': {
            const selected: string[] = field.value ?? [];
            return (
              <div className={p.options}>
                {question.options.map((option) => (
                  <label key={option} className={p.option}>
                    <input
                      type="checkbox"
                      checked={selected.includes(option)}
                      onChange={(e) =>
                        field.onChange(
                          e.target.checked
                            ? [...selected, option]
                            : selected.filter((o) => o !== option),
                        )
                      }
                    />
                    {option}
                  </label>
                ))}
              </div>
            );
          }
          case 'file':
            return (
              <FileUploadField
                value={field.value ?? ''}
                onChange={field.onChange}
              />
            );
          default:
            return (
              <input
                className={shared.input}
                type={inputTypes[question.type] ?? 'text'}
                {...field}
                value={field.value ?? ''}
              />
            );
        }
      }}
    />
    {error && <p className={page.error}>{error}</p>}
  </div>
 );
}
```

File: `components/FileUploadField.tsx`. File picker and upload.

```
'use client';

import { useState } from 'react';
import { getErrorMessage, uploadFile } from '@/lib/fetch';
import { page, shared } from '@/lib/responsive/pattrens/forms';

type Props = { value: string; onChange: (id: string) => void };

/** Checks the file, uploads it to /api/files, stores the returned id. */
export function FileUploadField({ value, onChange }: Props) {
  const [status, setStatus] = useState<string | null>(null);
  const [error, setError] = useState<string | null>(null);

  async function onPick(file: File | undefined) {
```

```
    if (!file) {
      return;
    }
    setError(null);
    setStatus('Uploading...');
    try {
      onChange(await uploadFile(file));
      setStatus(`Uploaded ${file.name}`);
    } catch (e) {
      setStatus(null);
      setError(getErrorMessage(e));
    }
  }

  return (
    <div>
      <input
        type="file"
        className={shared.input}
        onChange={(event) => onPick(event.target.files?.[0])}
      />
      {value && status && <p className={page.muted}>{status}</p>}
      {error && <p className={page.error}>{error}</p>}
    </div>
  );
}
```

File: `components/SurveyForm.tsx`. Public survey form.

```
'use client';

import { zodResolver } from '@hookform/resolvers/zod';
import { useMemo, useState } from 'react';
import { useForm, type FieldValues } from 'react-hook-form';
import { api, getErrorMessage } from '@/lib/fetch';
import { page, shared, survey as p } from '@/lib/responsive/pattrens/forms';
import type { Form } from '@/lib/schemas/form';
import { buildAnswerSchema } from '@/lib/schemas/submission';
import { QuestionField } from './QuestionField';

/** Fills in a survey with a schema built from its questions, then submits. */
export function SurveyForm({ form }: { form: Form }) {
  const [done, setDone] = useState(false);
  const [serverError, setServerError] = useState<string | null>(null);
  // The same rules the API applies, built from this form's own questions.
  const schema = useMemo(
    () => buildAnswerSchema(form.questions),
    [form.questions],
  );
  const defaults = useMemo(
    () =>
      Object.fromEntries(
        form.questions.map((q) => [q.id, q.type === 'multi_choice' ? [] : '']),
      ),
    [form.questions],
  );
  const {
    control,
    handleSubmit,
    formState: { errors, isSubmitting },
  } = useForm<FieldValues>({
    // The generic schema is checked on the server again.
    resolver: zodResolver(schema as never),
    defaultValues: defaults,
```

```
  });

  async function onSubmit(answers: FieldValues) {
    setServerError(null);
    try {
      await api('@post/forms/:id/submissions', {
        params: { id: form.id },
        body: { answers },
      });
      setDone(true);
    } catch (error) {
      setServerError(getErrorMessage(error));
    }
  }

  if (done) {
    return <p>Thank you. Your response was recorded.</p>;
  }

  return (
    <form className={p.form} onSubmit={handleSubmit(onSubmit)}>
      {form.questions.map((question) => (
        <QuestionField
          key={question.id}
          question={question}
          control={control}
          error={errors[question.id]?.message as string | undefined}
        />
      ))}
      {serverError && <p className={page.error}>{serverError}</p>}
      <button type="submit" className={shared.button} disabled={isSubmitting}>
        Submit
      </button>
    </form>
  );
}
```

File: `components/SurveyLoader.tsx`. Loads a form for the public page.

```
'use client';

import { api } from '@/lib/fetch';
import { page } from '@/lib/responsive/pattrens/forms';
import { useLoad } from '@/lib/useLoad';
import { SurveyForm } from './SurveyForm';

/** Loads a form for the public page. */
export function SurveyLoader({ formId }: { formId: string }) {
  const { data, error, loading } = useLoad(
    () => api('/forms/:id', { params: { id: formId } }),
    [formId],
  );
  if (loading) {
    return <p className={page.muted}>Loading...</p>;
  }
  if (error || !data) {
    return <p className={page.error}>{error ?? 'Form not found'}</p>;
  }
  return (
    <>
      <h1 className={page.heading}>{data.title}</h1>
      {data.description && <p className={page.muted}>{data.description}</p>}
      <SurveyForm form={data} />
    </>
```

```
  );
}
```

File: `components/FormList.tsx`. Dashboard list.

```
'use client';

import Link from 'next/link';
import { api } from '@/lib/fetch';
import { list, page, shared } from '@/lib/responsive/pattrens/forms';
import { useLoad } from '@/lib/useLoad';

/** Dashboard list with links to the survey and its responses. */
export function FormList() {
  const { data, error, loading } = useLoad(() => api('/forms'), []);
  if (loading) {
    return <p className={page.muted}>Loading...</p>;
  }
  if (error || !data) {
    return <p className={page.error}>{error}</p>;
  }
  if (data.length === 0) {
    return <p className={page.muted}>No forms yet.</p>;
  }
  return (
    <ul>
      {data.map((form) => (
        <li key={form.id} className={list.item}>
          <div>
            <div>{form.title}</div>
            <div className={page.muted}>
              {form.questionCount} questions, {form.responseCount} responses
            </div>
          </div>
          <div className={list.actions}>
            <Link className={shared.link} href={`/f/${form.id}`}>
              Open
            </Link>
            <Link className={shared.link} href={`/forms/${form.id}/responses`}>
              Responses
            </Link>
          </div>
        </li>
      ))}
    </ul>
  );
}
```

File: `components/ResponsesView.tsx`. Responses table with paging.

```
'use client';

import { useState } from 'react';
import { api } from '@/lib/fetch';
import { page, shared, table as t } from '@/lib/responsive/pattrens/forms';
import { useLoad } from '@/lib/useLoad';

const PAGE_SIZE = 20;

/** Table with one column per question and paging; file answers are links. */
export function ResponsesView({ formId }: { formId: string }) {
  const [pageNumber, setPageNumber] = useState(1);
  const { data, error, loading } = useLoad(async () => {
    const [form, responses] = await Promise.all([
```

```
    api('/forms/:id', { params: { id: formId } }),
    api('/forms/:id/submissions', {
      params: { id: formId },
      query: { page: pageNumber, limit: PAGE_SIZE },
    }),
  ]);
  return { form, responses };
}, [formId, pageNumber]);

if (loading) {
  return <p className={page.muted}>Loading...</p>;
}
if (error || !data) {
  return <p className={page.error}>{error}</p>;
}
const { form, responses } = data;
const pages = Math.max(1, Math.ceil(responses.total / PAGE_SIZE));

return (
  <>
    <h1 className={page.heading}>{form.title}: responses</h1>
    <div className={t.wrap}>
      <table className={t.table}>
        <thead>
          <tr>
            <th className={t.th}>Submitted</th>
            {form.questions.map((q) => (
              <th key={q.id} className={t.th}>
                {q.label}
              </th>
            ))}
          </tr>
        </thead>
        <tbody>
          {responses.items.map((item) => (
            <tr key={item.id}>
              <td className={t.td}>
                {new Date(item.createdAt).toLocaleString()}
              </td>
              {form.questions.map((q) => {
                const value = item.answers[q.id];
                return (
                  <td key={q.id} className={t.td}>
                    {q.type === 'file' && typeof value === 'string' ? (
                      <a className={shared.link} href={value}>
                        Download
                      </a>
                    ) : Array.isArray(value) ? (
                      value.join(', ')
                    ) : (
                      value
                    )}
                  </td>
                );
              })}
            </tr>
          ))}
        </tbody>
      </table>
    </div>
    <div className={t.pager}>
      <button
        className={shared.buttonGhost}
        disabled={pageNumber <= 1}
        onClick={() => setPageNumber(pageNumber - 1)}
```

```
        >
          Previous
        </button>
        <span>
          Page {pageNumber} of {pages}
        </span>
        <button
          className={shared.buttonGhost}
          disabled={pageNumber >= pages}
          onClick={() => setPageNumber(pageNumber + 1)}
        >
          Next
        </button>
      </div>
    </>
  );
}
```

13.8 Pages

File: `app/layout.tsx`. Root layout.

```
import type { Metadata } from 'next';
import './globals.css';

export const metadata: Metadata = {
  title: 'Survey Forms',
  description: 'Build a survey, share a link, collect validated responses.',
};

export default function RootLayout({ children }: LayoutProps<'/'>) {
  return (
    <html lang="en">
      {/* Browser extensions such as Grammarly add attributes before React loads. */}
      <body suppressHydrationWarning>{children}</body>
    </html>
  );
}
```

File: `app/page.tsx`. Dashboard.

```
import Link from 'next/link';
import { FormList } from '@/components/FormList';
import { list, page, shared } from '@/lib/responsive/pattrens/forms';

/** Dashboard: the "New form" button and the list of forms. */
export default function Home() {
  return (
    <main className={page.main}>
      <div className={list.header}>
        <h1 className={page.heading}>Survey forms</h1>
        <Link className={shared.button} href="/forms/new">
          New form
        </Link>
      </div>
      <FormList />
    </main>
  );
}
```

File: `app/forms/new/page.tsx`. Builder page.

```
import { Suspense } from 'react';
import { FormBuilder } from '@/components/FormBuilder';
import { page } from '@/lib/responsive/pattrens/forms';

/** The builder sits inside Suspense: its field array creates random ids. */
export default function NewFormPage() {
  return (
    <main className={page.main}>
      <h1 className={page.heading}>New form</h1>
      <Suspense fallback={<p className={page.muted}>Loading...</p>}>
        <FormBuilder />
      </Suspense>
    </main>
  );
}
```

File: `app/f/[formId]/page.tsx`. Public survey page.

```
import { Suspense } from 'react';
import { SurveyLoader } from '@/components/SurveyLoader';
import { page } from '@/lib/responsive/pattrens/forms';

/** Params are awaited inside Suspense, as Cache Components requires. */
async function Survey({ params }: PageProps<'/f/[formId]'>) {
  const { formId } = await params;
  return <SurveyLoader formId={formId} />;
}

export default function SurveyPage(props: PageProps<'/f/[formId]'>) {
  return (
    <main className={page.main}>
      <Suspense fallback={<p className={page.muted}>Loading...</p>}>
        <Survey {...props} />
      </Suspense>
    </main>
  );
}
```

File: `app/forms/[id]/responses/page.tsx`. Responses page.

```
import { Suspense } from 'react';
import { ResponsesView } from '@/components/ResponsesView';
import { page } from '@/lib/responsive/pattrens/forms';

/** Params are awaited inside Suspense, as Cache Components requires. */
async function Responses({ params }: PageProps<'/forms/[id]/responses'>) {
  const { id } = await params;
  return <ResponsesView formId={id} />;
}

export default function ResponsesPage(
  props: PageProps<'/forms/[id]/responses'>,
) {
  return (
    <main className={page.main}>
      <Suspense fallback={<p className={page.muted}>Loading...</p>}>
        <Responses {...props} />
      </Suspense>
    </main>
  );
}
```

Appendix: Mermaid Sources

The diagrams above were rendered from these Mermaid sources. They can be pasted into the Mermaid Live Editor, a GitHub README, or any Mermaid-aware viewer.

Database schema (`schema.mmd`)

```
erDiagram
    Form ||--o{ Question : "has (cascade delete)"
    Form ||--o{ Submission : "receives (cascade delete)"
    Submission ||--o{ Answer : "contains (cascade delete)"
    Question ||--o{ Answer : "is answered by (cascade delete)"

    Form {
        string id PK "cuid"
        string title
        string description "optional"
        boolean published "default true"
        datetime createdAt
    }
    Question {
        string id PK "cuid"
        string formId FK
        string label
        string type "short_text, long_text, number, email, date, single_choice, multi_choice, file
    "
        boolean required
        string_array options "choices for choice types"
        int order "position inside the form"
    }
    Submission {
        string id PK "cuid"
        string formId FK
        datetime createdAt
    }
    Answer {
        string id PK "cuid"
        string submissionId FK
        string questionId FK
        json value "string, list of strings, or file id"
    }
```

Firestore layout (`firestore.mmd`)

```
flowchart TB
    subgraph FS["Cloud Firestore (default) database: primary"]
        direction TB
        F["forms / {formId}<br/>title, description, createdAt,<br/>questions[ ] embedded,<br/>
    responseCount"]
        S["forms / {formId} / submissions / {submissionId}<br/>createdAt, answers { questionId:
    value }"]
        FI["files / {fileId}<br/>name, type,<br/>data (base64, max 700 KB)"]
    end
    F -- "subcollection" --> S
    S -. "file answer holds the fileId" .-> FI
    PG[("PostgreSQL<br/>local development copy only")]
    F -- "same ids, one-way copy (dev only)" --> PG
    S -- "same ids, one-way copy (dev only)" --> PG
```

Architecture (architecture.mmd)

```
flowchart LR
    subgraph Browser["Browser (Next.js client)"]
        direction TB
        RHF["react-hook-form<br/>+ zodResolver"]
        BF["better-fetch<br/>lib/fetch.ts"]
        UP["FileUploadField<br/>plain fetch + FormData"]
        DEL["DeleteFormButton<br/>(planned)"]
        EDT["Edit page + FormBuilder<br/>edit mode (planned)"]
        RHF --> BF
        DEL --> BF
        EDT --> BF
    end

    SH{{"Shared Zod schemas<br/>lib/schemas/*.ts<br/>+ updateFormSchema (planned)"}}

    subgraph Next["Next.js server (one deployment)"]
        direction TB
        RH["app/api/[[...route]]/route.ts<br/>hono/vercel handle()"]
        subgraph Hono["Hono app (lib/server/app.ts)"]
            direction TB
            RL["rateLimit middleware<br/>429 + Retry-After (planned)"]
            AUTH["auth middleware<br/>owner check (planned, separate work)"]
            ZV{{"validate()<br/>json / param / query"}}
            R1["routes/forms.ts<br/>GET, POST, PUT (planned), DELETE"]
            R2["routes/submissions.ts"]
            R3["routes/files.ts"]
            R4["routes/sync.ts<br/>status, full sync,<br/>retry (planned)"]
        end
        subgraph Repo["Repository layer (lib/server/repo)"]
            direction TB
            FAC["forms.ts / submissions.ts<br/>facade"]
            DUAL["dual.ts<br/>mirrorSafely (dev only), readWithFallback"]
            PGR["postgres/*<br/>Prisma (local dev copy)"]
            FSR["firestore/*<br/>Admin SDK (primary)"]
            FIL["files.ts<br/>chunked (planned)"]
            OUT["outbox.ts<br/>recordFailure, processTasks (planned)"]
            SYN["sync.ts"]
        end
        RH --> RL
        RL --> AUTH
        AUTH --> ZV
        ZV --> R1
        ZV --> R2
        ZV --> R3
        ZV --> R4
        R1 --> FAC
        R2 --> FAC
        R2 --> FIL
        R3 --> FIL
        R4 --> SYN
        R4 --> OUT
        FAC --> DUAL
        DUAL --> FSR
        DUAL -- "dev only" --> PGR
        DUAL -- "mirror failed" --> OUT
        OUT --> PGR
        OUT --> FSR
        SYN --> PGR
        SYN --> FSR
    end

    LS[("Rate-limit store<br/>memory, then Redis (planned)")]
```

```
    PG[("PostgreSQL (local dev only)<br/>Form, Question, Submission, Answer<br/>+ MirrorTask (
    planned)")]
    FS[("Cloud Firestore (primary)<br/>forms, submissions, files")]
    SCH["External scheduler<br/>cron / GitHub Actions (planned)"]

    BF -- "HTTP JSON" --> RH
    UP -- "multipart POST /api/files" --> RH
    SCH -- "Bearer SYNC_TOKEN" --> RH
    RL --> LS
    PGR --> PG
    OUT --> PG
    FSR --> FS
    FIL --> FS

    SH -. "imported by" .-> RHF
    SH -. "imported by" .-> BF
    SH -. "imported by" .-> ZV

    classDef planned stroke-dasharray: 5 4,stroke:#b45309,fill:#fffbeb,color:#78350f;
    class DEL,EDT,RL,AUTH,OUT,LS,SCH planned;
```

Architecture with planned extensions (`architecture_planned.mmd`)

```
flowchart LR
    subgraph Browser["Browser (Next.js client)"]
        direction TB
        RHF["react-hook-form<br/>+ zodResolver"]
        BF["better-fetch<br/>lib/fetch.ts"]
        UP["FileUploadField<br/>plain fetch + FormData"]
        DEL["DeleteFormButton<br/>(planned)"]
        EDT["Edit page + FormBuilder<br/>edit mode (planned)"]
        RHF --> BF
        DEL --> BF
        EDT --> BF
    end

    SH{{"Shared Zod schemas<br/>lib/schemas/*.ts<br/>+ updateFormSchema (planned)"}}

    subgraph Next["Next.js server (one deployment)"]
        direction TB
        RH["app/api/[[...route]]/route.ts<br/>hono/vercel handle()"]
        subgraph Hono["Hono app (lib/server/app.ts)"]
            direction TB
            RL["rateLimit middleware<br/>429 + Retry-After (planned)"]
            AUTH["auth middleware<br/>owner check (planned, separate work)"]
            ZV{{"validate()<br/>json / param / query"}}
            R1["routes/forms.ts<br/>GET, POST, PUT (planned), DELETE"]
            R2["routes/submissions.ts"]
            R3["routes/files.ts"]
            R4["routes/sync.ts<br/>status, full sync,<br/>retry (planned)"]
        end
        subgraph Repo["Repository layer (lib/server/repo)"]
            direction TB
            FAC["forms.ts / submissions.ts<br/>facade"]
            DUAL["dual.ts<br/>mirrorSafely, readWithFallback"]
            PGR["postgres/*<br/>Prisma"]
            FSR["firestore/*<br/>Admin SDK"]
            FIL["files.ts<br/>chunked (planned)"]
            OUT["outbox.ts<br/>recordFailure, processTasks (planned)"]
            SYN["sync.ts"]
        end
        RH --> RL
```

```
        RL --> AUTH
        AUTH --> ZV
        ZV --> R1
        ZV --> R2
        ZV --> R3
        ZV --> R4
        R1 --> FAC
        R2 --> FAC
        R2 --> FIL
        R3 --> FIL
        R4 --> SYN
        R4 --> OUT
        FAC --> DUAL
        DUAL --> PGR
        DUAL --> FSR
        DUAL -- "mirror failed" --> OUT
        OUT --> PGR
        OUT --> FSR
        SYN --> PGR
        SYN --> FSR
    end

    LS[("Rate-limit store<br/>memory, then Redis (planned)")]
    PG[("PostgreSQL<br/>Form, Question, Submission, Answer<br/>+ MirrorTask (planned)")]
    FS[("Cloud Firestore<br/>forms, submissions, files (mirror)")]
    SCH["External scheduler<br/>cron / GitHub Actions (planned)"]

    BF -- "HTTP JSON" --> RH
    UP -- "multipart POST /api/files" --> RH
    SCH -- "Bearer SYNC_TOKEN" --> RH
    RL --> LS
    PGR --> PG
    OUT --> PG
    FSR --> FS
    FIL --> FS

    SH -. "imported by" .-> RHF
    SH -. "imported by" .-> BF
    SH -. "imported by" .-> ZV

    classDef planned stroke-dasharray: 5 4,stroke:#b45309,fill:#fffbeb,color:#78350f;
    class DEL,EDT,RL,AUTH,OUT,LS,SCH planned;
```

Development workflow (`development.mmd`)

```
flowchart TB
    subgraph Setup["1. Set up (once)"]
        direction LR
        S1["create-next-app<br/>--no-src-dir, Tailwind v4"]
        S2["npm install<br/>packages pinned"]
        S3[".env + .env.example<br/>Firebase key, optional local Postgres URL,<br/>SYNC_TOKEN"]
        S4["prisma migrate dev<br/>prisma generate"]
        S1 --> S2 --> S3 --> S4
    end

    subgraph Build["2. Build in layers"]
        direction LR
        B1["lib/schemas<br/>one file per concern"]
        B2["lib/server<br/>env, db, firestore,<br/>errors, methods, validate"]
        B3["lib/server/repo<br/>postgres, firestore,<br/>dual, facade, files, sync"]
        B4["lib/server/routes + app.ts<br/>+ app/api route"]
        B5["lib/fetch.ts + patterns<br/>+ components + pages"]
```

```
        B1 --> B2 --> B3 --> B4 --> B5
    end

    subgraph Check["3. Check after every layer"]
        direction LR
        C1["prettier --check"]
        C2["tsc --noEmit"]
        C3["eslint ."]
        C4["npm run build"]
        C5["curl API checks<br/>405, 404, 400, 201<br/>(a failure sends you back<br/>to the layer
    that caused it)"]
        C1 --> C2 --> C3 --> C4 --> C5
    end

    subgraph Run["4. Run and try it"]
        direction LR
        R1["npm run dev"]
        R2["create form, open link,<br/>submit, read responses"]
        R3["sync status<br/>both databases equal"]
        R1 --> R2 --> R3
    end

    Setup --> Build
    Build --> Check
    Check -- "all pass" --> Run
```

Extension roadmap (`roadmap.mmd`)

```
flowchart TB
    DONE["Built: core app<br/>forms, validation, submissions,<br/>files, Firestore primary + local
     Postgres copy,<br/>405 / 404 / 500 handling"]
    E1["1. Login and form ownership"]
    E2["2. Rate limiting"]
    E3["3. Delete button<br/>+ delete a form's files"]
    E4["4. Sync outbox<br/>+ scheduled call"]
    E5["5. Form editing"]
    E6["6. File limits<br/>chunks or bucket"]
    END["Production-ready basic app"]

    DONE --> E1
    DONE --> E2
    E1 --> E3
    E2 --> E3
    E3 --> E4
    E3 --> E6
    E4 --> E5
    E5 --> END
    E6 --> END

    classDef built fill:#ecfdf5,stroke:#047857,color:#064e3b;
    classDef planned stroke-dasharray: 5 4,stroke:#b45309,fill:#fffbeb,color:#78350f;
    class DONE built;
    class E1,E2,E3,E4,E5,E6 planned;
```

Submission sequence (`sequence_write.mmd`)

```
sequenceDiagram
    autonumber
    actor U as Respondent
    participant P as Survey page
```

```
    participant A as Hono API
    participant FS as Firestore
    participant PG as Local PostgreSQL (dev only)

    opt File question
        P->>A: POST /api/files (multipart file)
        A->>A: re-check type and size (max 700 KB)
        A->>FS: files/{fileId} = name, type, base64
        A-->>P: 201 { id }
    end

    U->>P: Submit answers
    P->>P: zodResolver validates (client)
    P->>A: POST /api/forms/:id/submissions
    A->>FS: load form + questions
    A->>A: buildAnswerSchema(questions) validates body
    alt Invalid
        A-->>P: 400 invalid_answers + issues
    else Unknown file id
        A->>FS: file exists?
        A-->>P: 400 Unknown file
    else Valid
        A->>FS: transaction: set submission, responseCount +1 only if new
        FS-->>A: saved
        opt NODE_ENV is not production and DATABASE_URL is set
            A->>PG: copy submission + answers (same ids)
            Note over A,PG: a Postgres failure is logged, not returned
        end
        A-->>P: 201 { id }
    end
```

Read fallback and sync sequence (`sequence_read.mmd`)

```
sequenceDiagram
    autonumber
    participant P as Page
    participant A as Hono API
    participant R as readWithFallback
    participant FS as Firestore
    participant PG as Local PostgreSQL (dev only)
    participant O as Developer

    P->>A: GET /api/forms/:id
    A->>R: getForm(id)
    R->>FS: primary read
    alt Firestore answers (a form or null)
        FS-->>R: form or null
        R-->>A: result (null becomes 404)
    else Firestore throws and local Postgres is enabled
        FS--xR: error (logged)
        R->>PG: fallback read
        PG-->>R: form or null
        R-->>A: result
    else Firestore throws in production
        FS--xR: error
        R-->>A: error (500)
    end
    A-->>P: 200 form, or 404

    Note over O,PG: Refresh the local copy (local only)
    O->>A: GET /api/sync/status (Bearer token)
    A->>FS: form ids and submission counts
```

```
    A->>PG: form ids and submission count
    A-->>O: missingInPostgres, onlyInPostgres, inSync
    O->>A: POST /api/sync (Bearer token)
    A->>FS: read all forms and submissions
    A->>PG: upsert forms, questions and submissions
    A->>PG: delete forms that no longer exist in Firestore
    A-->>O: forms, submissions, removed
```