FAKULTA
INFORMAČNÍCH
TECHNOLOGIÍ
ČVUT V PRAZE

NI-NLM – Lecture 7

RAG, tool calling, structured outputs, agents.

Zdeněk Kasner

31 Mar 2026

Retrieval-augmented generation

Problems with LLM knowledge

LLM knowledge is **static, lossy and incomplete**.

This is a problem especially when we need:

- Up-to-date information (news, stock prices, weather).
- Domain-specific knowledge (internal company docs, medical records).
- Verifiable answers with sources.

Question

How can we give LLMs access to external knowledge **without retraining**?

Retrieval-augmented generation (RAG)

source: Lewis et al. (2020)

Idea

Combine the LLM with a **retrieval system**: first retrieve relevant documents, then use them as context for generation → "retrieval augmented generation"

The idea was first introduced by Lewis et al. (2020):



RAG pipeline

Phase #1: Indexing

1. Chunk the documents.
2. Compute the embeddings.
3. Store them in a vector database.



Phase #2: Querying

1. Embed the user prompt.
2. Retrieve relevant chunks.
3. Concatenate them with the prompt.
4. Generate an answer.



Indexing – Step 1: Document chunking

Raw documents need to be split into chunks before indexing:

- **Fixed-size chunks**: split every N tokens (simple, but can break context).
- **Semantic chunking**: split at sentence/paragraph/section boundaries.
- **Sliding-window with overlaps**: fixed-size chunks with some overlap to preserve context.



source: Medium.com

Typical chunk sizes: 256–1024 tokens, with 10–20% overlap.

Too small → loss of context. Too large → diluted relevance and noise.

Indexing – Step 2: Embedding

source: Grootendorst (2025)

Each chunk is converted to a dense vector (embedding).



Popular embedding models: OpenAI's `text-embedding-3`, `e5`, `qwen3-embedding`, …

→ based on Transformer **decoders**.

Encoder-based embedding models are available in the SentenceTransformers library.

Intermezzo: When prompting is critical

source: Sajdoková (2026)

Decoder-based embedding models perform much worse if not prompted properly:

```
# Each query must come with a one-sentence instruction that describes the task
task = 'Given a web search query, retrieve relevant passages that answer the query'
```

source: https://huggingface.co/Qwen/Qwen3-Embedding-8B



Indexing – Step 3: Vector database

source: https://qdrant.tech/articles/what-is-a-vector-database/

The created embeddings are stored in a **vector database** (Qdrant, Chroma, FAISS, ...):





Querying – Steps 1-2: Retrieval

source: CME295

At query time, we embed the user query and find the **most similar** chunks:



Similarity is typically measured using **cosine similarity** or **dot product** between the query and document embeddings.

Querying – Steps 3-4: Generation

The retrieved chunks are inserted into the prompt as **context**:

```
System: You are a helpful assistant. Answer based on the provided context.

Context:
[Chunk 1]: "The Transformer architecture was introduced by Vaswani et al. in 2017..."
[Chunk 2]: "Self-attention allows the model to weigh different positions..."

User: What is the key innovation of the Transformer?
```

Question

Can a RAG-based answer be *worse* than without RAG?

Towards better RAG

source: Gao et al. (2024)

The basic pipeline can be improved at every step:

- **Query rewriting**: rephrase the query for better retrieval.
- **Hybrid search**: combine dense retrieval with keyword-based (BM25) search.
- **Reranking**: use a cross-encoder to re-score the top-k results.
- **Iterative retrieval**: multiple retrieval-generation cycles.



RAG in practice

RAG is now a standard for building knowledge-intensive LLM applications:

- **Customer support bots**: retrieve from internal knowledge bases.
- **Code assistants**: retrieve from documentation and codebase.
- **Legal / medical AI**: retrieve from domain-specific corpora.
- **Enterprise search**: “talk to your documents”.

Frameworks: LangChain, LlamaIndex, Haystack, …

> ⚠️ **RAG is not a silver bullet**
>
> RAG depends heavily on retrieval quality. If the right documents are not retrieved, the LLM still hallucinates or produces wrong answers.

Tool calling

Tool use: the basic idea

source: Grootendorst (2025)

RAG works as long as the information can be fetched based on the user query.

But what if LLMs need to access external resources **during generation**?

Idea

We give the LLM the capability to generate tool calls.

Toolformer

source: Schick et al. (2023)

Toolformer (Schick et al. 2023): a paper that introduced the idea of **LLM tool-calling**.

- A Transformer model finetuned on a corpus containing tool calls.
- The corpus built in a self-supervised way:
  - A model suggests prompt calls
  - The good suggestions (the ones that reduce LM loss after exectuing the query) are kept.
- **Tools:** QA system, Wikipedia search, calculator, calendar, MT system

The New England Journal of Medicine is a registered trademark of [QA("Who is the publisher of The New England Journal of Medicine?") → Massachusetts Medical Society] the MMS.

Out of 1400 participants, 400 (or [Calculator(400 / 1400) → 0.29] 29%) passed the test.

The name derives from "la tortuga", the Spanish word for [MT("tortuga") → turtle] turtle.

The Brown Act is California's law [WikiSearch("Brown Act") → The Ralph M. Brown Act is an act of the California State Legislature that guarantees the public's right to attend and participate in meetings of local legislative bodies.] that requires legislative bodies, like city councils, to hold their meetings open to the public.

How tool calling works

source: https://rlhfbook.com/c/13-tools

Once the model generates the tool call:

1. the **output is evaluated** using an external tool,
2. the **result is appended** to the generated text.



How to scale tool calling

source: Grootendorst (2025)

There are many tools that a model can potentially call. Describing the interface of each of them can get cumbersome.



Welcome the MCP

source: https://modelcontextprotocol.io/docs/learn/server-concepts

Model Context Protocol (MCP): standardized way to access tools based on JSON.

Example tool specification

```
tools = [{"type": "function",
    "function": {
        "name": "get_weather",
        "description": "Get current weather for a city",
        "parameters": {
            "type": "object",
            "properties": {
                "city": {"type": "string", "description": "City name"}}}}]
```

Example: what the model returns

```
tool_calls = [{function: {name: "get_weather", arguments: '{"city": "Prague"}'}}]
```

MCP architecture

source: Grootendorst (2025)

MCP describes not just the JSON format, but the entire architecture around it:

- **MCP client**: the application managing the LLM (VSCode, Claude Code, ...)
- **MCP server**: the application that can be managed with tools (Github, database, ...)



Issues with MCP

source: https://demiliani.com/2025/09/04/model-context-protocol-and-the-too-many-tools-problem/

MCP tool descriptions can use up a lot of input tokens:



→ This is currently and open issue.

Can be mitigated with dynamic content discovery or using Skills (`.md` files that include description of the tool's CLI) instead.

Structured outputs

Enforcing output format

By default, there is no guarantee whatsoever on how the LLM output will look like.

Expected output:

```
{
  "companies": [
    {"name": "Apple", "revenue": 365},
    {"name": "Microsoft", "revenue": 168}
  ]
}
```

Actual output:

```
Sure! Here's the information you requested:
```json
{
  "companies": [
    {"name": "Apple", "revenue": 365},
...
```

I hope this helps!
```

Question

How might we enforce that the output will look exactly as required?

Basic ways to control LLM output

Solution 1: Answer prefix

Prefix model's answer to guide its response.

Prompt:

```
{
  "user" : "Generate a single-paragraph weather forecast based on the data: [data]"
  "assistant": "Sure, here is the required forecast: \n\""
}
```

→ Very simple cases only.

Solution 2: Prompt specifications + few-shot prompting

Describe the desired output format **very precisely** (+ include examples).

Prompt:

```
CRITICAL: You MUST respond in EXACTLY the
specified format with no additional text,
explanations, or commentary. Do NOT include any
introductory phrases, reasoning, or extra content.
Any deviation from this exact format will cause
system failure.
```

source: @ChatGPTapp

→ But how much pleading is enough? 🤔

Basic ways to control LLM output

Solution 3: Prompt chaining

1. Ask the model to **extract relevant facts:**

```
List all companies mentioned in the text along with their reported revenue and year.
```

2. Ask the model to **format those facts**:

```
Format the extracted information as a JSON array with fields: name, revenue, and year.
```

3. Ask the model to **validate the output**:

```
Check that all values in the JSON are correctly formatted.
```

→ More robust, but can run into the same issues as previous approaches.

(Less) basic ways to control LLM output

source: Wang et al. (2025)

Solution 4: Model finetuning

Finetune a small model to generate only the output in the desired format → use it to post-process the output from the large LLM.



Constrained decoding

source: dataiku.com

Idea

Instead of hoping the model produces valid output, we **force it** during decoding.

Token masking

→ At each step, allow only the tokens that are valid according to our constraints.



How to specify the constraints?

Question

Imagine we want to force the model output to be one of the following:

1. A valid **number** or **e-mail address**.
2. A **JSON object** with specific fields.
3. A **text string** with placeholders (numbers, multiple choice, etc.) infilled.

How to specify each of these options?

How to specify the constraints?

Number / email:

Regular expressions

```
# positive decimal
r"(^[1-9][0-9]*$)

# e-mail address (simple version)
r"(^[a-zA-Z0-9_.+-]+@[a-zA-Z0-9-]+\.[a-zA-Z0-9-.]+$)"
```

JSON object:

Pydantic models

```
class Company(BaseModel):
    name: str
    revenue: float
    year: int = 2021

class Response(BaseModel):
    companies: List[Company]
    total_count: int
```

Text string:

Generative constructs

```
"The answer is "
+
GENERATE(regex=r"\d+")
+
" with confidence "
+
GENERATE(choices=["high","med",
"low"])
```

Intermezzo: JSON schema vs Pydantic models

Pydantic models

```python
class Company(BaseModel):
    name: str
    revenue: float
    year: int = 2021

class Response(BaseModel):
    companies: List[Company]
    total_count: int
```

JSON schema (equivalent)

```json
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "Response",
  "type": "object",
  "properties": {
    "companies": {
      "type": "array",
      "items": {
        "type": "object",
        "properties": {
          "name": { "type": "string" },
          "revenue": { "type": "number" },
          "year": {
            "type": "integer",
            "default": 2021
          }
        },
        "required": ["name", "revenue", "year"]
      }
    },
    "total_count": { "type": "integer" }
  },
  "required": ["companies", "total_count"]
}
```

How to intervene on the generation process?

We can convert any regular expression to a **finite-state machine (FSM)** and use it to determine which tokens are valid at each step.

Regular expression

(positive decimal number)

```
r"[1-9][0-9]*"
```

Finite-state machine



- During decoding, we move along the edges in the FSM and keep track of the state.
- **Allowed tokens** = outgoing edges from the state we are currently in.

How to intervene on the generation process?

source: https://lmsys.org

What about **JSON schemas** or **interleaved generative constructs**?

→ We can convert them to a regular expression (and that to a FSM).



Regular Expression

Finite State Machine



Can we go deeper?

For arbitrarily nested structures (JSON with deep nesting, HTML, code), we need **context-free grammars (CFGs)** and **pushdown automata**:



+

Structured outputs & libraries

Libraries for **local open models** support JSON mode, enums, regexes, CFGs, ...:

Level	Frameworks	Note
API frameworks	vLLM, llama.cpp, SGLang, Ollama	API – use `response_format`
Libraries	Outlines, XGrammar, Guidance, BAML	For custom integration
Low-level	HF Transformers `LogitsProcessor`	Low-level implementation

Commercial providers (OpenAI, Gemini, Claude) support primarily JSON outputs:

Structured model outputs

Ensure text responses from the model adhere to a JSON schema you define.

JSON is one of the most widely used formats in the world for applications to exchange data.

Structured Outputs is a feature that ensures the model will always generate responses that adhere to your supplied JSON Schema, so you don't need to worry about the model omitting a required key, or hallucinating an invalid enum value.

source: OpenAI docs

Structured outputs

Copy page

Get validated JSON results from agent workflows

Structured outputs constrain Claude's responses to follow a specific schema, ensuring valid, parseable output for downstream processing. Two complementary features are available:

- **JSON outputs** (`output_config.format`): Get Claude's response in a specific JSON format
- **Strict tool use** (`strict: true`): Guarantee schema validation on tool names and inputs

source: Claude docs

Why constrained decoding can be tricky

source: Cooper (2024)

> *Most constrained decoding pitfalls are due to misalignment between what the model **wants** to output and what it is **forced** to output.*
>
> — *aidancooper.co.uk*

Main issues:

1. The model may perform worse if forced to output a **JSON instead of a "natural format"** (e.g., plain text, code diffs).
2. Some libraries still do not support **separating structured content from reasoning** → reasoning may be prevented with structured outputs.
3. **Token boundaries** do not match the FSM states based on characters (e.g., the sequence {"name":" can be a single token)

Pitfall: tokenization and FSMs

source: blog.dottxt.ai

The constraints are defined on the character level, but the model works with tokens.

The FSM must be **adapted to the tokenizer's vocabulary**:



Preprocessing is quite slow and the resulting FSM can be much larger (but this is now optimized using libraries like llguidance).

LLM agents

Reasoning and acting

So far, we considered reasoning and acting to be separate processes:



Reasoning Only
(e.g., chain-of-thought)

Act Only
(e.g., Toolformer)

Reasoning and acting

ReAct: Yao et al. (2023): combining **reasoning** and **acting** in a single loop.

→ A base paradigm for what is now called "LLM agents."



ReAct
(Reason + Act)

The ReAct framework

source: Grootendorst (2025)

The agent in ReAct iterates through the **thought** → **action** → **observation** loop until it reaches a final answer:

- **Thought**: reasoning about the current situation.
- **Action**: executing a tool.
- **Observation**: observing the result of the action.



What is an LLM agent?

source: Grootendorst (2025)

To a degree, the LLM agents classical AI agent definitions.

They can **observe** the environment (→input), **plan** (→reasoning), and **act** (→tools):



Simon Willison's Weblog

I was going slightly spare at the fact that every talk at this Anthropic developer conference has used the word "agents" dozens of times, but nobody ever stopped to provide a useful definition.

I'm now in the "Prompting for Agents" workshop and Anthropic's Hannah Moran finally broke the trend by saying that at Anthropic:

> Agents are models using tools in a loop

I can live with that! I'm glad someone finally said it out loud.

LLM agents in code assistants



Multi-agent systems

source: Grootendorst (2025)

Multi-agent systems: multiple specialized agents, each with their own tools and memory, coordinated by a supervisor:



OpenClaw

source: https://openclaw.ai

OpenClaw

source: OpenClaw (2025)

OpenClaw can integrate any LLM with various applications (Whatsapp, Spotify, Gmail, ...) via **MCPs**, making agents very useful and super dangerous at the same time 😈



I said "Check this inbox too and suggest what you would archive or delete, don't action until I tell you to." This has been working well for my toy inbox, but my real inbox was too huge and triggered compaction. During the compaction, it lost my original instruction 🤦‍♀️

source: https://x.com/JFPuget/status/2025877071939911791/photo/1

Summary

Summary

- **RAG**: retrieve relevant documents and use them as context for generation. The de facto standard for knowledge-intensive LLM apps.
- **Tool calling**: LLMs can use external tools (APIs, code, search). Pioneered by Toolformer, now a standard feature.
- **MCP**: an open protocol for standardizing tool access across LLM applications.
- **Structured outputs**: constrained decoding forces valid output formats (JSON, regex, CFG) during generation.
- **Agents**: LLMs wrapped with memory, tools, and planning (ReAct, Reflexion). Increasingly used in code assistants and autonomous systems.

Links and resources

- Lewis et al. (2020): Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks
- Gao et al. (2024): Retrieval-Augmented Generation for Large Language Models: A Survey
- Schick et al. (2023): Toolformer: Language Models Can Teach Themselves to Use Tools
- Anthropic: Model Context Protocol (MCP)
- Willard & Louf (2023): Efficient Guided Generation for Large Language Models (Outlines)
- OpenAI: Structured Outputs in the API
- Yao et al. (2023): ReAct: Synergizing Reasoning and Acting in Language Models
- Shinn et al. (2023): Reflexion: Language Agents with Verbal Reinforcement Learning
- Grootendorst (2025): A Visual Guide to LLM Agents