FAKULTA
INFORMAČNÍCH
TECHNOLOGIÍ
ČVUT V PRAZE

NI-NLM – Lecture 4

LLM inference

Zdeněk Kasner

10 Mar 2026

From training to text generation

Recap: training

Model stages:

random neural network

Recap: training

Model stages:

random neural network

Training stages:

1 **Pre-training** 🌍

⬇ **Prague is the capital of Czechia** (...)

Recap: training

Model stages:

random neural network

1 ⬇

"autocomplete on steroids"

base / foundational model

Training stages:

1 **Pre-training** 🌍

⬇ **Prague is the capital of Czechia** (...)

Recap: training

Model stages:

random neural network

1

"autocomplete on steroids"

base / foundational model

Training stages:

1 **Pre-training** 🌍

Prague is the capital of Czechia (...)

2 **Instruction tuning** 💬

user: What is the capital of Czechia?

assistant: **Prague**

Recap: training

Model stages:

random neural network

1 ⬇

"autocomplete on steroids"

base / foundational model

2 ⬇

assistant

instruction-tuned model

Training stages:

1 **Pre-training** 🌍

⬇ **Prague is the capital of Czechia** (...)

2 **Instruction tuning** 💬

user: What is the capital of Czechia?

⬇ assistant: **Prague**

Recap: training

Model stages:

random neural network

1

"autocomplete on steroids"

base / foundational model

2

assistant

instruction-tuned model

Training stages:

1 **Pre-training** 🌍

Prague is the capital of Czechia (...)

2 **Instruction tuning** 💬

user: What is the capital of Czechia?

assistant: **Prague**

3 **Human preference optimization** 🧑‍⚖️

user: What is the capital of Czechia?

answer #1: Prague.

answer #2: The capital of Czechia is Prague. It is the largest (...)

Recap: training

Model stages:

random neural network

1

"autocomplete on steroids"

base / foundational model

2

assistant

instruction-tuned model

3

helpful assistant

Training stages:

1 **Pre-training** 🌍

Prague is the capital of Czechia (...)

2 **Instruction tuning** 💬

user: What is the capital of Czechia?

assistant: **Prague**

3 **Human preference optimization** 🧑‍⚖️

user: What is the capital of Czechia?

answer #1: Prague.

answer #2: The capital of Czechia is Prague. It is the largest (...)

LLM inference

This lecture: **LLM inference** = we have a trained model and we want to **use it**.



LLM inference

This lecture: **LLM inference** = we have a trained model and we want to **use it**.



Question

What is the difference between inference, generation, and decoding?

LLM Inference

Inference – The concept of using a trained model for **making predictions** on new data (for classification, sequence tagging, text generation, ...).

Generation – The process of using a trained model for **producing a sequence of tokens**.

Decoding – The algorithm of **selecting the next token** using the model's internal representation.



Training vs. inference

Training



Teacher forcing: We know what token should come next, so we use it to train the model.

Inference



Decoding: We need to *select* what token should come next.

Generating text: autoregressive decoding

👩‍🍳 Recipe: How to generate text autoregressively

1. **Start with the context**: a sequence of tokens (a “prompt” if instruction-tuned).

Generating text: autoregressive decoding

👩‍🍳 Recipe: How to generate text autoregressively

1. **Start with the context**: a sequence of tokens (a “prompt” if instruction-tuned).
2. **Feed the context** into the LLM.

Generating text: autoregressive decoding

👩‍🍳 Recipe: How to generate text autoregressively

1. **Start with the context**: a sequence of tokens (a “prompt” if instruction-tuned).
2. **Feed the context** into the LLM.
3. **Select the next token** from the model-generated probability distribution.

Generating text: autoregressive decoding

👩‍🍳 Recipe: How to generate text autoregressively

1. **Start with the context**: a sequence of tokens (a “prompt” if instruction-tuned).
2. **Feed the context** into the LLM.
3. **Select the next token** from the model-generated probability distribution.
4. **Append the selected token** to the sequence.

Generating text: autoregressive decoding

👩‍🍳 Recipe: How to generate text autoregressively

1. **Start with the context**: a sequence of tokens (a “prompt” if instruction-tuned).
2. **Feed the context** into the LLM.
3. **Select the next token** from the model-generated probability distribution.
4. **Append the selected token** to the sequence.
5. **Repeat** from (3) until the EOS (end-of-sequence) token is selected.

What happens during LLM inference?

Inference for dummies 🐥



https://animatedllm.github.io/generation-simple

What happens during LLM inference?

Advanced version 🎓



https://animatedllm.github.io/generation-model

What happens during LLM inference?

Hardcore version 🤘



https://bbycroft.net/llm

Decoding algorithms

Decoding the next token

For each time step t, the decoder outputs **probability distribution** over the tokens given the previous context $P(y_t \mid y_{1:t-1}, X)$.



That is where the "job" of the Transformer decoder ends → it is up to us (or our decoding algorithm) to **use the distribution for decoding the next token**.

Exact inference

🏆 **Holy grail**: Find the most probable continuation to our prompt:

$$y^* = \arg\max_{y \in \mathcal{Y}} P(y) = \arg\max_{y \in \mathcal{Y}} \prod_{i=1}^{t} P(y_i \mid y_1, \ldots, y_{t-1})$$

Question

Why is this not possible in practice?

Exact inference

🏆 **Holy grail**: Find the most probable continuation to our prompt:

$$y^* = \arg\max_{y \in \mathcal{Y}} P(y) = \arg\max_{y \in \mathcal{Y}} \prod_{i=1}^{t} P(y_i \mid y_1, \ldots, y_{t-1})$$

Question

Why is this not possible in practice?

Intractable (exponential search space) → we need to approximate it.

Exact inference

🏆 **Holy grail**: Find the most probable continuation to our prompt:

$$y^* = \arg\max_{y \in \mathcal{Y}} P(y) = \arg\max_{y \in \mathcal{Y}} \prod_{i=1}^{t} P(y_i \mid y_1, \ldots, y_{t-1})$$

Question

Why is this not possible in practice?

Intractable (exponential search space) → we need to approximate it.

Question

And is it even our goal?

Decoding algorithms

Two approaches we typically combine in practice:

Approximating the most probable sequence 🤔

Greedy search / beam search

Adding stochasticity 🎲

Temperature / top-k sampling / nucleus (top-p) sampling

Greedy decoding

source: HF Blog

Algorithm

In each step t, select the most probable token: $y_t = \arg\max_{y_t \in \mathcal{V}} P(y_t \mid y_1, \ldots, y_{t-1})$

- Very fast, often works satisfactorily (especially with LLMs).
- Non-parametric (no hyperparameters to tune).
- But: may produce sequences that are too generic.



Beam search

source: HF Blog

Algorithm

Parameter k: number of sequences (beams).

Each step t:

1. Extend the sequences from step $t-1$ with all possible tokens.
2. Select the k most probable sequences for step $t+1$.



- $k = 1$ → greedy decoding; larger k → slower, but better approximation.
- $k > 1$ allows re-ranking results.

Adding stochasticity

source: HF Blog

Instead of picking the most probable token, we can randomly sample the next token y_t according to its conditional probability distribution:

$$y_t \sim P(y_t \mid y_1, \ldots, y_{t-1})$$



Adding stochasticity

source: HF Blog

Instead of picking the most probable token, we can randomly sample the next token y_t according to its conditional probability distribution:

$$y_t \sim P(y_t \mid y_1, \ldots, y_{t-1})$$



Question

Why is this sampling from the entire vocabulary not a good idea?

Top-k sampling

source: HF Blog

Selecting the token in each step randomly from $k \in \{1, \ldots, |\mathcal{V}|\}$ most probable tokens.

The truncated distribution is re-weighted using softmax.



Top-p (nucleus) sampling

source: HF Blog

Sampling from the **nucleus**: set of the most probable tokens with combined probability summing to $p \in (0, 1]$.

Similar to top-k, but with a **variable** k in each step.



Temperature

source: CME295

The shape of the output distribution can be adjusted using the **temperature** T:

$$\mathrm{softmax}(z) = \frac{\exp\left(\frac{z_t}{T}\right)}{\sum_j \exp\left(\frac{z_j}{T}\right)}$$

$T = 1$: **original distribution**

$T < 1$: **more peaked**

($T = 0$ → greedy decoding)

$T > 1$: **more uniformly random**







Is greediness all you need?

r/MachineLearning • 8 mo. ago
zyl1024

[D] What happened to "creative" decoding strategy?

Discussion

For GPT-2 and most models at that time, the naive greedy decoding is extremely prone to generating repetitive and nonsensical outputs very fast, and many techniques, such as top-p sampling, nucleus sampling, repetition penalty, n-gram penalty, etc. are needed. (e.g. https://arxiv.org/pdf/1904.09751)

For recent LLMs, I haven't been using any of these tricks, and instead, any temperature between 0 and 1 seems to work just fine. The only repetitive generation that I've observed seem to be in math reasoning, when the model wants to do some exhaustive search that didn't succeed.

So are all these custom decoding strategies a thing of the past, and we don't need to worry about degenerate content generation anymore?

23 12 Share

source: Reddit

Running LLMs locally

How to use LLMs



How to use LLMs

Proprietary APIs

- OpenAI (ChatGPT, GPT-4o)
- Anthropic (Claude)
- Google (Gemini)
- ...

✅ Easy to use, no hardware needed

❌ Paid, no control over the model

Open models (local)

- Meta (Llama)
- Mistral
- Qwen
- ...

✅ Free, full control

❌ Requires hardware (GPU)

Frameworks for running open LLMs

source: HF Transformers

HuggingFace transformers: Python library for loading models from the HuggingFace model repository.

Transformers

build failing | license Apache-2.0 | website online | release v4.49.0 | Contributor Covenant v2.0 adopted | DOI 10.5281/zenodo.7391177

English | 简体中文 | 繁體中文 | 한국어 | Español | 日本語 | हिन्दी | Русский | Português | తెలుగు | Français | Deutsch | Tiếng Việt | اردو | العربية |

State-of-the-art Machine Learning for JAX, PyTorch and TensorFlow

Frameworks for running open LLMs

source: Ollama

Ollama: running LLMs locally, easy to use, focus on quantized models.



Frameworks for running open LLMs

source: vLLM

vLLM: efficient library for serving of LLMs at scale.

Hands-on session 🧑‍💻

(continue until 14:50)

http://tiny.cc/nlm-gen

Summary

Summary

- **Terms**:
  - **inference** = using a trained model for predictions
  - **generation** = producing a sequence of tokens
  - **decoding** = selecting the next token.
- **Greedy decoding** is the simplest approach
- **beam search** improves it by keeping k hypotheses.
- **Stochastic methods** (top-k, top-p, temperature) add randomness to avoid repetitive and dull outputs.
- Open LLMs can be run locally using **HuggingFace transformers**, **Ollama**, or **vLLM**.

Links and resources

- HuggingFace models
- Awesome LLM: curated list of resources
- Transformer inference: 3D visualization
- HuggingFace decoding algorithms overview
- HuggingFace text generation strategies
- Common pitfalls when generating text with LLMs
- Visualizing decoding strategies
- Minimum Bayes Risk decoding

Further reading

- **On NMT Search Errors and Model Errors: Cat Got Your Tongue?** (Stahlberg and Byrne, 2019) – what happens if one manages to approximate exact inference
- **On decoding strategies for neural text generators** (Wiher et al., 2022) – language generation tasks vs. decoding strategies.
- **If beam search is the answer, what was the question?** (Meister et al., 2020) – why does beam search work so well?
- **Understanding the properties of Minimum Bayes Risk decoding in neural machine translation** (Müller and Sennrich, 2021) – when can MBR be useful?

Bonus: extra decoding algorithms

Minimum Bayes Risk (MBR) decoding

source: Minimum Bayes Risk Decoding

Selecting the sequence **most similar to other sequences** = "consensus decoding":

$$y^* = \arg\max_{y_k \in \mathcal{Y}} \sum_{y_\ell \in \mathcal{Y} \setminus \{y_k\}} \mathrm{sim}(y_k, y_\ell)$$

- Useful for minimizing pathological behavior.
- Intractable → we need a sampling algorithm.
- Application in ASR and machine translation.



Mirostat

source: Basu et al. (2021)

Aims to eliminate **repetition and incoherent text** in stochastic algorithms.

Adapting the k parameter based on the desired text perplexity.

Parameters:

- τ – the target perplexity
- η – learning rate

Algorithm 1: Adaptive top-k sampling for perplexity control

Target cross entropy τ, maximum cross entropy $\mu = 2 * \tau$, learning rate η
while *more words are to be generated* **do**
  Compute $\hat{s}$ from (40): $\frac{\sum_{i=1}^{N-1} t_i b_i}{\sum_{i=1}^{N-1} t_i^2}$
  Compute k from (41): $k = \left(\frac{\hat{\epsilon} 2^{\mu}}{1 - N^{-\hat{\epsilon}}}\right)^{\frac{1}{\hat{s}}}$
  Sample the next word X using top-k sampling
  Compute error: $e = \mathfrak{S}(X) - \tau$
  Update μ: $\mu = \mu - \eta * e$
end

Mirostat

"mirum" = surprise, "stat" = control

(Locally) typical sampling

source: Meister et al. (2023)

Similar to Mirostat, but **dynamic**: the perplexity is not pre-specified.

Ensures that in each decoding step, text perplexity is **close to the model perplexity**.

Example: coin toss

$p(H) = 0.75$, $p(T) = 0.25$:

- $HHHH$ → most probable sequence
- $HTHH$ → typical sequence



Originates from the information theory: **typical messages** are the messages that we would expect from the process.