Technical data sheet

MULTIline FORCE UV

High-strength, reinforced hose liner for the structural rehabilitation of pipes.

Product features	
Product name	Lateral Repairs MULTIline FORCE UV
Product code	FORCEUV
Length	50 m; 100 m / 164 feet; 328 feet
Diameter	100 mm – 600 mm / 4 inch – 24 inch
Wall thickness	3,30 mm / 0,13 inch
Liner undersized	10 %
Heat resistance	Max. 80 °C / 176 °F
Negotiating bends	Max. 45°

Material features	
Material	Polyester needle-punched fleece liner with filament reinforcement and a thermoplastic polyurethane (TPU) coating.
Textile	Polyester
Textile weight	500 g/m²
Coating	TPU
Coating weight	150 g/m²
Colour / coating	White / Transparent
Water penetration	≥ 500 mbar
Storage	Protected from light, dry

Features			Length		Resin	Pressure		Roller
Dimension	Flat (mm)	Bend	L + *	L + **	kg / m	Inversion (bar)	3D (bar)	Roller gap
DN 100	~140	2 x 45	~3 cm	–	~ 1.15	0,35-0,40	–	7mm
DN 125	~175	2 x 45	~3 cm	–	~1.44	0,30-0,45	–	7mm
DN 150	~212	2 x 45	~3 cm	–	~1.72	0,30-0,50	–	7mm
DN 200	~282	2 x 45	~3 cm	–	~2.30	0,25-0,40	–	7mm
DN 225	~318	2 x 45	~3 cm	–	~2.60	0,20-0,40	–	7mm
DN 250	~353	2 x 45	~3 cm	–	~2.90	0,20-0,40	–	7mm
DN 300	~424	2 x 45	~3 cm	–	~3.21	0,20-0,40	–	7mm

Additional length *per bend >45° **Approx 4 % loss in length for every 25 % change in dimension

Resin quantity

Calculate the exact resin amount with the free Lateral Repairs app.

iPhone · App Store

Android · Google Play

Notice

- Given the diversity of installation conditions, application areas and process techniques, the information in this data sheet can only be regarded as non-binding guideline values.
- Length addition: add the stated percentage of the liner length, plus the cm value per 45° bend; calculate the exact resin quantity with the Lateral Repairs app (scan the QR codes).
- The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher pressures and accept no liability.
- All data were determined at 20 °C / 68 °F and are bench-scale values that can differ on industrial job sites.

Issue: V2026.1 · 2026.06

www.lateralrepairs.com info@lateralrepairs.com +370 698 76 581 Paberžių g. 5, Tauragė, Lithuania, LT-72328