

Document Version: V2026.1

Date of first issue: 2021.01.21

Date viewed: 2026.05.01

MULTIline PRO 4.0 mm

Product name	Lateral Repairs MULTIline PRO 4.0 mm
Product code	PRO

Material composition	
	Multi (knitted) fleece with one sided TPU.

Supply data	
Pipe diameter	70, 80, 100, 125, 150, 200, 225, 250, 300. Other dimensions available on request
Liner undersized	13 %
Liner lengths	50 m; 100 m / 164 feet; 328 feet Other lengths available on request

General data	
Type of fibers	Polyester
Coating	One side TPU
Basic color	White
Color coating	Transparent
Type of basic material	Multi-layer knitted fleece with TPU coating
Used seam (stitched) and seam sealing	Seam construction with PES-Yarn Seam sealed with TPU-Tape

Physical properties			
Weight	DIN EN 12127	g/m ²	550*
Weight of coating		g/m ²	150*
Thickness		mm inch	4,00* 0,16*
Water penetration resistance (20 °C / 68 °F)	ISO 811	mbar psi	≤ 550 ≤ 7,97

Document Version: V2026.1

Date of first issue: 2021.01.21

Date viewed: 2026.05.01

MULTiline PRO 4.0 mm

Handling parameter	
Heat resistance	Max. 70 °C / 158 °F
Negotiating bends up to	Max. 90°
Pinch roller gap (impregnation)	2 x Wall thickness + 2 mm
Additional lengths	5 %

The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher inversion and/or curing pressures and accept no liability.

* = Modal value (typical value)

Additional Information – please see “methods of application”.

* WE RECOMMEND STEAM CURING WITH A CALIBRATION HOSE.