

# Safety data sheet

## MFE 7516 Vinyl Ester

Styrene-free vinyl ester resin — Safety Data Sheet according to Regulation (EC) No. 1272/2008.

### HAZARD OVERVIEW · GHS / CLP



#### Warning

**H315** Causes skin irritation. **H317** May cause an allergic skin reaction. **H319** Causes serious eye irritation.

**P280** Wear protective gloves. **P305+P351+P338** IF IN EYES: rinse cautiously with water for several minutes; remove contact lenses if easy; continue rinsing.

#### PRODUCT IDENTIFICATION

##### PRODUCT

MFE 7516 Vinyl Ester (styrene-free)

##### PRODUCT TYPE

Environmentally friendly, corrosion-resistant resin

##### INTENDED USE

SU3 Industrial · SU12 Manufacture of plastics · SU22 Professional uses

##### STABILISER

Mequinol (≥ 180 – ≤ 220 ppm)

#### MANUFACTURER & EMERGENCY

##### MANUFACTURER

Lateral Repairs UAB  
Paberžių g. 5, Tauragė, LT-72328, Lithuania

##### CONTACT

info@lateralrepairs.com · +370 612 12882 · Office +370 698 76581

##### EMERGENCY TELEPHONE

+370 612 12882, or your local emergency number

#### DOCUMENT

Safety Data Sheet

#### REGULATION

(EC) No. 1272/2008

#### VERSION

V2026.1

#### DATE OF ISSUE

2026.06

### FIRST AID · QUICK REFERENCE

#### EYE CONTACT

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### SKIN CONTACT

Wash off with soap and plenty of water. Consult a physician.

#### INHALATION

Move to fresh air and keep at rest. Get medical advice if you feel unwell.

#### IF SWALLOWED

Do NOT induce vomiting. Rinse mouth with water. Consult a physician.

## 1. Identification

**Product description:** MFE 7516 Vinyl Ester (styrene-free)

**Intended use:** Environmentally friendly, corrosion-resistant resin. SU3 — Industrial uses; SU12 — Manufacture of plastics products (compounding and conversion); SU22 — Professional uses.

**Uses advised against:** No information available

**Manufacturer:** Lateral Repairs UAB · Paberžių g. 5, Tauragė, LT-72328, Lithuania · info@lateralrepairs.com · Phone +370 612 12882 · Office +370 698 76581

**Emergency telephone:** +370 612 12882, or contact your local emergency telephone number

## 2. Hazards identification



### Signal word: Warning

**H315** Causes skin irritation. **H317** May cause an allergic skin reaction. **H319** Causes serious eye irritation.

**P280** Wear protective gloves. **P305+P351+P338** IF IN EYES: rinse cautiously with water for several minutes; remove contact lenses if present and easy to do; continue rinsing.

**Classification (EC 1272/2008):** Skin irritation H315 — Category 2; Eye irritation H319 — Category 2; Skin sensitization H317 — Category 1.

**Classification (67/548/EEC · 1999/45/EC):** Xi Irritant — R36/38; R43.

## 3. Composition / information on ingredients

**Type:** Vinyl ester resin, styrene-free

**Stabiliser:** Mequinol (≥ 180 – ≤ 220 ppm)

## 4. First-aid measures

**General advice:** Consult a physician. Show this safety data sheet to the doctor in attendance.

**If inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Consult a physician.

**Skin contact:** Wash off with soap and plenty of water. Consult a physician.

**Eye contact:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**If swallowed:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## 5. Firefighting measures

**Extinguishing media:** Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Special hazards:** Carbon oxides, nitrogen oxides (NOx).

**Advice for firefighters:** Wear self-contained breathing apparatus if necessary. Use water spray to cool unopened containers.

## 6. Accidental release measures

**Personal precautions:** Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation and remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations in low areas.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

**Containment / cleaning up:** Contain spillage, then collect with an electrically protected vacuum cleaner or by wet-brushing and place in a container for disposal according to local regulations.

## 7. Handling and storage

**Safe handling:** Avoid contact with skin and eyes; avoid inhalation of vapour or mist. Keep away from sources of ignition — no smoking. Prevent build-up of electrostatic charge.

**Storage:** Store in a cool place. Keep container tightly closed in a dry, well-ventilated place; reseal opened containers and keep upright. Recommended storage temperature ≤ 25 °C. Moisture- and light-sensitive.

## 8. Exposure controls / personal protection

**Exposure limits:** Contains no substances with occupational exposure limit values.

**Engineering controls:** Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling.

**Eye / face:** Face shield and safety glasses tested and approved to NIOSH (US) or EN 166 (EU).

**Skin:** Protective gloves to EU Directive 89/686/EEC and EN 374; inspect before use.

**Body:** Complete chemical-protective suit, selected per concentration and amount at the workplace.

**Respiratory:** Where required, full-face respirator with type ABEK (EN 14387) cartridges; if the sole means of protection, use a supplied-air respirator.

## 9. Physical and chemical properties

|                                  |                            |
|----------------------------------|----------------------------|
| Appearance                       | Clear liquid               |
| Colour                           | Yellow, transparent liquid |
| Odour                            | Ester-like                 |
| pH                               | No data available          |
| Melting / freezing point         | < -60 °C                   |
| Boiling point / range            | 67 °C at 4,7 hPa (lit.)    |
| Flash point                      | 96 °C — closed cup         |
| Vapour pressure                  | 0,1 hPa at 20 °C           |
| Relative density                 | 1,1 – 1,20 g/mL at 25 °C   |
| Partition coeff. (octanol/water) | log Pow -0,53 at 20 °C     |
| Other properties                 | No data available          |

## 10. Stability and reactivity

**Stability:** Contains stabiliser Mequinol. May polymerise on exposure to light.

**Conditions to avoid:** Exposure to light.

**Incompatible materials:** Strong acids, strong bases, strong oxidising agents, strong reducing agents.

**Hazardous decomposition:** No data available.

## 11. Toxicological information

**Acute toxicity:** LD50 oral, rat: 5050 mg/kg. LD50 dermal, rabbit: > 3 000 mg/kg.

**Skin / eye:** Skin (rabbit): irritating (24 h). Eyes (rabbit): moderate eye irritation (24 h, Draize).

**Sensitisation:** May cause sensitisation by skin contact (OECD 406).

**Carcinogenicity:** IARC: no component ≥ 0,1 % identified as a carcinogen.

**Reproductive toxicity:** Rat, female, oral — effects on fertility and on embryo/fetus reported.

## 12. Ecological information

**Toxicity to fish:** Pimephales promelas (fathead minnow): 227 mg/l — 96 h (flow-through).

**Persistence / degradability:** Readily biodegradable — 84 % (28 d, Closed Bottle test).

**PBT / vPvB:** Assessment not available (chemical safety assessment not required/conducted).

## 13. Disposal considerations

**Waste treatment:** May be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable material to a licensed disposal company.

**Contaminated packaging:** Dispose of as unused product.

## 14. Transport information

**Classification:** ADR/RID, IMDG and IATA: Not dangerous goods.

**UN number / class / packing group:** None.

**Environmental hazards:** IMDG marine pollutant: no.

## 15. Regulatory information

**Labelling:** According to Regulation (EC) No 1272/2008 — see Section 2.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**Inventory:** EINECS — substance included in the regulations (✓).

## 16. Other information

**H-statements:** H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

**R-phrases:** R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact.



The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. It is based on the present state of our knowledge and does not represent any guarantee of the properties of the product.

Safety data sheet · Issue V2026.1 · 2026.06

