

Connection Liners



Flexible polyester knitted hose with thermoplastic coating for the rehabilitation of lateral connections.

Lateral Repairs Connection Liner is a flexible, versatile solution for the rehabilitation of non-pressure pipelines, designed to restore lateral connections with precision and reliability. Manufactured from a durable polyester knitted hose with a thermoplastic coating, it is available in sizes ranging from DN50 to DN300, with 45°, 90° and 180° connection options. Custom sizes can be supplied in consultation with Lateral Repairs.

Stitched & Sealed Connection Liners

Delivery status · Material data · ISO test method

Weight	Approx. 450 g/m ²	DIN EN 29073 T1
Thickness with coating	Approx. 3.0 mm	DIN EN 29073 T2
Pore volume	Approx. 85 %	—
Fibers	Polyester	—
Coating	TPU; PUR	—
Coating thickness	Approx. 150 µm	—
Seam type	Stitched and sealed	—
Curing	Ambient, Hot Water, Steam Mix	—
Properties	DN50 to DN300 · 45°, 90°, 180° connections * other angles on request	—

Stitched (Not Sealed) Connection Liners

Delivery status · Material data · ISO test method

Weight	Approx. 450 g/m ²	DIN EN 29073 T1
Thickness with coating	Approx. 3.0 mm	DIN EN 29073 T2
Pore volume	Approx. 85 %	—
Fibers	Polyester	—
Coating	TPU; PUR	—
Coating thickness	Approx. 150 µm	—
Seam type	Stitched	—
Curing	Ambient, Hot Water, Steam Mix	—
Properties	DN50 to DN300 · 45°, 90°, 180° connections * other angles on request	—

Resin quantity

Calculate the exact resin amount with the free Lateral Repairs app.



iPhone · App Store



Android · Google Play

Notice

- The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher pressures and accept no liability.
- All data are guideline values determined under laboratory conditions and can differ on industrial job sites.