



Safety data sheet

MFE 7516 Vinyl Ester



Styrene-free vinyl ester resin — Safety Data Sheet according to Regulation (EC) No. 1272/2008.

1. Identification

Product description: MFE 7516 Vinyl Ester (styrene-free)

Intended use: Environmentally friendly, corrosion-resistant resin. SU3 — Industrial uses; SU12 — Manufacture of plastics products (compounding and conversion); SU22 — Professional uses.

Uses advised against: No information available

Manufacturer: Lateral Repairs UAB · Paberžių g. 5, Tauragė, LT-72328, Lithuania · info@lateralrepairs.com · Phone +370 612 12882 · Office +370 698 76581

Emergency telephone: +370 612 12882, or contact your local emergency telephone number

2. Hazards identification



Signal word: Warning

H315 Causes skin irritation. **H317** May cause an allergic skin reaction. **H319** Causes serious eye irritation.

P280 Wear protective gloves. **P305+P351+P338** IF IN EYES: rinse cautiously with water for several minutes; remove contact lenses if present and easy to do; continue rinsing.

Classification (EC 1272/2008): Skin irritation H315 — Category 2; Eye irritation H319 — Category 2; Skin sensitization H317 — Category 1.

Classification (67/548/EEC · 1999/45/EC): Xi Irritant — R36/38; R43.

3. Composition / information on ingredients

Type: Vinyl ester resin, styrene-free

Stabiliser: Mequinol ($\geq 180 - \leq 220$ ppm)

Relevant component: 2-Hydroxyethyl methacrylate (CAS 868-77-9)

4. First-aid measures

General advice: Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Consult a physician.

Skin contact: Wash off with soap and plenty of water. Consult a physician.

Eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5. Firefighting measures

Extinguishing media: Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards: Carbon oxides, nitrogen oxides (NOx).

Advice for firefighters: Wear self-contained breathing apparatus if necessary. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions: Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation and remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations in low areas.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Containment / cleaning up: Contain spillage, then collect with an electrically protected vacuum cleaner or by wet-brushing and place in a container for disposal according to local regulations.

7. Handling and storage

Safe handling: Avoid contact with skin and eyes; avoid inhalation of vapour or mist. Keep away from sources of ignition — no smoking. Prevent build-up of electrostatic charge.



Storage: Store in a cool place. Keep container tightly closed in a dry, well-ventilated place; reseal opened containers and keep upright. Recommended storage temperature $\leq 25^{\circ}\text{C}$. Moisture- and light-sensitive.

8. Exposure controls / personal protection

Exposure limits: Contains no substances with occupational exposure limit values.

Engineering controls: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling.

Eye / face: Face shield and safety glasses tested and approved to NIOSH (US) or EN 166 (EU).

Skin: Protective gloves to EU Directive 89/686/EEC and EN 374; inspect before use.

Body: Complete chemical-protective suit, selected per concentration and amount at the workplace.

Respiratory: Where required, full-face respirator with type ABEK (EN 14387) cartridges; if the sole means of protection, use a supplied-air respirator.

9. Physical and chemical properties

Appearance	Clear liquid
Colour	Yellow, transparent liquid
Odour	Ester-like
pH	No data available
Melting / freezing point	$< -60^{\circ}\text{C}$
Boiling point / range	67°C at 4,7 hPa (lit.)
Flash point	96°C — closed cup
Vapour pressure	0,1 hPa at 20°C
Relative density	1,1 – 1,20 g/mL at 25°C
Partition coeff. (octanol/water)	log Pow -0,53 at 20°C
Other properties	No data available

10. Stability and reactivity

Stability: Contains stabiliser Mequinol. May polymerise on exposure to light.

Conditions to avoid: Exposure to light.

Incompatible materials: Strong acids, strong bases, strong oxidising agents, strong reducing agents.

Hazardous decomposition: No data available.

11. Toxicological information

Component: 2-Hydroxyethyl methacrylate (CAS 868-77-9)

Acute toxicity: LD50 oral, rat: 5050 mg/kg. LD50 dermal, rabbit: $> 3\,000$ mg/kg.

Skin / eye: Skin (rabbit): irritating (24 h). Eyes (rabbit): moderate eye irritation (24 h, Draize).

Sensitisation: May cause sensitisation by skin contact (OECD 406).

Carcinogenicity: IARC: no component $\geq 0,1\%$ identified as a carcinogen.

Reproductive toxicity: Rat, female, oral — effects on fertility and on embryo/fetus reported.

12. Ecological information

Toxicity to fish: Pimephales promelas (fathead minnow): 227 mg/l — 96 h (flow-through).

Persistence / degradability: Readily biodegradable — 84 % (28 d, Closed Bottle test).

PBT / vPvB: Assessment not available (chemical safety assessment not required/conducted).

13. Disposal considerations

Waste treatment: May be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable material to a licensed disposal company.

Contaminated packaging: Dispose of as unused product.

14. Transport information

Classification: ADR/RID, IMDG and IATA: Not dangerous goods.

UN number / class / packing group: None.

Environmental hazards: IMDG marine pollutant: no.

15. Regulatory information

Labelling: According to Regulation (EC) No 1272/2008 — see Section 2.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Inventory: EINECS — substance included in the regulations (✓).

16. Other information

H-statements: H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

R-phrases: R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact.

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. It is based on the present state of our knowledge and does not represent any guarantee of the properties of the product.

Safety data sheet · Issue V2026.1 · 2026.06