

Document Version: V2026.1
 Date of first issue: 2021.01.21
 Date viewed: 2026.05.01

MULTiline FORCE

Product name	Lateral Repairs MULTiline FORCE
Product code	FORCE

Material composition	
	Polyester needle fleece liner with Polypropylene (PP) coating. Lateral Repairs quality product manufactured according to ISO 9001.

Supply data	
Pipe diameter	100 mm – 300 mm / 4 inch – 12 inch Other dimensions available on request
Liner undersized	10 %
Liner lengths	50 m; 100 m / 164 feet; 328 feet Other lengths available on request

General data	
Type of fibers	Polyester
Coating	PP
Basic color	White
Color coating	Milky white
Type of basic material	Needle-punched
Used seam (stitched) and seam sealing	Stitched seam with PES-thread
	Seam sealed with PP extrusion or seam tape
	Welded or glued seam
	Seam coating with PP extrusion or seam tape

Document Version: V2026.1
Date of first issue: 2021.01.21
Date viewed: 2026.05.01

MULTIline FORCE

Physical properties			
Weight per square meter	Varies according to liner construction		
Weight of coating	[Tracking force 20cN/cm ² bearing area 25 cm ²]	g/m ² lbs/inch ²	250 – 350 0,55 – 0,77
Thickness		mm inch	3 – 6 0,12 – 0,24
Water penetration resistance	ISO 811	mbar	≥ 500

Handling parameter	
Heat resistance	Max. 120 °C / 248 °F
Negotiating bends up to	Max. 45°
Pinch roller gap (impregnation)	2 x Wall thickness + 0,8 inch

Due to the variety of installation conditions, service environments, applications, and processing methods, the data provided in this technical datasheet should be considered as non-binding guideline values only.

Document Version: V2026.1
Date of first issue: 2021.01.21
Date viewed: 2026.05.01

MULTIline FORCE

Curing temperature max. 100 °C

Diameter		Wall thickness		<u>MIN.</u> Inversion pressure		<u>MAX.</u> Inversion pressure		<u>MIN.</u> Curing pressure at 10 °C / 50 °F		<u>MIN.</u> Curing pressure at 80 °C / 176 °F		<u>MAX.</u> Curing pressure		Resin amount	
mm	inch	mm	inch	bar	psi	bar	psi	bar	psi	bar	psi	bar	psi	Liter / m	Gallon (US) / feet
100	4,00	3,00	0,12	0,32	4,60	1,12	16,20	0,40	5,80	0,27	3,90	0,45	6,50	0,95	0,08
100	4,00	4,50	0,18	0,48	7,00	1,68	24,40	0,60	8,80	0,40	5,80	0,67	9,70	1,42	0,11
125	5,00	3,00	0,12	0,32	4,60	1,12	16,20	0,40	5,80	0,27	3,90	0,45	6,50	1,18	0,10
125	5,00	4,50	0,18	0,48	7,00	1,68	24,40	0,60	8,80	0,40	5,80	0,67	9,70	1,77	0,14
150	6,00	3,00	0,12	0,32	4,60	1,12	16,20	0,40	5,80	0,27	3,90	0,45	6,50	1,42	0,11
150	6,00	4,50	0,18	0,48	7,00	1,68	24,40	0,60	8,80	0,40	5,80	0,67	9,70	2,13	0,17
150	6,00	6,00	0,24	0,64	9,30	2,24	32,50	0,81	11,70	0,54	7,80	0,90	13,00	2,83	0,23
200	8,00	3,00	0,12	0,24	3,50	0,88	12,80	0,32	4,60	0,21	3,10	0,35	5,10	1,89	0,15
200	8,00	4,50	0,18	0,40	5,80	1,28	18,60	0,46	6,70	0,31	4,50	0,51	7,40	2,83	0,23
200	8,00	6,00	0,24	0,48	7,00	1,68	24,40	0,60	8,80	0,40	5,80	0,67	9,70	3,77	0,30
225	9,00	3,00	0,12	0,24	3,50	0,88	12,80	0,32	4,60	0,21	3,10	0,35	5,10	2,13	0,17
225	9,00	4,50	0,18	0,40	5,80	1,28	18,60	0,46	6,70	0,31	4,50	0,51	7,40	3,19	0,26
225	9,00	6,00	0,24	0,48	7,00	1,68	24,40	0,60	8,80	0,40	5,80	0,67	9,70	4,25	0,34
250	10,00	4,50	0,18	0,32	4,60	0,96	13,90	0,35	5,00	0,23	3,30	0,38	5,60	3,60	0,29
250	10,00	6,00	0,24	0,40	5,80	1,36	19,70	0,49	7,10	0,33	4,70	0,54	7,90	4,80	0,39
250	10,00	9,00	0,35	0,56	8,10	2,00	29,00	0,72	10,40	0,48	7,00	0,80	11,60	7,10	0,57
300	12,00	6,00	0,24	0,32	4,60	1,12	16,20	0,40	5,80	0,27	3,90	0,45	6,50	5,70	0,46
300	12,00	9,00	0,35	0,48	7,00	1,68	24,40	0,60	8,80	0,40	5,80	0,67	9,70	8,50	0,68
300	12,00	12,00	0,47	0,64	9,30	2,24	32,50	0,81	11,70	0,54	7,80	0,90	13,00	11,40	0,92