

Document Version: V2026.1
Date of first issue: 2021.01.21
Date viewed: 2026.06.18

MULTIline CORE

Product name	Lateral Repairs MULTIline CORE
Product code	CORE

Material composition

Multi-knitted fleece with one sided Polypropylene (PP) coating.

Supply data

Pipe diameter	70, 80, 100, 125, 150, 200, 225, 250. Other dimensions available on request
Liner undersized	13 %
Liner lengths	50 m; 100 m / 164 feet; 328 feet Other lengths available on request

General data

Type of fibers	Polyester
Coating	One side PP
Basic color	White
Color coating	Transparent
Type of basic material	Multi-layer knitted fleece with PP coating
Used seam (stitched) and seam sealing	Seam construction with PES-Yarn Seam sealed with PP seam tape

Physical properties

Weight	DIN EN 12127	g/m ²	550*
Weight of coating		g/m ²	150*
Thickness		mm inch	4,00* 0,16*
Water penetration resistance (20 °C / 68 °F)	ISO 811	mbar psi	≤ 550 ≤ 7,97

Handling parameter

Heat resistance	Max. 85 °C / 167 °F
Negotiating bends up to	Max. 90°
Pinch roller gap (impregnation)	2 x Wall thickness + 2 mm
Additional lengths	5 %

The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher inversion and/or curing pressures and accept no liability.

* = Modal value (typical value)

Additional Information – please see “methods of application”.