

Document Version: V2026.1
Date of first issue: 2021.01.21
Date viewed: 2026.06.18

MULTiline FORCE

Product name	Lateral Repairs MULTiline FORCE 3.0mm
Product code	FORCE

Material composition
Polyester needle-punched fleece liner with filament reinforcement and a polypropylene (PP) coating.

Supply data	
Pipe diameter	100 mm – 300 mm / 4 inch – 12 inch Other dimensions available on request
Liner undersized	10 %
Liner lengths	50 m; 100 m / 164 feet; 328 feet Other lengths available on request

General data	
Type of fibers	Polyester
Coating	PP
Basic color	White
Color coating	Milky white
Type of basic material	Needle-punched fleece with filament
Used seam (stitched) and seam sealing	Stitched seam with PES-thread Seam sealed with PP seam tape
	Welded or glued seam Seam coating with PP seam tape

Physical properties			
Weight		g/m²	650
Weight of coating	[Tracking force 20cN/cm² bearing area 25 cm²]	g/m²	300
Thickness		mm inch	3,00 0,12
Water penetration resistance	ISO 811	mbar	≥ 500

Handling parameter	
Heat resistance	Max. 100 °C / 212 °F
Negotiating bends up to	Max. 45°
Pinch roller gap (impregnation)	2 x Wall thickness + 2 mm
Additional lenghts	2 %

The final quality depends on the resin system used, the inversion pressure and the curing pressure. We advise against the use of other resin systems or higher inversion and/or curing pressures and accept no liability.